# **RF Exposure Compliance Requirement**

## 1 Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm²)	Averaging Times IEI <sup>2</sup> ,IHI <sup>2</sup> or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842/f	4.89/f	(900/f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100000			5	6	

## (a) Limits for Occupational / Controlled Exposure

#### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm²)	Averaging Times  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2 MPE Calculation Method

E (V/m)= $(30*P*G)^{0.5}/d$  Power Density: Pd(W/m<sup>2</sup>)=E<sup>2</sup>/377

E=Electric Field (V/m)

P= RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

Pd= (30\*P\*G)/(377\*d<sup>2</sup>)

From the average EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## 3 Calculated Result and Limit

(1)						
Frequency (MHz)	Antenna Gain (Numeric)	Output Power (dBm)	Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
WiFi						
2.4GHz	1.995	16.44	44.055	0.01749	1	Complies
802.11b						
WiFi						
2.4GHz	1.995	16.25	42.170	0.01674	1	Complies
802.11g						
WiFi						
2.4GHz	1.995	16.94	49.431	0.01962	1	Complies
802.11n20						

It does meet the RF Exposure Compliance Requirement.