

FCC&IC TEST REPORT

No. 151200867SHA-001

Applicant : Cixi City Yidong Electronic Co., Ltd.
Guanhaiwei Industrial West Zone, Cixi City, Ningbo,
315315, P.R.China.

Manufacturer : Cixi City Yidong Electronic Co., Ltd.
Guanhaiwei Industrial West Zone, Cixi City, Ningbo,
315315, P.R.China.

Product Name : Transmitter

Type/Model : RC-2U

TEST RESULT : PASS

SUMMARY

The equipment complies with the requirements according to the following standard(s) or specification:

47CFR Part 15 (2014): Radio Frequency Devices (Subpart C)


ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of
Unlicensed Wireless Devices

RSS-210 Issue 8 (December 2010): Low-power Licence-exempt Radio communication
Devices (All Frequency Bands): Category I Equipment

RSS-Gen Issue 4 (November 2014): General Requirements and Information for the
Certification of Radio communication Equipment

Date of issue: Jan 27, 2016

Prepared by:



Jesse Xu (*Project Engineer*)

Reviewed by:



Daniel Zhao (*Reviewer*)



Description of Test Facility

Name: Intertek Testing Service Limited Shanghai
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R. China

FCC Registration Number: 236597
IC Assigned Code: 2402B-1

Name of contact: Jonny Jing
Tel: 86 21 61278271
Fax: 86 21 54262353

Content

SUMMARY	1
1 GENERAL INFORMATION.....	4
1.1 Description of Client	4
1.2 Identification of the EUT	4
1.3 Technical Specification	5
2 TEST SPECIFICATIONS.....	6
2.1 Standards or specification	6
2.2 Mode of operation during the test	6
2.3 Test software list	6
2.4 Test peripherals list	6
2.5 Instrument list.....	7
2.6 Test Summary.....	8
3 FUNDAMENTAL & SPURIOUS EMISSION & RESTRICT BAND RADIATED EMISSION.....	9
3.1 Test limit.....	9
3.2 Test Configuration.....	10
3.3 Test procedure and test setup	10
3.4 Test protocol.....	11
4 DEACTIVATING TIME.....	13
4.1 Test limit.....	13
4.2 Test Configuration.....	14
4.3 Test procedure and test setup	14
4.4 Test protocol.....	14
5 EMISSION BANDWIDTH.....	15
5.1 Test limit.....	15
5.2 Test Configuration.....	15
5.3 Test procedure and test setup	15
5.4 Test protocol.....	16
6 CONDUCTED EMISSION.....	17
6.1 Limit	17
6.2 Test configuration.....	17
6.3 Test procedure and test set up	18
6.4 Test protocol.....	19
7 OCCUPIED BANDWIDTH	20
7.1 Test limit.....	20
7.2 Test Configuration.....	20
7.3 Test procedure and test setup	20
7.4 Test protocol.....	21

1 GENERAL INFORMATION

1.1 Description of Client

Applicant : Cixi City Yidong Electronic Co., Ltd.
Guanhaiwei Industrial West Zone, Cixi City, Ningbo, 315315,
P.R.China.

Name of contact : Mengjie Shen

Tel : +86 574 63630755

Fax : +86 574 63630188

Email : shenmengjie@cn-yidong.com

Manufacturer : Cixi City Yidong Electronic Co., Ltd.
Guanhaiwei Industrial West Zone, Cixi City, Ningbo, 315315,
P.R.China.

1.2 Identification of the EUT

Product Name : Transmitter

Type/model : RC-2U

FCC ID : S72-RC2U

IC : 10931A-RC2U

1.3 Technical Specification

Operation Frequency Band : 433.92MHz

Modulation : ASK

Antenna Designation : Integral antenna, non-user removable.

Description of EUT : There is one model only.
The EUT is a transmitter to control the working condition of the corresponding receiver.

Rating : Battery 3V

Category of EUT : Class B

EUT type : ☒ Table top
☐ Floor standing

Sample received date : Dec 25, 2015

Sample Identification No : 0151225-22-001

Date of test : 2015-12-30~2016-01-25

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2014)
ANSI C63.10 (2013)
RSS-210 Issue 8 (December 2010)
RSS-Gen Issue 4 (November 2014)

2.2 Mode of operation during the test

Within this test report, EUT was tested with modulation and tested under its rating voltage and frequency.

The EUT is a handheld device, so three axes (X, Y, Z) were observed while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description

2.5 Instrument list

Equipment	Type	Manu.	Internal no.	Cal. Date	Due date
Test Receiver	ESIB 26	R&S	EC 3045	2014-10-21	2016-10-20
Semi-anechoic chamber	-	Albatross project	EC 3048	2015-5-21	2016-5-20
Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2014-5-16	2016-5-15
Horn antenna	HF 906	R&S	EC 3049	2014-5-13	2016-5-12
Pre-amplifier	Pre-amp 18	R&S	EC 3222	2015-4-12	2016-4-11
Test Receiver	FSV40	R&S	/	2015-10-21	2016-10-20
Loop antenna	9230-1/9229-1	Schwarzbeck	086814/084814	2014-12-16	2016-12-15

2.6 Test Summary

This report applies to tested sample only. The test results have been compared directly with the limits, and the measurement uncertainty is recorded. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
Fundamental & spurious emission	15.231(b)	RSS-210 Issue 8 Annex A1.1.2	Pass
Restrict band radiated emission	15.205	RSS-210 Issue 8 Clause 2.2	Pass
Conducted emission	15.207	RSS-Gen Issue 4 Clause 8.8	NA
Emission bandwidth	15.231(c)	RSS-210 Issue 8 Annex A1.1.3	Pass
Deactivating time	15.231(a)(1)	RSS-210 Issue 8 Annex A1.1.1	Pass
Occupied bandwidth	-	RSS-Gen Issue 4 Clause 6.6	Tested

Notes: 1: NA =Not Applicable

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

TEST ITEM	MEASUREMENT UNCERTAINTY
Fundamental & spurious emission	$\pm 4.90\text{dB}$
Restrict band radiated emission	$\pm 4.90\text{dB}$
Conducted emission	$\pm 3.19\text{dB}$
Emission bandwidth	$\pm 1.56\text{dB}$
Deactivating time	$\pm 0.5\text{S}$
Occupied bandwidth	$\pm 1.56\text{dB}$

3 Fundamental & Spurious Emission & Restrict band radiated emission

Test result: Pass

3.1 Test limit

The emission shall test through the 10th harmonic or to 40GHz, whichever is lower. It must comply with the limits below:

Fundamental Frequency (MHz)	Fundamental limit (uV/m)	Spurious limit (uV/m)
<input type="checkbox"/> 40.66 – 40.70	2250	225
<input type="checkbox"/> 70 – 130	1250	125
<input type="checkbox"/> 130 - 174	1250 to 3750	125 to 375
<input type="checkbox"/> 174 - 260	3750	375
<input checked="" type="checkbox"/> 260 – 470	3750 to 12500	375 to 1250
<input type="checkbox"/> Above 470	12500	1250

The formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = $56.81818(\text{Frequency}) - 6136.3636$; for the band 260-470 MHz, uV/m at 3 meters = $41.6667(\text{Frequency}) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

For that the EUT use fundamental frequency of 433.92MHz, after calculation, the limit is:

Fundamental limit = $41.6667 * 433.92 - 7083.3333 = 10996.68 \text{ uV/m} = 80.80\text{dBuV/m}$


Spurious limit = $81 - 20 = 60.80\text{dBuV/m}$

////////////////////////////////////

The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

3.2 Test Configuration



3.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, the pre-amplifier and high pass filter is equipped just at the output terminal of the antenna.

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m.

The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1 meter to 4 meters to find out the maximum emission level.

Both horizontal and vertical polarities of the receiving antenna were assessed and the higher reading was listed in this report.

The radiated emission was measured using the test receiver with the resolutions bandwidth set as:

RBW=300 Hz, VBW=1 kHz (9 kHz~150 kHz);

RBW=10 kHz, VBW=30 kHz (150 kHz~30MHz);

RBW = 100 kHz, VBW = 300 kHz (30MHz~1GHz)

RBW = 1MHz, VBW = 3MHz (>1GHz for PK);

3.4 Test protocol

Temperature : 23 °C
Relative Humidity : 55 %

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Emission Type	Limit (dBuV/m)	Margin	Detector
H	433.92	81.20	19.90	Fundamental	100.80	19.60	PK
H	867.81	37.90	25.20	Spurious	80.80	42.90	PK
H	1296.59	32.02	-18.10	Spurious	80.80	48.78	PK
H	407.00	23.40	17.40	Restrict	46.00	22.60	PK
V	433.92	72.80	19.90	Fundamental	100.80	28.00	PK
V	867.81	33.50	25.20	Spurious	80.80	47.30	PK
V	1296.59	31.45	-18.10	Spurious	80.80	49.35	PK
V	2338.44	34.42	-10.55	Restrict	74.00	39.58	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz)
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If PK Corrected reading is less than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, limit = 40.00dBuV/m.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m; Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m; Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

Calculating the AV value according to the duty cycle:

Antenna Polarization	Frequency (MHz)	Corrected PK Reading (dBuV/m)	Duty Cycle Factor (dB)	Corrected AV Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
H	433.92	81.20	-8.60	72.60	80.80	8.20

Remark: 1. Duty Cycle Factor = $20\lg(\text{duty cycle}) = 20\lg(0.37) = -8.60\text{dB}$
 2. Corrected AV Reading = Corrected PK Reading + Duty Cycle Factor
 3. Margin = limit – Corrected AV Reading


4 Deactivating time

Test result: Pass

4.1 Test limit

- ☒ (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- ☐ (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- ☐ (3) Periodic transmissions at regular predetermined intervals are not permitted.
However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.
- ☐ (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.
- ☐ (5) Transmission of set-up information for security systems may exceed the transmission duration limits in (1) and (2) above, provided such transmission are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

4.2 Test Configuration



4.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber.

The central frequency of test receiver was set as the operating frequency of EUT and the Span was set as 0.

The EUT was switched once. The test receiver recorded the whole time from the triggered moment to the time of stopping radiating. For manual switching, to avoid uncertainty, the operating above would be repeated five times and the worst data is recorded.

4.4 Test protocol

Temperature : 23 °C

Relative Humidity : 55 %

Whole time from the triggered moment to the time of stopping radiating: 460ms.

As a result, the EUT complies with the limit of 5s' deactivating time.

5 Emission Bandwidth


Test Status: Pass

5.1 Test limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

The limit for the EUT = $0.25\% * 433.92\text{MHz} = 1085\text{kHz}$

5.2 Test Configuration



5.3 Test procedure and test setup

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

The central frequency of test receiver was set near the operating frequency of EUT.

The test was conducted using the Spectrum Analyzer with the resolutions bandwidth set below:

RBW = approximately 1% of the emission bandwidth.

VBW > RBW.

5.4 Test protocol

Temperature : 25 °C
Relative Humidity : 55 %

Channel	Emission Bandwidth (kHz)	Limit (kHz)
1	152	1085

6 Conducted emission


Test result: NA

6.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

6.2 Test configuration



☐ For table top equipment, wooden support is 0.8m height table

☐ For floor standing equipment, wooden support is 0.1m height rack.

6.3 Test procedure and test set up

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

6.4 Test protocol

Temperature : °C
Relative Humidity : %

Power line: L

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
Remark: If the margin higher than 20dB, it would be marked as *.						

Power line: N

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
Remark: If the margin higher than 20dB, it would be marked as *.						


7. Occupied Bandwidth

Test Status: Tested

7.1 Test limit

None

7.2 Test Configuration



7.3 Test procedure and test setup

The occupied bandwidth per RSS-Gen Issue 4 Clause 6.6 was measured using the Spectrum Analyzer with the resolutions bandwidth set at 10kHz, the video bandwidth set at 30kHz.

7.4 Test protocol

Temperature : 25 °C
Relative Humidity : 55 %

Channel	Occupied Bandwidth (MHz)	Max. Value MHz)
1	0.088	0.088

Remark: “Max. Value” is the maximum test result of all the measured occupied bandwidth.