

# Standalone SAR test exclusion considerations

April 1, 2015

- Min. transmitting frequency = 2480 MHz
- Min. test separation distance = 5 mm
- Max. power with turn-up tolerance = 12.00 dBm = 16 mW  
Typical Power: 8.50 dBm ± 3.50 dB  
Measured Output Power: 11.95 dBm

**Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances ≤ 50 mm =      Used**

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$$= [16.00 / 5] * [\sqrt{2.48}]$$

$$= \mathbf{5.04} \leq 7.5, \text{ for } 10\text{g extremitly SAR}$$

Thus SAR for this device is not required.

**Step 2-1) SAR test exclusion thresholds for 100MHz to 1500MHz at test separationn distances > 50 mm =      N/A**

[Threshold at 50 mm in step 1) + (test separation distance - 50 mm)·( f(MHz)/150)] mW

**Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separationn distances > 50 mm =      N/A**

[Threshold at 50 mm in step 1) + (test separation distance - 50 mm)·10] mW