



FCC TEST REPORT

**Test report
On Behalf of
Sena Technologies, Inc.
For
10Upad
Model No.: SP36**

FCC ID: S7A-SP36

Prepared for : Sena Technologies, Inc.
19, Heolleung-ro 569-gil, Gangnam-gu, Seoul, South Korea

Prepared By : Shenzhen HUAKE Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Aug. 29, 2018 ~ Sep. 04, 2018

Date of Report: Sep. 05, 2018

Report Number: HUAKE180830940E




TEST RESULT CERTIFICATION

Applicant's name : Sena Technologies, Inc.
 Address : 19, Heolleung-ro 569-gil, Gangnam-gu, Seoul, South Korea
Manufacturer's Name : Sena Technologies, Inc.
 Address : Floor 4G/4F, Science&Technology building, Maozhoushan industry park, BaoAn District, ShenZhen City, GuangDong province, China


Product description
 Trade Mark : SENA
 Product name..... : 10Upad
 Model and/or type reference : SP36
 APPLICATION PURPOSE..... : Class II Permissive Change
Standards : FCC Part 15 Subpart C Section 15.247

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.


Date of Test :
 Date (s) of performance of tests..... : Aug. 29, 2018 ~ Sep. 04, 2018
 Date of Issue..... : Aug. 05, 2018
 Test Result..... : **Pass**

Testing Engineer : 

 (Gary Qian)

Technical Manager : 

 (Eden Hu)

Authorized Signatory : 

 (Jason Zhou)



| Table of Contents | Page |
|--|-------------|
| 1 . TEST SUMMARY | 4 |
| 2 . GENERAL INFORMATION | 5 |
| 2.1 GENERAL DESCRIPTION OF EUT | 5 |
| 2.2 CARRIER FREQUENCY OF CHANNELS | 6 |
| 2.3 OPERATION OF EUT DURING TESTING | 7 |
| 2.4 DESCRIPTION OF TEST SETUP | 8 |
| 2.5 EQUIPMENT USED IN EUT SYSTEM | 8 |
| 2.6 MEASUREMENT INSTRUMENTS LIST | 9 |
| 3 . CONDUCTED EMISSIONS TEST | 10 |
| 3.1. LIMITS OF LINE CONDUCTED EMISSION TEST | 10 |
| 3.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST | 10 |
| 3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST | 11 |
| 3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST | 11 |
| 3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST | 12 |
| 4. RADIATED EMISSION TEST | 14 |
| 4.1 TEST LIMIT | 14 |
| 4.2. MEASUREMENT PROCEDURE | 15 |
| 4.3. TEST SETUP | 17 |
| 4.4. TEST RESULT | 18 |
| 5. ANTENNA REQUIREMENT | 42 |
| 6. PHOTOGRAPH OF TEST | 43 |
| 7. PHOTOGRAPHS OF EUT | 46 |



1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

| DESCRIPTION OF TEST | RESULT |
|--------------------------|-----------|
| CONDUCTED EMISSIONS TEST | COMPLIANT |
| RADIATED EMISSION TEST | COMPLIANT |
| PEAK OUTPUT POWER | COMPLIANT |

Note: Owing to the product under testing was identical with the AGC08321161101's product except for the brand name and antenna. So the test data may refer to the AGC00150180401 (FCC ID:S7A-SP36) except for the data of radiated emission and conducted emissions.

1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park,
Fuhai Street, Bao'an District, Shenzhen City, China

Designation Number: : CN1229

Test Firm Registration Number : 616276

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty(Above 1GHz) = 4.06dB, k=2



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|--|--|
| Operation Frequency | 2.402 GHz to 2.480GHz |
| Bluetooth Version | V4.1 |
| RF Output Power (for BR/EDR) | 19.73dBm(Max) |
| RF Output Power (for BLE) | 9.85dBm(Max) |
| Modulation | BR <input checked="" type="checkbox"/> GFSK, EDR <input checked="" type="checkbox"/> π /4-DQPSK, <input checked="" type="checkbox"/> 8DPSK BLE <input checked="" type="checkbox"/> GFSK |
| Number of channels | 79 for BR/EDR, 40 for BLE |
| Hardware Version | v1.0 |
| Software Version | v1.0 |
| Antenna Designation | Fixed Antenna |
| Antenna Gain | 0.48dBi |
| Power Supply | DC 3.7V by battery |
| Note: The USB port only be used for charging and can't be used to transfer data with PC. | |



2.2 CARRIER FREQUENCY OF CHANNELS

BR/EDR channel List

| Frequency Band | Channel Number | Frequency |
|----------------|----------------|-----------|
| 2400~2483.5MHz | 0 | 2402MHz |
| | 1 | 2403MHz |
| | : | : |
| | 38 | 2440 MHz |
| | 39 | 2441 MHz |
| | 40 | 2442 MHz |
| | : | : |
| | 77 | 2479 MHz |
| | 78 | 2480 MHz |

BLE Channel List

| Frequency Band | Channel Number | Frequency |
|----------------|----------------|-----------|
| 2400~2483.5MHz | 0 | 2402MHz |
| | 1 | 2404MHz |
| | : | : |
| | 38 | 2478 MHz |
| | 39 | 2480 MHz |




2.3 OPERATION OF EUT DURING TESTING

| NO. | TEST MODE DESCRIPTION |
|--|-------------------------------|
| 1 | Low channel GFSK |
| 2 | Middle channel GFSK |
| 3 | High channel GFSK |
| 4 | Low channel $\pi/4$ -DQPSK |
| 5 | Middle channel $\pi/4$ -DQPSK |
| 6 | High channel $\pi/4$ -DQPSK |
| 7 | Low channel 8DPSK |
| 8 | Middle channel 8DPSK |
| 9 | High channel 8DPSK |
| 10 | BT Link with charging |
| 11 | BT Link(Hopping mode) |
| <p>Note:</p> <ol style="list-style-type: none">1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.3. The EUT used fully-charged battery when tested. | |




2.4 DESCRIPTION OF TEST SETUP

Configure 1: (Normal hopping)



Note: Owing to the EUT has own battery, and testing may be performed while adapter or PC removed.

Configuration: Continuous TX



2.5 EQUIPMENT USED IN EUT SYSTEM

| Item | Equipment | Mfr/Brand | Model/Type No. | Remark |
|------|-------------|-----------|----------------|-----------|
| 1 | 10Upad | SENA | SENA | EUT |
| 2 | Battery | XK | 602248 | Accessory |
| 3 | PC | APPLE | A1465 | A.E |
| 4 | Control box | SERIAL | N/A | A.E |
| 6 | USB Cable | N/A | 1m unshielded | A.E |
| 7 | Adapter | I PRO | NTR-S01 | A.E |

**2.6 MEASUREMENT INSTRUMENTS LIST****TEST EQUIPMENT OF CONDUCTED EMISSION TEST**

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|---|--------------|-----------|------------|---------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | R&S | ENV216 | HKE-002 | Dec. 28, 2017 | 1 Year |
| 2. | Receiver | R&S | ESCI 7 | HKE-010 | Dec. 28, 2017 | 1 Year |

TEST EQUIPMENT OF RADIATED EMISSION TEST

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|----------------------------|--------------------|--------------|------------|---------------|---------------|
| 1. | Spectrum analyzer | Agilent | N9020A | HKE-048 | Dec. 28, 2017 | 1 Year |
| 2. | Preamplifier | Schwarzbeck | BBV 9743 | HKE-006 | Dec. 28, 2017 | 1 Year |
| 3. | EMI Test Receiver | Rohde & Schwarz | ESCI 7 | HKE-010 | Dec. 28, 2017 | 1 Year |
| 4. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | HKE-012 | Dec. 28, 2017 | 1 Year |
| 5. | Loop Antenna | Schwarzbeck | FMZB 1519 B | HKE-014 | Dec. 28, 2017 | 1 Year |
| 6. | Horn Antenna | Schwarzbeck | 9120D | HKE-013 | Dec. 28, 2017 | 1 Year |
| 7. | Broad-band Horn Antenna | Schwarzbeck | LB-180400-KF | HKE-031 | Dec. 28, 2017 | 1 Year |
| 8. | Pre-amplifier | EMCI | EMC051845SE | HKE-015 | Dec. 28, 2017 | 1 Year |
| 9. | Pre-amplifier | Agilent | 83051A | HKE-016 | Dec. 28, 2017 | 1 Year |
| 10. | Filter (2.4-2.483GHz) | Micro-tronics | 087 | -- | N/A | N/A |
| 11. | Radiation Cable 1 | MXT | HK1 | R05 | N/A | N/A |
| 12. | Radiation Cable 2 | MXT | HK1 | R06 | N/A | N/A |

3. CONDUCTED EMISSIONS TEST


3.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency | Maximum RF Line Voltage | |
|---------------|-------------------------|----------------|
| | Q.P.(dBuV) | Average(dBuV) |
| 150kHz~500kHz | 66-56 | 56-46 |
| 500kHz~5MHz | 56 | 46 |
| 5MHz~30MHz | 60 | 50 |

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

3.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10-2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.




3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

For BLE

BT Link with charging

By adapter(worst case)

Line Conducted Emission Test Line 1-L




| NO. | Freq. [MHz] | Factor [dB] | QP Value [dBμV] | QP Limit [dBμV] | QP Margin [dB] | AV Value [dBμV] | AV Limit [dBμV] | AV Margin [dB] |
|-----|-------------|-------------|-----------------|-----------------|----------------|-----------------|-----------------|----------------|
| 2 | 0.8159 | 10.05 | 45.69 | 56.00 | 10.31 | 30.53 | 46.00 | 15.47 |
| 3 | 0.7017 | 10.05 | 43.22 | 56.00 | 12.78 | 28.99 | 46.00 | 17.01 |
| 1 | 0.1795 | 10.06 | 45.80 | 64.51 | 18.71 | 31.94 | 54.51 | 22.57 |
| 4 | 2.6673 | 10.21 | 38.63 | 56.00 | 17.37 | 29.50 | 46.00 | 16.50 |
| 5 | 9.8095 | 10.07 | 37.05 | 60.00 | 22.95 | 27.70 | 50.00 | 22.30 |
| 6 | 21.2652 | 10.14 | 37.47 | 60.00 | 22.53 | 25.77 | 50.00 | 24.23 |



Line Conducted Emission Test Line 2-N

Test Graph



| NO. | Freq. [MHz] | Factor [dB] | QP Value [dBμV] | QP Limit [dBμV] | QP Margin [dB] | AV Value [dBμV] | AV Limit [dBμV] | AV Margin [dB] |
|-----|-------------|-------------|-----------------|-----------------|----------------|-----------------|-----------------|----------------|
| 1 | 0.1777 | 10.05 | 42.32 | 64.59 | 22.27 | 30.42 | 54.59 | 24.17 |
| 2 | 0.6167 | 10.05 | 44.78 | 56.00 | 11.24 | 31.67 | 46.00 | 14.33 |
| 3 | 1.3192 | 10.10 | 39.09 | 56.00 | 16.91 | 28.46 | 46.00 | 17.54 |
| 4 | 2.7837 | 10.21 | 39.35 | 56.00 | 16.65 | 30.93 | 46.00 | 15.07 |
| 5 | 9.7258 | 10.08 | 39.11 | 60.00 | 20.89 | 29.92 | 50.00 | 20.08 |
| 6 | 21.0896 | 10.13 | 42.93 | 60.00 | 17.07 | 31.14 | 50.00 | 18.86 |



4. RADIATED EMISSION TEST

4.1 TEST LIMIT

| Frequency (MHz) | Distance Meters | Field Strengths Limit | |
|--------------------|--------------------|---|----------------|
| | | μ V/m | dB(μ V)/m |
| 0.009 ~ 0.490 | 300 | 2400/F(kHz) | --- |
| 0.490 ~ 1.705 | 30 | 24000/F(kHz) | --- |
| 1.705 ~ 30 | 30 | 30 | --- |
| 30 ~ 88 | 3 | 100 | 40.0 |
| 88 ~ 216 | 3 | 150 | 43.5 |
| 216 ~ 960 | 3 | 200 | 46.0 |
| 960 ~ 1000 | 3 | 500 | 54.0 |
| Above 1000 | 3 | Other:74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average) | |

Remark: (1) Emission level $\text{dB}\mu$ V = 20 log Emission level μ V/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



4.2. MEASUREMENT PROCEDURE

1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
2. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
3. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
4. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)




The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---------------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |


| Receiver Parameter | Setting |
|---------------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |

4.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





4.4. TEST RESULT

For BR/EDR


(Worst modulation: 8DPSK)

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 70.4167 | 8.02 | 9.85 | 17.87 | 40.00 | -22.13 | peak | | | |
| 2 | | 148.0166 | 4.45 | 13.25 | 17.70 | 43.50 | -25.80 | peak | | | |
| 3 | | 327.4667 | 5.09 | 17.24 | 22.33 | 46.00 | -23.67 | peak | | | |
| 4 | | 631.3999 | 2.88 | 23.81 | 26.69 | 46.00 | -19.31 | peak | | | |
| 5 | * | 757.5000 | 4.00 | 26.73 | 30.73 | 46.00 | -15.27 | peak | | | |
| 6 | | 977.3667 | 2.79 | 29.74 | 32.53 | 54.00 | -21.47 | peak | | | |

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 80.1166 | 12.47 | 1.84 | 14.31 | 40.00 | -25.69 | peak | | | |
| 2 | | 170.6500 | 6.98 | 14.66 | 21.64 | 43.50 | -21.86 | peak | | | |
| 3 | | 240.1666 | 13.71 | 12.94 | 26.65 | 46.00 | -19.35 | peak | | | |
| 4 | | 426.0833 | 3.84 | 19.86 | 23.70 | 46.00 | -22.30 | peak | | | |
| 5 | | 744.5666 | 1.24 | 26.47 | 27.71 | 46.00 | -18.29 | peak | | | |
| 6 | * | 951.5000 | 1.11 | 29.99 | 31.10 | 46.00 | -14.90 | peak | | | |


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 68.7998 | 14.47 | 4.73 | 19.20 | 40.00 | -20.80 | peak | | | |
| 2 | | 240.1666 | 11.21 | 12.94 | 24.15 | 46.00 | -21.85 | peak | | | |
| 3 | | 406.6832 | 5.41 | 19.27 | 24.68 | 46.00 | -21.32 | peak | | | |
| 4 | | 634.6332 | 2.66 | 23.51 | 26.17 | 46.00 | -19.83 | peak | | | |
| 5 | | 804.3832 | 3.08 | 27.32 | 30.40 | 46.00 | -15.60 | peak | | | |
| 6 | * | 907.8500 | 4.46 | 28.83 | 33.29 | 46.00 | -12.71 | peak | | | |

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 115.6833 | 10.94 | 6.86 | 17.80 | 43.50 | -25.70 | peak | | | |
| 2 | | 211.0666 | 11.87 | 10.87 | 22.74 | 43.50 | -20.76 | peak | | | |
| 3 | | 445.4832 | 3.34 | 20.45 | 23.79 | 46.00 | -22.21 | peak | | | |
| 4 | | 633.0167 | 4.29 | 23.81 | 28.10 | 46.00 | -17.90 | peak | | | |
| 5 | * | 770.4333 | 2.97 | 26.91 | 29.88 | 46.00 | -16.12 | peak | | | |
| 6 | | 849.6499 | 1.87 | 27.31 | 29.18 | 46.00 | -16.82 | peak | | | |

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL

66.9 dBuV/m




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 67.1833 | 9.48 | 7.51 | 16.99 | 40.00 | -23.01 | peak | | | |
| 2 | | 215.9166 | 9.69 | 10.38 | 20.07 | 43.50 | -23.43 | peak | | | |
| 3 | | 359.8000 | 4.15 | 18.80 | 22.95 | 46.00 | -23.05 | peak | | | |
| 4 | | 626.5499 | 5.49 | 23.79 | 29.28 | 46.00 | -16.72 | peak | | | |
| 5 | | 763.9666 | 3.71 | 26.82 | 30.53 | 46.00 | -15.47 | peak | | | |
| 6 | * | 953.1167 | 2.43 | 29.97 | 32.40 | 46.00 | -13.60 | peak | | | |

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 109.2167 | 18.74 | 1.49 | 20.23 | 43.50 | -23.27 | peak | | | |
| 2 | | 298.3666 | 7.41 | 15.36 | 22.77 | 46.00 | -23.23 | peak | | | |
| 3 | | 359.8000 | 4.90 | 18.80 | 23.70 | 46.00 | -22.30 | peak | | | |
| 4 | | 652.4166 | 7.61 | 23.91 | 31.52 | 46.00 | -14.48 | peak | | | |
| 5 | | 781.7500 | 6.66 | 27.07 | 33.73 | 46.00 | -12.27 | peak | | | |
| 6 | * | 943.4166 | 4.31 | 29.82 | 34.13 | 46.00 | -11.87 | peak | | | |

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION ABOVE 1GHz

RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-LOW CHANNEL-HORIZONTAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | * | 2402.000 | 104.16 | 10.32 | 114.48 | 74.00 | 40.48 | peak | | | |
| 2 | | 3256.000 | 37.21 | 11.88 | 49.09 | 74.00 | -24.91 | peak | | | |
| 3 | | 5125.000 | 45.86 | 5.70 | 51.56 | 74.00 | -22.44 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-LOW CHANNEL –VERTICAL

126.0 dBuV/m




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2402.000 | 104.20 | 10.32 | 114.52 | 74.00 | 40.52 | peak | | | |
| 2 | | 3375.000 | 40.01 | 11.99 | 52.00 | 74.00 | -22.00 | peak | | | |
| 3 | | 5108.333 | 45.27 | 6.03 | 51.30 | 74.00 | -22.70 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-MIDDLE CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2441.000 | 104.80 | 10.36 | 115.16 | 74.00 | 41.16 | peak | | | |
| 2 | | 3600.000 | 39.32 | 12.73 | 52.05 | 74.00 | -21.95 | peak | | | |
| 3 | | 5033.333 | 43.49 | 7.53 | 51.02 | 74.00 | -22.98 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics) - MIDDLE CHANNEL –VERTICAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2441.000 | 104.43 | 10.36 | 114.79 | 74.00 | 40.79 | peak | | | |
| 2 | | 3533.333 | 37.25 | 12.32 | 49.57 | 74.00 | -24.43 | peak | | | |
| 3 | | 5050.000 | 43.31 | 7.20 | 50.51 | 74.00 | -23.49 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-HIGH CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2480.000 | 104.40 | 10.41 | 114.81 | 74.00 | 40.81 | peak | | | |
| 2 | | 3566.667 | 38.34 | 12.52 | 50.86 | 74.00 | -23.14 | peak | | | |
| 3 | | 5283.333 | 48.44 | 2.53 | 50.97 | 74.00 | -23.03 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-HIGH CHANNEL –VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2480.000 | 104.50 | 10.41 | 114.91 | 74.00 | 40.91 | peak | | | |
| 2 | | 3375.000 | 38.79 | 11.99 | 50.78 | 74.00 | -23.22 | peak | | | |
| 3 | | 5308.333 | 49.37 | 2.03 | 51.40 | 74.00 | -22.60 | peak | | | |

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

The “Factor” value can be calculated automatically by software of measurement system




For BLE

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 107.5999 | 7.25 | 8.72 | 15.97 | 43.50 | -27.53 | peak | | | |
| 2 | | 308.0667 | 6.19 | 15.95 | 22.14 | 46.00 | -23.86 | peak | | | |
| 3 | | 450.3333 | 3.25 | 20.59 | 23.84 | 46.00 | -22.16 | peak | | | |
| 4 | | 657.2667 | 0.84 | 24.04 | 24.88 | 46.00 | -21.12 | peak | | | |
| 5 | | 757.5000 | 2.00 | 26.73 | 28.73 | 46.00 | -17.27 | peak | | | |
| 6 | * | 951.5000 | 4.10 | 29.99 | 34.09 | 46.00 | -11.91 | peak | | | |

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 146.4000 | 5.48 | 15.24 | 20.72 | 43.50 | -22.78 | peak | | | |
| 2 | | 316.1499 | 4.57 | 16.49 | 21.06 | 46.00 | -24.94 | peak | | | |
| 3 | | 510.1499 | 2.01 | 21.40 | 23.41 | 46.00 | -22.59 | peak | | | |
| 4 | | 650.7999 | 4.32 | 23.87 | 28.19 | 46.00 | -17.81 | peak | | | |
| 5 | | 830.2500 | 2.02 | 27.31 | 29.33 | 46.00 | -16.67 | peak | | | |
| 6 | * | 919.1666 | 4.15 | 29.14 | 33.29 | 46.00 | -12.71 | peak | | | |

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL

66.9 dBuV/m




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 76.8833 | 15.29 | 2.57 | 17.86 | 40.00 | -22.14 | peak | | | |
| 2 | | 177.1167 | 7.57 | 14.25 | 21.82 | 43.50 | -21.68 | peak | | | |
| 3 | | 269.2667 | 12.71 | 14.48 | 27.19 | 46.00 | -18.81 | peak | | | |
| 4 | | 393.7500 | 6.39 | 19.03 | 25.42 | 46.00 | -20.58 | peak | | | |
| 5 | * | 678.2833 | 3.77 | 24.61 | 28.38 | 46.00 | -17.62 | peak | | | |
| 6 | | 970.8999 | 5.31 | 29.80 | 35.11 | 54.00 | -18.89 | peak | | | |

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL

66.9 dBuV/m



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 107.5999 | 14.46 | 8.72 | 23.18 | 43.50 | -20.32 | peak | | | |
| 2 | | 324.2332 | 5.32 | 17.02 | 22.34 | 46.00 | -23.66 | peak | | | |
| 3 | | 445.4832 | 3.84 | 20.45 | 24.29 | 46.00 | -21.71 | peak | | | |
| 4 | | 636.2500 | 3.96 | 23.82 | 27.78 | 46.00 | -18.22 | peak | | | |
| 5 | * | 770.4333 | 0.97 | 26.91 | 27.88 | 46.00 | -18.12 | peak | | | |
| 6 | | 962.8166 | 3.85 | 29.88 | 33.73 | 54.00 | -20.27 | peak | | | |


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 143.1665 | 4.06 | 14.43 | 18.49 | 43.50 | -25.01 | peak | | | |
| 2 | | 240.1666 | 16.70 | 7.90 | 24.60 | 46.00 | -21.40 | peak | | | |
| 3 | | 359.8000 | 6.15 | 18.80 | 24.95 | 46.00 | -21.05 | peak | | | |
| 4 | | 505.3000 | 6.45 | 21.27 | 27.72 | 46.00 | -18.28 | peak | | | |
| 5 | | 681.5167 | -1.06 | 24.69 | 23.63 | 46.00 | -22.37 | peak | | | |
| 6 | * | 873.8999 | 3.81 | 27.93 | 31.74 | 46.00 | -14.26 | peak | | | |

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | | 104.3666 | 18.30 | -0.93 | 17.37 | 43.50 | -26.13 | peak | | | |
| 2 | | 202.9833 | 13.84 | 9.29 | 23.13 | 43.50 | -20.37 | peak | | | |
| 3 | | 382.4332 | 3.77 | 18.95 | 22.72 | 46.00 | -23.28 | peak | | | |
| 4 | | 508.5332 | 4.35 | 21.36 | 25.71 | 46.00 | -20.29 | peak | | | |
| 5 | | 702.5333 | -0.20 | 25.26 | 25.06 | 46.00 | -20.94 | peak | | | |
| 6 | * | 943.4166 | 2.81 | 29.82 | 32.63 | 46.00 | -13.37 | peak | | | |

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION ABOVE 1GHz

RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-LOW CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| 1 | * | 2402.000 | 91.13 | 10.32 | 101.45 | 74.00 | 27.45 | peak | cm | degree | |
| 2 | | 3616.667 | 37.55 | 12.83 | 50.38 | 74.00 | -23.62 | peak | | | |
| 3 | | 4766.667 | 42.11 | 7.59 | 49.70 | 74.00 | -24.30 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-LOW CHANNEL –VERTICAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | * | 2402.000 | 91.25 | 10.32 | 101.57 | 74.00 | 27.57 | peak | | | |
| 2 | | 3375.000 | 39.01 | 11.99 | 51.00 | 74.00 | -23.00 | peak | | | |
| 3 | | 5608.333 | 52.52 | -1.76 | 50.76 | 74.00 | -23.24 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-MIDDLE CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2440.000 | 95.18 | 10.36 | 105.54 | 74.00 | 31.54 | peak | | | |
| 2 | | 3441.667 | 39.01 | 12.05 | 51.06 | 74.00 | -22.94 | peak | | | |
| 3 | | 5116.667 | 45.60 | 5.86 | 51.46 | 74.00 | -22.54 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics) - MIDDLE CHANNEL –VERTICAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2440.000 | 94.35 | 10.36 | 104.71 | 74.00 | 30.71 | peak | | | |
| 2 | | 3450.000 | 38.11 | 12.06 | 50.17 | 74.00 | -23.83 | peak | | | |
| 3 | | 4941.667 | 42.57 | 8.05 | 50.62 | 74.00 | -23.38 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-HIGH CHANNEL-HORIZONTAL




| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna | Table | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|---------|--------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | Height | Degree | |
| | | | | | | | | | cm | degree | |
| 1 | * | 2480.000 | 93.88 | 10.41 | 104.29 | 74.00 | 30.29 | peak | | | |
| 2 | | 3566.667 | 38.34 | 12.52 | 50.86 | 74.00 | -23.14 | peak | | | |
| 3 | | 4916.667 | 42.18 | 7.98 | 50.16 | 74.00 | -23.84 | peak | | | |

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz (1-10th Harmonics)-HIGH CHANNEL –VERTICAL



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | * | 2480.000 | 94.00 | 10.41 | 104.41 | 74.00 | 30.41 | peak | | | |
| 2 | | 3641.667 | 37.64 | 12.98 | 50.62 | 74.00 | -23.38 | peak | | | |
| 3 | | 4866.667 | 43.91 | 7.85 | 51.76 | 74.00 | -22.24 | peak | | | |

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system


5. ANTENNA REQUIREMENT

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.




6. PHOTOGRAPH OF TEST

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP







7. PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




VIEW OF EUT (PORT)




OPEN VIEW OF EUT




VIEW OF BATTERY




INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



VIEW OF ADAPTER (AE)



The adapter was supplied by HUAK

--END OF REPORT--