

MPE Calculation

Model Name : **SP88**
 FCC ID : **S7A-SP88**

Device Category : **Portable device**
 Separation distance : **40.5 mm**

KDB 447498 - 3.4.1 a)

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
 $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Modulation	Frequency (MHz)	Min. Test separation distance	Measured Maximum Average power	Tune-up tolerance	Max. Power with tune-up tolerance		Standalone SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance ≤ 50 mm	Limit	Result	
		(mm)	(dBm)	(dB)	(dBm)	(mW)				
GFSK	2402	40.50	7.78	± 1.00	8.78	7.55	0.2890	3.00	PASS	
	2441		7.63		8.63	7.29				0.2814
	2480		7.25		8.25	6.68				0.2599
$\pi/4$ DQPSK	2402	40.50	6.43	± 1.00	7.43	5.53	0.2118	3.00	PASS	
	2441		6.36		7.36	5.45				0.2101
	2480		6.03		7.03	5.05				0.1962
8DPSK	2402	40.50	6.66	± 1.00	7.66	5.83	0.2233	3.00	PASS	
	2441		6.59		7.59	5.74				0.2215
	2480		6.37		7.37	5.46				0.2122
BT LE	2402	40.50	3.79	± 1.00	4.79	3.01	0.1153	3.00	PASS	
	2442		4.03		5.03	3.18				0.1229
	2480		4.01		5.01	3.17				0.1232
MESH	2410	40.50	9.92	± 1.00	10.92	12.36	0.4738	3.00	PASS	
	2445		9.60		10.60	11.48				0.4433
	2475		9.09		10.09	10.21				0.3966

KDB 447498 - 3.4.2 b)

When an antenna qualifies for the standalone SAR test exclusion of 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value must be estimated according to the following to determine the simultaneous transmission SAR test exclusion criteria:36

1) $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$, for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

Modulation	Frequency (MHz)	Min. Test separation distance	Max. Power with tune-up tolerance		Simultaneous transmission SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance ≤ 50 mm ($x=7.5$)	Limit	Result
		(mm)	(dBm)	(mW)			
Bluetooth	2402	40.50	7.78	6.00	0.0938	0.40	PASS
BT LE	2442		4.03	2.53			
MESH	2410		9.92	9.82			