

# FCC ID: S7A-SP95

## Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

**2.4G WIFI:**

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,  
 Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: PCB Antenna

WIFI antenna gain: 1.5dBi;

R=20cm

mW=10<sup>(dBm/10)</sup>

antenna gain Numeric=10<sup>(dBi/10)</sup>= 10<sup>(1.5/10)</sup>=1.41

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna	Evaluation result at 20cm	Power density Limits (mW/cm2)
				tune-up power		Gain		
				(dBm)	(mW)	Numeric		
2412	802.11b	12.29	13±1	14	25.11886	1.41	0.00705	1
2437		13.66	13±1	14	25.11886	1.41	0.00705	1
2462		16.68	16±1	17	50.11872	1.41	0.01406	1
2412	802.11g	12.87	13±1	13	19.95262	1.41	0.00560	1
2437		13.85	13±1	13	19.95262	1.41	0.00560	1
2462		17.15	17±1	18	63.09573	1.41	0.01770	1
2412	802.11n H20	12.31	13±1	13	19.95262	1.41	0.00560	1
2437		13.34	13±1	13	19.95262	1.41	0.00560	1
2462		16.66	16±1	17	50.11872	1.41	0.01406	1

**Conclusion:**

For the max result : 0.01770 ≤ 1.0 for Max Power Density, No RF exposure evaluation is required.



**Signature:**

**Date:** 2021-03-12

**NAME AND TITLE** (Please print or type): alex li/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.