

Certificate of Test

NCT CO., LTD.

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, 18511, Republic of Korea
(Tel: +82-31-323-6070 / Fax: +82-31-323-6071)

Report No.:
NW2203-F002

Page (1) / (76)



1. Client

- Name : SENA TECHNOLOGIES.Inc
- Address : 19, Heolleung-ro 569-gil, Gangnam-gu, Seoul, Korea
- Date of Receipt : 2022-01-14

2. Use of Report : FCC & IC Approval

3. Test Sample

- Description / Model : 50S / SP113
- FCC ID : S7A-SP113 / IC : 8154A-SP113

4. Place of Test : ■ Fixed test □ Field test

(Address:211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, 18511, Republic of Korea)

5. Date of Test : 2022-01-24 ~ 2022-03-16

6. Test method used : FCC Part 15 Subpart C 15.247

RSS-247 Issue 2(2017-02), RSS-GEN Issue 5(2019-03)

7. Testing Environment :

- Temperature: (25 ± 5) °C, Humidity: Less than 75 % R.H.

* Unless specified otherwise in the individual methods, the tests were conducted on ambient conditions.

8. Test Results : Refer to the test results

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This Test Report cannot be reproduced, except in full
This test report is not related to KOLAS recognition and RRA designation.

| | | | | |
|-------------|----------------------------|---|--|---|
| Affirmation | Tested by Kwon E S Ther |  | Technical Manager Jong-Myoung, Shin |  |
|-------------|----------------------------|---|--|---|

Mar 30, 2022

NCT CO., LTD.



Contact us at report@nct.re.kr to confirm the authenticity of this report

Table of contents

| | |
|---|----------|
| 1. General Information ----- | 3 |
| 2. Information's about Test Item ----- | 3 |
| 3. Test Report ----- | 5 |
| 3.1 Test Summary ----- | 5 |
| 3.2 Test Report Version ----- | 6 |
| 3.3 Transmitter Requirements | |
| 3.3.1 Antenna Requirement ----- | 7 |
| 3.3.2 20 dB Bandwidth & Occupied Bandwidth (99%) ----- | 8 |
| 3.3.3 Number of Hopping Frequencies ----- | 15 |
| 3.3.4 Time of Occupancy (Dwell Time) ----- | 18 |
| 3.3.5 Carrier Frequencies Separation ----- | 20 |
| 3.3.6 Peak Output Power ----- | 24 |
| 3.3.7 TX Radiated Spurious Emission and Conducted Spurious Emission ----- | 31 |
| 3.3.8 Conducted Emission ----- | 68 |

APPENDIX

| | |
|--|-----------|
| APPENDIX I TEST SETUP ----- | 71 |
| APPENDIX II TEST EQUIPMENT USED FOR TESTS ----- | 73 |
| APPENDIX III UNCERTAIN ----- | 75 |



1. General Information's

1.1 Test Performed

Laboratory : NCT Co., Ltd.
Address : 211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, 18511, Korea
Telephone : +82-31-323-6070
Facsimile : +82-31-323-6071
FCC Designation No. : KR0166
FCC Registration No. : 409631
IC Site Registration No. : 25897

2. Information's about Test Item

2.1 Applicant Information

Company name : SENA TECHNOLOGIES.Inc
Address : 19, Heolleung-ro 569-gil, Gangnam-gu, Seoul, Korea
Telephone / Facsimile : +82-2-573-7772 / -

2.2 Equipment Under Test (EUT) description

Test item particulars : 50S
Model and/or type reference : SP113
Additional model name : -
Serial number : Prototype
Antenna type and gain : Chip Antenna(M/N:SENA_003) with Max gain: 0.3 dBi
Date (s) of performance of tests: : 2022-01-24 ~ 2022-03-16
Date of receipt of test item : 2022-01-14
EUT condition : Pre-production, not damaged
Number of channel : 79
EUT Power Source : DC 3.7 V
Type of Modulation : BDR Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)
Firmware version : 1.0
Hardware version : 1.0
Test software name(version) : CSR BlueTest V3.3.5

Test Repot No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Page 3 of 76

2.3 Tested Frequency

| Test Mode | Test frequency (MHz) | | |
|------------|----------------------|------------------|----------------|
| | Low frequency | Middle frequency | High frequency |
| GFSK | 2 402 | 2 441 | 2 480 |
| Pi/4 DQPSK | 2 402 | 2 441 | 2 480 |
| 8DPSK | 2 402 | 2 441 | 2 480 |

2.4 Used Test Software Setting Value

| Test Mode | Setting Item |
|------------|--------------|
| | Power |
| GFSK | 16 |
| Pi/4 DQPSK | 16 |
| 8DPSK | 16 |

2.5 Worst-Case

| | |
|-----|--------------|
| BDR | GFSK(DH5) |
| EDR | 8DPSK(3-DH5) |

Note: The power measurement has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.



3. Test Report

3.1 Test Summary

| Applied | FCC Rule | IC Rule | Test Items | Test Condition | Result |
|-------------------------------------|--------------------|-------------------------|--------------------------------|----------------------|--------|
| <input checked="" type="checkbox"/> | 15.203 | - | Antenna Requirement | Conducted | C |
| <input checked="" type="checkbox"/> | 15.247(a) | - | 20 dB Bandwidth | | C |
| <input checked="" type="checkbox"/> | - | RSS GEN (6.7) | Occupied Bandwidth (99%) | | C |
| <input checked="" type="checkbox"/> | 15.247(a) | RSS-247 (5.1) | Number of Hopping Frequencies | | C |
| <input checked="" type="checkbox"/> | 15.247(a) | RSS-247 (5.1) | Time of Occupancy (Dwell Time) | | C |
| <input checked="" type="checkbox"/> | 15.247(a) | RSS-247 (5.1) | Carrier Frequencies Separation | | C |
| <input checked="" type="checkbox"/> | 15.247(b) | RSS-247 (5.4) | Peak Output Power | | C |
| <input checked="" type="checkbox"/> | 15.247(d) | RSS-247 (5.5) | Conducted Spurious Emission | | C |
| <input checked="" type="checkbox"/> | 15.247(d) | RSS-247 (5.5) | Radiated Spurious Emission | Radiated | C |
| <input checked="" type="checkbox"/> | 15.205 & 15.209 | RSS-GEN (8.9 & 8.10) | | | |
| <input checked="" type="checkbox"/> | 15.207 | RSS-GEN (8.8) | Conducted Emissions | AC Line Conducted | C |

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

The sample was tested according to the following specification: ANSI C63.10:2013.

Compliance was determined by specification limits of the applicable standard according to customer requirements.

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Page 5 of 76

3.2 Test Report Version

| Test Report No. | Date | Description |
|-----------------|------------|---------------|
| NW2203-F002 | 2022-03-30 | Initial issue |
| | | |
| | | |
| | | |

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071



3.3 Transmitter Requirements

3.3.1 Antenna Requirement

According to §15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to §15.247(b)(4) e conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.1.1 Result

Complies

(The transmitter has a Chip Antenna. The directional peak gain of the antenna is 0.3 dBi.)

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Page 7 of 76

3.3.2 20 dB Bandwidth & Occupied Bandwidth (99%)

3.3.2.1 Test Setup

Refer to the APPENDIX I.

3.3.2.2 Limit

Limit : Not Applicable

3.3.2.3 Test Procedure

1. The 20 dB bandwidth & Occupied bandwidth were measured with a spectrum analyzer connected to RF antenna Connector (conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using below setting:
 RBW = 1% to 5% of the 20 dB Bandwidth & Occupied Bandwidth
 $VBW \geq 3 \times RBW$
 Span = between two times and five times the 20 dB Bandwidth & Occupied Bandwidth
 Sweep = Auto
 Detector function = Peak
 Trace = Max Hold


3.3.2.4 Test Result

| Test Mode | Test Frequency | 20 dB Bandwidth (MHz) | Occupied Bandwidth (MHz) |
|-----------|----------------|-----------------------|--------------------------|
| GFSK | Low | 0.892 | 0.860 |
| | Middle | 0.884 | 0.852 |
| | High | 0.888 | 0.860 |
| 8DPSK | Low | 1.250 | 1.154 |
| | Middle | 1.246 | 1.158 |
| | High | 1.246 | 1.158 |

3.3.2.5 Test Plot


GFSK _ Low frequency

20 dB Bandwidth



GFSK _ Middle frequency


20 dB Bandwidth



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
 www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

GFSK _ High frequency



8DPSK _ Low frequency



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

8DPSK _ Middle frequency

20 dB Bandwidth



8DPSK _ High frequency

20 dB Bandwidth




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


GFSK _ Low frequency

Occupied Bandwidth



GFSK _ Middle frequency

Occupied Bandwidth



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


GFSK _ High frequency

Occupied Bandwidth



8DPSK _ Low frequency

Occupied Bandwidth




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


8DPSK _ Middle frequency

Occupied Bandwidth



8DPSK _ High frequency

Occupied Bandwidth



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.3 Number of Hopping Frequencies

3.3.3.1 Test Setup

Refer to the APPENDIX I.

3.3.3.2 Limit

Limit : ≥ 15 hops

3.3.3.3 Test Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, two frequency ranges for FH mode within the 2400 ~ 2483.5 MHz were examined.

The spectrum analyzer is set to:

Span = 50 MHz

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW \geq RBW

Sweep = Auto


Detector = Peak

Trace = Max hold

3.3.3.4 Test Result

| Test Mode | Number of Hopping Channels |
|-----------|----------------------------|
| GFSK | 79 |
| 8DPSK | 79 |

3.3.3.5 Test Plot




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
 www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


8DPSK _ Hopping Mode

Number of Hopping Frequencies



8DPSK _ Hopping Mode

Number of Hopping Frequencies



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.4 Time of Occupancy (Dwell Time)

3.3.4.1 Test Setup

Refer to the APPENDIX I.

3.3.4.2 Limit

The maximum permissible time of occupancy is 400 ms within a period of 400 ms multiplied by the number of hopping channels employed.

3.3.4.3 Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

| | |
|---|-----------------|
| Center frequency = 2441 MHz | Span = Zero |
| RBW = 1 MHz (RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel) | |
| VBW \geq RBW | Detector = Peak |
| Trace = Max hold | |

3.3.4.4 Test Result


| Test Mode | Number of Hopping Channels | Burst On Time (ms) | Result (sec) | Limit (sec) |
|-----------------|----------------------------|--------------------|--------------|-------------|
| GFSK (non-AFH) | 79 | 2.900 | 0.31 | 0.40 |
| GFSK (AFH) | 79 | 2.900 | 0.15 | 0.40 |
| 8DPSK (non-AFH) | 79 | 2.900 | 0.31 | 0.40 |
| 8DPSK (AFH) | 79 | 2.900 | 0.15 | 0.40 |

Note: Dwell Time = 0.4 x Hopping channel x Burst On Time x ((Hopping rate / Time slots) / Hopping channel)


- Time slots for DH5 = 6 slots (TX = 5 slot / RX = 1 slot)
- Hopping Rate = 1600 for FH mode & 800 for AFH mode

3.3.4.5 Test Plot

GFSK



8DPSK



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.5 Carrier Frequencies Separation

3.3.5.1 Test Setup

Refer to the APPENDIX I.

3.3.5.2 Limit

Limit : ≥ 25 kHz or \geq Two-Thirds of the 20 dB Bandwidth whichever is greater.

3.3.5.3 Test Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal,

while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = wide enough to capture the peaks of two adjacent channels

RBW = Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW \geq RBW

Sweep = Auto

Detector = Peak

Trace = Max hold

3.3.5.4 Test Result

| Test Mode | Test Frequency | Carrier Frequencies Separation (kHz) | Min. Limit (kHz) |
|-----------|----------------|--------------------------------------|------------------|
| GFSK | Low | 1.008 | 0.595 |
| | Middle | 1.008 | 0.589 |
| | High | 1.002 | 0.592 |
| 8DPSK | Low | 1.005 | 0.833 |
| | Middle | 1.005 | 0.831 |
| | High | 1.002 | 0.831 |


Note: Limit(kHz) = Test Result of 20 dB BW * 2/3

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.5.5 Test Plot




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


GFSK _ High frequency

Carrier Frequency Separation



8DPSK _ Low frequency

Carrier Frequency Separation




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


8DPSK _ Middle frequency

Carrier Frequency Separation



8DPSK _ High frequency

Carrier Frequency Separation



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.6 Peak Output Power

3.3.6.1 Test Setup

Refer to the APPENDIX I.

3.3.6.2 Limit

■ FCC Requirements

The maximum peak output power of the intentional radiator shall not exceed the following:

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. §15.247(b)(1), For frequency hopping systems operating in the 2400 – 2483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725 – 5805 MHz band: 1 Watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

■ IC Requirements

1. RSS-247(5.4) (b), For FHSS operating in the band 2400 - 2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels, the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p shall not exceed 4 W, except as provided in section 5.4(e)

3.3.6.3 Test Procedure

1. The RF output power was measured with a spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, a spectrum analyzer was used to record the shape of the transmit signal.
2. The peak output power of the fundamental frequency was measured with the spectrum analyzer using;
Span = approximately 5 times of the 20 dB bandwidth, centered on a hopping channel
RBW \geq 20 dB Bandwidth
VBW \geq RBW
Sweep = Auto
Detector function = Peak
Trace = Max Hold

3.3.6.4 Test Result


| Test Mode | Test Frequency | Peak Output Power | |
|------------|----------------|-------------------|-------|
| | | dBm | mW |
| GFSK | Low | 14.48 | 28.05 |
| | Middle | 17.05 | 50.70 |
| | High | 16.58 | 45.50 |
| Pi/4 DQPSK | Low | 9.73 | 9.40 |
| | Middle | 12.61 | 18.24 |
| | High | 12.22 | 16.67 |
| 8DPSK | Low | 10.59 | 11.46 |
| | Middle | 13.47 | 22.23 |
| | High | 13.07 | 20.28 |

 Test Report No.: NW2203-F002


 211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
 www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.6.5 Test Plot

GFSK _ Low frequency



GFSK _ Middle frequency




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


GFSK _ High frequency

Peak Output Power



Pi/4 DQPSK _ Low frequency

Peak Output Power




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


Pi/4 DQPSK _ Middle frequency

Peak Output Power



Pi/4 DQPSK _ High frequency

Peak Output Power




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


8DPSK _ Low frequency

Peak Output Power



8DPSK _ Middle frequency

Peak Output Power




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

8DPSK _ High frequency

Peak Output Power



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.7 TX Radiated Spurious Emission and Conducted Spurious Emission

3.3.7.1 Test Setup

Refer to the APPENDIX I.

3.3.7.2 Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

| Frequency (MHz) | Limit (uV/m) | Measurement Distance (meter) |
|-----------------|---------------|------------------------------|
| 0.009 ~ 0.490 | 2400/F (kHz) | 300 |
| 0.490 ~ 1705 | 24000/F (kHz) | 30 |
| 1705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 ** | 3 |
| 88 ~ 216 | 150 ** | 3 |
| 216 ~ 960 | 200 ** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 - 72 MHz, 76 - 88 MHz, 174 - 216 MHz or 470 – 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|---------------------|-----------------------|-----------------|---------------|
| 0.009 ~ 0.110 | 16.42 ~ 16.423 | 399.90 ~ 410 | 4.5 ~ 5.15 |
| 0.495 ~ 0.505 | 16.69475 ~ 16.69525 | 608 ~ 614 | 5.35 ~ 5.46 |
| 2.1735 ~ 2.1905 | 16.80425 ~ 16.80475 | 960 ~ 1240 | 7.25 ~ 7.75 |
| 4.125 ~ 4.128 | 25.5 ~ 25.67 | 1300 ~ 1427 | 8.025 ~ 8.5 |
| 4.17725 ~ 4.17775 | 37.5 ~ 38. | 1435 ~ 1626.5 | 9.0 ~ 9.2 |
| 4.20725 ~ 4.20775 | 25.73 ~ 74.6 | 1645.5 ~ 1646.5 | 9.3 ~ 9.5 |
| 4.17725 ~ 4.17775 | 74.8 ~ 75.2 | 1660 ~ 1710 | 10.6 ~ 12.7 |
| 6.215 ~ 6.218 | 108 ~ 121.94 | 1718.8 ~ 1722.2 | 13.25 ~ 13.4 |
| 6.26775 ~ 6.26825 | 149.9 ~ 150.05 | 2200 ~ 2300 | 14.47 ~ 14.5 |
| 6.31175 ~ 6.31225 | 156.52475 ~ 156.52525 | 2310 ~ 2390 | 15.35 ~ 16.2 |
| 8.291 ~ 8.294 | 156.7 ~ 156.9 | 2483.5 ~ 2500 | 17.7 ~ 21.4 |
| 8.362 ~ 8.366 | 162.0125 ~ 167.17 | 2690 ~ 2900 | 22.01 ~ 23.12 |
| 8.37625 ~ 8.38675 | 3345.8 ~ 3358 | 3260 ~ 3267 | 23.6 ~ 24.0 |
| 8.41425 ~ 8.41475 | 3600 ~ 4400 | 3332 ~ 3339 | 31.2 ~ 31.8 |
| 12.51975 ~ 12.52025 | 3345.8 ~ 3358 | 240 ~ 285 | 36.43 ~ 36.5 |
| 12.57675 ~ 12.57725 | 3600 ~ 4400 | 322 ~ 335.4 | Above 38.6 |
| 13.36 ~ 13.41 | | | |

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

3.3.7.3 Test Procedure for Radiated Spurious Emission

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 or 3 meter away from the interference-receiving antenna.
3. For measurements above 1 GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.
4. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
(The EUT was pre-tested with three axes (X, Y, Z) and the final test was performed at the worst case.)
6. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Measurement Instrument Setting

1. Frequency Range: Below 1 GHz
RBW = 100 or 120 kHz, VBW = 3 x RBW, Detector = Peak or Quasi Peak

2. Frequency Range: Above 1 GHz
Peak Measurement
RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto,
Trace mode = Max Hold until the trace stabilizes

Average Measurement
RBW = 1MHz, VBW \geq 1/T, Detector = Peak, Sweep Time = Auto,
Trace Mode = Max Hold until the trace stabilizes



3.3.7.4 Test Procedure for Conducted Spurious Emission

1. The transmitter output was connected to the spectrum analyzer.
2. The reference level of the fundamental frequency was measured with the spectrum analyzer using RBW = 100 kHz, VBW = 300 kHz.
3. The conducted spurious emission was tested each ranges were set as below.

Frequency range: 30 MHz ~ 26.5 GHz
RBW = 100 kHz, VBW = 300 kHz, Sweep Time = Auto, Detector = Peak,
Trace = Max Hold

LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Page 34 of 76

3.3.7.5 Test Result

9 kHz ~ 25 GHz Data (Modulation: GFSK)

- Low frequency

| Frequency | Reading | | Pol. | Factor (dB) | DCCF (dB) | Limits | | Result | | Margin | | | | |
|-----------|----------|-----------|------|----------------|--------------|-----------|-----------|-----------|-----------|-----------|-----------|--|--|--|
| | (dBuV/m) | | | | | (dBuV/m) | | (dBuV/m) | | (dB) | | | | |
| | (MHz) | AV / Peak | | | | AV / Peak | | | |
| 2 558.08 | N/A | 35.05 | V | 31.91 | -24.73 | 54.0 | 74.0 | 42.2 | 67.0 | 11.8 | 7.0 | | | |
| 4 803.78 | N/A | 42.37 | V | 6.56 | -24.73 | 54.0 | 74.0 | 24.2 | 48.9 | 29.8 | 25.1 | | | |
| 7 206.40 | N/A | 45.73 | V | 7.49 | -24.73 | 54.0 | 74.0 | 28.5 | 53.2 | 25.5 | 20.8 | | | |
| 9 608.68 | N/A | 46.12 | V | 6.94 | -24.73 | 54.0 | 74.0 | 28.3 | 53.1 | 25.7 | 20.9 | | | |
| 12 010.78 | N/A | 44.51 | V | 16.7 | -24.73 | 54.0 | 74.0 | 36.5 | 61.2 | 17.5 | 12.8 | | | |
| 14 412.72 | N/A | 45.12 | V | 16.38 | -24.73 | 54.0 | 74.0 | 36.8 | 61.5 | 17.2 | 12.5 | | | |

- Middle frequency

| Frequency | Reading | | Pol. | Factor (dB) | DCCF (dB) | Limits | | Result | | Margin | | | | |
|-----------|----------|-----------|------|----------------|--------------|-----------|-----------|-----------|-----------|-----------|-----------|--|--|--|
| | (dBuV/m) | | | | | (dBuV/m) | | (dBuV/m) | | (dB) | | | | |
| | (MHz) | AV / Peak | | | | AV / Peak | | | |
| 2 545.02 | N/A | 30.10 | V | -4.40 | -24.73 | 54.0 | 74.0 | 1.0 | 25.7 | 53.0 | 48.3 | | | |
| 4 881.90 | N/A | 52.03 | V | 2.48 | -24.73 | 54.0 | 74.0 | 29.8 | 54.5 | 24.2 | 19.5 | | | |
| 7 322.60 | N/A | 47.19 | V | 6.92 | -24.73 | 54.0 | 74.0 | 29.4 | 54.1 | 24.6 | 19.9 | | | |
| 9 763.10 | N/A | 46.70 | V | 7.81 | -24.73 | 54.0 | 74.0 | 29.8 | 54.5 | 24.2 | 19.5 | | | |
| 12 204.38 | N/A | 44.48 | V | 7.43 | -24.73 | 54.0 | 74.0 | 27.2 | 51.9 | 26.8 | 22.1 | | | |
| 14 646.76 | N/A | 47.28 | V | 16.6 | -24.73 | 54.0 | 74.0 | 39.1 | 63.9 | 14.9 | 10.1 | | | |

- High frequency

| Frequency (MHz) | Reading | | Pol. | Factor (dB) | DCCF (dB) | Limits | | Result | | Margin | | | | |
|--------------------|-----------|-----------|------|----------------|--------------|-----------|-----------|-----------|-----------|-----------|-----------|--|--|--|
| | (dBuV/m) | | | | | (dBuV/m) | | (dBuV/m) | | (dB) | | | | |
| | AV / Peak | AV / Peak | | | | AV / Peak | | | |
| 2 324.00 | N/A | 31.20 | V | -4.26 | -24.73 | 54.0 | 74.0 | 2.2 | 26.9 | 51.8 | 47.1 | | | |
| 2 483.50 | N/A | 42.00 | V | 2.65 | -24.73 | 54.0 | 74.0 | 19.9 | 44.7 | 34.1 | 29.4 | | | |
| 4 959.66 | N/A | 53.59 | V | 7.11 | -24.73 | 54.0 | 74.0 | 36.0 | 60.7 | 18.0 | 13.3 | | | |
| 7 439.84 | N/A | 42.80 | V | 7.26 | -24.73 | 54.0 | 74.0 | 25.3 | 50.1 | 28.7 | 23.9 | | | |
| 9 919.36 | N/A | 46.30 | V | 7.10 | -24.73 | 54.0 | 74.0 | 28.7 | 53.4 | 25.3 | 20.6 | | | |
| 12 400.70 | N/A | 46.65 | V | 16.38 | -24.73 | 54.0 | 74.0 | 38.3 | 63.0 | 15.7 | 11.0 | | | |
| 14 880.84 | N/A | 44.59 | V | 16.26 | -24.73 | 54.0 | 74.0 | 36.1 | 60.9 | 17.9 | 13.2 | | | |

Note 1: The radiated emissions were investigated 9 kHz to 25 GHz. And no other spurious and harmonic emissions were found above listed frequencies.

Note 2: DCCF(Duty Cycle Correction Factor)

- Time to cycle through all channels = $\Delta t = T \text{ [ms]} \times 20$ minimum hopping channels, where $T = \text{pulse width} = 2.884 \text{ ms}$
- $100 \text{ ms} / \Delta t \text{ [ms]} = H \rightarrow \text{Round up to next highest integer, to account for worst case, } H' = 100 / (2.884 \times 20) = 1.73 \approx 2$
- The Worst Case Dwell Time = $T \text{ [ms]} \times H' = 2.884 \text{ ms} \times 2 = 5.77 \text{ ms}$
- DCCF = $20 \times \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \times \log(5.77 / 100) = -24.78 \text{ dB}$

Note 3: Sample Calculation.

Margin = Limit – Result / Peak Result = Peak Reading + TF / Average Result = Peak Reading + TF + DCCF
 TF = Ant factor + Cable Loss + Filter Loss – Amp Gain

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

9 kHz ~ 25 GHz Data (Modulation: 8DPSK)

● Low frequency

| Frequency (MHz) | Reading | | Pol. | Factor (dB) | DCCF (dB) | Limits | | Result | | Margin | | | | |
|--------------------|----------|-------|------|----------------|--------------|----------|------|----------|------|--------|------|--|--|--|
| | (dBuV/m) | | | | | (dBuV/m) | | (dBuV/m) | | (dB) | | | | |
| | AV | Peak | | | | AV | Peak | AV | Peak | AV | Peak | | | |
| 2 557.76 | N/A | 31.31 | V | 2.44 | -24.73 | 54.0 | 74.0 | 9.0 | 33.8 | 45.0 | 40.3 | | | |
| 4 804.00 | N/A | 48.12 | H | 6.55 | -24.73 | 54.0 | 74.0 | 29.9 | 54.7 | 24.1 | 19.3 | | | |
| 7 206.00 | N/A | 39.78 | V | 7.72 | -24.73 | 54.0 | 74.0 | 22.8 | 47.5 | 31.2 | 26.5 | | | |
| 9 607.00 | N/A | 39.47 | V | 16.70 | -24.73 | 54.0 | 74.0 | 31.4 | 56.2 | 22.6 | 17.8 | | | |
| 12 010.10 | N/A | 41.24 | V | 16.38 | -24.73 | 54.0 | 74.0 | 32.9 | 57.6 | 21.1 | 16.4 | | | |

● Middle frequency

| Frequency (MHz) | Reading | | Pol. | Factor (dB) | DCCF (dB) | Limits | | Result | | Margin | | | | |
|--------------------|----------|-------|------|----------------|--------------|----------|------|----------|------|--------|------|--|--|--|
| | (dBuV/m) | | | | | (dBuV/m) | | (dBuV/m) | | (dB) | | | | |
| | AV | Peak | | | | AV | Peak | AV | Peak | AV | Peak | | | |
| 2 596.98 | N/A | 29.44 | V | -4.40 | -24.73 | 54.0 | 74.0 | 0.3 | 25.0 | 53.7 | 49.0 | | | |
| 4 881.60 | N/A | 55.56 | H | 2.48 | -24.73 | 54.0 | 74.0 | 33.3 | 58.0 | 20.7 | 16.0 | | | |
| 7 322.90 | N/A | 41.21 | V | 6.92 | -24.73 | 54.0 | 74.0 | 23.4 | 48.1 | 30.6 | 25.9 | | | |
| 9 763.74 | N/A | 42.32 | V | 7.81 | -24.73 | 54.0 | 74.0 | 25.4 | 50.1 | 28.6 | 23.9 | | | |
| 12 204.94 | N/A | 40.89 | V | 16.7 | -24.73 | 54.0 | 74.0 | 32.9 | 57.6 | 21.1 | 16.4 | | | |

 Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

● High frequency

| Frequency (MHz) | Reading | | Pol. | Factor (dB) | DCCF (dB) | Limits | | Result | | Margin | | | | |
|--------------------|-----------|-----------|------|----------------|--------------|-----------|-----------|-----------|-----------|-----------|-----------|--|--|--|
| | (dBuV/m) | | | | | (dBuV/m) | | (dB) | | (dB) | | | | |
| | AV / Peak | AV / Peak | | | | AV / Peak | | | |
| 2 323.80 | N/A | 29.64 | V | -4.26 | -24.73 | 54.0 | 74.0 | 0.6 | 25.4 | 53.4 | 48.6 | | | |
| 2 483.50 | N/A | 41.25 | V | 2.65 | -24.73 | 54.0 | 74.0 | 19.2 | 43.9 | 34.8 | 30.1 | | | |
| 4 959.98 | N/A | 50.29 | H | 7.11 | -24.73 | 54.0 | 74.0 | 32.7 | 57.4 | 21.3 | 16.6 | | | |
| 7 440.06 | N/A | 38.55 | V | 7.26 | -24.73 | 54.0 | 74.0 | 21.1 | 45.8 | 32.9 | 28.2 | | | |
| 9 919.26 | N/A | 43.75 | V | 16.38 | -24.73 | 54.0 | 74.0 | 35.4 | 60.1 | 18.6 | 13.9 | | | |
| 12 400.24 | N/A | 36.04 | V | 16.26 | -24.73 | 54.0 | 74.0 | 27.6 | 52.3 | 26.4 | 21.7 | | | |

Note 1: The radiated emissions were investigated 9 kHz to 25 GHz.

Note 2: DCCF(Duty Cycle Correction Factor)

- Time to cycle through all channels = $\Delta t = T \text{ [ms]} \times 20$ minimum hopping channels, where $T = \text{pulse width} = 2.900 \text{ ms}$
- $100 \text{ ms} / \Delta t \text{ [ms]} = H \rightarrow$ Round up to next highest integer, to account for worst case, $H' = 100 / (2.900 \times 20) = 1.72 \approx 2$
- The Worst Case Dwell Time = $T \text{ [ms]} \times H' = 2.900 \text{ ms} \times 2 = 5.80 \text{ ms}$
- $\text{DCCF} = 20 \times \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB} = 20 \times \log(5.80 / 100) = -24.73 \text{ dB}$

Note 3: Sample Calculation.

Margin = Limit – Result / Peak Result = Peak Reading + TF / Average Result = Peak Reading + TF + DCCF
 TF = Ant factor + Cable Loss + Filter Loss – Amp Gain

Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


3.3.7.6 Test Plot for Radiated Spurious Emission

- GFSK _ Low frequency

Spurious – Peak



Spurious – Peak




Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak




Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak





Spurious – Peak



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


- GFSK _ Middle frequency




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak




Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak



Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511


www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

- GFSK _ High frequency

Spurious – Peak




Restricted Band – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak



Spurious – Peak




Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak




Spurious – Peak



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
 www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071



Restricted Band – Peak



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


- 8DPSK _ Low frequency




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak



Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071



Spurious – Peak



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

- 8DPSK _ Middle frequency




Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak



Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak




Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

- 8DPSK _ High frequency

Spurious – Peak




Restriced Band – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak




Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Spurious – Peak



Spurious – Peak




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


3.3.7.7 Test Plot for Conducted Spurious Emission

- GFSK _ Low frequency

Reference



Bandedge _ Single




Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Bandedge _ Hopping





Spurious



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071



- GFSK _ Middle frequency



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


- GFSK _ High frequency




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Bandedge _ Hopping





Spurious



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071


- 8DPSK _ Low frequency




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Bandedge _ Hopping





Spurious



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

- 8DPSK _ Middle frequency




Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

- 8DPSK _ High frequency

Reference




Bandedge _ Single




Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Bandedge _ Hopping



Spurious



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

3.3.8 Conducted Emission

3.3.8.1 Test Setup

See test photographs for the actual connections between EUT and support equipment.

3.3.8.2 Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall be on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

| Frequency Range (MHz) | Conducted Limit (dBuV) | |
|-----------------------|------------------------|------------|
| | Quasi-Peak | Average |
| 0.15 ~ 0.5 | 66 to 56 * | 56 to 46 * |
| 0.5 ~ 5 | 56 | 46 |
| 5 ~ 30 | 60 | 50 |

* Decreases with the logarithm of the frequency

3.3.8.3 Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.


3.3.8.4 Test Result

- AC Line Conducted Emission (Graph)

Test Report

Common Information

Test Model: SP113
 Test Standard: FCC Part 15 Subpart B
 Test Mode: BT
 Test Conditions: AC 120 V, 60 Hz / 24.5 °C, 45.8 % R. H.
 Operator Name: ESTher, Kwon
 Comment: LINE
 Order Number: -



Final Result

| Frequency (MHz) | QuasiPeak (dBuV) | CAverage (dBuV) | Limit (dBuV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.150000 | 22.67 | --- | 66.00 | 43.33 | 1000.0 | 9.000 | L1 | 10.3 |
| 0.172000 | 21.45 | --- | 64.86 | 43.41 | 1000.0 | 9.000 | L1 | 10.3 |
| 0.188000 | 20.70 | --- | 64.12 | 43.42 | 1000.0 | 9.000 | L1 | 10.2 |
| 0.192000 | 20.45 | --- | 63.95 | 43.50 | 1000.0 | 9.000 | L1 | 10.2 |
| 0.588000 | 23.23 | --- | 56.00 | 32.77 | 1000.0 | 9.000 | L1 | 10.2 |
| 2.206000 | 16.38 | --- | 56.00 | 39.62 | 1000.0 | 9.000 | L1 | 10.3 |
| 2.786000 | 15.93 | --- | 56.00 | 40.07 | 1000.0 | 9.000 | L1 | 10.4 |
| 16.680000 | 16.92 | --- | 60.00 | 43.08 | 1000.0 | 9.000 | L1 | 11.3 |
| 20.440000 | 29.29 | --- | 60.00 | 30.71 | 1000.0 | 9.000 | L1 | 11.5 |
| 21.120000 | 33.82 | --- | 60.00 | 26.18 | 1000.0 | 9.000 | L1 | 11.5 |
| 22.120000 | 32.55 | --- | 60.00 | 27.45 | 1000.0 | 9.000 | L1 | 11.5 |
| 27.120000 | 28.85 | --- | 60.00 | 31.15 | 1000.0 | 9.000 | L1 | 11.7 |

Test Report No.: NW2203-F002


211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

Test Report

Common Information

Test Model: SP113
 Test Standard: FCC Part 15 Subpart B
 Test Mode: BT
 Test Conditions: AC 120 V, 60 Hz / 24.5 °C, 45.8 % R. H.
 Operator Name: ESTher, Kwon
 Comment: NEUTRAL
 Order Number: -



Final Result

| Frequency (MHz) | QuasiPeak (dBuV) | CAverage (dBuV) | Limit (dBuV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.256000 | 18.23 | --- | 61.56 | 43.33 | 1000.0 | 9.000 | N | 10.2 |
| 0.264000 | 18.16 | --- | 61.31 | 43.14 | 1000.0 | 9.000 | N | 10.2 |
| 0.288000 | 17.21 | --- | 60.58 | 43.38 | 1000.0 | 9.000 | N | 10.2 |
| 0.584000 | 27.26 | --- | 56.00 | 28.74 | 1000.0 | 9.000 | N | 10.2 |
| 1.638000 | 19.60 | --- | 56.00 | 36.40 | 1000.0 | 9.000 | N | 10.3 |
| 2.200000 | 20.72 | --- | 56.00 | 35.28 | 1000.0 | 9.000 | N | 10.3 |
| 2.814000 | 20.12 | --- | 56.00 | 35.88 | 1000.0 | 9.000 | N | 10.4 |
| 3.440000 | 18.49 | --- | 56.00 | 37.51 | 1000.0 | 9.000 | N | 10.5 |
| 4.010000 | 16.14 | --- | 56.00 | 39.86 | 1000.0 | 9.000 | N | 10.6 |
| 21.120000 | 25.58 | --- | 60.00 | 34.42 | 1000.0 | 9.000 | N | 11.6 |
| 21.560000 | 25.88 | --- | 60.00 | 34.12 | 1000.0 | 9.000 | N | 11.6 |
| 27.200000 | 24.77 | --- | 60.00 | 35.23 | 1000.0 | 9.000 | N | 11.7 |

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071




APPENDIX I

TEST SETUP


Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

- Radiated Measurement



- Conducted Measurement



Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511

www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071



APPENDIX II

TEST EQUIPMENT USED FOR TESTS

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

| | Description | Manufacturer | Serial No. | Model No. | Cal. Date | Next Cal. Date |
|----|--------------------------------------|------------------|--------------|---------------|------------|----------------|
| 1 | SPECTRUM ANALYZER | R&S | 100250 | FSU26 | 2021-09-29 | 2022-09-29 |
| 2 | Power supply | GWInstek | EH120798 | PST-3202 | 2022-03-07 | 2023-03-07 |
| 3 | Humi./Baro/Temp. data recorder | Lutron | 38420 | MHB-382SD | 2021-11-17 | 2022-11-17 |
| 4 | LOOP-ANTENNA | Schwarzbeck | 00124 | FMZB1519 B | 2021-06-01 | 2023-06-01 |
| 5 | TRILOG Broadband Antenna | Schwarzbeck | 01027 | VULB 9168 | 2021-06-08 | 2023-06-08 |
| 6 | Double Ridged Broadband Horn Antenna | Schwarzbeck | 02087 | BBHA 9120D | 2021-06-02 | 2022-06-02 |
| 7 | Broadband Horn Antenna | Schwarzbeck | 00938 | BBHA 9170 | 2021-06-01 | 2022-06-01 |
| 8 | Low Noise Amplifier | LTC MICROWAVE | 143 | LLA01185025Q | 2021-09-03 | 2022-09-03 |
| 9 | ATTENUATOR | INMET | 279465 | 40AH2W | 2021-07-27 | 2022-07-27 |
| 10 | ATTENUATOR | Weinschel | none | WA41/12-30-12 | 2022-03-07 | 2023-03-07 |
| 11 | High Pass Filter | WT Microwave INC | WT210907-1-2 | WT-A3289-HS | 2021-09-24 | 2022-09-24 |
| 12 | LISN | Schwarzbeck | 00984 | NSLK 8127 | 2021-05-27 | 2022-05-27 |
| 13 | EMI Test Receiver | R&S | 102116 | ESRP3 | 2021-05-27 | 2022-05-27 |
| 14 | Signal Analyzer | Anritsu | 6261745943 | MS2850A | 2021-12-07 | 2022-12-07 |

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071



APPENDIX III

UNCERTAINTY

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071

| Measurement Item | Expanded Uncertainty $U = kU_c (k=2)$ |
|------------------------------|--|
| Conducted RF power | 0.40 dB |
| Conducted Spurious Emissions | 0.40 dB |
| Radiated Spurious Emissions | 5.16 dB |
| Conducted Emissions | 3.68 dB |

Test Report No.: NW2203-F002

211-71, Geumgok-ro, Hwaseong-si, Gyeonggi-do, Korea 18511
www.nct.re.kr TEL: +82-31-323-6070 FAX: +82-31-323-6071