

**** MPE Calculations ****

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

$EIRP = P + G$ $EIRP = 13.42dBm + 5.37dBi$ $EIRP = 18.79 dBm$	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)
---	--

Power density at the specific separation:

$S = PG / (4R^2 \pi)$ $S = (21.98 * 3.44) / (4 * 20^2 * \pi)$ $S = 0.0151 mW/cm^2$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--	---

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm² .

The power density does not exceed the 1 mW/cm² limit.

Therefore, the exposure condition is compliant with FCC rules.

Estimated safe separation:

$R = \sqrt{PG / 4 \pi}$ $R = \sqrt{(21.98 * 3.44 / 4 \pi)}$ $R = 2.45Cm$	Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--	--

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

$$G = \text{Log}^{-1} (0 / 10)$$

$$G = 3.44$$