## FCC ID: S7J-S30

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

## BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	6.86	4.85	7±1	8	6.31	<5	1.95576	3.00	YES
	2.44	7.71	5.90	7±1	8	6.31	<5	1.97117	3.00	YES
	2.480	7.47	5.58	7±1	8	6.31	<5	1.98727	3.00	YES
π/4- DQPSK	2.402	4.51	2.82	5±1	6	3.98	<5	1.23400	3.00	YES
	2.44	5.13	3.26	5±1	6	3.98	<5	1.24373	3.00	YES
	2.480	4.85	3.05	5±1	6	3.98	<5	1.25388	3.00	YES
8-DPSK	2.402	5.05	3.20	5±1	6	3.98	<5	1.23400	3.00	YES
	2.44	5.78	3.78	5±1	6	3.98	<5	1.24373	3.00	YES
	2.480	5.45	3.51	5±1	6	3.98	<5	1.25388	3.00	YES

Conclusion:

For the max result: 1.98727W/Kg ≤ 3.0 for 1g SAR, No SAR is required.

Jason chen

**Signature: Date:** 2019-03-30

NAME AND TITLE (Please print or type): Jason Chen /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.