

FCC CERTIFICATION
On Behalf of
Shenzhen Yifang Digital Technologies Co.,Ltd.

MP3 PLAYER
Model No.: EM191F, EM192F

FCC ID: S7JEM1912

Prepared for : Shenzhen Yifang Digital Technologies Co.,Ltd.
Address : 5/F.,Bldg.H-3, Huaqiaocheng East Industrial Park, No.1
Xiangshan East Rd., Nanshan District, Shenzhen City,
Guangdong, P.R.China
Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20051711
Date of Test : October 13, 2005
Date of Report : October 17, 2005

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	4
1.3. Measurement Uncertainty.....	4
2. MEASURING DEVICE AND TEST EQUIPMENT	5
3. RADIATED EMISSION FOR FCC PART 15 SECTION 15.239(C).....	6
3.1. Block Diagram of Test Setup.....	6
3.2. The Emission Limit for section 15.239(c)	6
3.3. Configuration of EUT on Measurement	7
3.4. Operating Condition of EUT	7
3.5. Test Procedure	7
3.6. The Field Strength of Radiation Emission Measurement Results	8
4. FUNDAMENTAL RADIATED EMISSION FOR FCC PART 15 SECTION 15.239(B)	12
4.1. Block Diagram of Test Setup.....	12
4.2. The Emission Limit For Section 15.239(b)	12
4.3. EUT Configuration on Measurement	13
4.4. Operating Condition of EUT	13
4.5. Test Procedure	13
4.6. The Emission Measurement Result	14
5. OCCUPIED BANDWIDTH FOR FCC PART 15 SECTION 15.239(A)	15
5.1. The Requirement For Section 15.239(a).....	15
5.2. EUT Configuration on Measurement	15
5.3. Operating Condition of EUT	15
5.4. Test Procedure	15
5.5. Test Result	16
APPENDIX I (TEST CURVES) (6pages)	

Test Report Certification

Applicant : Shenzhen Yifang Digital Technologies Co., Ltd.
Manufacturer : Shenzhen Yifang Digital Technologies Co., Ltd.
EUT Description : MP3 PLAYER
(A) MODEL NO.: EM191F, EM192F
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: 12V DC

Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.239: 2004
& ANSI C63.4: 2003

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.239 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : October 13, 2005

Prepared by : 
(Engineer)

Reviewer : 
(Quality Manager)

Approved & Authorized Signer : 
(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : MP3 PLAYER

Model Number : EM191F, EM192F
(Note: The samples are same except the appearance are different, So we prepare EM192F for test only.)

Power Supply : 12V DC

Applicant : Shenzhen Yifang Digital Technologies Co., Ltd.
Address : 5/F., Bldg.H-3, Huaqiaocheng East Industrial Park, No.1 Xiangshan East Rd., Nanshan District, Shenzhen City, Guangdong, P.R.China

Manufacturer : Shenzhen Yifang Digital Technologies Co., Ltd.
Address : 5/F., Bldg.H-3, Huaqiaocheng East Industrial Park, No.1 Xiangshan East Rd., Nanshan District, Shenzhen City, Guangdong, P.R.China

Date of sample received : October 10, 2005
Date of Test : October 13, 2005

1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen, May 10, 2004
Accredited by FCC, May 10, 2004
The Certificate Registration Number is 253065
Accredited by Industry Canada, May 18, 2004
The Certificate Registration Number is IC 5077

Name of Firm : ACCURATE TECHNOLOGY CO. LTD
Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3. Measurement Uncertainty

Conducted Emission Uncertainty = $\pm 2.66\text{dB}$

Radiated Emission Uncertainty = $\pm 4.26\text{dB}$

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	01.02.2006
EMI Test Receiver	Rohde&Schwarz	ESI26	838786/013	01.02.2006
Bilog Antenna	Schwarzbeck	VULB9163	9163-194	01.02.2006
Horn Antenna	Rohde&Schwarz	HF906	100013	01.02.2006
Spectrum Analyzer	Anritsu	MS2651B	6200238856	01.02.2006
Pre-Amplifier	Agilent	8447D	2944A10619	01.02.2006
Signal Generator	GW	GAG-810	0913317	01.02.2006

3. RADIATED EMISSION FOR FCC PART 15 SECTION 15.239(C)


3.1. Block Diagram of Test Setup

3.1.1. Block diagram of connection between the EUT and simulators



(EUT: MP3 PLAYER)

3.1.2. Anechoic Chamber Test Setup Diagram



3.2. The Emission Limit for section 15.239(c)

3.2.1 The field strength of any emissions radiated on any frequency outside of the specified 200kHz band shall not exceed the general radiated emission limits in section 15.209

Radiation Emission Measurement Limits According to Section 15.209

Frequency (MHz)	Limit,		The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dBµV/m)	
30 - 88	100	40	
88 - 216	150	43.5	

216 - 960	200	46	frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
Above 960	500	54	

3.3.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

3.3.1.MP3 PLAYER(EUT)

Model Number : EM192F
Serial Number : N/A
Manufacturer : Shenzhen Yifang Digital Technologies Co., Ltd.

3.4.Operating Condition of EUT

3.4.1.Setup the EUT and simulator as shown as Section 3.1.

3.4.2.Turn on the power of all equipment.

Let the EUT work in TX modes (On with 1kHz signal) measure it. The transmit frequency are 88.1-88.9M, 106.7-107.9MHz.We are select 88.1M, 107.9MHz TX frequency to transmitted.

3.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver (R&S ESI26) is set at 120KHz in 30-1000MHz; Set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 1100MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

3.6. The Field Strength of Radiation Emission Measurement Results

PASS.

The frequency range 30MHz to 1100MHz is investigated.

Date of Test:	October 13, 2005	Temperature:	22°C
EUT:	MP3 PLAYER	Humidity:	50%
Model No.:	EM192F	Power Supply:	12V DC
Test Mode:	TX 88.1MHz	Test Engineer:	Andy

Polarization	Frequency (MHz)	Reading(dBμV/m) QP	Factor Corr.(dB)	Result(dBμV/m) QP	Limits(dBμV/m) QP	Margin(dBμV/m) QP
Horizontal	66.1	15.0	20.8	35.8	40	4.2
Horizontal	110.1	22.0	15.3	37.3	43.5	6.2
Horizontal	133.0	25.0	13.7	38.7	43.5	4.8
Horizontal	154.2	25.0	14.4	39.4	43.5	4.1
Horizontal	174.8	17.9	16.0	33.9	43.5	9.6
Horizontal	198.2	14.0	18.6	32.6	43.5	10.9
Horizontal	220.2	18.0	19.7	37.7	46.0	8.3
Horizontal	242.3	17.0	20.5	37.5	46.0	8.5
Horizontal	264.3	17.1	20.0	37.1	46.0	8.9
Horizontal	286.3	18.0	19.9	37.9	46.0	8.1
Horizontal	308.3	20.0	20.6	40.6	46.0	5.4
Horizontal	352.4	14.0	22.0	36.0	46.0	10.0
Horizontal	374.4	14.0	21.8	35.8	46.0	10.2
Horizontal	396.4	12.0	23.1	35.1	46.0	10.9
Horizontal	418.5	11.1	23.3	34.4	46.0	11.6
Vertical	66.1	14.0	16.8	30.8	40	9.2
Vertical	110.1	18.1	20.2	38.3	43.5	5.2
Vertical	132.1	17.6	20.1	37.7	43.5	5.8
Vertical	154.2	20.4	19.0	39.4	43.5	4.1
Vertical	174.8	12.9	19.0	31.9	43.5	11.6

Vertical	220.2	10.6	20.1	30.7	46.0	15.3
Vertical	286.3	13.7	23.2	36.9	46.0	9.1
Vertical	352.4	9.5	24.5	34.0	46.0	12.0
Vertical	374.4	8.8	24.0	32.8	46.0	13.2


The spectral diagrams in appendix I display the measurement of un-weighted peak values.

The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

Reviewer :



Date of Test:	<u>October 13, 2005</u>	Temperature:	<u>22°C</u>
EUT:	<u>MP3 PLAYER</u>	Humidity:	<u>50%</u>
Model No.:	<u>EM192F</u>	Power Supply:	<u>12V DC</u>
Test Mode:	<u>TX 107.9MHz</u>	Test Engineer:	<u>Andy</u>

Polarization	Frequency (MHz)	Reading(dBμV/m)	Factor Corr.(dB)	Result(dBμV/m)	Limits(dBμV/m)	Margin(dBμV/m)
		QP		QP	QP	QP
Horizontal	43.1	9.0	25.8	34.8	40	5.2
Horizontal	64.8	14.0	21.5	35.5	40	4.5
Horizontal	86.3	20.0	15.4	35.4	40	4.6
Horizontal	129.5	25.7	13.7	39.4	43.5	4.1
Horizontal	151.1	25.0	14.2	39.2	43.5	4.3
Horizontal	172.6	22.0	15.7	37.7	43.5	5.8
Horizontal	194.2	21.1	18.0	39.1	43.5	4.4
Horizontal	215.8	20.0	19.5	39.5	43.5	4.0
Horizontal	237.4	20.0	20.4	40.4	46.0	5.6
Horizontal	258.9	21.0	20.2	41.2	46.0	4.8
Horizontal	280.5	21.0	19.8	40.8	46.0	5.2
Horizontal	302.1	19.0	20.3	39.3	46.0	6.7
Horizontal	323.7	16.1	21.3	37.4	46.0	8.6
Horizontal	345.3	18.0	22.0	40.0	46.0	6.0
Horizontal	366.9	19.0	21.8	40.8	46.0	5.2
Horizontal	388.5	17.0	22.6	39.6	46.0	6.4
Horizontal	410.0	14.0	23.4	37.4	46.0	8.6
Horizontal	453.2	11.0	22.8	33.8	46.0	12.2
Horizontal	474.8	11.0	22.0	33.0	46.0	13.0
Horizontal	496.3	12.0	23.7	35.7	46.0	10.3
Horizontal	517.9	12.0	24.6	36.6	46.0	9.4
Horizontal	539.5	10.0	25.3	35.3	46.0	10.7
Horizontal	561.1	9.0	25.4	34.4	46.0	11.6

Horizontal	581.1	9.0	25.1	34.1	46.0	11.9
Vertical	64.7	17.5	17.0	34.5	40	5.5
Vertical	86.3	18.5	17.4	35.9	40	4.1
Vertical	129.5	18.6	20.1	38.7	43.5	4.8
Vertical	151.1	20.0	19.3	39.3	43.5	4.2
Vertical	172.6	20.0	19.0	39.0	43.5	4.5
Vertical	194.2	18.7	19.4	38.1	43.5	5.4
Vertical	215.8	19.5	20.0	39.5	43.5	4.0
Vertical	237.4	19.7	20.7	40.4	46.0	5.6
Vertical	258.9	16.1	22.1	38.2	46.0	7.8
Vertical	280.5	17.2	23.6	40.8	46.0	5.2
Vertical	345.3	12.3	24.7	37.0	46.0	9.0
Vertical	366.9	16.6	24.2	40.8	46.0	5.2
Vertical	388.4	13.4	24.0	37.4	46.0	8.6
Vertical	410.0	12.6	24.8	37.4	46.0	8.6
Vertical	453.2	10.2	26.6	36.8	46.0	9.2
Vertical	474.8	10.6	27.4	38.0	46.0	8.0
Vertical	496.3	11.7	27.0	38.7	46.0	7.3
Vertical	517.9	8.8	26.8	35.6	46.0	10.4

The spectral diagrams in appendix I display the measurement of un-weighted peak values.

The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

Reviewer : 

4. FUNDAMENTAL RADIATED EMISSION FOR FCC PART 15

SECTION 15.239(B)


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: MP3 PLAYER)

4.1.2. Anechoic Chamber Test Setup Diagram



(EUT: MP3 PLAYER)

4.2. The Emission Limit For Section 15.239(b)

4.2.1 The field strength of any emission within the permitted 200kHz band shall not exceed 250microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in section 15.35 for limiting peak emissions apply.

4.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1.MP3 PLAYER(EUT)

Model Number : EM192F
Serial Number : N/A
Manufacturer : Shenzhen Yifang Digital Technologies Co., Ltd.

4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

Let the EUT work in TX modes (On with 1kHz signal) measure it. The transmit frequency are 88.1-88.9M, 106.7-107.9MHz.We are select 88.1M, 107.9MHz TX frequency to transmitted.

4.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

4.6.The Emission Measurement Result

PASS.


Date of Test:	<u>October 13, 2005</u>	Temperature:	<u>22°C</u>
EUT:	<u>MP3 PLAYER</u>	Humidity:	<u>50%</u>
Model No.:	<u>EM192F</u>	Power Supply:	<u>12V DC</u>
Test Mode:	<u>TX</u>	Test Engineer:	<u>Andy</u>

Fundamental Radiated Emissions

Test conditions		Fundamental Frequency	
		88.1MHz	
T _{nom} (22°C)	Unit	(dBμV/m)/ (μ V/m) AV	(dBμV/m)/(μ V/m) PEAK
	Horizontal	42.8/138	56.8/692
	Vertical	41.8/123	55.8/617
limit		48/250	68/2500
Note: Measurement was performed with modulated signal with average detector and peak detector.			

Test conditions		Fundamental Frequency	
		107.9MHz	
T _{nom} (22°C)	Unit	(dBμV/m)/ (μ V/m) AV	(dBμV/m)/(μ V/m) PEAK
	Horizontal	43.1/143	57.7/767
	Vertical	42.6/135	56.6/676
limit		48/250	68/2500
Note: Measurement was performed with modulated signal with average detector and peak detector.			

Reviewer :



5. OCCUPIED BANDWIDTH FOR FCC PART 15 SECTION

15.239(A)

5.1.The Requirement For Section 15.239(a)

5.1.1. Emission from the device shall be confined within a band 200kHz wide centered on the operating frequency. The 200kHz band shall lie wholly within the frequency range of 88-108MHz.

5.2.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.2.1.MP3 PLAYER(EUT)

Model Number : EM192F
Serial Number : N/A
Manufacturer : Shenzhen Yifang Digital Technologies Co., Ltd.

5.3.Operating Condition of EUT

5.3.1.Setup the EUT and simulator as shown as Section 4.1.

5.3.2.Turn on the power of all equipment.

Let the EUT work in TX modes (On with 1kHz signal) measure it. The transmit frequency are 88.1-88.9M, 106.7-107.9MHz.We are select 88.1M, 107.9MHz TX frequency to transmitted.


5.4.Test Procedure

The zero level was set without modulation. A small sample of the transmitter output was fed into the spectrum analyzer and above photo was taken. The vertical scale is set to 10dB per division; the horizontal scale is set to 20kHz per division.


5.5. Test Result

The EUT does meet the FCC requirement.

Reviewer :

A handwritten signature in black ink, appearing to read "Sean", is written over a light blue rectangular background. The signature is positioned above a horizontal line that extends to the right.

APPENDIX I (Test Curves)




Trace:

Ref Trace:

Condition: FCC SECTION15.209 3m
eut : MP3 PLAYER M/N:EM192F
power: DC 12.0V
memo : TX(88.1MHz)
manuf: YIFANG

HORIZONTAL




Trace:

Ref Trace:

Condition: FCC SECTION15.209 3m
eut : MP3 PLAYER M/N:EM192F
power: DC 12.0V
memo : TX(88.1MHz)
manuf: YIFANG

VERTICAL




Trace:

Ref Trace:

Condition: FCC SECTION15.209 3m
cut : MP3 PLAYER M/N:EM192F
power: DC 12.0V
memo : TX(107.9MHz)
manuf: YIFANG

HORIZONTAL



Trace:

Ref Trace:

Condition: FCC SECTION15.209 3m
eut : MP3 PLAYER M/N:EM192F
power: DC 12.0V
memo : TX(107.9MHz)
manuf: YIFANG

VERTICAL




*RBW 10 kHz Delta 3 [T1]
*VBW 10 kHz -20.18 dB
*SWT 50 ms 31.200000000 kHz

Ref 80 dBuV

*Att 0 dB

1 PK
VIEW



Center 88.1 MHz

20 kHz/

Span 200 kHz




*RBW 10 kHz Delta 3 [T1]
*VBW 10 kHz -20.01 dB
*SWT 50 ms 31.200000000 kHz

Ref 80 dBμV

*Att 0 dB

1 PK
VIEW



Center 107.9008 MHz

20 kHz/

Span 200 kHz