

## FCC ID: S7JM1010FP

### WLAN (Portable device)

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power: 802.11b

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	Result calculation	1-g SAR
2.437	802.11b	9.72	0.293	3.0
2.412	802.11g	9.69	0.289	3.0
2.412	802.11n	9.15	0.255	3.0

#### Conclusion:

For the max result 802.11b:  $0.293 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Sincerely,



Signature

Company Name: SHENZHEN EMTEK CO., LTD.

Address: Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, China

David Lee / Manager