

<b>Prüfbericht-Nr.:</b> Test Report No.:	<b>17040273 003</b>	<b>Auftrags-Nr.:</b> Order No.:	<b>164013498</b>	<b>Seite 1 von 22</b> Page 1 of 22	
<b>Kunden-Referenz-Nr.:</b> Client Reference No.:	<b>N/A</b>	<b>Auftragsdatum:</b> Order date:	<b>29.04.2014</b>		
<b>Auftraggeber:</b> Client:	<b>Shenzhen Yifang Digital Technology Co., Ltd.</b> Building NO.23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd., Nanshan, Shenzhen, Guangdong 518108, China				
<b>Prüfgegenstand:</b> Test item:	<b>MID</b>				
<b>Bezeichnung / Typ-Nr.:</b> Identification / Type No.:	<b>NS-15AT07</b>				
<b>Auftrags-Inhalt:</b> Order content:	<b>FCC Certification</b>		<b>IC Verification</b>		
<b>Prüfgrundlage:</b> Test specification:	<b>CFR47 FCC Part 15: Subpart B Section 15.107</b> <b>CFR47 FCC Part 15: Subpart B Section 15.109</b> <b>ICES-003 Issue 5 August 2012</b>				
<b>Wareneingangsdatum:</b> Date of receipt:	<b>15.05.2014</b>				
<b>Prüfmuster-Nr.:</b> Test sample No.:	<b>A000055953-006</b>				
<b>Prüfzeitraum:</b> Testing period:	<b>17.05.2014 - 24.05.2014</b>				
<b>Ort der Prüfung:</b> Place of testing:	<b>Accurate Technology Co., Ltd.</b>				
<b>Prüflaboratorium:</b> Testing laboratory:	<b>TÜV Rheinland (Shenzhen) Co., Ltd.</b>				
<b>Prüfergebnis*:</b> Test result*:	<b>Pass</b>				
<b>geprüft von / tested by:</b>			<b>kontrolliert von / reviewed by:</b>		
					
<b>12.06.2014</b>	<b>Tom Wang/ Assistant Project Manager</b>		<b>12.06.2014</b>	<b>Sam Lin/Technical Certifier</b>	
<b>Datum</b> Date	<b>Name / Stellung</b> Name / Position	<b>Unterschrift</b> Signature	<b>Datum</b> Date	<b>Name / Stellung</b> Name / Position	<b>Unterschrift</b> Signature
<b>Sonstiges / Other:</b> This test report is for evaluation of "Peripheral" function of the test item.					
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> Condition of the test item at delivery:			<b>Prüfmuster vollständig und unbeschädigt</b> Test item complete and undamaged		
* Legende: 1 = sehr gut      2 = gut      3 = befriedigend      4 = ausreichend      5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n)      F(ail) = entspricht nicht o.g. Prüfgrundlage(n)      N/A = nicht anwendbar      N/T = nicht getestet					
Legend: 1 = very good      2 = good      3 = satisfactory      4 = sufficient      5 = poor P(ass) = passed a.m. test specification(s)      F(ail) = failed a.m. test specification(s)      N/A = not applicable      N/T = not tested					
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.					

## TEST SUMMARY

### 5.1.1 CONDUCTED EMISSIONS

*RESULT: Pass*

### 5.2.1 RADIATED EMISSION

*RESULT: Pass*

## CONTENTS

<b>1.</b>	<b>GENERAL REMARKS.....</b>	<b>4</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>4</b>
<b>2.</b>	<b>TEST SITES .....</b>	<b>4</b>
<b>2.1</b>	<b>TEST FACILITIES.....</b>	<b>4</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>5</b>
<b>2.3</b>	<b>TRACEABILITY .....</b>	<b>6</b>
<b>2.4</b>	<b>CALIBRATION .....</b>	<b>6</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>6</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA .....</b>	<b>6</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING.....</b>	<b>6</b>
<b>2.8</b>	<b>TEST SETUP DIAGRAM.....</b>	<b>7</b>
<b>3.</b>	<b>GENERAL PRODUCT INFORMATION .....</b>	<b>8</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>8</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>8</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>8</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>8</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS .....</b>	<b>8</b>
<b>4.</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>9</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>	<b>9</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>9</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>9</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE ERM COMPLIANCE .....</b>	<b>9</b>
<b>5.</b>	<b>TEST RESULTS EMISSION .....</b>	<b>10</b>
<b>5.1</b>	<b>EMISSION IN THE FREQUENCY RANGE UP TO 30 MHZ .....</b>	<b>10</b>
<b>5.1.1</b>	<b><i>Conducted emissions</i> .....</b>	<b>10</b>
<b>5.2</b>	<b>EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHZ.....</b>	<b>13</b>
<b>5.2.1</b>	<b><i>Radiated Emission</i> .....</b>	<b>13</b>
<b>6.</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>	<b>20</b>
<b>7.</b>	<b>LIST OF TABLES .....</b>	<b>22</b>
<b>8.</b>	<b>LIST OF PHOTOGRAPHS .....</b>	<b>22</b>

## 1. General Remarks

### 1.1 Complementary Materials

None.

## 2. Test Sites

### 2.1 Test Facilities

Accurate Technology Co., Ltd.

**(FCC Registration No.: 752051)**

**(Test site Industry Canada No.: 5077A-2)**

F1, Bldg. A, Changyuan New Material Port  
Keyuan Rd., Science & Industry Park, Nanshan  
Shenzhen, P.R. China

The tests at the test site have been conducted under the supervision of a TÜV engineer.

## 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
<b>Conducted Emission</b>				
Test Receiver	Rohde & Schwarz	ESCS30	100307	2015-01-11
L.I.S.N.	Schwarzbeck	NLSK8126	8126431	2015-01-11
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	2015-01-11
50Ω Coaxial Switch	Anritsu Corp	MP59B	6200283933	2015-01-11
<b>Radiated Emission</b>				
Spectrum Analyzer	Agilent	E7405A	MY45115511	2015-01-11
Test Receiver	Rohde & Schwarz	ESCS30	100307	2015-01-11
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	2015-01-11
Loop Antenna	Schwarzbeck	FMZB1516	1516131	2015-01-11
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	2015-01-11
50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	2015-01-11
Pre-Amplifier	Rohde & Schwarz	CBLU118354 0-01	3791	2015-01-11
RF Coaxial Cable (966 Chamber) (for below 1GHz test)	Suhner	N-3m	No.8	2015-01-11
RF Coaxial Cable (966 Chamber) (for below 1GHz test)	Resenberger	N-3.5m	No.9	2015-01-11
RF Coaxial Cable (966 Chamber) (for below 1GHz test)	Suhner	N-6m	No.10	2015-01-11
RF Coaxial Cable (966 Chamber) (for above 1GHz test)	Resenberger	N-12m	No.11	2015-01-11
RF Coaxial Cable (966 Chamber) (for above 1GHz test)	Resenberger	N-0.5m	No.12	2015-01-11

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO/IEC 17025 are:

**Table 2: Measurement Uncertainty**

Items		Extended Uncertainty
Conducted Emission (0.15-30MHz)	Disturbance Voltage (dBuV)	$U=\pm 2.23\text{dB}$ , $k=2$ , $\sigma=95\%$
Radiated Emission (30-1000MHz)	Field strength (dBuV/m)	$U=\pm 4.42\text{dB}$ , $k=2$ , $\sigma=95\%$
Radiated Emission (1-25GHz)	Field strength (dBuV/m)	$U=\pm 4.06\text{dB}$ , $k=2$ , $\sigma=95\%$

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

Accurate Technology Co., Ltd. test facility located at F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan, Shenzhen, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

## 2.8 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test





Diagram of Measurement Equipment Configuration for Conduction Measurement



### 3. General Product Information

#### 3.1 Product Function and Intended Use

The EUT is 7" tablet with Wi-Fi & Bluetooth function.  
For details refer to the User Manual and Circuit Diagram.

#### 3.2 Ratings and System Details

**Table 3: Technical Specification of EUT**

Technical Specification	Value
Kind of Equipment	MID
Type Designation	NS-15AT07
FCC ID	S7JNS15AT07
IC	8082A-NS15AT07
Extreme Temperature Range	-30~+75°C
Operation Voltage	DC 3.7V (via built in battery)
	DC 5V (via AC/DC adapter)

#### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, connecting to PC
- B. Standby
- C. Off

#### 3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

#### 3.5 Submitted Documents

- Bill of Material
- Constructional Drawing
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label



## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.4: 2003.

### 4.3 Special Accessories and Auxiliary Equipment

The EUT was tested together with the following accessories:

Description	Manufacturer	Part No.	S/N
Notebook PC	Lenovo	4290-RT8	R9-FW93G
Printer	HP	HP laserjet 1015	CNFG030424

The EUT was tested with following cables:

Interface(s)/Port(s):	Max. cable length, shielding	Cable classification
Micro USB port	4 cores, non-shielded port, 3m	DC Power Input

### 4.4 Countermeasures to Achieve ERM Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF). No additional measures were employed to achieve compliance.

## 5. Test Results EMISSION

### 5.1 Emission in the Frequency Range up to 30 MHz

#### 5.1.1 Conducted emissions

**RESULT:****Pass**

Date of testing : 2014-05-24  
Test standard : FCC Part 15.107 (a)  
ICES-003 Issue 5 August 2012  
Basic standard : ANSI C63.4: 2003  
Frequency range : 0.15 – 30MHz  
Limits : FCC Part 15.107(a)  
ICES-003 Issue 5 August 2012  
Kind of test site : Shield room

**Test setup**

Input Voltage : AC 120V, 60Hz  
Operation Mode : A  
Earthing : Not Connected  
Ambient temperature : 25°C  
Relative humidity : 52%  
Atmospheric pressure : 101kPa


For details refer to following test plot.

**ACCURATE TECHNOLOGY CO.,LTD**
**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:NS-15AT07  
 Manufacturer: Yifang  
 Operating Condition: Transfer data  
 Test Site: 1#Shielding Room  
 Operator: PEI  
 Test Specification: L 120V/60Hz  
 Comment:  
 Start of Test: 5/24/2014 / 6:48:48PM

**SCAN TABLE: "V 150K-30MHz fin"**

Short Description: \_SUB\_STD\_VTERM2 1.70  
 Start Stop Step Detector Meas. IF Transducer  
 Frequency Frequency Width Time Bandw.  
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008  
 Average


**MEASUREMENT RESULT: "PEI-0524-V10\_fin"**

5/24/2014 6:57PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.151202	56.40	10.5	66	9.5	QP	L1	GND
0.173876	49.10	10.5	65	15.7	QP	L1	GND
0.487008	38.40	10.7	56	17.8	QP	L1	GND

**MEASUREMENT RESULT: "PEI-0524-V10\_fin2"**

5/24/2014 6:57PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.153024	35.70	10.5	56	20.1	AV	L1	GND
0.492876	33.50	10.7	46	12.6	AV	L1	GND
2.009114	21.90	11.0	46	24.1	AV	L1	GND

**ACCURATE TECHNOLOGY CO.,LTD**
**CONDUCTED EMISSION STANDARD FCC PART 15 B**

EUT: MID M/N:NS-15AT07  
 Manufacturer: Yifang  
 Operating Condition: Transfer data  
 Test Site: 1#Shielding Room  
 Operator: PEI  
 Test Specification: N 120V/60Hz  
 Comment:  
 Start of Test: 5/24/2014 / 6:38:40PM

**SCAN TABLE: "V 150K-30MHz fin"**

Short Description: \_SUB\_STD\_VTERM2 1.70  
 Start Stop Step Detector Meas. IF Transducer  
 Frequency Frequency Width Time Bandw.  
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008  
 Average


**MEASUREMENT RESULT: "PEI-0524-V09\_fin"**

5/24/2014 6:46PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	52.80	10.5	66	13.2	QP	N	GND
0.167739	49.50	10.5	65	15.6	QP	N	GND
0.494848	38.10	10.7	56	18.0	QP	N	GND

**MEASUREMENT RESULT: "PEI-0524-V09\_fin2"**

5/24/2014 6:46PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.152414	36.20	10.5	56	19.7	AV	N	GND
0.171806	33.90	10.5	55	21.0	AV	N	GND
0.490912	33.60	10.7	46	12.6	AV	N	GND

## 5.2 Emission in the Frequency Range above 30 MHz

### 5.2.1 Radiated Emission

**RESULT:****Pass**

Date of testing : 2014-05-24  
Test standard : FCC Part 15.109 (a)  
ICES-003 Issue 5 August 2012  
Test procedure : ANSI C63.4: 2003  
Frequency range : 30 - 25000MHz  
Equipment Classification : Class B  
Limits : FCC Part 15.109(a)  
ICES-003 Issue 5 August 2012  
Kind of test site : 3m Semi-Anechoic Chamber

**Test setup**

Input Voltage : AC 120V, 60Hz  
Operation mode : A  
Earthing : Not connected  
Ambient temperature : 25°C  
Relative humidity : 52%  
Atmospheric pressure : 101kPa

For details refer to following test plot.



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: PHY #1653	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/05/17/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: MID	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT07	
Manufacturer: Yifang	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	360.0441	50.01	-7.61	42.40	46.00	-3.60	QP			
2	480.0100	49.20	-5.35	43.85	46.00	-2.15	QP			



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: PHY #1652	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/05/17/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: MID	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT07	
Manufacturer: Yifang	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	127.9581	51.04	-13.81	37.23	43.50	-6.27	QP			
2	360.0521	51.59	-7.61	43.98	46.00	-2.02	QP			
3	480.0240	48.84	-5.35	43.49	46.00	-2.51	QP			



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: PHY #1852	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/05/24/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: MID	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT07	
Manufacturer: Yifang	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1800.821	62.92	-10.04	52.88	74.00	-21.12	peak			
2	1800.821	47.39	-10.04	37.35	54.00	-16.65	AVG			





**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: PHY #1853	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/05/24/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: MID	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT07	
Manufacturer: Yifang	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1079.918	64.02	-12.64	51.38	74.00	-22.62	peak			
2	1079.918	48.46	-12.64	35.82	54.00	-18.18	AVG			



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: PHY #1855	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/05/24/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: MID	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT07	
Manufacturer: Yifang	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	24958.889	33.26	18.84	52.10	74.00	-21.90	peak			
2	24958.889	20.74	18.84	39.58	54.00	-14.42	AVG			



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 2# Chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: PHY #1854	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 14/05/24/
Temp.( C)/Hum.(%) 23 C / 48 %	Time:
EUT: MID	Engineer Signature: PEI
Mode: Transfer data	Distance:
Model: NS-15AT07	
Manufacturer: Yifang	

Note:




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	24901.446	33.47	18.76	52.23	74.00	-21.77	peak			
2	24901.446	20.35	18.76	39.11	54.00	-14.89	AVG			

## 6. Photographs of the Test Set-Up

Photograph 1: Set-up for Conducted Emission



Photograph 2: Set-up for Radiated Emission of below 1GHz



**Photograph 3: Set-up for Radiated Emission of 1 - 18GHz**



**Photograph 4: Set-up for Radiated Emission of 18 - 25GHz**



## 7. List of Tables

Table 1: List of Test and Measurement Equipment .....	5
Table 2: Measurement Uncertainty .....	6
Table 3: Technical Specification of EUT .....	8

## 8. List of Photographs

Photograph 1: Set-up for Conducted Emission .....	20
Photograph 2: Set-up for Radiated Emission of below 1GHz .....	20
Photograph 3: Set-up for Radiated Emission of 1 - 18GHz .....	21
Photograph 4: Set-up for Radiated Emission of 18 - 25GHz.....	21