

FCC ID: S7JNXW9QC132

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

802.11b/g/n HT20/n HT40:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.412	11b	9.28	7.8dBm-9.8dBm	2.966	3.0
2.437	11b	9.57	7.8dBm-9.8dBm	2.980	3.0
2.462	11b	9.40	7.8dBm-9.8dBm	2.997	3.0
2.412	11g	9.72	7.8dBm-9.8dBm	2.966	3.0
2.437	11g	9.70	7.8dBm-9.8dBm	2.980	3.0
2.462	11g	9.65	7.8dBm-9.8dBm	2.997	3.0
2.412	11n HT20	9.67	7.8dBm-9.8dBm	2.966	3.0
2.437	11n HT20	9.61	7.8dBm-9.8dBm	2.980	3.0
2.462	11n HT20	9.64	7.8dBm-9.8dBm	2.997	3.0
2.422	11n HT40	8.66	7.8dBm-9.8dBm	2.972	3.0
2.437	11n HT40	8.60	7.8dBm-9.8dBm	2.980	3.0
2.452	11n HT40	8.69	7.8dBm-9.8dBm	2.991	3.0

BT DTS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	3.52	2dBm-4dBm	0.78	3.0
2.440	GFSK	3.46	2dBm-4dBm	0.78	3.0
2.480	GFSK	3.38	2dBm-4dBm	0.79	3.0

BT DSS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	3.33	2dBm-4dBm	0.78	3.0
2.441	GFSK	3.56	2dBm-4dBm	0.78	3.0
2.480	GFSK	3.14	2dBm-4dBm	0.79	3.0
2.402	$\pi/4$ -DQPSK	3.50	2dBm-4dBm	0.78	3.0
2.441	$\pi/4$ -DQPSK	3.42	2dBm-4dBm	0.78	3.0
2.480	$\pi/4$ -DQPSK	3.08	2dBm-4dBm	0.79	3.0
2.402	8DPSK	3.22	2dBm-4dBm	0.78	3.0
2.441	8DPSK	3.47	2dBm-4dBm	0.78	3.0
2.480	8DPSK	3.35	2dBm-4dBm	0.79	3.0

Conclusion:

For the max result: $2.997 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature:

Date: 2015-08-15

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China