

RF EXPOSURE EVALUATION

EUT Specification

EUT	300Mbps Universal WiFi Range Extender
FCC ID	S8J-WA730RE
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	21.43dBm for 802.11b; 20.46dBm for 802.11g; 20.10dBm for 802.11n(HT20); 19.61dBm for 802.11n(HT40);
Antenna gain (Max)	2.0dBi (for per antenna port Max) 5.01dBi for MIMO(Ant3+Ant4 Directional Gain)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Applicable Standard:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J. Section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m Normally can be maintained between the user and the device.

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm², P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale, $\pi=3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Max power Result:

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)			Limit (dBm)	Verdict
			Ant3	Ant4	Sum		
802.11b	1	2412	19.33	19.23	--	30	PASS
	6	2437	20.13	20.24	--	30	PASS
	11	2462	21.43	20.75	--	30	PASS
802.11g	1	2412	18.75	19.11	--	30	PASS
	6	2437	19.03	19.42	--	30	PASS
	11	2462	20.42	20.46	--	30	PASS
802.11n (HT20)	1	2412	16.02	16.17	19.11	30	PASS
	6	2437	16.25	16.29	19.28	30	PASS
	11	2462	17.12	17.05	20.10	30	PASS
802.11n (HT40)	3	2422	14.48	14.23	17.37	30	PASS
	6	2437	15.13	15.02	18.09	30	PASS
	9	2452	16.75	16.45	19.61	30	PASS

Antenna 3:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	1	19±1	20	100.000	2	1.585	0.031530	1
	6	20±1	21	125.893	2	1.585	0.039694	1
	11	21±1	22	158.489	2	1.585	0.049972	1
802.11g	1	19±1	20	100.000	2	1.585	0.031530	1
	6	19±1	20	100.000	2	1.585	0.031530	1
	11	20±1	21	125.893	2	1.585	0.039694	1
802.11n (H20)	1	16±1	17	50.119	2	1.585	0.015803	1
	6	16±1	17	50.119	2	1.585	0.015803	1
	11	17±1	18	63.096	2	1.585	0.019894	1
802.11n (H40)	3	14±1	15	31.623	2	1.585	0.009971	1
	6	15±1	16	39.811	2	1.585	0.012552	1
	9	17±1	18	63.096	2	1.585	0.019894	1

Antenna 4:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	1	19±1	20	100.000	2	1.585	0.031530	1
	6	20±1	21	125.893	2	1.585	0.039694	1
	11	21±1	22	158.489	2	1.585	0.049972	1
802.11g	1	19±1	20	100.000	2	1.585	0.031530	1
	6	19±1	20	100.000	2	1.585	0.031530	1
	11	20±1	21	125.893	2	1.585	0.039694	1
802.11n (H20)	1	16±1	17	50.119	2	1.585	0.015803	1
	6	16±1	17	50.119	2	1.585	0.015803	1
	11	17±1	18	63.096	2	1.585	0.019894	1
802.11n (H40)	3	14±1	15	31.623	2	1.585	0.009971	1
	6	15±1	16	39.811	2	1.585	0.012552	1
	9	16±1	17	50.119	2	1.585	0.015803	1

MPE Result:

Operation Mode	Channel Number	Channel Frequency (MHz)	Power density at 20cm (mW/cm ²)			Power density Limits (mW/cm ²)	Verdict
			Ant3	Ant4	Sum		
802.11b	1	2412	0.031530	0.031530	--	1	PASS
	6	2437	0.039694	0.039694	--	1	PASS
	11	2462	0.049972	0.049972	--	1	PASS
802.11g	1	2412	0.031530	0.031530	--	1	PASS
	6	2437	0.031530	0.031530	--	1	PASS
	11	2462	0.039694	0.039694	--	1	PASS
802.11n (HT20)	1	2412	0.015803	0.015803	0.031606	1	PASS
	6	2437	0.015803	0.015803	0.031606	1	PASS
	11	2462	0.019894	0.019894	0.039788	1	PASS
802.11n (HT40)	3	2422	0.009971	0.009971	0.019942	1	PASS
	6	2437	0.012552	0.012552	0.025104	1	PASS
	9	2452	0.019894	0.015803	0.035697	1	PASS