

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

750Mbps Wireless Dual Band 11AC Router

Model No.: BL-WDR3750

FCC ID: S8J-WDR3750

Trademark: LB-LINK

Report No.: KAD150123103E

Issue Date: March 26, 2015

Prepared for

**Shenzhen Bilian Electronic Co., Ltd.
Building B1, Zhongxing Industrial Zone, Juling Jutang Community,
Guanlan street, Bao'an, Shenzhen China**

Prepared by

**DONGGUAN EMTEK CO., LTD.
No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

**This report shall not be reproduced, except in full, without the written approval of
DONGGUAN EMTEK CO., LTD.**

VERIFICATION OF COMPLIANCE

Applicant:	Shenzhen Bilian Electronic Co., Ltd. Building B1, Zhongxing Industrial Zone, Juling Jutang Community, Guanlan street, Bao'an, Shenzhen China
Manufacturer:	Shenzhen Bilian Electronic Co., Ltd. Building B1, Zhongxing Industrial Zone, Juling Jutang Community, Guanlan street, Bao'an, Shenzhen China
Product Description:	750Mbps Wireless Dual Band 11AC Router
Model Number:	BL-WDR3750
Trade Mark:	LB-LINK
Date of Test:	January 23, 2015 to March 24, 2015

We hereby certify that:

The above equipment was tested by DONGGUAN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2014) and ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2014).

Approved By



**Sam Lv / Q.A. Manager
DONGGUAN EMTEK CO., LTD.**

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	KAD150123103E

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. DESCRIPTION OF TEST MODES.....	8
4. SUMMARY OF TEST RESULTS.....	9
5. TEST METHODOLOGY	9
6. TEST FACILITY.....	9
7. TEST SYSTEM UNCERTAINTY	10
8. CONDUCTED EMISSIONS TEST	11
8.1 MEASUREMENT PROCEDURE	11
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
8.3 MEASUREMENT EQUIPMENT USED	11
8.4 CONDUCTED EMISSION LIMIT	11
8.5 MEASUREMENT RESULT	11
9. RADIATED EMISSION TEST.....	16
9.1 MEASUREMENT PROCEDURE	16
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
9.3 MEASUREMENT EQUIPMENT USED	18
9.4 RADIATED EMISSION LIMIT	18
9.5 MEASUREMENT RESULT	20
10. 6DB BANDWIDTH TEST	29
10.1 MEASUREMENT PROCEDURE	29
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	29
10.3 MEASUREMENT EQUIPMENT USED	29
10.4 MEASUREMENT RESULTS	29
11. MAXIMUM PEAK OUTPUT POWER TEST.....	38
11.1 MEASUREMENT PROCEDURE	38
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	38
11.3 MEASUREMENT EQUIPMENT USED	38
11.4 PEAK POWER OUTPUT LIMIT	38
11.5 MEASUREMENT RESULTS	39
12. BAND EDGE TEST	40
12.1 MEASUREMENT PROCEDURE	40
12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	41
12.3 MEASUREMENT EQUIPMENT USED	41
12.4 MEASUREMENT RESULTS	41
13. MAXIMUM POWER SPECTRAL DENSITY	70
13.1 TEST EQUIPMENT	70
13.2 MEASURING INSTRUMENTS AND SETTING	70
13.3 TEST PROCEDURES	70
13.4 BLOCK DIAGRAM OF TEST SETUP	70

13.5 LIMIT.....70
13.6 TEST RESULT71
14. ANTENNA APPLICATION80
14.1 ANTENNA REQUIREMENT80
14.2 RESULT.....80

APPENDIX I (PHOTOS OF EUT)(3PAGES)

1. General Information

1.1 Product Description

Characteristics	Description
Modulation	802.11b: DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM(BPSK/QPSK/16QAM/64QAM) 802.11ac:OFDM(BPSK/QPSK/16QAM/64QAM/256QAM)
Operating Frequency Range	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40) 5745-5825MHz for 802.11a/n/ac
Number of Channels	<u>For 2.4GHz Band:</u> 11 for 20MHz bandwidth; 7 for 40MHz bandwidth <u>For 5GHz Band:</u> 5 for 20MHz bandwidth; 2 for 40MHz bandwidth; 1 for 80MHz bandwidth
Transmit Power Max	<u>For 2.4GHz Band:</u> 802.11b: 17.42dBm(0.055208W) 802.11g: 14.59dBm (0.028774W) 802.11n(HT20): 12.62dBm(0.018281W) 802.11n(HT40): 11.85dBm (0.015311W) <u>For 5GHz Band:</u> 802.11a: 13.59dBm(0.022856W) 802.11n(HT20): 11.45dBm(0.013964W) 802.11n(HT40): 10.42dBm(0.011015W) 802.11ac(HT20): 9.03dBm(0.007998W) 802.11ac(HT40): 8.42dBm(0.006850W) 802.11ac(HT80): 5.73dBm(0.003741W)
Antenna Port	<input checked="" type="checkbox"/> Ant0(TX2.4G); <input checked="" type="checkbox"/> Ant1(TX2.4G); <input checked="" type="checkbox"/> Ant2(TX5G); <input type="checkbox"/> Ant3; <input type="checkbox"/> Ant4
Antenna Gain	5.0dBi (for per antenna port Max) 8.01dBi for MIMO(Ant0+Ant1 Directional Gain)
Power Supply for Adapter	Model: JY-12100 Input: AC 100-240V~50/60Hz 0.5A Output:DC 12V 1A

Note: for more details, please refer to the User's manual of the EUT.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2014.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	750Mbps Wireless Dual Band 11AC Router	LB-LINK	BL-WDR3750	S8J-WDR3750	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

For 2.4G Band:

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1-Channel 11.

For 40MHz band width systems, use Channel 3-Channel 9.

Frequency Band	Channel	Frequency (MHz)	Channel	Frequency (MHz)
2400-2483.5MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

For 5G Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165

For 40MHz band width systems, use Channel 151, 159

For 40MHz band width systems, use Channel 157

Frequency Band	Channel	Frequency (MHz)	Channel	Frequency (MHz)
5725-5850MHz Band 4	149	5745	157	5785
	151	5755	159	5795
	153	5765	161	5805
	155	5775	165	5825

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

Test Frequency and channel for 5725-5850MHz Band 4:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785	165	5825

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: S8J-WDR3750 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure

5. Test Methodology

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

6. Test Facility

Site Description

EMC Lab : Accredited by FCC, June 18, 2014
The Certificate Number is 247565

Accredited by Industry Canada, February 19, 2014
The Certificate Number is 9444A

Name of Firm : DONGGUAN EMTEK CO., LTD.
Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

7. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%

8. Conducted Emissions Test

8.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde&Schwarz	ESCS30	100018	May 16, 2014	1 Year
2.	L.I.S.N.	Rohde&Schwarz	ENV216	100017	May 16, 2014	1Year
3.	RF Switching Unit	CDS	RSU-M2	38401	May 16, 2014	1Year


8.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

- Note:** 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.5 Measurement Result


Please refer to following pages.



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.4300	40.41	10.17	50.58	57.25	-6.67	QP	
2		0.4300	17.07	10.17	27.24	47.25	-20.01	AVG	
3		0.8460	29.70	10.18	39.88	56.00	-16.12	QP	
4		0.8460	5.58	10.18	15.76	46.00	-30.24	AVG	
5		1.2340	32.70	10.18	42.88	56.00	-13.12	QP	
6		1.2340	7.06	10.18	17.24	46.00	-28.76	AVG	
7		1.4940	32.99	10.17	43.16	56.00	-12.84	QP	
8		1.4940	6.77	10.17	16.94	46.00	-29.06	AVG	
9		2.5660	34.32	10.15	44.47	56.00	-11.53	QP	
10		2.5660	10.76	10.15	20.91	46.00	-25.09	AVG	
11		2.6140	34.52	10.15	44.67	56.00	-11.33	QP	
12		2.6140	8.96	10.15	19.11	46.00	-26.89	AVG	


*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: QIU



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	35.01	10.11	45.12	66.00	-20.88	QP	
2		0.1500	22.02	10.11	32.13	56.00	-23.87	AVG	
3		0.4140	35.16	10.17	45.33	57.57	-12.24	QP	
4		0.4140	18.54	10.17	28.71	47.57	-18.86	AVG	
5		0.8580	29.56	10.18	39.74	56.00	-16.26	QP	
6		0.8580	13.42	10.18	23.60	46.00	-22.40	AVG	
7		1.4300	27.24	10.17	37.41	56.00	-18.59	QP	
8		1.4300	12.49	10.17	22.66	46.00	-23.34	AVG	
9	*	2.7300	34.84	10.15	44.99	56.00	-11.01	QP	
10		2.7300	17.07	10.15	27.22	46.00	-18.78	AVG	
11		7.0660	32.87	10.14	43.01	60.00	-16.99	QP	
12		7.0660	18.54	10.14	28.68	50.00	-21.32	AVG	


*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: QIU



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/60Hz Humidity: 55 %
 Mode: TX
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4050	37.27	0.00	37.27	57.75	-20.48	QP	
2	*	0.4050	33.61	0.00	33.61	47.75	-14.14	AVG	
3		1.1300	36.82	0.00	36.82	56.00	-19.18	QP	
4		1.1300	26.03	0.00	26.03	46.00	-19.97	AVG	
5		1.8850	39.94	0.00	39.94	56.00	-16.06	QP	
6		1.8850	30.45	0.00	30.45	46.00	-15.55	AVG	
7		2.4400	37.96	0.00	37.96	56.00	-18.04	QP	
8		2.4400	28.95	0.00	28.95	46.00	-17.05	AVG	
9		4.8800	37.53	0.00	37.53	56.00	-18.47	QP	
10		4.8800	28.80	0.00	28.80	46.00	-17.20	AVG	
11		16.1750	37.38	0.00	37.38	60.00	-22.62	QP	
12		16.1750	27.76	0.00	27.76	50.00	-22.24	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver.



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/60Hz Humidity: 55 %
 Mode: TX
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4500	40.40	0.00	40.40	56.88	-16.48	QP	
2	*	0.4500	38.63	0.00	38.63	46.88	-8.25	AVG	
3		0.9050	37.86	0.00	37.86	56.00	-18.14	QP	
4		0.9050	32.07	0.00	32.07	46.00	-13.93	AVG	
5		1.4300	39.24	0.00	39.24	56.00	-16.76	QP	
6		1.4300	27.80	0.00	27.80	46.00	-18.20	AVG	
7		1.7550	40.09	0.00	40.09	56.00	-15.91	QP	
8		1.7550	35.66	0.00	35.66	46.00	-10.34	AVG	
9		4.0100	39.12	0.00	39.12	56.00	-16.88	QP	
10		4.0100	29.61	0.00	29.61	46.00	-16.39	AVG	
11		6.1200	36.51	0.00	36.51	60.00	-23.49	QP	
12		6.1200	27.10	0.00	27.10	50.00	-22.90	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver.

9. Radiated Emission Test

9.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

9.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



9.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Spectrum Analyzer	HP	E4407B	839840481	05/16/2014	05/15/2015
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2014	05/15/2015
Pre-Amplifier	HP	8447D	2944A07999	05/16/2014	05/15/2015
Bilog Antenna	Schwarzbeck	VULB9163	142	05/19/2014	05/18/2015
Loop Antenna	Schwarzbeck	FMZB 1519	012	05/19/2014	05/18/2015
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/19/2014	05/18/2015
Horn Antenna	Schwarzbeck	BBHA9120D	D143	05/19/2014	05/18/2015
Spectrum Analyzer	Agilent	E4446A	US44300399	05/16/2014	05/15/2015

9.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark 1. Emission level in dBuV/m=20 log (uV/m)
: 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

9.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	March 08, 2015
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (ANT0: TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:



Site: Chamber #1
 Limit: (RE)FCC PART 15 class B 3m
 Mode: TX2412
 Note:


Polarization: **Horizontal**
 Power: AC 120V/60Hz

Temperature: 24
 Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		63.9827	45.27	-20.56	24.71	40.00	-15.29	QP		
2	*	97.9000	55.85	-19.47	36.38	43.50	-7.12	QP		
3		147.3700	53.08	-17.56	35.52	43.50	-7.98	QP		
4		193.9300	53.26	-17.97	35.29	43.50	-8.21	QP		
5		227.8800	51.38	-16.05	35.33	46.00	-10.67	QP		
6		250.1900	45.64	-15.48	30.16	46.00	-15.84	QP		

*:Maximum data x:Over limit !:over margin

Operator: Snake




Site Chamber #1 Polarization: **Vertical** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		34.8500	45.80	-14.19	31.61	40.00	-8.39	QP		
2	!	97.9000	57.90	-19.47	38.43	43.50	-5.07	QP		
3	!	106.6300	56.30	-17.99	38.31	43.50	-5.19	QP		
4		125.0600	52.90	-16.40	36.50	43.50	-7.00	QP		
5	*	142.5200	56.40	-17.22	39.18	43.50	-4.32	QP		
6		193.9300	54.30	-17.97	36.33	43.50	-7.17	QP		

*:Maximum data x:Over limit !:over margin

Operator: Snake




Site Chamber #1 Polarization: **Horizontal** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2437
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		97.9000	55.70	-19.47	36.23	43.50	-7.27	QP		
2		106.7587	52.80	-17.98	34.82	43.50	-8.68	QP		
3		147.3700	54.30	-17.56	36.74	43.50	-6.76	QP		
4	*	193.9300	55.10	-17.97	37.13	43.50	-6.37	QP		
5		227.8800	51.90	-16.05	35.85	46.00	-10.15	QP		
6		500.4500	40.40	-10.35	30.05	46.00	-15.95	QP		

*:Maximum data x:Over limit !:over margin

Operator: Snake




Site: Chamber #1 Polarization: **Vertical** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2437
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	62.0100	54.60	-19.98	34.62	40.00	-5.38	QP		
2	!	97.9000	57.25	-19.47	37.78	43.50	-5.72	QP		
3		125.0600	53.36	-16.40	36.96	43.50	-6.54	QP		
4		142.8240	54.68	-17.25	37.43	43.50	-6.07	QP		
5		193.9300	55.42	-17.97	37.45	43.50	-6.05	QP		
6		210.4200	46.54	-16.99	29.55	43.50	-13.95	QP		

*:Maximum data x:Over limit !:over margin

Operator: Snake




Site Chamber #1 Polarization: **Horizontal** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2462
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		30.3170	44.40	-15.07	29.33	40.00	-10.67			QP
2		97.9000	50.30	-19.47	30.83	43.50	-12.67			QP
3	*	106.7587	51.90	-17.98	33.92	43.50	-9.58			QP
4		142.5200	50.70	-17.22	33.48	43.50	-10.02			QP
5		189.0800	51.10	-18.35	32.75	43.50	-10.75			QP
6		235.6400	49.60	-15.87	33.73	46.00	-12.27			QP

*:Maximum data x:Over limit !:over margin

Operator: Snake



Site Chamber #1 Polarization: **Vertical** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2462
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		96.0985	53.80	-19.80	34.00	43.50	-9.50	QP			
2		104.6900	54.20	-18.26	35.94	43.50	-7.56	QP			
3		110.5686	52.70	-17.53	35.17	43.50	-8.33	QP			
4		125.0600	53.50	-16.40	37.10	43.50	-6.40	QP			
5	*	137.6700	54.30	-16.79	37.51	43.50	-5.99	QP			
6		193.9300	53.70	-17.97	35.73	43.50	-7.77	QP			

*:Maximum data x:Over limit !:over margin

Operator: Snake

Above 1000MHz:

Operation Mode: 802.11b Lowest Test Date : March 08, 2015

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	65.03	45.72	74	54	-8.97	-8.28
7236	V	64.18	44.05	74	54	-9.82	-9.95
9648	V	63.59	43.19	74	54	-10.41	-10.81
12060	V	62.04	42.95	74	54	-11.96	-11.05
14472	V	61.82	41.75	74	54	-12.18	-12.25
16884	V	60.89	40.22	74	54	-13.11	-13.78
4824	H	66.78	45.12	74	54	-7.22	-8.88
7236	H	65.19	44.03	74	54	-8.81	-9.97
9648	H	64.07	43.92	74	54	-9.93	-10.08
12060	H	63.85	42.71	74	54	-10.15	-11.29
14472	H	62.79	41.09	74	54	-11.21	-12.91
16884	H	60.57	40.78	74	54	-13.43	-13.22

Operation Mode: 802.11b Middle Test Date : March 08, 2015

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	66.33	45.72	74	54	-7.67	-8.28
7311	V	65.71	44.15	74	54	-8.29	-9.85
9688	V	64.19	43.95	74	54	-9.81	-10.05
12185	V	63.85	42.85	74	54	-10.15	-11.15
14622	V	62.79	41.62	74	54	-11.21	-12.38
17059	V	60.59	40.72	74	54	-13.41	-13.28
4874	H	65.12	46.13	74	54	-8.88	-7.87
7311	H	65.78	45.95	74	54	-8.22	-8.05
9688	H	64.96	44.13	74	54	-9.04	-9.87
12185	H	63.01	43.05	74	54	-10.99	-10.95
14622	H	62.74	42.56	74	54	-11.26	-11.44
17059	H	61.95	41.79	74	54	-12.05	-12.21

Operation Mode: 802.11b Highest

Test Date : March 08, 2015

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	63.55	45.72	74	54	-10.45	-8.28
7386	V	62.74	44.15	74	54	-11.26	-9.85
9848	V	61.05	43.92	74	54	-12.95	-10.08
12310	V	60.89	42.05	74	54	-13.11	-11.95
14772	V	59.74	41.72	74	54	-14.26	-12.28
17234	V	58.23	40.36	74	54	-15.77	-13.64
4924	H	65.78	46.85	74	54	-8.22	-7.15
7386	H	64.35	45.72	74	54	-9.65	-8.28
9848	H	63.92	44.72	74	54	-10.08	-9.28
12310	H	62.45	43.19	74	54	-11.55	-10.81
14772	H	61.04	42.08	74	54	-12.96	-11.92
17234	H	60.59	40.94	74	54	-13.41	-13.06

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20Db below the permissible limits or the field strength is too small to be measured.


10. 6dB Bandwidth Test

10.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015

10.4 Measurement Results

6 Bandwidth Test Data Chart:

Spectrum Detector:	PK	Test Date :	March 08, 2015
Test By:	Andy	Temperature :	28°C
Humidity :	60%		

Refer to attached data chart.

For 2.4GHz Band:

IEEE 802.11b SISO Ant0			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	10050	>500	Pass
2437	9071	>500	
2462	9191	>500	

IEEE 802.11b SISO Ant1			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	9071	>500	Pass
2437	9271	>500	
2462	10050	>500	

IEEE 802.11g SISO Ant0			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	16464	>500	Pass
2437	16484	>500	
2462	16344	>500	

IEEE 802.11g SISO Ant1			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	16304	>500	Pass
2437	16464	>500	
2462	16444	>500	

IEEE 802.11n(HT20) MIMO				
Channel frequency (MHz)	Measurement level (KHz)		Required Limit (KHz)	Result
	Ant0	Ant1		
2412	17584	17622	>500	Pass
2437	17582	17582	>500	
2462	17622	17043	>500	

IEEE 802.11n (HT40) MIMO				
Channel frequency (MHz)	Measurement level (KHz)		Required Limit (KHz)	Result
	Ant0	Ant1		
2422	36004	36004	>500	Pass
2437	36364	36004	>500	
2452	36364	35764	>500	

For 5GHz Band:

IEEE 802.11a			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
5745	10030	>500	Pass
5785	9750	>500	
5825	9790	>500	

IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
5745	16903	>500	Pass
5785	17003	>500	
5825	17243	>500	

IEEE 802.11n(HT40)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
5755	35604	>500	Pass
5795	35485	>500	

IEEE 802.11ac(HT20)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
5745	16304	>500	Pass
5785	16324	>500	
5825	16324	>500	


IEEE 802.11ac(HT40)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
5755	35604	>500	Pass
5795	35884	>500	

IEEE 802.11ac(HT80)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
5785	75205	>500	Pass


Note: All the test values were listed in the report.

For plots, only the channels with worst result was shown.


6dB Bandwidth Plot on Configuration IEEE 802.11b/2437MHz(Ant0)




6dB Bandwidth Plot on Configuration IEEE 802.11b/2462MHz(Ant0)




6dB Bandwidth Plot on Configuration IEEE 802.11b/2412MHz(Ant1)




6dB Bandwidth Plot on Configuration IEEE 802.11b/2437MHz(Ant1)




6dB Bandwidth Plot on Configuration IEEE 802.11n(HT20) MIMO /2462MHz




6dB Bandwidth Plot on Configuration IEEE 802.11n(HT40)/2412MHz




6dB Bandwidth Plot on Configuration IEEE 802.11a/5785MHz




6dB Bandwidth Plot on Configuration IEEE 802.11n(HT20)/5745MHz




6dB Bandwidth Plot on Configuration IEEE 802.11n(HT40)/5795MHz




6dB Bandwidth Plot on Configuration IEEE 802.11ac(HT20)/5745MHz



6dB Bandwidth Plot on Configuration IEEE 802.11ac(HT40)/5755MHz



6dB Bandwidth Plot on Configuration IEEE 802.11ac(HT80)/5785MHz



11. Maximum Peak Output Power Test

11.1 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/16/2014	05/15/2015
Power sensor	MA2411B	0738172	05/16/2014	05/15/2015

11.4 Peak Power output limit

For systems using digital modulation in the 2400-2483.5MHz and 5725-5850MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6dBi. In case of point-to-point operation. The limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

11.5 Measurement Results

Spectrum Detector: PK Test Date : March 08, 2015
 Test By: Andy Temperature : 28°C
 Test Result: PASS Humidity : 60%

For 2.4GHz Band:

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)			Limit (dBm)	Verdict
			Ant0	Ant1	Sum		
802.11b	1	2412	17.42	17.02	--	30	PASS
	6	2437	16.05	15.22	--	30	PASS
	11	2462	15.72	14.52	--	30	PASS
802.11g	1	2412	14.59	13.05	--	30	PASS
	6	2437	12.68	12.49	--	30	PASS
	11	2462	11.45	11.41	--	30	PASS
802.11n (HT20)	1	2412	9.42	9.12	12.28	28	PASS
	6	2437	9.86	9.35	12.62	28	PASS
	11	2462	8.05	9.42	11.80	28	PASS
802.11n (HT40)	3	2422	7.06	7.42	10.25	28	PASS
	6	2437	8.42	7.69	11.08	28	PASS
	9	2452	9.42	8.16	11.85	28	PASS

Note:

1. For MIMO System of 802.11n(HT20) and 802.11n(HT40), total power is calculated by combining the output power of each antenna according to KDB662911.
2. Antenna 0 Gain: 5dBi, Antenna 1 Gain: 5dBi. For antennas with gains of 6dBi or less, maximum allowed Transmitter output watt(+30dBm)
3. In MIMO, Ant0+Ant1 Directional Gain= $G_{ANT}+10\text{Log}(N)\text{dBi}=5+10\log(2)=8.01\text{dBi}$. so the Power limit will reduce to 28dBm(630mW).

For 5GHz Band:

Test Channel	Max Output Power (dBm)						Limit (dBm)	Result
	802.11a	802.11n (HT20)	802.11n (HT40)	802.11ac (HT20)	802.11ac (HT40)	802.11a (HT80)		
Lowest	12.40	11.45	10.42	8.46	8.42	5.73	30	Pass
Middle	11.04	10.59	8.05	9.03	7.06			
Highest	13.59	9.42		7.46	6.45			

12. Band Edge Test

12.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.


When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

12.2 Test SET-UP (Block Diagram of Configuration)



12.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015

12.4 Measurement Results


All the test values wer listed in the report.

For plots, only the channel with worst result was shown.



For 2.4G Band


1. Conducted Test

Test Mode: IEEE 802.11b SISO Ant0




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11b SISO Ant1




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11g SISO Ant0




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11g SISO Ant1




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11n(HT20) MIMO




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11n(HT40) MIMO



Lowest Channel








Lowest Channel


For 5G Band

Test Mode: IEEE 802.11a




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11n(HT20)




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11n(HT40)




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11ac(HT20)




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11ac(HT40)




Lowest Channel








Lowest Channel

Test Mode: IEEE 802.11ac(HT80)







2. Radiated emission Test

Spectrum Detector: PK/AV Test Date : March 08, 2015
 Test By: Andy Temperature : 28 °C
 Humidity : 65 %

IEEE 802.11b SISO Ant0							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	65.03	45.05	74	54	-8.97	-8.95
<2400	V	60.49	38.72	74	54	-13.51	-15.28
>2483.5	H	63.59	44.16	74	54	-10.41	-9.84
>2483.5	V	57.28	39.45	74	54	-16.72	-14.55

IEEE 802.11b SISO Ant1							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	64.79	44.15	74	54	-9.21	-9.85
<2400	V	60.28	40.75	74	54	-13.72	-13.25
>2483.5	H	66.13	45.92	74	54	-7.87	-8.08
>2483.5	V	59.73	39.18	74	54	-14.27	-14.82

IEEE 802.11g SISO Ant0							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	63.59	45.13	74	54	-10.41	-8.87
<2400	V	57.05	42.03	74	54	-16.95	-11.97
>2483.5	H	64.82	46.92	74	54	-9.18	-7.08
>2483.5	V	61.49	40.72	74	54	-12.51	-13.28

IEEE 802.11g SISO Ant1							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	65.79	45.28	74	54	-8.21	-8.72
<2400	V	60.59	41.79	74	54	-13.41	-12.21
>2483.5	H	63.59	40.19	74	54	-10.41	-13.81
>2483.5	V	59.65	36.59	74	54	-14.35	-17.41

IEEE 802.11n(HT20) MIMO							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	63.49	45.72	74	54	-10.51	-8.28
<2400	V	58.72	40.95	74	54	-15.28	-13.05
>2483.5	H	64.18	45.79	74	54	-9.82	-8.21
>2483.5	V	59.28	39.58	74	54	-14.72	-14.42

IEEE 802.11n(HT40) MIMO							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	65.32	45.08	74	54	-8.68	-8.92
<2400	V	60.95	40.59	74	54	-13.05	-13.41
>2483.5	H	63.74	46.82	74	54	-10.26	-7.18
>2483.5	V	57.49	41.72	74	54	-16.51	-12.28

13. Maximum Power Spectral Density

13.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015

13.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3KHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

13.3 Test Procedures

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- d. Set the RBW=3KHz. Set the VBW=10KHz
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level.

13.4 Block Diagram of Test Setup



13.5 Limit

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

13.6 Test Result

Spectrum Detector: PK Test Date : March 08, 2015
 Test By: Andy Temperature : 28°C
 Humidity : 60%

For 2.4GHz Band:

IEEE 802.11b SISO Ant0			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	2.28	8	Pass
2437	1.83		
2462	-0.61		

IEEE 802.11b SISO Ant1			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-3.75	8	Pass
2437	-0.92		
2462	-2.55		

IEEE 802.11g SISO Ant0			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	0.41	8	Pass
2437	-2.36		
2462	-3.04		

IEEE 802.11g SISO Ant1			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-8.37	8	Pass
2437	-7.55		
2462	-5.04		

IEEE 802.11n(HT20) MIMO(Antenna Gain=8.01dBi)					
Channel frequency (MHz)	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
	Ant0	Ant1	Total		
2412	-2.14	-4.59	-0.18	6	Pass
2437	-2.80	-6.99	-1.40		
2462	-0.58	-8.58	0.06		
Note: In MIMO, Ant0+Ant1 Directional Gain= $G_{ant}+10\log(N)$ dBi=5+10Log(2)=8.01dBi. Directional Gain was according to KDB662911.					

IEEE 802.11n(HT40) MIMO(Antenna Gain=8.01dBi)					
Channel frequency (MHz)	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
	Ant0	Ant1	Total		
2422	-5.73	-10.20	-4.40	6	Pass
2437	-6.45	-10.24	-4.93		
2452	-6.93	-10.88	-5.46		
Note: In MIMO, Ant0+Ant1 Directional Gain= $G_{ant}+10\log(N)$ dBi=5+10Log(2)=8.01dBi. Directional Gain was according to KDB662911.					

For 5GHz Band:

IEEE 802.11a			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
5745	-15.79	8	Pass
5785	-16.33		
5825	-18.25		

IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
5745	-14.93	8	Pass
5785	-16.50		
5825	-16.40		

IEEE 802.11n(HT40)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
5755	-17.39	8	Pass
5795	-18.59		


IEEE 802.11ac(HT20)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
5745	-14.99	8	Pass
5785	-16.01		
5825	-16.35		

IEEE 802.11ac(HT40)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
5755	-16.67	8	Pass
5795	-18.59		


IEEE 802.11ac(HT80)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
5785	-20.87	8	Pass

Note: All the test values wer listed in the report.
For plots, only the channel with worst result was shown.


Power Density Plot on Configuration IEEE 802.11b/2462MHz SISO Ant0




Power Density Plot on Configuration IEEE 802.11b/2412MHz SISO Ant1




Power Density Plot on Configuration IEEE 802.11g/2462MHz SISO Ant0




Power Density Plot on Configuration IEEE 802.11g/2412MHz SISO Ant1




Power Density Plot on Configuration IEEE 802.11n(HT20)/2412MHz MIMO




Power Density Plot on Configuration IEEE 802.11n(HT40)/2452MHz MIMO




Power Density Plot on Configuration IEEE 802.11a/5825MHz




Power Density Plot on Configuration IEEE 802.11n(HT20)/5785MHz




Power Density Plot on Configuration IEEE 802.11n(HT40)/5795MHz




Power Density Plot on Configuration IEEE 802.11ac(HT20)/5825MHz



Power Density Plot on Configuration IEEE 802.11ac(HT40)/5795MHz



Power Density Plot on Configuration IEEE 802.11ac(HT80)/5785MHz



14. Antenna Application

14.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

14.2 Result

The EUT'S antenna, permanent attach antenna, is external antenna. The antenna's gain is 5dBi and meets the requirement.

APPENDIX I (PHOTOS OF EUT)



