

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

300Mbps High Gain Wireless N Router

Model No.: BL-WR4300H

FCC ID: S8J-WR4300H

Trademark: LB-LINK

Report No.: KAD141127096E

Issue Date: January 26, 2015

Prepared for

**Shenzhen Bilian Electronic Co., Ltd.
Building B1, Zhongxing Industrial Zone, Juling Jutang Community,
Guanlan street, Bao'an, Shenzhen China**

Prepared by

**DONGGUAN EMTEK CO., LTD.
No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

**This report shall not be reproduced, except in full, without the written approval of
DONGGUAN EMTEK CO., LTD.**

VERIFICATION OF COMPLIANCE

Applicant:	Shenzhen Bilian Electronic Co., Ltd. Building B1, Zhongxing Industrial Zone, Juling Jutang Community, Guanlan street, Bao'an, Shenzhen China
Manufacturer:	Shenzhen Bilian Electronic Co., Ltd. Building B1, Zhongxing Industrial Zone, Juling Jutang Community, Guanlan street, Bao'an, Shenzhen China
Product Description:	300Mbps High Gain Wireless N Router
Model Number:	BL-WR4300H
Trade Mark:	LB-LINK
Date of Test:	November 27, 2014 to January 04, 2015

We hereby certify that:

The above equipment was tested by DONGGUAN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2014) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2014).

Approved By



Sam Lv / Q.A. Manager
DONGGUAN EMTEK CO., LTD.

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	KAD141127096E

Table of Contents

1. GENERAL INFORMATION.....	6
1.1 PRODUCT DESCRIPTION	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3. DESCRIPTION OF TEST MODES	8
4. SUMMARY OF TEST RESULTS	9
5. TEST METHODOLOGY.....	9
6. TEST FACILITY	9
7. TEST SYSTEM UNCERTAINTY.....	10
8. CONDUCTED EMISSIONS TEST	11
8.1 MEASUREMENT PROCEDURE	11
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	11
8.3 MEASUREMENT EQUIPMENT USED	11
8.4 CONDUCTED EMISSION LIMIT	11
8.5 MEASUREMENT RESULT	11
9. RADIATED EMISSION TEST	14
9.1 MEASUREMENT PROCEDURE	14
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	15
9.3 MEASUREMENT EQUIPMENT USED	16
9.4 RADIATED EMISSION LIMIT	16
9.5 MEASUREMENT RESULT	18
10. 6DB BANDWIDTH TEST.....	27
10.1 MEASUREMENT PROCEDURE	27
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	27
10.3 MEASUREMENT EQUIPMENT USED	27
10.4 MEASUREMENT RESULTS	27
11. MAXIMUM PEAK OUTPUT POWER TEST	43
11.1 MEASUREMENT PROCEDURE	43
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	43
11.3 MEASUREMENT EQUIPMENT USED	43
11.4 PEAK POWER OUTPUT LIMIT	43
11.5 MEASUREMENT RESULTS.....	44
12. BAND EDGE TEST.....	45
12.1 MEASUREMENT PROCEDURE	45
12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	46
12.3 MEASUREMENT EQUIPMENT USED	46
12.4 MEASUREMENT RESULTS	46
13. MAXIMUM POWER SPECTRAL DENSITY	66
13.1 TEST EQUIPMENT.....	66
13.2 MEASURING INSTRUMENTS AND SETTING	66
13.3 TEST PROCEDURES	66

13.4 BLOCK DIAGRAM OF TEST SETUP	66
13.5 LIMIT	66
13.6 TEST RESULT.....	67
14. ANTENNA PORT EMISSION	83
14.1 TEST EQUIPMENT.....	83
14.2 MEASURING INSTRUMENTS AND SETTING	83
14.3 TEST PROCEDURES	83
14.4 BLOCK DIAGRAM OF TEST SETUP	83
14.5 TEST RESULT.....	83
15. ANTENNA APPLICATION	93
15.1 ANTENNA REQUIREMENT	93
15.2 RESULT	93

APPENDIX I (PHOTOS OF EUT)(3PAGES)

1. General Information

1.1 Product Description

Characteristics	Description
IEEE 802.11 WLAN Mode Supported	<input checked="" type="checkbox"/> 802.11b(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11g(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11n(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11n(40MHz channel bandwidth)
Data Rate	802.11 b:1,2,5.5,11Mbps; 802.11 g:6,9,12,18,24,36,48,54Mbps; 802.11n(H20):MCS0-MCS7; 802.11n(H40):MCS0-MCS7; 802.11n(H40):MCS8-MCS15;
MIMO Mode	802.11n(H20), 802.11n(H40)
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range	2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels	11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40);
Transmit Power Max	17.65dBm for 802.11b; 14.05dBm for 802.11g; 16.03dBm for 802.11n(HT20); 14.84dBm for 802.11n(HT40);
Antenna Type	2TX2RX
Antenna Port	<input checked="" type="checkbox"/> Ant0; <input checked="" type="checkbox"/> Ant1; <input type="checkbox"/> Ant2; <input type="checkbox"/> Ant3
Smart system	<input checked="" type="checkbox"/> SISO for 802.11b/g <input checked="" type="checkbox"/> MIMO for 802.11n
Antenna Gain	5.0dBi (for per antenna port Max) 8.01dBi for MIMO(Ant0+Ant1 Directional Gain)
Power Supply for Adapter	Model: JY-12100 Input: AC 100-240V~50/60Hz 0.5A Output:DC 12V 1A

Note: for more details, please refer to the User's manual of the EUT.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2014 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2014.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	300Mbps High Gain Wireless N Router	LB-LINK	BL-WR4300H	S8J-WR4300H	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS8) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: S8J-WN4300H filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure

5. Test Methodology

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

6. Test Facility

Site Description

EMC Lab : Accredited by FCC, June 18, 2014
The Certificate Number is 247565

Accredited by Industry Canada, February 19, 2014
The Certificate Number is 9444A

Name of Firm : DONGGUAN EMTEK CO., LTD.
Site Location : No.281, Guantai Road, Nancheng District,
Donguan, Guangdong, China

7. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Power Density	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%

8. Conducted Emissions Test

8.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde&Schwarz	ESCS30	100018	May 16, 2014	1 Year
2.	L.I.S.N.	Rohde&Schwarz	ENV216	100017	May 16, 2014	1Year
3.	RF Switching Unit	CDS	RSU-M2	38401	May 16, 2014	1Year

8.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.5 Measurement Result


Please refer to following pages.



Site site #1	Phase: L1	Temperature: 24
Limit: (CE)FCC PART 15 class B_QP	Power: AC 120V/60Hz	Humidity: 55 %
Mode: TX		
Note:		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
			MHz	dBuV	dB	dBuV	dB	Detector
1		0.2000	48.62	0.00	48.62	63.61	-14.99	QP
2		0.2000	26.65	0.00	26.65	53.61	-26.96	AVG
3		0.2600	47.36	0.00	47.36	61.43	-14.07	QP
4		0.2600	30.64	0.00	30.64	51.43	-20.79	AVG
5		0.4650	45.98	0.00	45.98	56.60	-10.62	QP
6		0.4650	21.81	0.00	21.81	46.60	-24.79	AVG
7		1.6100	44.30	0.00	44.30	56.00	-11.70	QP
8		1.6100	29.69	0.00	29.69	46.00	-16.31	AVG
9 *		2.2400	48.55	0.00	48.55	56.00	-7.45	QP
10		2.2400	31.62	0.00	31.62	46.00	-14.38	AVG
11		2.3800	46.66	0.00	46.66	56.00	-9.34	QP
12		2.3800	28.86	0.00	28.86	46.00	-17.14	AVG

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver.



Site site #1 Phase: **N** Temperature: 24
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
Mode: TX
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.2650	48.30	0.00	48.30	61.27	-12.97	QP	
2		0.2650	27.62	0.00	27.62	51.27	-23.65	AVG	
3		0.4650	44.28	0.00	44.28	56.60	-12.32	QP	
4		0.4650	25.56	0.00	25.56	46.60	-21.04	AVG	
5		1.6700	45.09	0.00	45.09	56.00	-10.91	QP	
6		1.6700	35.45	0.00	35.45	46.00	-10.55	AVG	
7		1.9550	45.07	0.00	45.07	56.00	-10.93	QP	
8 *		1.9550	35.76	0.00	35.76	46.00	-10.24	AVG	
9		3.2410	44.66	0.00	44.66	56.00	-11.34	QP	
10		3.2410	30.01	0.00	30.01	46.00	-15.99	AVG	
11		5.3200	44.90	0.00	44.90	60.00	-15.10	QP	
12		5.3200	30.08	0.00	30.08	50.00	-19.92	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver.

9. Radiated Emission Test

9.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

9.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



9.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Spectrum Analyzer	HP	E4407B	839840481	05/16/2014	05/15/2015
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2014	05/15/2015
Pre-Amplifier	HP	8447D	2944A07999	05/16/2014	05/15/2015
Bilog Antenna	Schwarzbeck	VULB9163	142	05/19/2014	05/18/2015
Loop Antenna	Schwarzbeck	FMZB 1519	012	05/19/2014	05/18/2015
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/19/2014	05/18/2015
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/19/2014	05/18/2015
Spectrum Analyzer	Agilent	E4446A	US44300399	05/16/2014	05/15/2015

9.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table15.209(a):

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

- : 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

9.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	December 24, 2014
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--


Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (ANT 1: TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		30.0000	42.92	-15.15	27.77	40.00	-12.23	QP			
2		53.2800	44.48	-16.70	27.78	40.00	-12.22	QP			
3		63.9500	44.94	-20.56	24.38	40.00	-15.62	QP			
4		80.4400	47.89	-22.43	25.46	40.00	-14.54	QP			
5		221.0900	47.02	-16.15	30.87	46.00	-15.13	QP			
6	*	500.4500	45.50	-10.35	35.15	46.00	-10.85	QP			


*:Maximum data x:Over limit !:over margin

Operator: QIU



*:Maximum data x:Over limit !:over margin

Operator: QIU



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 class B 3m

Power: AC 120V/60Hz

Humidity: 55 %


Mode: TX2437

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		53.2800	43.11	-16.70	26.41	40.00	-13.59	QP		
2		63.9500	44.48	-20.56	23.92	40.00	-16.08	QP		
3		80.4400	47.23	-22.43	24.80	40.00	-15.20	QP		
4	*	222.0600	51.86	-16.16	35.70	46.00	-10.30	QP		
5		500.4500	45.17	-10.35	34.82	46.00	-11.18	QP		
6		823.4600	36.96	-4.44	32.52	46.00	-13.48	QP		

*:Maximum data x:Over limit !:over margin


Operator: QIU



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	32.9100	50.55	-14.46	36.09	40.00	-3.91	QP			
2	!	34.8500	48.30	-14.19	34.11	40.00	-5.89	QP			
3	!	40.6700	49.09	-13.64	35.45	40.00	-4.55	QP			
4		55.2200	50.72	-17.46	33.26	40.00	-6.74	QP			
5	!	63.9500	54.81	-20.56	34.25	40.00	-5.75	QP			
6		76.5600	54.81	-22.66	32.15	40.00	-7.85	QP			

*:Maximum data x:Over limit !:over margin


Operator: QIU



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		36.7900	39.42	-13.95	25.47	40.00	-14.53	QP		
2		53.2800	44.98	-16.70	28.28	40.00	-11.72	QP		
3		63.9500	44.04	-20.56	23.48	40.00	-16.52	QP		
4		80.4400	46.59	-22.43	24.16	40.00	-15.84	QP		
5	*	222.0600	51.65	-16.16	35.49	46.00	-10.51	QP		
6		500.4500	45.14	-10.35	34.79	46.00	-11.21	QP		

*:Maximum data x:Over limit !:over margin

Operator: QIU



Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	!	30.0000	50.30	-15.15	35.15	40.00	-4.85	QP			
2	*	34.8500	49.65	-14.19	35.46	40.00	-4.54	QP			
3	!	41.6400	47.61	-13.58	34.03	40.00	-5.97	QP			
4		47.4600	48.01	-14.38	33.63	40.00	-6.37	QP			
5		55.2200	50.76	-17.46	33.30	40.00	-6.70	QP			
6		63.9500	53.90	-20.56	33.34	40.00	-6.66	QP			

*:Maximum data x:Over limit !:over margin

Operator: QIU

Above 1000MHz:

Operation Mode: 802.11b Lowest Test Date : December 24, 2014

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	66.39	46.89	74	54	-7.61	-7.11
7236	V	65.72	45.33	74	54	-8.28	-8.67
9648	V	64.28	44.95	74	54	-9.72	-9.05
12060	V	63.95	43.72	74	54	-10.05	-10.28
14472	V	61.85	42.19	74	54	-12.15	-11.81
16884	V	60.78	41.08	74	54	-13.22	-12.92
4824	H	65.33	45.95	74	54	-8.67	-8.05
7236	H	64.82	44.22	74	54	-9.18	-9.78
9648	H	63.79	43.95	74	54	-10.21	-10.05
12060	H	62.85	42.17	74	54	-11.15	-11.83
14472	H	61.72	40.95	74	54	-12.28	-13.05
16884	H	60.33	37.59	74	54	-13.67	-16.41

Operation Mode: 802.11b Middle Test Date : December 24, 2014

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	67.33	46.38	74	54	-6.67	-7.62
7311	V	66.72	45.72	74	54	-7.28	-8.28
9688	V	65.95	44.19	74	54	-8.05	-9.81
12185	V	64.12	43.28	74	54	-9.88	-10.72
14622	V	63.72	42.19	74	54	-10.28	-11.81
17059	V	61.82	40.87	74	54	-12.18	-13.13
4874	H	66.72	45.92	74	54	-7.28	-8.08
7311	H	65.28	44.08	74	54	-8.72	-9.92
9688	H	64.72	43.67	74	54	-9.28	-10.33
12185	H	63.92	42.19	74	54	-10.08	-11.81
14622	H	62.19	41.08	74	54	-11.81	-12.92
17059	H	60.95	38.75	74	54	-13.05	-15.25

Operation Mode: 802.11b Highest

Test Date : December 24, 2014

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		H/V	PK	AV	PK	AV	PK
4924	V	65.35	46.72	74	54	-8.65	-7.28
7386	V	64.07	45.29	74	54	-9.93	-8.71
9848	V	63.92	44.19	74	54	-10.08	-9.81
12310	V	62.72	43.08	74	54	-11.28	-10.92
14772	V	61.08	42.72	74	54	-12.92	-11.28
17234	V	60.82	41.09	74	54	-13.18	-12.91
4924	H	66.38	46.28	74	54	-7.62	-7.72
7386	H	65.19	45.37	74	54	-8.81	-8.63
9848	H	64.08	44.19	74	54	-9.92	-9.81
12310	H	63.95	43.08	74	54	-10.05	-10.92
14772	H	62.72	42.19	74	54	-11.28	-11.81
17234	H	60.95	41.08	74	54	-13.05	-12.92

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20Db below the permissible limits or the field strength is too small to be measured.

10. 6dB Bandwidth Test

10.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11g, 802.11n(H20), 802.11n(H40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2014	05/15/2015

10.4 Measurement Results


6 Bandwidth Test Data Chart:



Refer to attached data chart.

Spectrum Detector: PK
Test By: Andy
Humidity : 60%


Test Date : December 24, 2014
Temperature : 28°C



IEEE 802.11b SISO Ant0			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	9011	>500	Pass
2437	8991	>500	
2462	8991	>500	








IEEE 802.11b SISO Ant1			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	8991	>500	Pass
2437	8991	>500	
2462	8991	>500	








IEEE 802.11g SISO Ant0			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	16404	>500	Pass
2437	16444	>500	
2462	16464	>500	






IEEE 802.11g SISO Ant1			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	17602	>500	Pass
2437	17602	>500	
2462	17602	>500	









IEEE 802.11n(H20) MIMO				
Channel frequency (MHz)	Measurement level (KHz)		Required Limit (KHz)	Result
	Ant0	Ant1		
2412	17582	16384	>500	Pass
2437	17582	16384	>500	
2462	17602	16444	>500	


Ant0







Ant1







IEEE 802.11n (H40) MIMO				
Channel frequency (MHz)	Measurement level (KHz)		Required Limit (KHz)	Result
	Ant0	Ant1		
2422	35644	35884	>500	Pass
2437	35644	36044	>500	
2452	35644	36244	>500	



Ant0





Ant1





11. Maximum Peak Output Power Test

11.1 Measurement Procedure

(1) According to FCC Part 15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The testing follows FCC public Notice DA 00-705 Measurement Guidelines.

The RF output of EUT was connected to the power meter by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

(2) According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain - 6)

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/16/2014	05/15/2015
Power sensor	MA2411B	0738172	05/16/2014	05/15/2015

11.4 Peak Power output limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

11.5 Measurement Results

Spectrum Detector: PK Test Date : December 24, 2014
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 60%

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)			Limit (dBm)	Verdict
			Ant0	Ant1	Sum		
802.11b	1	2412	17.65	17.53	--	30	PASS
	6	2437	16.82	15.49	--	30	PASS
	11	2462	15.04	14.72	--	30	PASS
802.11g	1	2412	13.42	14.05	--	30	PASS
	6	2437	12.69	13.69	--	30	PASS
	11	2462	11.82	11.43	--	30	PASS
802.11n (HT20)	1	2412	13.08	12.95	16.03	28	PASS
	6	2437	12.72	11.04	14.97	28	PASS
	11	2462	11.16	9.72	13.51	28	PASS
802.11n (HT40)	3	2422	12.16	11.48	14.84	28	PASS
	6	2437	10.74	10.69	13.73	28	PASS
	9	2452	9.85	9.46	12.67	28	PASS

Note:

1. For MIMO System of 802.11n(HT20) and 802.11n(HT40), total power is calculated by combining the output power of each antenna according to KDB662911.
2. Antenna 0 Gain: 5dBi, Antenna 3 Gain: 5dBi. For antennas with gains of 6dBi or less, maximum allowed Transmitter output watt(+30dBm)
3. In MIMO, $\text{Ant0+Ant1 Directional Gain} = G_{\text{ANT}} + 10\log(N)\text{dBi} = 5 + 10\log(2) = 8.01\text{dBi}$. so the Power limit will reduce to 28dBm(630mW).

12. Band Edge Test

12.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

12.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)


12.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.


12.4 Measurement Results

1. Conducted Test


Test Mode: IEEE 802.11b SISO Ant0





Lowest Channel




Middle Channel




Highest Channel




Test Mode: IEEE 802.11b SISO Ant1





Lowest Channel




Middle Channel




Highest Channel




Test Mode: IEEE 802.11g SISO Ant0





Lowest Channel




Middle Channel




Highest Channel




Test Mode: IEEE 802.11g SISO Ant1





Lowest Channel




Middle Channel




Highest Channel




Test Mode: IEEE 802.11n(H20) MIMO





Lowest Channel




Middle Channel




Highest Channel




Test Mode: IEEE 802.11n(H40) MIMO





Lowest Channel



Middle Channel



Highest Channel



2. Radiated emission Test

Spectrum Detector:	PK/AV	Test Date :	December 24, 2014
Test By:	Andy	Temperature :	28 °C
Humidity :	65 %		

IEEE 802.11b SISO Ant0							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	66.89	46.36	74	54	-7.11	-7.64
<2400	V	61.82	41.95	74	54	-12.18	-12.05
>2483.5	H	65.08	45.09	74	54	-8.92	-8.91
>2483.5	V	60.75	41.74	74	54	-13.25	-12.26

IEEE 802.11b SISO Ant1							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	65.08	45.05	74	54	-8.92	-8.95
<2400	V	61.72	41.09	74	54	-12.28	-12.91
>2483.5	H	66.33	44.35	74	54	-7.67	-9.65
>2483.5	V	60.82	39.72	74	54	-13.18	-14.28

IEEE 802.11g SISO Ant0							
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
<2400	H	65.13	45.33	74	54	-8.87	-8.67
<2400	V	60.72	40.72	74	54	-13.28	-13.28
>2483.5	H	64.38	46.38	74	54	-9.62	-7.62
>2483.5	V	60.72	39.82	74	54	-13.28	-14.18

IEEE 802.11g SISO Ant1						
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)
		PK	AV	PK	AV	
<2400	H	66.85	46.38	74	54	-7.15
<2400	V	60.71	40.82	74	54	-13.29
>2483.5	H	65.72	45.32	74	54	-8.28
>2483.5	V	59.72	39.87	74	54	-14.28
						-14.13

IEEE 802.11n(H20) MIMO						
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)
		PK	AV	PK	AV	
<2400	H	64.33	46.38	74	54	-9.67
<2400	V	60.72	40.85	74	54	-13.28
>2483.5	H	65.95	45.72	74	54	-8.05
>2483.5	V	59.31	39.48	74	54	-14.69
						-14.52

IEEE 802.11n(H40) MIMO						
Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)
		PK	AV	PK	AV	
<2400	H	66.33	46.35	74	54	-7.67
<2400	V	62.71	41.08	74	54	-11.29
>2483.5	H	65.95	45.72	74	54	-8.05
>2483.5	V	60.46	39.56	74	54	-13.54
						-14.44

13. Maximum Power Spectral Density

13.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2014	05/15/2015

13.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	100KHz
VB	300KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

13.3 Test Procedures

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- d. Set the RBW=3KHz. Set the VBW=10KHz
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level.

13.4 Block Diagram of Test Setup



13.5 Limit

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

13.6 Test Result

Spectrum Detector:

PK

Test By:

Andy


Humidity :



60%

Test Date : December 24, 2014


Temperature : 28°C



IEEE 802.11b SISO Ant0			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-5.70	8	Pass
2437	-7.15		
2462	-5.85		






IEEE 802.11b SISO Ant1			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-4.28	8	Pass
2437	-4.75		
2462	-4.57		








IEEE 802.11g SISO Ant0



Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-10.09	8	Pass
2437	-10.01		
2462	-10.87		





IEEE 802.11g SISO Ant1			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-8.87	8	Pass
2437	-9.20		
2462	-9.55		








IEEE 802.11n(H20) MIMO(Antenna Gain=8.01dBi)					
Channel frequency (MHz)	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
	Ant0	Ant1	Total		
2412	-10.82	-8.87	-6.72	6	Pass
2437	-10.13	-9.42	-6.75		
2462	-10.17	-8.69	-6.35		



Note: In MIMO, Ant0+Ant1 Directional Gain=G_{ant}+10Log(N)dBi=5+10Log(2)=8.01dBi.
 Directional Gain was according to KDB662911.


Ant0





Ant1








IEEE 802.11n(H40) MIMO(Antenna Gain=8.01dBi)					
Channel frequency (MHz)	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
	Ant0	Ant1	Total		
2422	-12.67	-9.30	-7.65	6	Pass
2437	-11.98	-10.61	-8.23		
2452	-12.11	-10.76	-8.37		



Note: In MIMO, Ant0+Ant1 Directional Gain=G_{ant}+10Log(N)dBi=5+10Log(2)=8.01dBi.
 Directional Gain was according to KDB662911.


Ant0





Ant1





14. Antenna Port Emission

14.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2014	05/15/2015

14.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

14.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

14.4 Block Diagram of Test setup




14.5 Test Result


PASS.

Please refer to the following pages.


Test Mode: IEEE 802.11b SISO Ant0



Lowest Channel




Middle Channel




Highest Channel


Test Mode: IEEE 802.11b SISO Ant1



Lowest Channel




Middle Channel




Highest Channel


Test Mode: IEEE 802.11g SISO Ant0



Lowest Channel




Middle Channel




Highest Channel


Test Mode: IEEE 802.11g SISO Ant1



Lowest Channel




Middle Channel




Highest Channel


Test Mode: IEEE 802.11n(H20) MIMO



Lowest Channel




Middle Channel





Highest Channel

Test Mode: IEEE802.11n(H40) MIMO



Lowest Channel



15. Antenna Application

15.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

15.2 Result

The EUT'S antenna, permanent attach antenna, is external antenna. The antenna's gain is 5dBi and meets the requirement.