

Advanced
Compliance Laboratory

6 Randolph Way
Hillsborough, NJ 08844
Tel: (908) 927 9288
Fax: (908) 927 0728

**Electromagnetic
Emission
Compliance
Test Report**



Equipment Under Test (EUT) OneBase™ Micro-Cabinet Cell Extender
OBE-1900-M831/M821/M811

Applicant Andrew Corporation

In Accordance With FCC Part 24, Subpart E

Test by Advanced Compliance Laboratory, Inc.
6 Randolph Way
Hillsborough, New Jersey 08844

Authorized by Wei Li
Lab Manager

Signature

Date March 26, 2009

AC Lab Report Number 0048-090121-01



Lab Code:200101-0

The test result in this report is supported and covered by the NVLAP accreditation.

Index

Section 1. Summary of Test Results	3
Section 2. General Equipment Specification	5
Section 3. RF Output Power	7
Section 4. Occupied Bandwidth	10
Section 5. Spurious Emissions at Antenna Terminals	36
Section 6. Field Strength of Spurious	71
Section 7. Frequency Stability	76
Section 8. Out of Band Rejection	78
Section 9. Test Equipment List.....	80
Section 10. FCC ID Labeling.....	81
Section 11. Maximum Permissible Exposure	82
Section 12. Setup Photos	83
Section 13. EUT Photos	87

Section 1. Summary of Test Results

Manufacturer: Andrew Corporation

Product Name: OneBase Micro-Cabinet Cell Extender

Model No: OBE-1900-M831/M821/M811

S/N: P001

General: **All measurements are traceable to national standards**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 24.

New Submission

Production Unit

Class II Permissive Change

Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

“See Summary of Test Data”



NVLAP LAB CODE: 200101-0

Advance Compliance Laboratory, Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Advance Compliance Laboratory, Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Summary of Test Data

RF Power Output	22.913(a)	500W ERP	N/A*
	24.232(a)	100W EIRP	Complies
Occupied Bandwidth (Voice & SAT)	2.1049(i)	Mask	N/A*
Occupies Bandwidth (Wideband Data)	2.1049(i)	Mask	N/A*
Occupied Bandwidth (Digital)	2.1049(i)	Mask	Complies
Spurious Emissions at Antenna Terminals	22.917	-13 dBm	N/A*
	24.238	-13 dBm	Complies
Field Strength of Spurious Emissions	22.917	-13 dBm	N/A*
	24.238	-13 dBm E.I.R.P.	Complies
Frequency Stability	22.355	1.5 ppm	N/A*
	24.235	0.05 ppm	N/A*

* These items are NOT applied to the EUT.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
 Lab Manager
 Advanced Compliance Lab

Date: March 26, 2009

Section 2. General Equipment Specification

Supply Voltage		100-240Vac (27V for PA Module)				
Frequency Range	Cellular	N/A				
	PCS	DL/1930-1990MHz				
	Modulation	CDMA 2000 <input checked="" type="checkbox"/>	WCDMA <input checked="" type="checkbox"/>	GSM <input checked="" type="checkbox"/>	EDGE <input checked="" type="checkbox"/>	TDMA <input type="checkbox"/>
Output Impedance		50ohm				
Total Rated Power		125W (+50.97dBm) per sector				
Typical Operating Power/carrier		WCDMA/CDMA: 40W GSM/EDGE: 25W				
Frequency Translation		F1-F1 <input checked="" type="checkbox"/>	F1-F2 <input type="checkbox"/>	N/A <input type="checkbox"/>		
		Software <input type="checkbox"/>	Duplexer Change <input type="checkbox"/>	Full Band Coverage <input checked="" type="checkbox"/>		

DC voltages and DC currents per 2.1033(c)(8)

The input supply to the transmitter was set at 27 Volts DC. The RF power output was measured with the indicated voltage and current applied into the final RF amplifying device(s).

OBE-1900-M831/M821/M811 Power Amplifier

RF Output, DC Current and RF Input Power are all average values.

Measured Rated RF output at MicroCabinet: 50.98dBm (125.4W)

Measured DC voltage: 26.72V

Measured DC current: 34.6A

Measured Minimum RF output at MicroCabinet: 1.51dBm (1.42mW)

Measured DC voltage: 26.70V

Measured DC current: 13.0A

Tune-up procedure per 2.1033(c) (9)


There are no user accessible adjustments or tuning in this amplifier. All necessary adjustments and tuning are performed during manufacture of the product. Any adjustments or tuning after service or repair are done as part of that process as special equipment is required to perform such adjustments.

Description of System and Operation


Max. Three Sectors, 1 MCPA Module per sector application, Operated in the downlink spectrum of PCS band.

The MCPA Multi-sector Micro-cabinet may be utilized for many customer applications, from 1 to 3 sectors (M811,M821,M831), in a single outdoor enclosure. The system with 3-sector configuration contains 3 MCPA modules and 3 Input/Output Duplexer Modules. The Micro-cabinet can support 1 sector applications with the installation of only a single MCPA module and single Input/Output Duplexer Module, and similarly support 2 sector applications with the installation of 2 MCPA modules and 2 Input/Output Duplexer Modules.

System Diagram (top level per Sector)



General EUT Setup



All final measurements were made on M831 configuration (max. three-sector installed, representing the max. load case) at room temperature and at nominal AC/DC input voltage.

Section 3. RF Output Power

Name of Test:	<i>RF Output Power</i>	Test Standard:	22.913(a)(N/A) 24.232(a)
Tested By:	DAVID TU	Test Date:	01/21/2009-03/12/2009

Minimum Standard: Para. No. 22.913(a). The maximum effective radiated power (ERP) of base station transmitters and cellular repeaters must not exceed 500 Watts (57dBm). -----N/A
Para. No. 24.232(a). The maximum peak output power of base transmitters should not exceed 100 Watts EIRP (50dBm).

Method of Measurement: Per 2.1046: The RF Power Output shall be measured at the output connector of the EUT. The Max. output level shall be +50.97 dBm (125 watts) ± 1 dB over the operation frequency bands. The tolerance range is per TIA/EIA-97-D, Section 4.3.1.3.

Using power meter, power measurements shall be taken at the low band edge, mid, and high band edge frequencies for all modulations listed on Page 5. The power meter was offset for all the path losses. The power was monitored and maintained throughout testing.

The EUT is a RF amplifier/Extender. The manufacturer does not provide an antenna for sale with the product; hence EIRP is not measured nor calculated.

Test Result:

Complies

Test Data:

The EUT's measured composite output power per sector was: 125W

Typical supported Output Power per carrier:

WCDMA/CDMA: 40W/Carrier

GSM/EDGE: 25W/Carrier

Rated Output Power – Normal Condition

The inputs are set to generate rated average output power and crest factor for the multi-carrier signals intended.

PCS Band	Channel	Modulation	Power Output (dBm)	Rated Power (dBm)	Tolerance
Downlink	Low	CDMA	50.88	50.97	-0.09
	Mid	CDMA	50.94	50.97	-0.03
	High	CDMA	50.05	50.97	-0.92
	Low	WCDMA	51.16	50.97	0.19
	Mid	WCDMA	50.93	50.97	-0.04
	High	WCDMA	50.45	50.97	-0.52
	Low	GSM	51.20	50.97	0.23
	Mid	GSM	50.94	50.97	-0.03
	High	GSM	50.17	50.97	-0.8
	Low	EDGE	50.87	50.97	-0.1
	Mid	EDGE	50.92	50.97	-0.05
	High	EDGE	50.07	50.97	-0.9
Total Power at Amplifier RF Input (dBm)	+45.8dBm @each Filter Kit Input (total three)				
Ref Offset	Ref offset=Cable&Attenuator&Coupler Attenuation=60.2dB				

Conclusion:

The total rated RF power is 125W per sector for multiple-carrier operation. As indicated on Page 5, supported output power per carrier is 40W for CDMA & WCDMA and 25W for GSM&EDGE, which does not exceed the 100 Watt peak power limit.

Section 4. Occupied Bandwidth

Name of Test:	<i>Occupied Bandwidth</i>	Test Standard:	<i>2.1049(i)</i>
Tested By:	DAVID TU	Test Date:	01/21/2009-03/12/2009

Minimum Standard: Not defined by FCC. Input vs. Output.

Method of Measurement: Spectrum Analyzer Settings:
RBW: CDMA (30 kHz), WCDMA (100KHz), CDMA(30KHz), GSM (30 kHz), EDGE (30KHz), NADC (1 kHz) and CDPD (1 kHz)
VBW: \geq RBW
Span: As required
Sweep: Auto
Input Signal Characteristics: Generated from Signal Generator
RF level: Rated, recommended by manufacturer


Test Result:

Complies

Test Data:


Attached Plots

Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%
Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, CDMA Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, CDMA Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, CDMA Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, CDMA Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, CDMA Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, CDMA Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, WCDMA Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, WCDMA Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, WCDMA Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, WCDMA Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, WCDMA Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, WCDMA Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, GSM Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, GSM Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, GSM Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, GSM Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, GSM Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, GSM Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, EDGE Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Hi-Channel, EDGE Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, EDGE Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Mid-Channel, EDGE Modulation
Configuration:	Input: SG




Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, EDGE Modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT



Project Number:	0048-090121-01
EUT:	Andrew OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Occupied Bandwidth: PCS Bands
Plot Name:	Downlink, Low-Channel, EDGE Modulation
Configuration:	Input: SG



Section 5. Spurious Emissions at Antenna Terminals

Name of Test:	<i>Spurious Emissions at Antenna Terminals</i>	Test Standard:	22.917(N/A) 24.238(a)
Tested By:	DAVID TU DAVID TU	Test Date:	01/21/2009-03/12/2009

Minimum Standard: Para. No. 22.917(e). The mean power of emissions must be attenuated below the mean power of the unmodulated carrier on any frequency twice or more than twice the fundamental emission by at least $43 + 10 \log P$. This is equivalent to -13 dBm absolute power. -----N/A
 Para. No. 24.238(a). The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under conditions specified in the instruction manual and/or alignment procedure, shall not less than $43+10 \log$ (mean output power in watts) dBc below the mean power output outside a licensee’s frequency block (-13dBm).

Method of Measurement: Spectrum Analyzer Settings:
 RBW: 100 kHz. As required for digital modulations.
 RBW: 1MHz. When frequency is located above 1GHz.
 VBW: $\geq \square$ RBW
 Start Frequency: 9KHz or Lowest Clock Frequency
 Stop Frequency: 10 GHz (Cellular), 20GHz (PCS)
 Sweep: Auto
 Using in-band filter if needed.
 For Inter-modulation measurement: Two RF signals set as inputs. The frequencies of RF signals shall be within the repeater’s operating band: two signals will close to each other at the lower band edge, the middle of the band and the upper band edge. The level of both RF input signals shall be increased, until the maximum rated output power per channel, as declared by the manufacturer (CDMA/WCDMA:40W &GSM/EDGE:25W), is reached.

Out of band plots show nearly identical noise floor readings for the frequency ranges below 20MHz and above 6.5GHz.

Test Result:


Complies

Test Data:

Attached Plots


Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
t Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA&WCDMA&GSM Modulation
Plot Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA&WCDMA&EDGE Modulation
Plot Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA&GSM&EDGE Modulation
Plot Name:	Downlink, H-CH Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA&GSM&EDGE Modulation
Plot Name:	Downlink, Inter-modulation
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Low-Chn, Lower Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Hi-Chn, Upper Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Low-Chn, Lower Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Hi-Chn, Upper Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
Plot Name:	Downlink, Low-Chn, Lower Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
Plot Name:	Downlink, Hi-Chn, Upper Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Low-Chn, Lower Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Hi-Chn, Upper Bandedge
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Hi-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Hi-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Mid-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Low-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Hi-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Mid-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Low-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
Plot Name:	Downlink, Hi-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
Plot Name:	Downlink, Mid-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
Plot Name:	Downlink, Low-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Hi-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Mid-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Low-Channel
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / CDMA Modulation
Plot Name:	Downlink, Middle-Channel, 3C carrier
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / WCDMA Modulation
Plot Name:	Downlink, Middle-Channel, 3C carrier
Configuration:	Input: SG, Output Port: EUT RF OUTPUT




Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / GSM Modulation
Plot Name:	Downlink, Middle-Channel, 3C carrier
Configuration:	Input: SG, Output Port: EUT RF OUTPUT



Project Number:	0048-090121-01
EUT:	OneBase Micro-Cabinet Cell Extender OBE-1900-M831/M821/M811
PARTS NO.:	P001
Tested By:	David Tu
Temperature:	70°F
Humidity:	30%

Section:	Spurious Emissions at RF Output Port: PCS Bands / EDGE Modulation
Plot Name:	Downlink, Middle-Channel, 3C carrier
Configuration:	Input: SG, Output Port: EUT RF OUTPUT



Section 6. Field Strength of Spurious

Name of Test:	<i>Field Strength of Spurious</i>	Test Standard:	22.917(N/A) 24.238
Tested By:	DAVID TU	Test Date:	01/21/2009-03/12/2009

Minimum Standard: Para. No. 22.917(e). The mean power of emissions must be attenuated below the mean power of the unmodulated carrier on any frequency twice or more than twice the fundamental emission by at least $43 + 10 \log P$. This is equivalent to -13 dBm absolute power.

-----N/A

Para. No. 24.238(a). The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under conditions specified in the instruction manual and/or alignment procedure, shall not less than $43+10 \log$ (mean output power in watts) dBc below the mean power output outside a licensee's frequency block (-13dBm).

Method of Measurement: TIA/EIA-603-C-2004, Section 2.2.12
 The antenna substitution method was used to determine the equivalent radiated power at spurious frequencies. The spurious emissions were measured at a distance of 3 meters. The EUT was then replaced with a reference substitution antenna with a known gain referenced to a dipole. This antenna was fed with a signal at the spurious frequency. The level of the signal was adjusted to repeat the previously measured level. The resulting ERP is the signal level fed to the reference antenna corrected for gain referenced to a dipole.

Test Result:

Complies

Test Data:

See Attached Table(s)

Configuration	PCS
Band	Downlink
Channel	Low

Freq. (MHz)	H,V	SA Reading (dBuV)	SG Reading (dBm)	CL (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
3862	V	48.8	-76	1.8	9.6	-60.2	-13	-47.2
5793	H	49.8	-69	2.4	10.8	-60.6	-13	-47.6
7725*	H	54.0	-66	2.8	10.6	-58.2	-13	-45.2
1873	H	41.7	-73	1.2	7.3	-66.9	-13	-53.9
2017	H	42.6	-73	1.3	7.8	-66.5	-13	-53.5
2132	H	43.8	-72	1.3	7.9	-65.4	-13	-52.4

NOTE:

* Measured noise floor

SA: Spectrum Analyzer

SG: Signal Generator

CL: SMA cable loss (6ft)

Worse case data presented

H=horizontal and V=vertical

EIRP = SG reading - CL + Gain (dBi)

Margin = EIRP – Limit

Configuration	PCS
Band	Downlink
Channel	Mid

Freq. (MHz)	H,V	SA Reading (dBuV)	SG Reading (dBm)	CL (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
3920	V	48.7	-68	1.8	9.6	-60.2	-13	-47.2
5880	V	51.5	-67	2.4	10.8	-59.6	-13	-46.6
7840*	V	52.1	-68	2.8	10.6	-60.2	-13	-45.2
1873	H	41.7	-73	1.2	7.3	-66.9	-13	-53.9
2017	H	42.6	-73	1.3	7.8	-66.5	-13	-53.5
2132	H	43.8	-72	1.3	7.9	-65.4	-13	-52.4

NOTE:

* Measured noise floor

SA: Spectrum Analyzer

SG: Signal Generator

CL: SMA cable loss (6ft)

Worse case data presented

H=horizontal and V=vertical

EIRP = SG reading - CL + Gain (dBi)

Margin = EIRP – Limit

Configuration	PCS
Band	Downlink
Channel	High

Freq. (MHz)	H,V	SA Reading (dBuV)	SG Reading (dBm)	CL (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
3976	H	48.8	-67	1.8	9.7	-59.1	-13	-46.1
5864	H	51.9	-68	2.4	10.9	-58.5	-13	-46.5
7952*	H	53.5	-65	2.8	10.2	-57.6	-13	-44.6
1873	H	41.7	-73	1.2	7.3	-66.9	-13	-53.9
2017	H	42.6	-73	1.3	7.8	-66.5	-13	-53.5
2132	H	43.8	-72	1.3	7.9	-65.4	-13	-52.4

NOTE:

* Measured noise floor

SA: Spectrum Analyzer

SG: Signal Generator

CL: SMA cable loss (6ft)

Worse case data presented

H=horizontal and V=vertical

EIRP = SG reading - CL + Gain (dBi)

Margin = EIRP – Limit

Section 7. Frequency Stability

Name of Test:	<i>Frequency Stability</i>	Test Standard:	<i>2.1055 22.355&24.235</i>
Tested By:	DAVID TU	Test Date:	06/02-06/14/2005

Minimum Standard: Para. No. 22.355. The transmitter carrier frequency shall remain within the tolerances given in Table C-1.

TABLE C-1.—FREQUENCY TOLERANCE FOR TRANSMITTERS IN THE PUBLIC MOBILE SERVICES

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤=3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

Para No. 24.235. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Method of Measurement: Frequency Stability With Voltage Variation:
 The E.U.T. is placed in an environmental chamber and allowed to stabilize at +25 degrees Celsius for at least 15 minutes. Set SA resolution bandwidth low enough (30Hz) to obtain the desired frequency resolution. (Using frequency counter method: The frequency counter and signal generator are phase locked with the same 10 MHz reference frequency by connecting the 10 MHz ref. out of the counter to the 10MHz ref, in of the signal generator). With the voltage input to the E.U.T. set to 85% S.T.V., the frequency is measured in 30 second intervals for a period of 5 minutes. This procedure is repeated at 100% S.T.V. and 115% S.T.V.

Frequency Stability With Temperature Variation:
 The input voltage to the E.U.T. is set to S.T.V. and the temperature of the environmental chamber is varied in 10 degree steps from -30 degrees C to +50 degrees C. The E.U.T. is allowed to stabilize at each temperature and the frequency is measured in 30 second intervals for a period of 5 minutes.

Test Result:

Complies

Test Data:

See Attached Table(s)

Not Applicable

Section 8. Out of Band Rejection

Name of Test:	<i>Out of Band Rejection</i>	Test Standard:	
Tested By:	David Tu	Test Date:	01/21/2009-03/12/2009

Minimum Standard: The passband gain shall not exceed the nominal gain by more than 1.0 dB. The 20 dB bandwidth shall not exceed the nominal bandwidth that is stated by the manufacturer. Outside of the 20 dB bandwidth, the gain shall not exceed the gain at the 20 dB point.

Method of Measurement: Adjust the internal gain control of the equipment under test to the nominal gain for which equipment certification is sought. With the aid of a signal generator and spectrum analyzer, measure the 20 dB bandwidth of the amplifier (i.e. at the point where the gain has fallen by 20 dB). Measure the gain-versus-frequency response of the amplifier from the midband frequency f_0 of the passband up to at least $f_0 \pm 250\%$ of the 20 dB bandwidth.

Test Result:

Complies

Test Data:

See Attached Table(s)

PER PRODUCT DESIGN & OPERATION CRITERIA ON SINGAL INPUTS, THIS SYSTEM HAS NO OUT-BAND AMPLIFING ACTVITY.

Not Applicable

Section 9. Test Equipment List

Manufacture	Model	Serial No.	Description	Cal Due dd/mm/ yy
HP	HP8546A	3448A00290	EMI Receiver	15/09/09
HP	E4432B	US38220355	250K-3GHz Signal Generator	15/07/09
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	15/09/09
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	09/02/10
Fischer Custom	LIPARTS NO.-2	900-4-0008	Line Impedance Stabilization Networks	15/09/09
Fischer Custom	LIPARTS NO.-2	900-4-0009	Line Impedance Stabilization Networks	23/08/09
EMCO	6502	2665	10KHz-30MHz Active Loop Antenna	27/02/10
EMCO	3115	4945	Double Ridge Guide Horn Antenna	13/09/09
R&S	ESPI	100018	EMI Receiver	16/07/09
HP	8569B	2607A02802	1GHz-22GHz Spectrum Analyzer	10/02/10
Delta Design	5900C	0-67-26	Temperature Chamber	24/03/09
HP	E8254A	US42110367	Signal Generator	23/03/09
Electro-Metrics	RGA-15	8-95	Double Ridge Guide Horn Antenna	10/02/10
EMCO	3116	4943	Double Ridge Guide Horn Antenna	11/01/10
Scientific-Atlanta	12A-18	441	Wave Guide Horn Antenna	04/08/10
HP	4419A	US37292112	RF Power Meter w/ Sensor Probe	20/07/08
Chamber	GD-32-33	LN2	Temperature Chamber	28/07/08
HP	6032A	3323A-09526	System Power Supply	01/07/09
Agilent	E4438C	US41460731	ESG Vector Signal Generator	01/07/09
Agilent	E4438C	US41460771	ESG Vector Signal Generator	01/07/09
Agilent	E4438C	US41460400	ESG Vector Signal Generator	01/07/09
Agilent	E4440A	US40420700	3Hz-26.5GHz Spectrum Analyzer	12/05/09
Lorch Microwave	5NF- 800/1000-S	AC3	Notch Filter	
Lorch Microwave	5NF- 1800/2200-S	AE10	Notch Filter	
RES-NET	RFA500NFF 30	0108	30dB in-line Power Attenuator	
Narda	3022	80986	Directional Coupler	
General Purpose			0-60V, 50A DC Power Supply	