



**FCC 47 CFR PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**CERTIFICATION TEST REPORT**

*For*  
**MEMOBIRD**

**MODEL NUMBER: MEMOBIRD GT1**

**FCC ID: S96000GT1  
IC: 22175-000GT1**

**REPORT NUMBER: 4788533948.1-1**

**ISSUE DATE: July 02, 2018**

*Prepared for*

**Xiamen Intretech Inc.  
No.588.Jiahe Road,Xiamen,Fujian,China 361006**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road,  
Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China  
Tel: +86 769-22038881  
Fax: +86 769 33244054  
Website: www.ul.com**

Revision History

Rev.	Issue Date	Revisions	Revised By
--	2/7/2018	Initial Issue	\

<b>Summary of Test Results</b>			
<b>Clause</b>	<b>Test Items</b>	<b>FCC/IC Rules</b>	<b>Test Results</b>
1	20dB Bandwidth And 99% Bandwidth	FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a)	Complied
2	Peak Conducted Output Power	FCC 15.247 (b) (1) RSS-247 Clause 5.1 (b)	Complied
3	Carrier Hopping Channel Separation	FCC 15.247 (a) (1) RSS-247 Clause 5.1 (b)	Complied
4	Number of Hopping Frequency	15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Complied
5	Time of Occupancy (Dwell Time)	15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Complied
6	Conducted Bandedge	FCC 15.247 (d) RSS-247 Clause 5.5	Complied
7	Radiated Bandedge and Spurious	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	Complied
8	Conducted Emission Test For AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	Complied
9	Antenna Requirement	FCC 15.203 RSS-GEN Clause 8.3	Complied

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>6</b>
<b>2. TEST METHODOLOGY .....</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY.....</b>	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY .....</i>	<i>8</i>
<b>5. EQUIPMENT UNDER TEST.....</b>	<b>9</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>9</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>9</i>
5.3. <i>PACKET TYPE CONFIGURATION.....</i>	<i>9</i>
5.4. <i>CHANNEL LIST .....</i>	<i>10</i>
5.5. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>10</i>
5.6. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>11</i>
5.8. <i>WORST-CASE CONFIGURATIONS .....</i>	<i>11</i>
5.9. <i>TEST ENVIRONMENT .....</i>	<i>11</i>
5.10. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>12</i>
5.11. <i>MEASURING INSTRUMENT AND SOFTWARE USED.....</i>	<i>13</i>
<b>6. ANTENNA PORT TEST RESULTS .....</b>	<b>14</b>
6.1. <i>ON TIME AND DUTY CYCLE .....</i>	<i>14</i>
6.1. <i>20 dB BANDWIDTH AND 99% BANDWIDTH.....</i>	<i>16</i>
6.1.1. <i>GFSK MODE.....</i>	<i>17</i>
6.1.2. <i>8DPSK MODE.....</i>	<i>21</i>
6.2. <i>PEAK CONDUCTED OUTPUT POWER .....</i>	<i>25</i>
6.2.1. <i>GFSK MODE.....</i>	<i>26</i>
6.2.2. <i>π/4-DQPSK .....</i>	<i>26</i>
6.2.3. <i>8DPSK MODE.....</i>	<i>26</i>
6.3. <i>CARRIER HOPPING CHANNEL SEPARATION.....</i>	<i>27</i>
6.3.1. <i>GFSK MODE.....</i>	<i>28</i>
6.3.2. <i>8DPSK MODE.....</i>	<i>29</i>
6.4. <i>NUMBER OF HOPPING FREQUENCY.....</i>	<i>30</i>
6.4.1. <i>GFSK MODE.....</i>	<i>31</i>
6.4.2. <i>8DPSK MODE.....</i>	<i>33</i>
6.5. <i>TIME OF OCCUPANCY (DWELL TIME) .....</i>	<i>35</i>
6.5.1. <i>GFSK MODE.....</i>	<i>36</i>
6.5.2. <i>8DPSK MODE.....</i>	<i>38</i>
6.6. <i>CONDUCTED SPURIOUS EMISSION.....</i>	<i>40</i>

6.6.1.	GFSK MODE.....	41
6.6.2.	8DPSK MODE.....	45
<b>7.</b>	<b>RADIATED TEST RESULTS.....</b>	<b>49</b>
7.1.	LIMITS AND PROCEDURE.....	49
7.2.	RESTRICTED BANDEDGE.....	53
7.2.1.	GFSK MODE.....	53
7.2.2.	8DPSK MODE.....	59
7.3.	SPURIOUS EMISSIONS (1~18GHz).....	64
7.3.1.	GFSK MODE.....	64
7.3.2.	8DPSK MODE.....	70
7.4.	SPURIOUS EMISSIONS 18G ~ 26GHz.....	76
7.4.1.	GFSK MODE.....	76
7.5.	SPURIOUS EMISSIONS 30M ~ 1 GHz.....	78
7.5.1.	GFSK MODE.....	78
7.6.	SPURIOUS EMISSIONS BELOW 30M.....	80
7.6.1.	GFSK MODE.....	80
<b>8.</b>	<b>AC POWER LINE CONDUCTED EMISSIONS.....</b>	<b>84</b>
8.1.1.	GFSK MODE.....	85
<b>9.</b>	<b>ANTENNA REQUIREMENTS.....</b>	<b>87</b>

# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: Xiamen Intretech Inc.  
Address: No.588.Jiahe Road,Xiamen,Fujian,China 361006

## Manufacturer Information


Company Name: Xiamen Intretech Inc.  
Address: No.588.Jiahe Road,Xiamen,Fujian,China 361006

## EUT Description

Product Name MEMOBIRD  
Model Name MEMOBIRD GT1  
Sample Status Normal  
Sample Received date June 13, 2018  
Date Tested June 14~30, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Tested By:



---

Kebo Zhang  
Engineer

Checked By:



---

Shawn Wen  
Laboratory Leader

Approved By:



---

Stephen Guo  
Laboratory Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with DA 00-705, KDB414788 D01 Radiated Test Site v01, ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 5, and RSS-247 Issue 2.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>IAS (Lab Code: TL-702)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has demonstrated compliance with ISO/IEC Standard 17025:2005, General requirements for the competence of testing and calibration laboratories</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>IC(Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.90dB
Uncertainty for Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	2.2dB
Uncertainty for Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.52dB
Uncertainty for Radiation Emission test (1GHz to 26GHz)( include Fundamental emission)	5.04dB(1-6GHz)
	5.30dB (6GHz-18Gz)
	5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

Equipment	MEMOBIRD		
Model Name	MEMOBIRD GT1		
Product Description (Bluetooth)	Operation Frequency	2402 MHz ~ 2480 MHz	
	Modulation Type	Data Rate	
	GFSK	1Mbps	
	π/4-DQPSK	2Mbps	
	8DPSK	3Mbps	
Power Supply	AC120V/60Hz		
Bluetooth Version	BT4.0+V2.1+EDR		
Hardware Version	SS016A_PA2.1		
Software Version	V1.x		

### 5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max Output Power (dBm)	EIRP (dBm)
GFSK	2402-2480	0-78[79]	5.221	7.421
8DPSK	2402-2480	0-78[79]	6.772	8.972

### 5.3. PACKET TYPE CONFIGURATION

Test Mode	Packet Type	Setting(Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
π/4-DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679
8DPSK	3-DH1	83
	3-DH3	552
	3-DH5	1021

### 5.4. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	\	\

### 5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel Number	Test Channel
GFSK	CH 00, CH 39, CH 78	Low, Middle, High
8DPSK	CH 00, CH 39, CH 78	Low, Middle, High

### 5.6. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		FCCTool		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 00	CH 39	CH 78
GFSK	1	2	2	2
8DPSK	1	2	2	2

### 5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2402-2480	PCB antenna	2.2

Test Mode	Transmit and Receive Mode	Description
GFSK	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.
8DPSK	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.

### 5.8. WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BR	FHSS	GFSK	1Mbit/s
EDR	FHSS	8DPSK	3Mbit/s

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

### 5.9. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	23 ~ 28 °C
Voltage :	VL	N/A
	VN	AC 120V 60Hz
	VH	N/A

Note: VL= Lower Extreme Test Voltage  
 VN= Nominal Voltage.  
 VH= Upper Extreme Test Voltage  
 TN= Normal Temperature

## 5.10. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	PC	Dell	Vostro 3902	8KNDDDB2
2	USB TO RS232	N/A	N/A	N/A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	N/A	N/A	0.15	N/A


### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	N/A	N/A	N/A	N/A

### TEST SETUP

The EUT can work in an engineer mode with software through a PC.

### SETUP DIAGRAM FOR TESTS



### 5.11. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions							
Instrument							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	101961	Dec.20, 2016	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	101983	Dec.20, 2016	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Feb.10, 2017	Dec.12, 2017	Dec.11, 2018
Software							
Used	Description	Manufacturer	Name	Version			
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance	Farad	EZ-EMC	Ver. UL-3A1			
Radiated Emissions							
Instrument							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Feb. 24, 2017	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Jan.09, 2016	Jan.09, 2016	Jan.09, 2019
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A09099	Feb. 13, 2017	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec. 20, 2016	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Jan. 09, 2016	Jan. 09, 2016	Jan. 09, 2019
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Jan.06, 2016	Jan.06, 2016	Jan.06, 2019
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Jan. 14, 2017	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec. 20, 2016	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Mar. 26, 2016	Mar. 26, 2016	Mar. 26, 2019
Software							
Used	Description	Manufacturer	Name	Version			
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance	Farad	EZ-EMC	Ver. UL-3A1			
Other instruments							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec. 20, 2016	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Power Meter	Keysight	N9031A	MY55416024	Feb. 13, 2017	Dec.12, 2017	Dec.11, 2018
<input checked="" type="checkbox"/>	Power Sensor	Keysight	N9323A	MY55440013	Feb. 13, 2017	Dec.12, 2017	Dec.11, 2018

## 6. ANTENNA PORT TEST RESULTS

### 6.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method



#### TEST SETUP



#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (KHz)
GFSK	2.880	3.060	0.94	94	0.3	0.347
8DPSK	2.892	3.072	0.94	94	0.3	0.346

Note: Duty Cycle Correction Factor= $10\log(1/x)$ .  
Where: x is Duty Cycle(Linear)  
Where: T is On Time (transmit duration)



## 6.1. 20 dB BANDWIDTH AND 99% BANDWIDTH

### LIMITS

FCC Part15 (15.247) Subpart C RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a)	20dB Bandwidth	N/A	2400-2483.5
RSS-Gen Clause 6.6	99% Bandwidth	N/A	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 20dB Bandwidth: 1% of the 20 dB bandwidth For 99% Bandwidth: 1% to 5% of the occupied bandwidth
VBW	For 20dB Bandwidth: $\geq$ RBW For 99% Bandwidth: approximately $3 \times$ RBW
Span	approximately 2 to 3 times the 20 dB bandwidth
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP








**RESULTS**



**6.1.1. GFSK MODE**


Channel	Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
Low	2402	1.026	0.916	PASS
Middle	2441	1.028	0.917	PASS
High	2480	1.030	0.918	PASS

**Test Graph**















### 6.1.2. 8DPSK MODE

Channel	Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
Low	2402	1.288	1.192	PASS
Middle	2441	1.290	1.195	PASS
High	2480	1.290	1.198	PASS











## 6.2. PEAK CONDUCTED OUTPUT POWER


### LIMITS

FCC Part15 (15.247) , Subpart C RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247 (b) (1) RSS-247 Clause 5.4 (b)	Peak Conducted Output Power	1 watt or 30dBm	2400-2483.5

### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.  
Measure peak power each channel.

### TEST SETUP



**RESULTS**

**6.2.1. GFSK MODE**

Channel	Frequency	Maximum Conducted Output Power(PK)	Result
	(MHz)	(dBm)	
Low	2402	4.226	Pass
Middle	2441	4.924	Pass
High	2480	5.211	Pass

**6.2.2.  $\pi/4$ -DQPSK**

Channel	Frequency	Maximum Conducted Output Power(PK)	Result
	(MHz)	(dBm)	
Low	2402	4.143	Pass
Middle	2441	5.213	Pass
High	2480	5.158	Pass

**6.2.3. 8DPSK MODE**

Channel	Frequency	Maximum Conducted Output Power(PK)	Result
	(MHz)	(dBm)	
Low	2402	5.731	Pass
Middle	2441	6.296	Pass
High	2480	6.772	Pass

### 6.3. CARRIER HOPPING CHANNEL SEPARATION

#### LIMITS

FCC Part15 (15.247) , Subpart C RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247 (a) (1) RSS-247 Clause 5.1 (b)	Carrier Hopping Channel Separation	25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.	2400-2483.5

#### TEST PROCEDURE

Connect the UUT to the spectrum Analyzer and use the following settings:


Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

A plot of the data shall be included in the test report.


#### TEST SETUP



**RESULTS**

**6.3.1. GFSK MODE**


Channel	Carrier Hopping Channel Separation (MHz)	Limit (MHz)	Result
Middle	1.0	≥ two-thirds of the 20 dB Bandwidth Of The Hopping Channel	PASS



Note: For 20 dB Bandwidth of The Hopping Channel, please refer to clause 6.1.1.

### 6.3.2. 8DPSK MODE

Channel	Carrier Hopping Channel Separation (MHz)	Limit (MHz)	Result
Middle	1.0	≥ two-thirds of the 20 dB Bandwidth Of The Hopping Channel	PASS



Note: For 20 dB Bandwidth of The Hopping Channel, please refer to clause 6.1.2.

## 6.4. NUMBER OF HOPPING FREQUENCY

### LIMITS

FCC Part15 (15.247) , Subpart C RSS-247 ISSUE 2		
Section	Test Item	Limit
15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Number of Hopping Frequency	at least 15 hopping channels

### TEST PROCEDURE

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation
Trace	Max hold
Sweep time	Auto couple


Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer.

Count the quantity of peaks to get the number of hopping channels.

Normal Mode: 79 Channels observed.

AFH Mode: 20 Channels declared.

### TEST SETUP




### RESULTS


### 6.4.1. GFSK MODE

Hopping numbers	Limit	Results
79	>15	Pass


Count 1



Count 2



Count 3







### 6.4.2. 8DPSK MODE

Hopping numbers	Limit	Results
79	>15	Pass


Count 1



Count 2



Count 3



## 6.5. TIME OF OCCUPANCY (DWELL TIME)

### LIMITS

FCC Part15 (15.247) , Subpart C RSS-247 ISSUE 2		
Section	Test Item	Limit
15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

### TEST PROCEDURE

Connect the UUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1 MHz
VBW	≥RBW
Span	zero span
Trace	Max hold
Sweep time	As necessary to capture the entire dwell time per hopping channel

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.  
 $A \text{ Period Time} = (\text{channel number}) * 0.4$

For Normal Mode (79 Channel):

DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)

DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)


DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

For AFH Mode (20 Channel):

DH1 Time Slot: Reading \* (1600/2)\*8/(channel number)

DH3 Time Slot: Reading \* (1600/4)\*8/(channel number)

DH5 Time Slot: Reading \* (1600/6)\*8/(channel number)






**RESULTS**

**6.5.1. GFSK MODE**

Normal Mode					
Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time [ms]	Duty Cycle [%]	Results
DH1	MCH	0.370	0.118	65.5	PASS
DH3	MCH	1.632	0.261	90.1	PASS
DH5	MCH	2.880	0.307	94.1	PASS
AFH Mode					
DH1	MCH	0.370	0.118	65.5	PASS
DH3	MCH	1.632	0.261	90.1	PASS
DH5	MCH	2.880	0.307	94.1	PASS

**Test Graph**








### 6.5.2. 8DPSK MODE

Normal Mode					
Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time [ms]	Duty Cycle [%]	Results
3DH1	MCH	0.390	0.124	66.7	PASS
3DH3	MCH	1.632	0.261	88.9	PASS
3DH5	MCH	2.892	0.308	94.1	PASS
AFH Mode					
3DH1	MCH	0.390	0.124	66.7	PASS
3DH3	MCH	1.632	0.261	88.9	PASS
3DH5	MCH	2.892	0.308	94.1	PASS

### Test Graph





## 6.6. CONDUCTED SPURIOUS EMISSION

### LIMITS

FCC Part15 (15.247) , Subpart C RSS-247 ISSUE 2		
Section	Test Item	Limit
FCC §15.247 (d) RSS-247 5.5	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Please refer to the ANSI C63.10 section 6.10.

For Bandedge use the following settings:


Detector	Peak
RBW	100KHz
VBW	300KHz
Span	wide enough to fully capture the emission being measured
Trace	Max hold
Sweep time	Auto couple.

For Spurious Emission use the following settings:

Detector	Peak
RBW	100KHz
VBW	300KHz
Span	wide enough to fully capture the emission being measured
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.



### TEST SETUP









### 6.6.1. GFSK MODE



#### SPURIOUS EMISSIONS, LOW CHANNEL



**SPURIOUS EMISSIONS, MID CHANNEL**















### 6.6.2. 8DPSK MODE

#### SPURIOUS EMISSIONS, LOW CHANNEL











## 7. RADIATED TEST RESULTS

### 7.1. LIMITS AND PROCEDURE

#### LIMITS

Please refer to FCC §15.205 and §15.209

Please refer to RSS-GEN Clause 8.9 and Clause 8.10

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3


Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54


About Restricted bands of operation please refer to RSS-Gen section 8.10 and FCC §15.205 (a)



The setting of the spectrum Analyzer

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Trace	Max hold


1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)
8. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.



The setting of the spectrum Analyzer

RBW	120K
VBW	300K
Sweep	Auto
Trace	Max hold


1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report.



RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
  2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
  3. The EUT was placed on a turntable with 80cm above ground.
  4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
  5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
  6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector. For the Duty Cycle please refer to clause 6.1.ON TIME AND DUTY CYCLE.
- If that calculated VBW is not available on the analyzer then the next higher value should be used.  
 In this case 500Hz should be used.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:




Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

## 7.2. RESTRICTED BANDEGE

### 7.2.1. GFSK MODE

#### PEAK

#### RESTRICTED BANDEGE (LOW CHANNEL, HORIZONTAL)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	*	2361.900	22.33	33.34	55.67	74.00	-18.33	peak			
2		2390.000	14.25	33.14	47.39	74.00	-26.61	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG


**RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)**



- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
  4. For transmit duration, please refer to clause 6.1.
  5. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

PEAK

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		2390.000	15.01	33.24	48.25	74.00	-25.75			peak	
2	*	2362.300	19.27	33.44	52.71	74.00	-21.29			peak	
3		2321.500	16.14	33.79	49.93	74.00	-24.07			peak	

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1	2321.900	5.60	33.79	39.39	54.00	-14.61	AVG			
2 *	2362.000	11.81	33.44	45.25	54.00	-8.75	AVG			
3	2390.000	1.59	33.24	34.83	54.00	-19.17	AVG			

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.  
 4. For transmit duration, please refer to clause 6.1.  
 5. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.



PEAK


RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Table			
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Height	Degree	Comment
1	2483.500	16.50	32.78	49.28	74.00	-24.72	peak	cm	degree	
2 *	2495.175	16.82	32.78	49.60	74.00	-24.40	peak			

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Table			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Height	Table Degree	Comment
1		2483.500	15.06	32.88	47.94	74.00	-26.06	peak	cm	degree	
2	*	2494.700	16.86	32.87	49.73	74.00	-24.27	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

**7.2.2. 8DPSK MODE**

**PEAK**

**RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)**




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Table		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Height	Table Degree
									cm	degree
1		2321.800	18.13	33.64	51.77	74.00	-22.23	peak		
2	*	2361.700	22.08	33.35	55.43	74.00	-18.57	peak		
3		2390.000	14.71	33.14	47.85	74.00	-26.15	peak		

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

**RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)**




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	2321.900	8.69	33.63	42.32	54.00	-11.68	AVG			
2 *	2362.000	16.11	33.34	49.45	54.00	-4.55	AVG			
3	2390.000	1.92	33.14	35.06	54.00	-18.94	AVG			

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. AVG: VBW=1/Ton where: ton is transmit duration.  
 4. For transmit duration, please refer to clause 6.1.  
 5. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

PEAK

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2322.200	16.09	33.79	49.88	74.00	-24.12			peak
2	*	2361.500	18.33	33.45	51.78	74.00	-22.22			peak
3		2390.000	14.49	33.24	47.73	74.00	-26.27			peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

PEAK

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	15.67	32.78	48.45	74.00	-25.55			peak
2	*	2496.375	16.63	32.78	49.41	74.00	-24.59			peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 6. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

**PEAK**

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	14.89	32.88	47.77	74.00	-26.23			peak
2	*	2485.825	16.69	32.89	49.58	74.00	-24.42			peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.

### 7.3. SPURIOUS EMISSIONS (1~18GHz)

#### 7.3.1. GFSK MODE

##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree degree	Comment
1		2360.000	60.20	-8.76	51.44	74.00	-22.56			peak
2		3414.000	50.48	-6.52	43.96	74.00	-30.04			peak
3		7477.000	38.56	6.48	45.04	74.00	-28.96			peak
4		11591.000	34.96	14.36	49.32	74.00	-24.68			peak
5		13546.000	32.13	18.27	50.40	74.00	-23.60			peak
6	*	17779.000	28.71	23.96	52.67	74.00	-21.33			peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.




**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	2360.000	56.61	-8.66	47.95	74.00	-26.05	peak			
2	4247.000	47.21	-3.35	43.86	74.00	-30.14	peak			
3	6015.000	45.37	2.10	47.47	74.00	-26.53	peak			
4	11047.00	35.87	12.92	48.79	74.00	-25.21	peak			
5	13954.00	32.39	18.65	51.04	74.00	-22.96	peak			
6 *	17796.00	28.44	24.59	53.03	74.00	-20.97	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		1000.000	60.95	-14.68	46.27	74.00	-27.73	peak			
2		2360.000	48.98	-8.76	40.22	74.00	-33.78	peak			
3		4876.000	42.80	-0.95	41.85	74.00	-32.15	peak			
4		7256.000	38.25	6.45	44.70	74.00	-29.30	peak			
5		13818.00	31.99	18.57	50.56	74.00	-23.44	peak			
6	*	17864.00	27.68	24.18	51.86	74.00	-22.14	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	2122.000	53.43	-10.03	43.40	74.00	-30.60	peak			
2	3193.000	47.40	-6.49	40.91	74.00	-33.09	peak			
3	6015.000	45.31	2.10	47.41	74.00	-26.59	peak			
4	11880.000	33.32	14.74	48.06	74.00	-25.94	peak			
5	13971.000	31.94	18.62	50.56	74.00	-23.44	peak			
6 *	17745.000	27.97	23.91	51.88	74.00	-22.12	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		2513.000	53.23	-9.25	43.98	74.00	-30.02	peak			
2		4247.000	45.31	-3.45	41.86	74.00	-32.14	peak			
3		5998.000	42.27	1.97	44.24	74.00	-29.76	peak			
4		12305.00	34.59	14.29	48.88	74.00	-25.12	peak			
5		13597.00	32.35	18.53	50.88	74.00	-23.12	peak			
6	*	17745.00	28.28	23.56	51.84	74.00	-22.16	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		2122.000	52.24	-10.03	42.21	74.00	-31.79	peak			
2		3193.000	46.76	-6.49	40.27	74.00	-33.73	peak			
3		6015.000	45.16	2.10	47.26	74.00	-26.74	peak			
4		11999.000	34.80	14.65	49.45	74.00	-24.55	peak			
5		14090.000	31.77	18.46	50.23	74.00	-23.77	peak			
6	*	17813.000	28.30	24.44	52.74	74.00	-21.26	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

### 7.3.2. 8DPSK MODE


#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Table		
								Height	Table	Degree
								cm	degree	Comment
1		2360.000	59.26	-8.76	50.50	74.00	-23.50			peak
2		3397.000	47.28	-6.60	40.68	74.00	-33.32			peak
3		7171.000	38.42	6.36	44.78	74.00	-29.22			peak
4		11319.00	34.50	13.48	47.98	74.00	-26.02			peak
5		13971.00	31.91	18.52	50.43	74.00	-23.57			peak
6	*	18000.00	27.39	24.81	52.20	74.00	-21.80			peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		2360.000	56.60	-8.66	47.94	74.00	-26.06	peak			
2		6015.000	45.29	2.10	47.39	74.00	-26.61	peak			
3		7171.000	39.53	6.46	45.99	74.00	-28.01	peak			
4		11982.000	34.30	14.68	48.98	74.00	-25.02	peak			
5		13903.000	31.54	18.73	50.27	74.00	-23.73	peak			
6	*	17813.000	28.35	24.44	52.79	74.00	-21.21	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1		2360.000	49.54	-8.76	40.78	74.00	-33.22	peak			
2		4247.000	47.98	-3.45	44.53	74.00	-29.47	peak			
3		7256.000	38.36	6.45	44.81	74.00	-29.19	peak			
4		11880.00	32.99	14.84	47.83	74.00	-26.17	peak			
5		13954.00	32.12	18.55	50.67	74.00	-23.33	peak			
6	*	17745.00	28.95	23.56	52.51	74.00	-21.49	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.




**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1	2122.000	53.52	-10.03	43.49	74.00	-30.51	peak			
2	4264.000	44.40	-3.25	41.15	74.00	-32.85	peak			
3	6015.000	46.01	2.10	48.11	74.00	-25.89	peak			
4	11863.000	33.79	14.73	48.52	74.00	-25.48	peak			
5	13546.000	32.08	18.87	50.95	74.00	-23.05	peak			
6 *	17796.000	27.62	24.59	52.21	74.00	-21.79	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	2513.000	53.48	-9.25	44.23	74.00	-29.77	peak			
2	5998.000	41.52	1.97	43.49	74.00	-30.51	peak			
3	7647.000	37.99	6.44	44.43	74.00	-29.57	peak			
4	11914.00	33.68	15.02	48.70	74.00	-25.30	peak			
5	13971.00	31.47	18.52	49.99	74.00	-24.01	peak			
6 *	17779.00	28.22	23.96	52.18	74.00	-21.82	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		2122.000	52.89	-10.03	42.86	74.00	-31.14	peak			
2		4264.000	44.56	-3.25	41.31	74.00	-32.69	peak			
3		6015.000	45.86	2.10	47.96	74.00	-26.04	peak			
4		11557.00	34.25	14.20	48.45	74.00	-25.55	peak			
5		13971.00	31.71	18.62	50.33	74.00	-23.67	peak			
6	*	17779.00	28.47	24.36	52.83	74.00	-21.17	peak			

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.

## 7.4. SPURIOUS EMISSIONS 18G ~ 26GHZ

### 7.4.1. GFSK MODE

#### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18978.830	49.86	-5.24	44.62	74.00	-29.38	peak
2	19331.007	50.83	-5.58	45.25	74.00	-28.75	peak
3	20359.743	50.27	-5.50	44.77	74.00	-29.23	peak
4	21776.975	50.34	-4.35	45.99	74.00	-28.01	peak
5	23395.870	49.19	-3.23	45.96	74.00	-28.04	peak
6	25942.698	51.50	-0.96	50.54	74.00	-23.46	peak

Note: 1. Peak Result= Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18674.225	49.84	-5.38	44.46	74.00	-29.54	peak
2	20510.030	50.86	-5.35	45.51	74.00	-28.49	peak
3	21784.984	49.67	-4.34	45.33	74.00	-28.67	peak
4	22843.290	49.97	-3.60	46.37	74.00	-27.63	peak
5	25033.649	49.82	-2.04	47.78	74.00	-26.22	peak
6	25818.977	50.73	-0.74	49.99	74.00	-24.01	peak


Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

Note: All the modulation and channels had been tested, but only the worst data recorded in the report.

## 7.5. SPURIOUS EMISSIONS 30M ~ 1 GHz

### 7.5.1. GFSK MODE


#### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	84.3200	53.30	-21.77	31.53	40.00	-8.47	QP
2	95.9600	59.13	-21.84	37.29	43.50	-6.21	QP
3	107.6000	54.60	-20.69	33.91	43.50	-9.59	QP
4	191.9900	46.13	-14.67	31.46	43.50	-12.04	QP
5	408.3000	41.82	-11.93	29.89	46.00	-16.11	QP
6	455.8300	42.25	-11.37	30.88	46.00	-15.12	QP

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	54.00	-19.35	34.65	40.00	-5.35	QP
2	48.4300	54.44	-20.22	34.22	40.00	-5.78	QP
3	84.3200	57.70	-21.77	35.93	40.00	-4.07	QP
4	107.6000	59.59	-20.69	38.90	43.50	-4.60	QP
5	120.2100	58.88	-18.78	40.10	43.50	-3.40	QP
6	504.3300	45.06	-10.69	34.37	46.00	-11.63	QP


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All the modulation and channels had been tested, but only the worst data recorded in the report.

## 7.6. SPURIOUS EMISSIONS BELOW 30M

### 7.6.1. GFSK MODE

#### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0106	54.54	20.22	74.76	127.24	-52.48	peak
2	0.0160	48.83	20.27	69.10	123.99	-54.89	peak
3	0.0302	43.46	20.31	63.77	118.01	-54.24	peak
4	0.0454	38.09	20.31	58.40	114.51	-56.11	peak
5	0.0892	35.45	20.25	55.70	108.60	-52.90	peak
6	0.1189	32.06	20.30	52.36	106.10	-53.74	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



**150KHz ~ 30M**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1833	35.33	20.39	55.72	102.34	-46.62	peak
2	0.3933	31.99	20.27	52.26	95.73	-43.47	peak
3	1.2157	26.20	20.44	46.64	65.91	-19.27	peak
4	2.9618	22.77	20.89	43.66	69.54	-25.88	peak
5	10.2873	20.15	21.05	41.20	69.54	-28.34	peak
6	21.0350	18.12	21.15	39.27	69.54	-30.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

**9KHz~ 150KHz**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0094	49.90	20.26	70.16	128.06	-57.90	peak
2	0.0154	44.87	20.26	65.13	124.35	-59.22	peak
3	0.0252	42.29	20.31	62.60	119.75	-57.15	peak
4	0.0473	39.53	20.31	59.84	114.14	-54.30	peak
5	0.0623	37.34	20.31	57.65	111.73	-54.08	peak
6	0.0976	34.92	20.23	55.15	107.82	-52.67	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

**150KHz ~ 30M**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1539	35.82	20.42	56.24	103.86	-47.62	peak
2	0.6471	28.60	20.31	48.91	71.41	-22.50	peak
3	0.9889	26.85	20.37	47.22	67.70	-20.48	peak
4	6.6977	21.21	20.90	42.11	69.54	-27.43	peak
5	12.2530	18.71	21.00	39.71	69.54	-29.83	peak
6	29.3704	17.23	21.94	39.17	69.54	-30.37	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

Note: All the modulation and channels had been tested, but only the worst data recorded in the report.


## 8. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

Please refer to FCC §15.207 (a) and RSS-Gen Clause 8.8.

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

### TEST SETUP AND PROCEDURE




The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### 8.1.1. GFSK MODE

#### TEST RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)


#### LINE N RESULTS



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1751	28.13	9.62	37.75	64.71	-26.96	QP
2	0.1751	14.36	9.62	23.98	54.71	-30.73	AVG
3	0.4378	27.44	9.63	37.07	57.10	-20.03	QP
4	0.4378	22.15	9.63	31.78	47.10	-15.32	AVG
5	1.2238	15.50	9.64	25.14	56.00	-30.86	QP
6	1.2238	8.82	9.64	18.46	46.00	-27.54	AVG
7	7.5692	21.23	9.83	31.06	60.00	-28.94	QP
8	7.5692	10.75	9.83	20.58	50.00	-29.42	AVG
9	11.9002	26.85	10.01	36.86	60.00	-23.14	QP
10	11.9002	22.82	10.01	32.83	50.00	-17.17	AVG
11	23.7995	24.71	9.94	34.65	60.00	-25.35	QP
12	23.7995	22.00	9.94	31.94	50.00	-18.06	AVG

- Note: 1. Result = Reading +Correct Factor.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

**LINE L RESULTS**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1756	28.92	9.63	38.55	64.69	-26.14	QP
2	0.1756	14.56	9.63	24.19	54.69	-30.50	AVG
3	0.2627	26.56	9.63	36.19	61.35	-25.16	QP
4	0.2627	18.10	9.63	27.73	51.35	-23.62	AVG
5	0.4369	30.55	9.63	40.18	57.12	-16.94	QP
6	0.4369	26.18	9.63	35.81	47.12	-11.31	AVG
7	0.4967	22.90	9.63	32.53	56.06	-23.53	QP
8	0.4967	16.37	9.63	26.00	46.06	-20.06	AVG
9	11.8999	28.90	10.00	38.90	60.00	-21.10	QP
10	11.8999	23.98	10.00	33.98	50.00	-16.02	AVG
11	23.7991	31.21	9.90	41.11	60.00	-18.89	QP
12	23.7991	24.80	9.90	34.70	50.00	-15.30	AVG

Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

Note: All the modulation and channels had been tested, but only the worst data recorded in the report.

## **9. ANTENNA REQUIREMENTS**

### **APPLICABLE REQUIREMENTS**

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **ANTENNA CONNECTOR**

EUT has a PCB antenna without antenna connector.

### **ANTENNA GAIN**

The antenna gain of EUT is less than 6 dBi.

**END OF REPORT**