

Prüfbericht-Nr.: <i>Test report no.:</i>	IN23CPI5 001 & IN23HOHV 001 ULR-TC5688233000000094F&95F	Auftrags-Nr.: <i>Order no.:</i>	0146716970 020	Seite 1 von 4 Page 1 of 4
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	2269507	Auftragsdatum: <i>Order date:</i>	2023-06-01	
Auftraggeber: <i>Client:</i>	Trimble Inc. 5475 Kellenburger Road , Building 2, Dayton, Ohio 45424, United States			
Prüfgegenstand: <i>Test item:</i>	GS920			
Bezeichnung <i>Identification</i>	GS920	Serien -Nr.: <i>Serial no.:</i>	Engineering Sample	
Auftrags-Inhalt: <i>Order content:</i>	Maximum Permissible Expsoure			
Prüfgrundlage: <i>Test specification:</i>	FCC 1.1310, and RSS 102 Issue 5 KDB 447498 D01			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2022-11-11			
Prüfmuster-Nr.: <i>Test sample no:</i>	A003370833-001 A003370833-002 A003370833-003			
Prüfzeitraum: <i>Testing period:</i>	2022-11-12 - 2022-11-20			
Ort der Prüfung: <i>Place of testing:</i>	Wireless laboratory, Bangalore			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (India) Pvt. Ltd. 27/B,2nd cross road, Electronic city Phase1, Banglore-560100, India FCC Test Site Registration No: 496599 IC Test Site Registration No: 27711 HVIN: MB119-00SD-A			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	Yogesh V Senior Engineer		genehmigt von: <i>authorized by:</i>	Madhu K.N Assistant Manager
Datum: <i>Date:</i>	2022-11-22		Ausstellatum: <i>Issue date:</i>	2023-09-12
Sonstiges / Other:	FCC ID: S9E-131488 IC: 5817A-131488			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				



1 Maximum Permissible Exposure

1.1 RF Exposure Compliance Requirement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

1.2 RF Exposure Limits:

1.2.1 For FCC

1. According to FCC Part 1 Subpart I 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b) showed in Table 1.

Table 1: Limits for Maximum Permissible Exposure (MPE) as per FCC

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 - 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 - 100000	--	--	1.0

F or f = Frequency in MHz

Friss Formula

Friss Transmission Formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

Prüfbericht - Nr.:
Test Report No.:

**IN23CPI5 001, IN23HOHV 001,
ULR-TC568823300000094F&95F**

Seite 3 von 4
Page 3 of 4

Test Results:

Manufacturer has declared the tune-up value as 1 dB is considered in MPE calculation.

Antenna Gain: 2dBi for SubGHz & 0dBi for BLE

Classification	Frequency (MHz)	Maximum measured RF output power at antenna terminal (dBm)	Max power Including tune-up tolerance * (mW)	Antenna Gain in linear scale (dB)	Min Separation distance (CM)	Power Density (Pd) (W/m ²)	FCC Limit (mW/cm ²)
SubGHz	903.00	4.09	3.2284	1.58	20	0.0010	0.6020
	916.00	4.44	3.4994	1.58	20	0.0011	0.6107
	927.00	3.91	3.0974	1.58	20	0.0009	0.6180
BLE	2402.00	7.99	7.9250	1.00	20	0.0015	1.0000
	2440.00	7.43	6.9662	1.00	20	0.0013	1.0000
	2480.00	5.60	4.5708	1.00	20	0.0009	1.0000

Note: Maximum conducted output power taken from test Reports: **IN23HOHV 001 & AR19-0034275-01**

1.2.2 For IC

According to IC RSS 102 Issue 5: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radiofrequency (RF) radiation as specified in section 4 showed in Table 4.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}

Note: f is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

Classification	Frequency (MHz)	Maximum measured RF output power at antenna terminal (dBm)	Max power Including tune-up tolerance * (mW)	Antenna Gain in linear (dBd)	Min Separation distance (CM)	Power Density (Pd) (W/m ²)	RSS Limit (W/m ²)
SubGHz	903.00	4.09	3.2284	1.58	20	0.0100	2.7419
	916.00	4.44	3.4994	1.58	20	0.0110	2.7688
	927.00	3.91	3.0974	1.58	20	0.0090	2.7915
BLE	2402.00	7.99	7.9250	1.00	20	0.0150	5.3508
	2440.00	7.43	6.9662	1.00	20	0.0130	5.4085
	2480.00	5.60	4.5708	1.00	20	0.0090	5.4689

Note: Maximum conducted output power taken from test Reports: **IN23HOHV 001 & AR19-0034275-01**

Prüfbericht - Nr.:
Test Report No.:

**IN23CPI5 001, IN23HOHV 001,
ULR-TC568823300000094F&95F**

Seite 4 von 4
Page 4 of 4

Exemption calculation for simultaneous Operation:

Region	RF Protocol	Frequency (MHz)	Calculated MPE	Final MPE	Limit
For FCC	Wi-Fi BLE + SubGHz	903 + 2402	0.0010+0.0015	0.0025	<1
For IC	Wi-Fi BLE + SubGHz	903 + 2402	0.0100 + 0.0150	0.0250	<1

Note:

1. For above table, to calculate MPE following formula is used

$$\text{MPE RF 1} / \text{Limit RF 1} + \text{MPE RF2} / \text{LIMIT RF 2} + \dots + \text{MPE RFn} / \text{Limit RFn} < 1$$

1.3 Conclusion

The Power density of the EUT is less than defined limit as shown above, hence EUT is exempted from routine SAR.