

FCC Test Report

Product Name	RUGGED TABLET COMPUTER
Model No	104961, 104962, 104963
FCC ID.	S9E-7265NGW

Applicant	Trimble Navigation Limited
Address	345 SW Avery Ave, Corvallis, OR, United States

Date of Receipt	Apr. 14, 2015
Issue Date	Jun. 24, 2015
Report No.	1540296R-RFUSP38V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report

Issue Date: Jun. 24, 2015

Report No.: 1540296R-RFUSP38V00



Product Name	RUGGED TABLET COMPUTER
Applicant	Trimble Navigation Limited
Address	345 SW Avery Ave, Corvallis, OR, United States
Manufacturer	Ubiqconn Technology, Inc.
Model No.	104961, 104962, 104963
EUT Rated Voltage	AC 100-240V, 50-60Hz
EUT Test Voltage	AC 120V/ 60Hz
Trade Name	Trimble
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2014 ANSI C63.4: 2014, ANSI C63.10: 2013 KDB 558074 D01 DTS Meas Guidance v03r02
Test Result	Complied

Documented By : Genie Chang
(Senior Adm. Specialist / Genie Chang)

Tested By : Nick Chen
(Engineer / Nick Chen)

Approved By : 
(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. EUT Description.....	5
1.2. Operational Description	7
1.3. Tested System Details.....	8
1.4. Configuration of Tested System	8
1.5. EUT Exercise Software	8
1.6. Test Facility	9
2. Conducted Emission.....	10
2.1. Test Equipment.....	10
2.2. Test Setup	10
2.3. Limits	11
2.4. Test Procedure	11
2.5. Uncertainty	11
2.6. Test Result of Conducted Emission.....	12
3. Maximum Conducted Power.....	14
3.1. Test Equipment.....	14
3.2. Test Setup	14
3.3. Limits	14
3.4. Test Procedure	14
3.5. Uncertainty	14
3.6. Test Result of Maximum Conducted Power.....	15
4. Radiated Emission.....	19
4.1. Test Equipment.....	19
4.2. Test Setup	20
4.3. Limits	21
4.4. Test Procedure	22
4.5. Uncertainty	22
4.6. Test Result of Radiated Emission.....	23
5. RF Antenna conducted test.....	39
5.1. Test Equipment.....	39
5.2. Test Setup	39
5.3. Limits	39
5.4. Test Procedure	40
5.5. Uncertainty	40
5.6. Test Result of RF antenna conducted test.....	41
6. Band Edge	47
6.1. Test Equipment.....	47
6.2. Test Setup	47
6.3. Limits	48
6.4. Test Procedure	48
6.5. Uncertainty	48
6.6. Test Result of Band Edge	49

7.	Occupied Bandwidth	65
7.1.	Test Equipment	65
7.2.	Test Setup	65
7.3.	Limits	65
7.4.	Test Procedure	65
7.5.	Uncertainty	65
7.6.	Test Result of Occupied Bandwidth	66
8.	Power Density	78
8.1.	Test Equipment	78
8.2.	Test Setup	78
8.3.	Limits	78
8.4.	Test Procedure	78
8.5.	Uncertainty	78
8.6.	Test Result of Power Density	79
9.	EMI Reduction Method During Compliance Testing	91

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	RUGGED TABLET COMPUTER
Trade Name	Trimble
Model No.	104961, 104962, 104963
FCC ID.	S9E-7265NGW
Frequency Range	802.11b/g/n-20MHz: 2412-2462MHz, 802.11n-40MHz: 2422-2452MHz
Number of Channels	802.11b/g/n-20MHz: 11, n-40MHz: 7
Data Speed	802.11b: 1-11Mbps, 802.11a/g: 6-54Mbps, 802.11n: up to 300Mbps
Type of Modulation	802.11b:DSSS, DBPSK, DQPSK, CCK 802.11g/n: OFDM, BPSK, QPSK, 16QAM, 64QAM
Antenna Type	PIFA Antenna
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto
Power Adapter	MFR: FSP, M/N: FSP065-REB Input: 100-240V~1.5A 50-60 Hz Output: 19V, 3.42A Cable Out: Non-Shielded, 1.6m, with one ferrite core bonded.
Contain Module	Intel / 7265NGW

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Taiwan Anjie Electronics CO. LTD.	N/A (Main) N/A (Aux)	PIFA Antenna	0.43dBi For 2.4GHz

Note: The antenna of EUT is conform to FCC 15.203

802.11b/g/n-20MHz Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 01:	2412 MHz	Channel 02:	2417 MHz	Channel 03:	2422 MHz	Channel 04:	2427 MHz
Channel 05:	2432 MHz	Channel 06:	2437 MHz	Channel 07:	2442 MHz	Channel 08:	2447 MHz
Channel 09:	2452 MHz	Channel 10:	2457 MHz	Channel 11:	2462 MHz		

802.11n-40MHz (2.4G Band) Center Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 1:	2422 MHz	Channel 2:	2427 MHz	Channel 3:	2432 MHz	Channel 4:	2437 MHz
Channel 5:	2442 MHz	Channel 6:	2447 MHz	Channel 7:	2452 MHz		

Note:

1. This device is a RUGGED TABLET COMPUTER with a built-in WLAN transceiver.
2. The EUT is including three models and the different of each model is shown as below:

Regulation		LTE module	WIFI + BT	2.4G long-range	GPS
Mode NO.		EM7355	AC7265	WIT2410	NEO-M8T
sku 1	104961		★		★
sku 2	104962	★	★		★
sku 3	104963	★	★	★	★

3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps 、 802.11g is 6Mbps 、 802.11n(20M-BW) is 14.4Mbps and, 802.11n(40M-BW) is 30Mbps).
5. At result of pretests, module supports dual-channel transmission, only the worst case is shown in the report. (802.11b is chain A, 802.11g is chain A)
6. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g/n transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.
7. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test Mode:	Mode 1: Transmit (802.11b 1Mbps)
	Mode 2: Transmit (802.11g 6Mbps)
	Mode 3: Transmit - 802.11n-20BW_14.4Mbps
	Mode 4: Transmit - 802.11n-40BW_30Mbps


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
(1)	Keyboard	Dell	SK-8175	MY-0W217F-71619-092-0459-A01	N/A
(2)	USB Mouse	Logitech	M-U0003	LZ024HR	N/A
(3)	Earphone	Dr.AV	CD-806B	N/A	N/A
(4)	Modem	ACEEX	DM-1414	0102027536	N/A

Signal Cable Type	Signal cable Description
A	USB Cable Shielded, 1.8m
B	Earphone Cable Non-Shielded, 1.0m
C	USB Cable Shielded, 1.8m
D	Modem Cable Shielded, 1.5m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown on 1.4
- (2) Execute “DRTU V1.7.6-1091” program on the Notebook PC.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Start the continuous transmission.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site : <http://www.quietek.com/chinese/about/certificates.aspx?bval=5>
 The address and introduction of Quietek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>

Site Description: File on
 Federal Communications Commission
 FCC Engineering Laboratory
 7435 Oakland Mills Road
 Columbia, MD 21046
 Registration Number: 92195

Site Name: Quietek Corporation
 Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
 Lin-Kou Shiang, Taipei,
 Taiwan, R.O.C.
 TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
 E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Conducted Emission


2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2015	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2015	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar., 2015	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2015	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

Product : RUGGED TABLET COMPUTER
Test Item : Conducted Emission Test
Power Line : Line 1
Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps (2437MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV	Margin dB	Limit dBuV
Line 1					
Quasi-Peak					
0.162	9.667	37.950	47.617	-18.040	65.657
0.173	9.664	34.300	43.964	-21.379	65.343
0.209	9.661	32.230	41.891	-22.423	64.314
0.220	9.662	29.400	39.062	-24.938	64.000
15.525	10.021	19.840	29.861	-30.139	60.000
18.002	10.044	22.480	32.524	-27.476	60.000
Average					
0.162	9.667	22.400	32.067	-23.590	55.657
0.173	9.664	14.520	24.184	-31.159	55.343
0.209	9.661	18.780	28.441	-25.873	54.314
0.220	9.662	12.150	21.812	-32.188	54.000
15.525	10.021	14.090	24.111	-25.889	50.000
18.002	10.044	16.910	26.954	-23.046	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. “█” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : RUGGED TABLET COMPUTER
 Test Item : Conducted Emission Test
 Power Line : Line 2
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps (2437MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV	Margin dB	Limit dBuV
Line 2					
Quasi-Peak					
0.158	9.668	39.600	49.268	-16.503	65.771
0.209	9.661	31.000	40.661	-23.653	64.314
0.228	9.662	30.350	40.012	-23.759	63.771
0.283	9.665	23.590	33.255	-28.945	62.200
15.263	10.099	19.940	30.039	-29.961	60.000
18.841	10.181	22.640	32.821	-27.179	60.000
Average					
0.158	9.668	23.650	33.318	-22.453	55.771
0.209	9.661	10.800	20.461	-33.853	54.314
0.228	9.662	17.640	27.302	-26.469	53.771
0.283	9.665	10.010	19.675	-32.525	52.200
15.263	10.099	14.200	24.299	-25.701	50.000
18.841	10.181	16.990	27.171	-22.829	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "█" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

3. Maximum Conducted Power


3.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Power Meter	Anritsu	ML2495A/6K00003357	May, 2015
X	Power Sensor	Anritsu	MA2411B/0738448	Jun, 2015
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

3.2. Test Setup



3.3. Limits

The maximum average power shall be less 1 Watt. (Section 15.247 (b)(3))

3.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 D01 DTS Meas Guidance v03r02 section 9.1.2 PKPM1 Peak power meter method.

3.5. Uncertainty

± 1.27 dB

3.6. Test Result of Maximum Conducted Power

Product : RUGGED TABLET COMPUTER
 Test Item : Maximum Conducted Power
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit	Result
		1	2	5.5	11			
		Measurement Level (dBm)						
01	2412	13.67	--	--	--	16.79	<30dBm	Pass
06	2437	13.68	13.57	13.46	13.35	16.71	<30dBm	Pass
11	2462	14.40	--	--	--	17.53	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : RUGGED TABLET COMPUTER
 Test Item : Maximum Conducted Power
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		6	9	12	18	24	36	48	54			
		Measurement Level (dBm)										
01	2412	11.29	--	--	--	--	--	--	--	16.57	<30dBm	Pass
06	2437	13.56	13.53	13.50	13.47	13.44	13.41	13.38	13.35	18.72	<30dBm	Pass
11	2462	11.01	--	--	--	--	--	--	--	16.34	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : RUGGED TABLET COMPUTER
 Test Item : Maximum Conducted Power
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps

CHAIN A

Channel No	Frequency (MHz)	Average Power								Peak Power
		For different Data Rate (Mbps)								
		14.4	28.9	43.3	57.8	86.7	115.6	130	144.4	
Measurement Level (dBm)										
01	2412	9.09	--	--	--	--	--	--	--	14.61
06	2437	10.83	10.8	10.77	10.75	10.72	10.69	10.65	10.63	16.34
11	2462	10.53	--	--	--	--	--	--	--	16.09

Note: Peak Power Output Value = Reading value on power meter + cable loss

CHAIN B

Channel No	Frequency (MHz)	Average Power								Peak Power
		For different Data Rate (Mbps)								
		14.4	28.9	43.3	57.8	86.7	115.6	130	144.4	
Measurement Level (dBm)										
01	2412	9.18	--	--	--	--	--	--	--	14.93
06	2437	10.61	10.59	10.57	10.55	10.52	10.49	10.47	10.44	16.39
11	2462	10.16	--	--	--	--	--	--	--	15.83

Note: Peak Power Output Value = Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency (MHz)	Data Rata (Mbps)	Chain A Power (dBm)	Chain B Power (dBm)	Chain A+B Power (dBm)	Limit (dBm)	Result
1	2412	14.4	14.61	14.93	17.78	<30dBm	Pass
6	2437	14.4	16.34	16.39	19.38	<30dBm	Pass
11	2462	14.4	16.09	15.83	18.97	<30dBm	Pass

Note: Peak Power Output Value (dBm) = 10*LOG (Chain A (mW) + Chain B (mW))

Product : RUGGED TABLET COMPUTER
 Test Item : Maximum Conducted Power
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps

CHAIN A

Channel No	Frequency (MHz)	Average Power								Peak Power
		For different Data Rate (Mbps)								
		30	60	90	120	180	240	270	300	
		Measurement Level (dBm)								
3	2422	6.93	--	--	--	--	--	--	--	11.79
6	2437	11.05	11.01	10.98	10.96	10.92	10.89	10.84	10.81	16.31
9	2452	7.28	--	--	--	--	--	--	--	12.08

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN B

Channel No	Frequency (MHz)	Average Power								Peak Power
		For different Data Rate (Mbps)								
		30	60	90	120	180	240	270	300	
		Measurement Level (dBm)								
3	2422	6.68	--	--	--	--	--	--	--	11.58
6	2437	10.31	10.28	10.26	10.23	10.19	10.16	10.13	10.11	15.78
9	2452	7.10	--	--	--	--	--	--	--	11.92

Note: Peak Power Output Value =Reading value on power meter + cable loss

CHAIN A+B

Channel	Frequency (MHz)	Data Rata (Mbps)	Chain A Power (dBm)	Chain B Power (dBm)	Chain A+B Power (dBm)	Limit (dBm)	Result
3	2422	30	11.79	11.58	14.70	<30dBm	Pass
6	2437	30	16.31	15.78	19.06	<30dBm	Pass
9	2452	30	12.08	11.92	15.01	<30dBm	Pass

Note: Peak Power Output Value (dBm) = 10*LOG (Chain A (mW) + Chain B (mW))

4. Radiated Emission

4.1. Test Equipment

The following test equipments are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep, 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun, 2015
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun, 2015
	X	Coaxial Cable	QTK(Armist)	RG 214/ LC003-RG	Jun, 2015
	X	Coaxial signal switch	Armist	MP59B/ 6200798682	Jun, 2015


- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
 2. The test instruments marked with “X” are used to measure the final test results.

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct, 2014
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar, 2015
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan, 2015
	X	Horn Antenna	TRC	AH-0801/95051	Aug, 2014
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan, 2015
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul, 2014
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul, 2014


- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
 2. The test instruments marked with “X” are used to measure the final test results.

4.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 30dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

4.6. Test Result of Radiated Emission

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4824.000	0.212	32.130	32.343	-41.657	74.000
7236.000	5.860	31.980	37.840	-36.160	74.000
9648.000	11.325	34.660	45.984	-28.016	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4824.000	11.201	33.080	44.282	-29.718	74.000
7236.000	13.019	32.270	45.289	-28.711	74.000
9648.000	14.887	34.210	49.096	-24.904	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

Horizontal

Peak Detector:

4874.000	0.106	32.360	32.466	-41.534	74.000
7311.000	5.772	31.930	37.703	-36.297	74.000
9748.000	11.810	33.860	45.671	-28.329	74.000

**Average
Detector:**

--

Vertical

Peak Detector:

4874.000	10.981	32.870	43.850	-30.150	74.000
7311.000	12.962	32.030	44.993	-29.007	74.000
9748.000	14.851	34.100	48.952	-25.048	74.000

**Average
Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4924.000	0.266	31.610	31.876	-42.124	74.000
7386.000	6.651	32.140	38.791	-35.209	74.000
9848.000	13.211	33.910	47.122	-26.878	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4924.000	11.026	32.260	43.285	-30.715	74.000
7386.000	13.445	32.420	45.865	-28.135	74.000
9848.000	15.731	34.190	49.921	-24.079	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4824.000	0.212	32.190	32.403	-41.597	74.000
7236.000	5.860	31.650	37.510	-36.490	74.000
9648.000	11.325	34.370	45.694	-28.306	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4824.000	11.201	33.420	44.622	-29.378	74.000
7236.000	13.019	32.490	45.509	-28.491	74.000
9648.000	14.887	34.130	49.016	-24.984	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

Horizontal

Peak Detector:

4874.000	0.106	32.250	32.356	-41.644	74.000
7311.000	5.772	32.350	38.123	-35.877	74.000
9748.000	11.810	34.610	46.421	-27.579	74.000

Average

Detector:

--

Vertical

Peak Detector:

4874.000	10.981	33.810	44.790	-29.210	74.000
7311.000	12.962	32.280	45.243	-28.757	74.000
9748.000	14.851	34.260	49.112	-24.888	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4924.000	0.266	32.120	32.386	-41.614	74.000
7386.000	6.651	32.270	38.921	-35.079	74.000
9648.000	11.325	34.520	45.844	-28.156	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4924.000	11.026	33.510	44.535	-29.465	74.000
7386.000	13.445	32.540	45.985	-28.015	74.000
9848.000	15.731	34.670	50.401	-23.599	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4824.000	0.212	32.610	32.823	-41.177	74.000
7236.000	5.860	31.650	37.510	-36.490	74.000
9648.000	11.325	34.370	45.694	-28.306	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4824.000	11.201	33.210	44.412	-29.588	74.000
7236.000	13.019	32.950	45.969	-28.031	74.000
9648.000	14.887	34.870	49.756	-24.244	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss –Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps (2437 MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level	dB	dBuV/m
	dB	dBuV	dBuV/m		

Horizontal

Peak Detector:

4874.000	0.106	32.790	32.896	-41.104	74.000
7311.000	5.772	32.460	38.233	-35.767	74.000
9748.000	11.810	34.630	46.441	-27.559	74.000

Average

Detector:

--

Vertical

Peak Detector:

4874.000	10.981	33.390	44.370	-29.630	74.000
7311.000	12.962	32.820	45.783	-28.217	74.000
9748.000	14.851	34.390	49.242	-24.758	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4924.000	0.266	32.580	32.846	-41.154	74.000
7386.000	6.651	31.270	37.921	-36.079	74.000
9848.000	13.211	34.850	48.062	-25.938	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4924.000	11.026	33.510	44.535	-29.465	74.000
7386.000	13.445	32.540	45.985	-28.015	74.000
9848.000	15.731	34.670	50.401	-23.599	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps (2422MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4844.000	0.208	32.320	32.528	-41.472	74.000
7266.000	5.790	31.620	37.410	-36.590	74.000
9688.000	11.447	34.170	45.617	-28.383	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4844.000	11.151	33.890	45.041	-28.959	74.000
7266.000	12.970	32.610	45.580	-28.420	74.000
9688.000	14.801	34.520	49.321	-24.679	74.000
Average Detector:					
--					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss –Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4874.000	0.106	32.750	32.856	-41.144	74.000
7311.000	5.772	31.740	37.513	-36.487	74.000
9748.000	11.810	34.630	46.441	-27.559	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4874.000	10.981	33.810	44.790	-29.210	74.000
7311.000	12.962	32.820	45.783	-28.217	74.000
9748.000	14.851	34.490	49.342	-24.658	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : Harmonic Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps (2452 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
Peak Detector:					
4904.000	0.294	32.910	33.204	-40.796	74.000
7356.000	6.060	31.990	38.050	-35.950	74.000
9808.000	12.744	34.860	47.604	-26.396	74.000
Average Detector:					
--					
Vertical					
Peak Detector:					
4904.000	11.100	33.910	45.009	-28.991	74.000
7356.000	13.017	32.560	45.577	-28.423	74.000
9808.000	15.472	34.370	49.842	-24.158	74.000
Average Detector:					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : RUGGED TABLET COMPUTER
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
117.300	-7.350	39.281	31.931	-11.569	43.500
239.520	-6.878	41.619	34.741	-11.259	46.000
383.080	1.305	32.810	34.115	-11.885	46.000
505.300	2.126	40.798	42.924	-3.076	46.000
825.400	7.346	24.638	31.984	-14.016	46.000
930.160	7.530	22.697	30.227	-15.773	46.000
Vertical					
45.520	-10.625	36.338	25.713	-14.287	40.000
179.380	-0.824	30.273	29.449	-14.051	43.500
346.220	-0.527	26.435	25.908	-20.092	46.000
505.300	0.056	31.319	31.375	-14.625	46.000
815.700	2.931	23.274	26.205	-19.795	46.000
951.500	3.083	21.997	25.080	-20.920	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : RUGGED TABLET COMPUTER
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
115.360	-7.390	36.754	29.365	-14.135	43.500
299.660	-4.751	36.239	31.488	-14.512	46.000
456.800	2.432	36.411	38.843	-7.157	46.000
600.360	3.472	31.238	34.710	-11.290	46.000
769.140	5.118	23.741	28.859	-17.141	46.000
889.420	6.654	23.018	29.672	-16.328	46.000
Vertical					
115.360	-3.870	29.689	25.820	-17.680	43.500
239.520	-6.138	34.089	27.951	-18.049	46.000
503.360	-0.086	30.570	30.484	-15.516	46.000
697.360	0.691	31.176	31.867	-14.133	46.000
840.920	2.284	23.672	25.956	-20.044	46.000
970.900	2.967	23.552	26.519	-27.481	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : RUGGED TABLET COMPUTER
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
119.240	-7.291	38.150	30.860	-12.640	43.500
288.020	-5.557	37.021	31.464	-14.536	46.000
383.080	1.305	35.495	36.800	-9.200	46.000
600.360	3.472	31.197	34.669	-11.331	46.000
699.300	2.956	31.395	34.351	-11.649	46.000
930.160	7.530	22.030	29.560	-16.440	46.000
Vertical					
88.200	-4.076	27.559	23.483	-20.017	43.500
179.380	-0.824	28.234	27.410	-16.090	43.500
348.160	-0.890	26.318	25.428	-20.572	46.000
600.360	1.302	27.686	28.988	-17.012	46.000
699.300	-0.024	34.023	33.999	-12.001	46.000
928.220	3.640	21.726	25.366	-20.634	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : RUGGED TABLET COMPUTER
 Test Item : General Radiated Emission Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
119.240	-7.291	37.119	29.829	-13.671	43.500
264.740	-5.501	35.373	29.873	-16.127	46.000
383.080	1.305	33.835	35.140	-10.860	46.000
503.360	1.994	39.768	41.762	-4.238	46.000
693.480	3.608	28.169	31.777	-14.223	46.000
922.400	6.670	22.844	29.514	-16.486	46.000
Vertical					
115.360	-3.870	30.214	26.345	-17.155	43.500
179.380	-0.824	31.267	30.443	-13.057	43.500
348.160	-0.890	27.272	26.382	-19.618	46.000
503.360	-0.086	30.082	29.996	-16.004	46.000
695.420	1.352	26.465	27.817	-18.183	46.000
930.160	3.830	22.351	26.181	-19.819	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

5. RF Antenna conducted test


5.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
 2. The test instruments marked with “X” are used to measure the final test results.

5.2. Test Setup

RF antenna Conducted Measurement:



5.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.

5.5. Uncertainty


The measurement uncertainty

Conducted is defined as $\pm 1.27\text{dB}$


5.6. Test Result of RF antenna conducted test

Product : RUGGED TABLET COMPUTER
 Test Item : RF antenna conducted test
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)


Channel 01 (2412MHz) 30MHz-25GHz



Channel 06 (2437MHz) 30MHz -25GHz




Channel 11 (2462MHz) 30MHz -25GHz




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : RUGGED TABLET COMPUTER
Test Item : RF Antenna Conducted Spurious
Test Site : No.3 OATS
Test Mode : Mode 2: Transmit (802.11g 6Mbps)


Channel 01 (2412MHz) 30MHz -25GHz



Channel 06 (2437MHz) 30MHz -25GHz




Channel 11 (2462MHz) 30MHz -25GHz




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : RUGGED TABLET COMPUTER
Test Item : RF Antenna Conducted Spurious
Test Site : No.3 OATS
Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps


Channel 01 (2412MHz) 30MHz -25GHz-Chain A



Channel 06 (2437MHz) 30MHz -25GHz-Chain A




Channel 11 (2462MHz) 30MHz -25GHz-Chain A




Note: The above test pattern is synthesized by multiple of the frequency range.


Channel 01 (2412MHz) 30MHz -25GHz-Chain B



Channel 06 (2437MHz) 30MHz -25GHz-Chain B




Channel 11 (2462MHz) 30MHz -25GHz-Chain B




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : RUGGED TABLET COMPUTER
Test Item : RF Antenna Conducted Spurious
Test Site : No.3 OATS
Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps


Channel 03 (2422MHz) 30MHz -25GHz-Chain A



Channel 06 (2437MHz) 30MHz -25GHz-Chain A




Channel 09 (2452MHz) 30MHz -25GHz-Chain A




Note: The above test pattern is synthesized by multiple of the frequency range.


Channel 03 (2422MHz) 30MHz -25GHz-Chain B



Channel 06 (2437MHz) 30MHz -25GHz-Chain B



Channel 09 (2452MHz) 30MHz -25GHz-Chain B



Note: The above test pattern is synthesized by multiple of the frequency range.

6. Band Edge

6.1. Test Equipment

RF Radiated Measurement:


The following test equipments are used during the band edge tests:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X Spectrum Analyzer	R&S	FSP40/ 100339	Oct, 2014
	X Horn Antenna	ETS-Lindgren	3117/ 35205	Mar, 2015
	X Horn Antenna	Schwarzbeck	BBHA9170/209	Jan, 2015
	X Horn Antenna	TRC	AH-0801/95051	Aug, 2014
	X Pre-Amplifier	EMCI	EMC012630SE/980210	Jan, 2015
	X Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul, 2014
	X Pre-Amplifier	NARDA	DBL-1840N506/013	Jul, 2014

- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
 2. The test instruments marked with "X" are used to measure the final test results.

6.2. Test Setup

RF Radiated Measurement:



6.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 30dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

6.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.

6.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

6.6. Test Result of Band Edge

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBUV)	Emission Level (dBUV/m)	Peak Limit (dBUV/m)	Average Limit (dBUV/m)	Result
01 (Peak)	2390.000	-2.687	59.828	57.141	74.00	54.00	Pass
01 (Peak)	2397.000	-2.665	68.127	65.462	--	--	--
01 (Peak)	2400.000	-2.660	63.918	61.258	--	--	--
01 (Peak)	2413.000	-2.642	108.466	105.823	--	--	--
01 (Average)	2387.600	-2.697	49.767	47.070	74.00	54.00	Pass
01 (Average)	2390.000	-2.687	49.178	46.491	74.00	54.00	Pass
01 (Average)	2396.800	-2.665	62.881	60.216	--	--	--
01 (Average)	2400.000	-2.660	56.636	53.976	--	--	--
01 (Average)	2411.200	-2.643	104.057	101.414	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	-4.159	58.507	54.348	74.00	54.00	Pass
01 (Peak)	2397.000	-4.172	66.095	61.923	--	--	--
01 (Peak)	2400.000	-4.171	61.394	57.223	--	--	--
01 (Peak)	2411.000	-4.169	105.920	101.751	--	--	--
01 (Average)	2388.000	-4.152	47.719	43.567	74.00	54.00	Pass
01 (Average)	2390.000	-4.159	47.364	43.205	74.00	54.00	Pass
01 (Average)	2396.800	-4.172	59.802	55.630	--	--	--
01 (Average)	2400.000	-4.171	54.678	50.507	--	--	--
01 (Average)	2411.200	-4.168	101.765	97.597	--	--	--

Figure Channel 01: Vertical (Peak)





Figure Channel 01: Vertical (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2462.900	-2.622	107.771	105.149	--	--	--
11 (Peak)	2483.500	-2.601	57.911	55.309	74.00	54.00	Pass
11 (Peak)	2486.700	-2.598	59.896	57.297	74.00	54.00	Pass
11 (Peak)	2462.700	-2.621	103.412	100.790	--	--	--
11 (Average)	2483.500	-2.601	46.805	44.203	74.00	54.00	Pass
11 (Average)	2486.500	-2.598	49.993	47.394	74.00	54.00	Pass

Figure Channel 11: Horizontal (Peak)





Figure Channel 11: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2462.900	-4.032	106.039	102.007	--	--	--
11 (Peak)	2483.500	-3.966	56.207	52.240	74.00	54.00	Pass
11 (Peak)	2486.300	-3.957	58.129	54.171	74.00	54.00	Pass
11 (Peak)	2461.100	-4.037	101.555	97.518	--	--	--
11 (Average)	2483.500	-3.966	45.506	41.539	74.00	54.00	Pass
11 (Average)	2486.500	-3.957	47.843	43.886	74.00	54.00	Pass

Figure Channel 11: Vertical (Peak)





Figure Channel 11: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBUV)	Emission Level (dBUV/m)	Peak Limit (dBUV/m)	Average Limit (dBUV/m)	Result
01 (Peak)	2386.800	-2.701	67.616	64.915	74.00	54.00	Pass
01 (Peak)	2390.000	-2.687	67.316	64.629	74.00	54.00	Pass
01 (Peak)	2399.400	-2.661	86.444	83.783	--	--	--
01 (Peak)	2400.000	-2.660	86.275	83.615	--	--	--
01 (Peak)	2415.600	-2.642	110.315	107.673	--	--	--
01(Average)	2390.000	32.287	54.533	51.846	74.00	54.00	Pass
01(Average)	2400.000	32.308	68.388	65.728	--	--	--
01(Average)	2407.800	32.320	99.029	96.381	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
 4. “ * ”, means this data is the worst emission level.
 5. Measurement Level = Reading Level + Correct Factor.
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	-4.159	66.332	62.173	74.00	54.00	Pass
01 (Peak)	2400.000	-4.171	84.973	80.802	--	--	--
01 (Peak)	2409.400	-4.168	107.891	103.722	--	--	--
01 (Average)	2390.000	-4.159	51.922	47.763	74.00	54.00	Pass
01 (Average)	2400.000	-4.171	66.763	62.592	--	--	--
01 (Average)	2408.600	-4.169	97.340	93.171	--	--	--

Figure Channel 01: Vertical (Peak)





Figure Channel 01: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2465.300	-2.619	107.615	104.996	--	--	--
11 (Peak)	2483.500	-2.601	59.970	57.368	74.00	54.00	Pass
11 (Peak)	2485.300	-2.600	64.250	61.650	74.00	54.00	Pass
11 (Average)	2465.700	-2.620	96.561	93.942	--	--	--
11 (Average)	2483.500	-2.601	48.723	46.121	74.00	54.00	Pass

Figure Channel 11: Horizontal (Peak)





Figure Channel 11: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2465.700	-4.024	105.758	101.735	--	--	--
11 (Peak)	2483.500	-3.966	61.067	57.100	74.00	54.00	Pass
11 (Peak)	2490.700	-3.944	62.427	58.483	74.00	54.00	Pass
11 (Average)	2459.700	-4.042	95.698	91.656	--	--	--
11 (Average)	2483.500	-3.966	47.127	43.160	74.00	54.00	Pass

Figure Channel 11: Vertical (Peak)





Figure Channel 11: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2389.600	-2.688	67.761	65.072	74.00	54.00	Pass
01 (Peak)	2390.000	-2.687	65.908	63.221	74.00	54.00	Pass
01 (Peak)	2400.000	-2.660	88.192	85.532	--	--	--
01 (Peak)	2407.800	-2.648	110.093	107.445	--	--	--
01 (Average)	2390.000	-2.687	50.006	47.319	74.00	54.00	Pass
01 (Average)	2400.000	-2.660	66.510	63.850	--	--	--
01 (Average)	2409.600	-2.645	98.490	95.844	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2389.800	-4.158	67.969	63.811	74.00	54.00	Pass
01 (Peak)	2390.000	-4.159	67.566	63.407	74.00	54.00	Pass
01 (Peak)	2400.000	-4.171	88.811	84.640	--	--	--
01 (Peak)	2410.200	-4.169	110.616	106.447	--	--	--
01 (Average)	2390.000	-4.159	49.474	45.315	74.00	54.00	Pass
01 (Average)	2400.000	-4.171	64.177	60.006	--	--	--
01 (Average)	2412.400	-4.166	93.476	89.311	--	--	--

Figure Channel 01: Vertical (Peak)





Figure Channel 01: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2466.300	-2.618	111.087	108.469	--	--	--
11 (Peak)	2483.500	-2.601	66.014	63.412	74.00	54.00	Pass
11 (Average)	2464.300	-2.620	98.085	95.465	--	--	--
11 (Average)	2483.500	-2.601	49.678	47.076	74.00	54.00	Pass

Figure Channel 11: Horizontal (Peak)





Figure Channel 11: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmit - 802.11n-20BW_14.4Mbps

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2459.100	-4.043	111.218	107.175	--	--	--
11 (Peak)	2483.500	-3.966	61.360	57.393	74.00	54.00	Pass
11 (Peak)	2484.100	-3.965	64.972	61.007	74.00	54.00	Pass
11 (Average)	2465.300	-4.024	98.870	94.846	--	--	--
11 (Average)	2483.500	-3.966	48.049	44.082	74.00	54.00	Pass

Figure Channel 11: Vertical (Peak)





Figure Channel 11: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
03 (Peak)	2390.000	-2.687	65.326	62.639	74.00	54.00	Pass
03 (Peak)	2400.000	-2.660	80.095	77.435	--	--	--
03 (Peak)	2410.200	-2.645	106.174	103.529	--	--	--
03 (Average)	2390.000	-2.687	51.464	48.777	74.00	54.00	Pass
03 (Average)	2399.200	-2.661	58.813	56.151	--	--	--
03 (Average)	2400.000	-2.660	58.336	55.676	--	--	--
03 (Average)	2431.800	-2.639	89.380	86.742	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
03 (Peak)	2389.600	-4.157	65.234	61.077	74.00	54.00	Pass
03 (Peak)	2390.000	-4.159	65.121	60.962	74.00	54.00	Pass
03 (Peak)	2400.000	-4.171	79.187	75.016	--	--	--
03 (Peak)	2410.600	-4.169	105.133	100.964	--	--	--
03 (Average)	2390.000	-4.159	49.610	45.451	74.00	54.00	Pass
03 (Average)	2400.000	-4.171	57.951	53.780	--	--	--
03 (Average)	2425.800	-4.132	86.896	82.763	--	--	--

Figure Channel 01: Vertical (Peak)





Figure Channel 01: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
09 (Peak)	2454.700	-2.628	103.895	101.267	--	--	--
09 (Peak)	2483.500	-2.601	61.890	59.288	74.00	54.00	Pass
09 (Average)	2463.300	-2.622	91.430	88.809	--	--	--
09 (Average)	2483.500	-2.601	47.076	44.474	74.00	54.00	Pass

Figure Channel 07: Horizontal (Peak)





Figure Channel 07: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : RUGGED TABLET COMPUTER
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmit - 802.11n-40BW_30Mbps

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
09 (Peak)	2454.500	-4.057	105.060	101.003	--	--	--
09 (Peak)	2483.500	-3.966	58.800	54.833	74.00	54.00	Pass
09 (Peak)	2484.500	-3.964	59.807	55.843	74.00	54.00	Pass
09 (Average)	2457.300	-4.049	89.558	85.509	--	--	--
09 (Average)	2483.500	-3.966	45.921	41.954	74.00	54.00	Pass

Figure Channel 07: Vertical (Peak)





Figure Channel 07: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ * ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

7. Occupied Bandwidth


7.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

7.2. Test Setup



7.3. Limits

The minimum bandwidth shall be at least 500 kHz.

7.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2013; tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 1-5% of the emission bandwidth, $VBW \geq 3 * RBW$

7.5. Uncertainty


$\pm 150\text{Hz}$

7.6. Test Result of Occupied Bandwidth

Product : RUGGED TABLET COMPUTER
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412.00	10150	>500	Pass


Figure Channel 1:



Product : RUGGED TABLET COMPUTER
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6	2437.00	10150	>500	Pass


Figure Channel 6:



Product : RUGGED TABLET COMPUTER
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11	2462.00	10150	>500	Pass


Figure Channel 11:



Product : RUGGED TABLET COMPUTER
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412.00	15450	>500	Pass


Figure Channel 1:



Product : RUGGED TABLET COMPUTER
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6	2437.00	15250	>500	Pass

Figure Channel 6:



Product : RUGGED TABLET COMPUTER
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11	2462.00	15200	>500	Pass

Figure Channel 11:

