4 FCC §15.247(i), §2.1091 & IC RSS-102 - RF Exposure

4.1 Applicable Standard

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
	Limits for Gene	eral Population/Uncontro	olled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	$*(180/f^2)$	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

Before equipment certification is granted, the procedure of IC RSS-102 must be followed concerning the exposure of humans to RF fields.

According to RSS-102 Issue 2 section 4.1, RF limits used for general public will be applied to the EUT.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m²)	Time Averaging (min)
0.003 - 1	280	2.19	-	6
1 - 10	280 / f	2.19 / f	-	6
10 - 30	28	2.19 / f	-	6
30 – 300	28	0.073	2*	6
300 – 1 500	1.585 f ^{0.5}	$0.0042 \text{ f}^{0.5}$	f / 150	6
1 500 – 15 000	61.4	0.163	10	6
15 000 – 150 000	61.4	0.163	10	616000 / f ^{1.2}
150 000- 300 000	$0.158 \text{ f}^{0.5}$	4.21 x 10 -4 f ^{0.5}	6.67 x 10 ⁻⁵ f	616000 / f ^{1.2}

Note: *f* is frequency in MHz

^{* =} Plane-wave equivalent power density

^{*} Power density limit is applicable at frequencies greater than 100 MHz

4.2 **MPE Prediction**

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G =power gain of the antenna in the direction of interest relative to an isotropic radiator R =distance to the center of radiation of the antenna

4.3 **MPE Results**

Antenna gain 5 dBi

Maximum peak output power at antenna input terminal (dBm):	<u>25.72</u>
Maximum peak output power at antenna input terminal (mW):	<u>373.25</u>
Prediction distance (cm):	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>2462</u>
Maximum Antenna Gain, typical (dBi):	<u>5.0</u>
Maximum Antenna Gain (numeric):	<u>3.16</u>
Power density of prediction frequency at 20.0 cm (mW/cm ²):	0.23
Power density of prediction frequency at 20.0 cm (W/m ²):	<u>2.3</u>
MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	<u>1.0</u>
MPE limit for uncontrolled exposure at prediction frequency (W/m ²):	<u>10</u>

Antenna gain 9 dBi

<u>23.46</u>	Maximum peak output power at antenna input terminal (dBm):
221.82	Maximum peak output power at antenna input terminal (mW):
<u>20</u>	<u>Prediction distance (cm):</u>
<u>2452</u>	<u>Prediction frequency (MHz):</u>
<u>9.0</u>	Maximum Antenna Gain, typical (dBi):
<u>7.94</u>	Maximum Antenna Gain (numeric):
<u>0.35</u>	Power density of prediction frequency at 20.0 cm (mW/cm ²):
<u>3.5</u>	Power density of prediction frequency at 20.0 cm (W/m ²):
<u>1.0</u>	MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):
<u>10</u>	MPE limit for uncontrolled exposure at prediction frequency (W/m ²):

Antenna gain 19 dBi

Maximum peak output power at antenna input terminal (dBm):16.95Maximum peak output power at antenna input terminal (mW):49.55Prediction distance (cm):20Prediction frequency (MHz):2412Maximum Antenna Gain, typical (dBi):19.0Maximum Antenna Gain (numeric):79.43Power density of prediction frequency at 20.0 cm (mW/cm²):0.78

Power density of prediction frequency at 20.0 cm (W/m²): 7.8

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

MPE limit for uncontrolled exposure at prediction frequency (W/m²): 10

Device is compliance with the requirement MPE limit at 20 cm distance for the uncontrolled exposure.