

5.15-5.875 GHz 5.5dBi Omni directional Antenna

Specifications				
MTI PART NUMBER	MT - 481003/NV			
ELECTRICAL				
REGULATORY COMPLIANCE	RoHS, CE 0682			
FREQUENCY RANGE	5.15 - 5.875 GHz			
PEAK GAIN + AZIMUTH RIPPLE	5.0 dBi ± 1 dB @ 5.15 - 5.25 GHz 5.5 dBi ± 1 dB @ 5.25 - 5.47 GHz 6.0 dBi ± 1 dB @ 5.47 - 5.875 GHz			
GAIN + AZIMUTH RIPPLE @ HORIZON	4.0 dBi ± 1 dB @ 5.15 GHz, 5.5 dBi ± 1 dB @ 5.35 GHz 6.0 dBi ± 1 dB @ 5.55 GHz, 5.5 dBi ± 1 dB @ 5.75 GHz 4.0 dBi ± 1 dB @ 5.875 GHz			
VSWR	1.7:1 (max) 1.5:1 (typ)			
AZIMUTH BEAMWIDTH	Omni - 360°			
POLARIZATION	Linear Vertical			
ELECTRICAL TILT	-8° @ 5.15 GHz, -2°@ 5.35 GHz +1°@ 5.55 GHz, +5°@ 5.75 GHz +8°@ 5.875 GHz			
E - PLANE BEAMWIDTH	22° (typ)			
INPUT IMPEDANCE	50 (ohm)			
INPUT POWER	6W (max)			
LIGHTNING PROTECTION	DC Grounded			
MECHANICAL				
DIMENSIONS WITH CONNECTOR : DIAMETER X HEIGHT	16mm X 191 mm (max)			
WEIGHT	0.1 kg (max)			
CONNECTOR	N-Type Female			
RADOME	Plastic, UV Resistant			
OUTLINE DRAWING	(a			


MECHANICAL	
DIMENSIONS WITH CONNECTOR: DIAMETER X HEIGHT	16mm X 191 mm (max)
WEIGHT	0.1 kg (max)
CONNECTOR	N-Type Female
RADOME	Plastic, UV Resistant
OUTLINE DRAWING	See page 2
MOUNTING KIT	Mounted to pole ø1.5" - ø3" by the means of 2 clamps.

ENVIRONMENTAL				
TEST	STANDARD	DURATION	TEMPERTURE	NOTES
LOW TEMPERATURE	IEC 68-2-1	72 h	-55°C	-
HIGH TEMPERATURE	IEC 68-2-2	72 h	+71 °C	-
TEMP. CYCLING	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles
VIBRATION	IEC 60721-3-4	30 min/axis	-	Random 4M5
SHOCK MECHANICAL	IEC 60721-3-4	-	-	4M5
HUMIDITY	ETSI EN300-2-4 T4.1E	144 h	-	95%
WATER TIGHTNESS	IEC 529	-	-	IP64
SOLAR RADIATION	ASTAM G53	1000 h	-	-
SALT SPRAY	IEC 68-2-11 Ka	500 h	-	-
ICE AND SNOW	-	-	-	25mm Radial
WIND SPEED SURVIVAL	-	-	-	220 Km/h
OPERATION		-	-	160 Km/h



5.15-5.875 GHz 5.5dBi Omni directional Antenna

Azimuth Radiation Pattern Elevation Radiation Pattern Midband Freq. 5.35 GHz Midband Freq. 5.35 GHz -15 -15 15 -30 30 -30 30 -45 45 -45 45 -60 60 -60 60 -75 75 -75 75 -90 90 -90 90 20 -20 -105 105 -105 105 -120 120 -120 120 -135 135 -135 135 -150 150 -150 150 -165 165 -165 165 180 180



MTI Wireless Edge is certified according to ISO 9001 and ISO 14001.

WAIVER.

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

MTI Wireless Edge Ltd.

11 Hamelacha St. Afek Industrial Park Rosh Ha'ayin 48091, Israel Tel: +972-3-9008900 Fax: +972-3-9008901 www.mtiwe.com