



# FCC RADIO EXPOSURE TEST REPORT

**FCC ID** : S9GQ710US00  
**Equipment** : Q710 LTE Access Point  
**Brand Name** : Ruckus  
**Model Name** : Q710-US00  
**Applicant** : Ruckus Wireless, Inc.  
350 West Java Drive Sunnyvale California 94089  
USA  
**Manufacturer** : Ruckus Wireless, Inc.  
350 West Java Drive Sunnyvale California 94089  
USA  
**Standard** : 47 CFR Part 2.1091

The product was received on May 10, 2018, and testing was started from May 14, 2018 and completed on Dec. 04, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jordan Hsiao

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 EUT General Information .....	5
1.2 Testing Location .....	5
<b>2 Maximum Permissible Exposure .....</b>	<b>6</b>
2.1 Limit of Maximum Permissible Exposure .....	6
2.2 MPE Calculation Method.....	6
2.3 Calculated Result and Limit.....	7
<b>Photographs of EUT v01</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FA850948	01	Initial issue of report	Jul. 16, 2018
FA850948	02	Update the MPE test result	Oct. 04, 2018
FA850948	03	Add the antenna cable loss for the antenna. Thus update the MPE test result	Dec. 18, 2018



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Reviewed by: Jordan Hsiao

Report Producer: Sharon Jiang



# 1 General Description

## 1.1 EUT General Information

RF General Information	
Operating Frequency (MHz)	Modulation Type
10MHz: 3555 MHz ~ 3695 MHz 20MHz: 3560 MHz ~ 3690 MHz	QPSK, 16QAM, 64QAM

## 1.2 Testing Location

Testing Location		
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456      FAX : 886-3-327-0973
<input type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065      FAX : 886-3-656-9085

Test site Designation No. TW1190 with FCC.

Test site registered number IC 4086B-1 with Industry Canada.



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
20MHz (QPSK) 3690MHz	2.25	26.32	28.57	2.00	30.57	1.14025	20	0.22684	1

—THE END—