

MPE CALCULATION

FCC ID: S9GT710

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band: 2.4GHz	2412-2462 MHz
EUT Frequency Band: 5 GHz	5180- 5320MHz, 5500-5720MHz, 5745-5825MHz 5210-5290MHz, 5530-5610MHz, 5690-5775MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	1 mW / cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 25cm

Array Gain = 3dBi

EUT: ZoneFlex T710 Access Point

(2.4GHz Band): Power = 26.56 dBm, Array Gain + Antenna Gain = 5.5 dBi, Power density = 0.204mW/ cm²

(5 GHz Band) : Power = 26.37 dBm, Array Gain + Antenna Gain = 6.5 dBi, Power density = 0.246mW/ cm²

Total Ratio= $(P_{2.4GHz}/1) + (P_{5GHzUNI}/1) = 0.204 \text{ mW/ cm}^2 + 0.246 \text{ mW/ cm}^2 = 0.450 \text{ mW/ cm}^2$

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Gary Chou

Gary Chou

SIEMIC, Inc.

775 Montague Expressway, Milpitas, CA 95035

Date: 02/12/2016