

RF TEST REPORT



Report No.: FCC_RF_SL15091701-RUC-034A1_UNII Rev 1.0
Supersede Report No.: FCC_RF_SL15091701-RUC-034A1_UNII

Applicant	:	Ruckus Wireless, Inc.
Product Name	:	ZoneFlex T710 Access Point
Model No.	:	T710
Test Standard	:	47 CFR 15.407
Test Method	:	ANSI C63.4: 2014 789033 D02 General UNII Test Procedures New Rules v01
FCC ID	:	S9GRT710
IC ID	:	5912A-T710
Dates of test	:	11/01/2015 to 11/20/2015
Issue Date	:	02/09/2016
Test Result	:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		

This Test Report is Issued Under the Authority of:	
Gary Chou	Chen Ge
Test Engineer	Engineer Reviewer
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only	

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile (+1) 408 526 1088

Visit us at: www.siemic.com; Follow us at:

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety
Israel	MOC, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

CONTENTS

1 REPORT REVISION HISTORY4

2 EXECUTIVE SUMMARY5

3 CUSTOMER INFORMATION5

4 TEST SITE INFORMATION5

5 MODIFICATION5

6 EUT INFORMATION6

6.1 EUT Description 6

6.2 Radio Description 6

7 SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION8

7.1 Supporting Equipment 8

7.2 Cabling Description 8

7.3 Test Software Description 8

8 TEST SUMMARY9

9 MEASUREMENT UNCERTAINTY 10

10 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 11

10.1 Conducted Emissions 11

10.2 6dB & 26 dB Bandwidth 16

10.3 Output Power 23

10.4 Peak Power Spectral Density 26

10.5 Band Edge Measurement 47

10.6 Radiated Spurious Emissions below 1GHz 60

10.7 Radiated Spurious Emissions above 1GHz 62

ANNEX A. TEST INSTRUMENT 72

ANNEX B. SIEMIC ACCREDITATION 73

1 Report Revision History

Report No.	Report Version	Description	Issue Date
FCC_RF_SL15091701-RUC-034A1_UNII	None	Original	01/25/2016
FCC_RF_SL15091701-RUC-034A1_UNII Rev 1.0	1.0	Updated per TCB reviewer	02/09/2016

2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: Ruckus Wireless, Inc.
Product: ZoneFlex T710 Access Point
Model: T710

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

Applicant Name	:	Ruckus Wireless, Inc.
Applicant Address	:	350 West Java Drive, Sunnyvale, California 94089 U.S.A
Manufacturer Name	:	Ruckus Wireless, Inc.
Manufacturer Address	:	350 West Java Drive, Sunnyvale, California 94089 U.S.A

4 Test site information

Lab performing tests	SIEMIC Laboratories
Lab Address	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	881796
IC Test Site No.	4842D-2
VCCI Test Site No.	A0133

5 Modification

Index	Item	Description	Note
-	-	-	-

6 EUT Information

6.1 EUT Description

Product Name	ZoneFlex T710 Access Point
Model No.	T710
Trade Name	Ruckus
Serial No.	421506000085
Host Model No.	N/A
Input Power	100Vac-240Vac 50-60Hz / 48VDC 1.0A (PoE)
Poe Power Adapter Manu/Model	Ruckus Wireless, Inc. / GRT-480125A(740-64216-001)
AC/DC Power Adapter SN	N/A
PoE Power Adapter SN	20150129
Product Hardware version	705-60425-001
Product Software version	812-72410-002
Radio Hardware version	705-60425-001
Radio Software version	812-72410-002
Test Software version	117-11325-001
Date of EUT received	11/05/2015
Equipment Class/ Category	DTS, UNII
Clock Frequencies	N/A
Port/Connectors	PoE, Ethernet

6.2 Radio Description

Radio Type	802.11a	802.11n-20M	802.11n-40M	802.11ac-80M
Operating Frequency	5260-5320MHz 5500-5720MHz	5260-5320MHz 5500-5720MHz	5270-5310MHz 5510-5710MHz	5290MHz, 5530MHz 5610MHz, 5690MHz
Modulation	OFDM (BPSK, QPSK, 16QAM, 64QAM)	OFDM (BPSK, QPSK, 16QAM, 64QAM)	OFDM (BPSK, QPSK, 16QAM, 64QAM)	OFDM (BPSK, QPSK, 16QAM, 64QAM)
Channel Spacing	20MHz	20MHz	40MHz	80MHz
Number of Channels	16	16	6	4
Antenna Type	Internal Omnidirectional Antenna			
Antenna Gain (Peak)	2.4GHz: Horizontal 1dBi, Vertical 2.5dBi 5GHz: Horizontal 2dBi, Vertical 3.5dBi			
Antenna Connector Type	U.FL			
Note	<p>EUT has 4 antennas, 2 antennas are in horizontal polarity, and 2 antennas in vertical polarity. The 802.11b/g/a is in CDD mode with all 4 antenna transmit simultaneously.</p> <p>Since they're in 90 deg phase shift between the horizontal and vertical antennas, for radiated limit, the result from different polarization antenna will not be combined. So only the result for 2 vertical polarity antennas and 2 horizontal polarity antennas will be combined for MIMO mode separately. For Cross-polarized antenna, the total gain—including array gain—is computed separately for each of polarizations using the procedures presented in this document. The highest of the total gains shall apply. For this case, the highest of the total gain will be the directional gain of 2 antennas.</p> <p>For conducted limit like power and psd, the result from all 4 chains will be summed.</p> <p>For 802.11b/g/a mode under CDD mode, the array gain for power will be 0 and for PSD will be 10 log (Nant/Nss) dB</p>			

	to be calculated separately for horizontal and vertical polarity. Reference to the following KDB for clarification. <u>662911 D01 Multiple Transmitter Output v02r01</u> <u>662911 D02 MIMO with Cross-Polarized Antennas v01</u>
--	---

EUT Power level setting

Mode	Frequency	Power Setting
802.11-a	5260	17
802.11-a	5280	17
802.11-a	5320	17
802.11-n-20	5260	17
802.11-n-20	5280	17
802.11-n-20	5320	17
802.11-n-40	5270	17
802.11-n-40	5310	17
802.11-ac-80	5290	17
802.11-a	5550	17
802.11-a	5580	17
802.11-a	5700	17
802.11-n-20	5500	17
802.11-n-20	5580	17
802.11-n-20	5700	17
802.11-n-40	5510	17
802.11-n-40	5590	17
802.11-n-40	5670	17
802.11-ac-80	5530	17
802.11-ac-80	5530	17

CROSS Band channels power setting

Mode	Frequency	Power Setting
802.11-a	5720	17
802.11-n-20	5720	17
802.11-n-40	5710	17
802.11-ac-80	5690	17

Note: All data rate has been verified and worst case was used for all test items.

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

Item	Supporting Equipment Description	Model	Serial Number	Manufacturer	Note
1	Laptop	PP01L Latitude C610	CN-06P823-48643-37P-4153	Dell	-
2	EUT power Supply	HK-AD-120A100-US	740-64190-011	Ruckus	-

7.2 Cabling Description

Name	Connection Start		Connection Stop		Length / shielding Info		Note
	From	I/O Port	To	I/O Port	Length (m)	Shielding	
RJ45	EUT	RJ45	POE	RJ45	2	Unshielded	-
RJ45	POE	RJ45	Laptop	RJ45	3	Unshielded	-

7.3 Test Software Description

Test Item	Software	Description
RF Testing	Command Line in windows	Set the EUT to transmit continuously in diferent test mode

8 Test Summary

Test Item	Test standard	Test Method/Procedure	Pass / Fail
Restricted Band of Operation	FCC 15.205	ANSI C63.4 – 2014 789033 D02 General UNII Test Procedures New Rules v01	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
AC Conducted Emissions Voltage	FCC 15.207(a)	ANSI C63.4 – 2014	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A

Test Item	Test standard	Test Method/Procedure	Pass / Fail
26 & 6 dB Emission Bandwidth	FCC 15.407 (a) (2)	789033 D02 General UNII Test Procedures New Rules v01	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Maximum conducted Output Power	FCC 15.407 (a) (2)	789033 D02 General UNII Test Procedures New Rules v01	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Power reduction (Antenna Gain > 6 dBi)	FCC 15.407 (a) (2)	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
Band Edge and Radiated Spurious Emissions	FCC 15.407(b)(2), 15.407(b)(6)	ANSI C63.4 – 2014 789033 D02 General UNII Test Procedures New Rules v01	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Power Spectral Density	FCC 15.407 (a) (2)	789033 D02 General UNII Test Procedures New Rules v01	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
Frequency Stability	FCC 15.407 (g)	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
Transmit Power Control (TPC)	FCC 15.407 (h)(1)	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
User Manual	FCC -	-	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A

Remark	<ol style="list-style-type: none"> All measurement uncertainties are not taken into consideration for all presented test result. The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual.
--------	---

9 Measurement Uncertainty


Emissions			
Test Item	Frequency Range	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	30MHz – 1GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
Band Edge and Radiated Spurious Emissions	1GHz – 40GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+4.3dB/-4.1dB

10 Measurements, Examination and Derived Results

10.1 Conducted Emissions

Conducted Emission Limit

Frequency ranges (MHz)	Limit (dBuV)	
	QP	Average
0.15 ~ 0.5	66 – 56	56 – 46
0.5 ~ 5	56	46
5 ~ 30	60	50

Spec	Item	Requirement	Applicable
47CFR§15.207	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequency ranges.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes</p>		
Procedure	<ul style="list-style-type: none"> - The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B. - The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. - All other supporting equipment was powered separately from another main supply. 		
Remark	EUT tested with AC 120V 60Hz		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data Yes N/A

Test Plot Yes (See below) N/A

Conducted Emission Test Results (Line)

Test specification:	Conducted Emissions			Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Environmental Conditions:	Temp(°C):	22.2		
	Humidity (%):	37.1		
	Atmospheric(mbar):	1020.5		
Mains Power:	120Vac, 60Hz			
Tested by:	Teody Manansala			
Test Date:	2015-11-17			
Remarks:	Line – Tested with AC Line Power Cord			

AC Line – Line Plot @ 120V 60Hz



Power Line Conducted Emissions
Filename: c:\program files\emisoft - vasona\results\ruc-034 FCC ac source @ Line.emi


AC Line - Line Measurements @ 120V 60Hz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
15.16	32.11	10.06	0.60	42.77	Quasi Peak	Line	60.00	-17.23	Pass
16.11	35.03	10.06	0.62	45.71	Quasi Peak	Line	60.00	-14.29	Pass
3.43	22.84	10.03	0.55	33.42	Quasi Peak	Line	56.00	-22.58	Pass
14.85	33.91	10.06	0.60	44.57	Quasi Peak	Line	60.00	-15.43	Pass
15.80	38.06	10.06	0.62	48.73	Quasi Peak	Line	60.00	-11.27	Pass
3.90	22.92	10.03	0.55	33.50	Quasi Peak	Line	56.00	-22.50	Pass
15.16	29.52	10.06	0.60	40.18	Average	Line	50.00	-9.82	Pass
16.11	32.89	10.06	0.62	43.57	Average	Line	50.00	-6.43	Pass
3.43	14.97	10.03	0.55	25.55	Average	Line	46.00	-20.45	Pass
14.85	29.94	10.06	0.60	40.60	Average	Line	50.00	-9.40	Pass
15.80	37.70	10.06	0.62	48.38	Average	Line	50.00	-1.62	Pass
3.90	14.59	10.03	0.55	25.17	Average	Line	46.00	-20.83	Pass

Conducted Emission Test Results (Neutral)

Test specification:	Conducted Emissions		
Environmental Conditions:	Temp(°C):	22.2	Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
	Humidity (%):	37.1	
	Atmospheric(mbar):	1020.5	
Mains Power:	120Vac, 60Hz		
Tested by:	Teody Manansala		
Test Date:	2015-11-17		
Remarks:	Neutral – Tested with AC Line Power Cord		

AC Line – Neutral Plot @ 120V 60Hz




Power Line Conducted Emissions
Filename: c:\program files\emisoft - vasona\results\ruc-034 FCC ac source @Neutral.emi

AC Line - Neutral Measurements @ 120V 60Hz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
16.14	36.45	10.06	0.62	47.13	Quasi Peak	Neutral	60.00	-12.87	Pass
15.80	36.86	10.06	0.62	47.54	Quasi Peak	Neutral	60.00	-12.46	Pass
3.71	22.51	10.03	0.55	33.09	Quasi Peak	Neutral	56.00	-22.91	Pass
4.06	20.97	10.03	0.55	31.55	Quasi Peak	Neutral	56.00	-24.45	Pass
15.48	35.04	10.06	0.61	45.71	Quasi Peak	Neutral	60.00	-14.29	Pass
15.40	34.96	10.06	0.61	45.63	Quasi Peak	Neutral	60.00	-14.37	Pass
16.14	33.11	10.06	0.62	43.80	Average	Neutral	50.00	-6.20	Pass
15.80	36.53	10.06	0.62	47.20	Average	Neutral	50.00	-2.80	Pass
3.71	13.40	10.03	0.55	23.98	Average	Neutral	46.00	-22.02	Pass
4.06	13.23	10.03	0.55	23.82	Average	Neutral	46.00	-22.18	Pass
15.48	32.03	10.06	0.61	42.70	Average	Neutral	50.00	-7.30	Pass
15.40	32.06	10.06	0.61	42.73	Average	Neutral	50.00	-7.27	Pass

Conducted Emission Test Results (Line)

Test specification:	Conducted Emissions			
Environmental Conditions:	Temp(°C):	21	Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
	Humidity (%):	42		
	Atmospheric(mbar):	1021		
Mains Power:	120Vac, 60Hz			
Tested by:	Teody Manansala			
Test Date:	11/17/2015			
Remarks	Line – Tested with Poe			




Live Line Plot at 120Vac, 60Hz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line	Limit (dBuV)	Margin (dB)	Pass /Fail
0.45	34.77	10.01	0.71	45.49	Quasi Peak	Line	56.90	-11.41	Pass
0.81	31.99	10.01	0.60	42.60	Quasi Peak	Line	56.00	-13.40	Pass
0.53	32.18	10.01	0.67	42.86	Quasi Peak	Line	56.00	-13.14	Pass
0.29	36.72	10.00	0.94	47.66	Quasi Peak	Line	60.51	-12.85	Pass
0.58	29.70	10.01	0.65	40.35	Quasi Peak	Line	56.00	-15.65	Pass
0.74	30.86	10.01	0.61	41.48	Quasi Peak	Line	56.00	-14.52	Pass
0.45	26.69	10.01	0.71	37.41	Average	Line	46.90	-9.49	Pass
0.81	21.06	10.01	0.60	31.67	Average	Line	46.00	-14.33	Pass
0.53	19.15	10.01	0.67	29.83	Average	Line	46.00	-16.17	Pass
0.29	30.08	10.00	0.94	41.02	Average	Line	50.51	-9.50	Pass
0.58	20.03	10.01	0.65	30.68	Average	Line	46.00	-15.32	Pass
0.74	19.00	10.01	0.61	29.62	Average	Line	46.00	-16.38	Pass

Conducted Emission Test Results (Neutral)

Test specification:	Conducted Emissions			
Environmental Conditions:	Temp(°C):	21	Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
	Humidity (%):	42		
	Atmospheric(mbar):	1021		
Mains Power:	120Vac, 60Hz			
Tested by:	Teody Manansala			
Test Date:	11/17/2015			
Remarks	Neutral – Tested with Poe			




Neutral Line@ 120Vac, 60Hz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line	Limit (dBuV)	Margin (dB)	Pass /Fail
0.45	32.91	10.01	0.71	43.63	Quasi Peak	Neutral	56.84	-13.21	Pass
0.34	32.32	10.01	0.83	43.16	Quasi Peak	Neutral	59.22	-16.06	Pass
0.17	38.90	10.00	1.59	50.50	Quasi Peak	Neutral	65.14	-14.64	Pass
0.28	34.48	10.00	0.95	45.43	Quasi Peak	Neutral	60.68	-15.25	Pass
0.53	29.23	10.01	0.67	39.91	Quasi Peak	Neutral	56.00	-16.09	Pass
0.81	30.99	10.01	0.60	41.60	Quasi Peak	Neutral	56.00	-14.40	Pass
0.45	25.11	10.01	0.71	35.83	Average	Neutral	46.84	-11.01	Pass
0.34	25.19	10.01	0.83	36.03	Average	Neutral	49.22	-13.19	Pass
0.17	25.06	10.00	1.59	36.66	Average	Neutral	55.14	-18.48	Pass
0.28	28.89	10.00	0.95	39.85	Average	Neutral	50.68	-10.84	Pass
0.53	15.95	10.01	0.67	26.63	Average	Neutral	46.00	-19.37	Pass
0.81	20.22	10.01	0.60	30.83	Average	Neutral	46.00	-15.17	Pass

Note: The results above show only the worst case.

10.2 6dB & 26 dB Bandwidth

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.407	-	26 dB Emission BW: Report only for reference.	<input checked="" type="checkbox"/>
	-	6 dB Emission BW: Report only for reference(Cross Band)	<input checked="" type="checkbox"/>
	a) (2)	26 dB Emission BW: Report only for power limit calculation.	<input type="checkbox"/>
Test Setup			
Test Procedure	<p>789033 D02 General UNII Test Procedures New Rules v01</p> <p><u>26dB Emission bandwidth measurement procedure (Other than 5.725-5.85 GHz)</u></p> <ul style="list-style-type: none"> - Use the spectrum analyzer built-in measurement function to determine the 26dB BW. <ul style="list-style-type: none"> o Set RBW = around 1% of emission bandwidth o Set VBW > RBW o Detector = Peak o Trace mode = max hold - Allow the trace to stabilize. - Capture the plot. - Repeat above steps for different test channel and other modulation type. <p><u>6dB Emission bandwidth measurement procedure</u></p> <ul style="list-style-type: none"> - Use the spectrum analyzer built-in measurement function to determine the 26dB BW. <ul style="list-style-type: none"> o Set RBW = 100kHz o Set VBW > 3RBW o Detector = Peak o Trace mode = max hold - Allow the trace to stabilize. - Capture the plot. - Repeat above steps for different test channel and other modulation type. 		
Test Date	11/25/2015	Environmental condition	Temperature 23°C Relative Humidity 42% Atmospheric Pressure 1021mbar
Remark	N/A		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A
Test Plot Yes N/A

26dB Bandwidth measurement result for 5.3GHz

Type	Test mode	Freq (MHz)	CH	Result (MHz)
26dB BW	802.11a	5260	Low	18.61
26dB BW	802.11a	5280	Mid	19.02
26dB BW	802.11a	5320	High	18.68
26dB BW	802.11n-20	5260	Low	19.72
26dB BW	802.11n-20	5280	Mid	19.45
26dB BW	802.11n-20	5320	High	19.67
26dB BW	802.11n-40	5270	Low	38.26
26dB BW	802.11n-40	5310	High	38.14
26dB BW	802.11ac-80	5290	Mid	83.92

26dB Bandwidth measurement result for 5.5GHz

Type	Test mode	Freq (MHz)	CH	Result (MHz)
26dB BW	802.11a	5500	Low	18.76
26dB BW	802.11a	5580	Mid	18.59
26dB BW	802.11a	5700	High	18.17
26dB BW	802.11n-20	5500	Low	19.86
26dB BW	802.11n-20	5580	Mid	19.76
26dB BW	802.11n-20	5700	High	19.95
26dB BW	802.11n-40	5510	Low	39.05
26dB BW	802.11n-40	5590	Mid	38.50
26dB BW	802.11n-40	5670	High	38.41
26dB BW	802.11ac-80	5530	Low	82.29


26dB Bandwidth measurement result for cross channels


Type	Test mode	Freq (MHz)	CH	Result (MHz)
26dB BW	802.11a	5720	CROSS	18.37
26dB BW	802.11n-20	5720	CROSS	19.76
26dB BW	802.11n-40	5710	CROSS	38.34
26dB BW	802.11ac-80	5690	CROSS	82.46

6 Bandwidth measurement result for cross channels


Type	Test mode	Freq (MHz)	CH	Result (MHz)
26dB BW	802.11a	5720	CROSS	16.44
26dB BW	802.11n-20	5720	CROSS	17.55
26dB BW	802.11n-40	5710	CROSS	35.02
26dB BW	802.11ac-80	5690	CROSS	73.7

26dB Bandwidth Test Plots







26dB BW -802.11n-40M 5310MHz




26dB BW -802.11ac-80M 5290MHz




26dB BW -802.11a 5500MHz




26dB BW -802.11a 5580MHz




26dB BW -802.11a 5700MHz




26dB BW -802.11n-20M 5500MHz




26dB BW -802.11n-20M 5580MHz



26dB BW -802.11n-20M 5700MHz




26dB BW -802.11n-40M 5510MHz




26dB BW -802.11n-40M 5550MHz




26dB BW -802.11n-40M 5670MHz




26dB BW -802.11ac-80M 5530MHz




26dB BW -802.11a CROSS 5720MHz




26dB BW -802.11n-20M 5720MHz




26dB BW -802.11n-40M CROSS 5710MHz




26dB BW -802.11ac CROSS 5690MHz




6dB BW -802.11a CROSS 5720MHz



6dB BW -802.11n-20M CROSS 5720MHz




6dB BW -802.11n-40M CROSS 5710MHz



6dB BW -802.11ac CROSS 5690MHz

10.3 Output Power

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.407	a)(1)(i)	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).	<input type="checkbox"/>
	a)(1)(ii)	For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.	<input type="checkbox"/>
	a)(1)(iv)	For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.	<input type="checkbox"/>
	a)(2)	For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz.	<input checked="" type="checkbox"/>
	a)(3)	For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram shows a blue power meter with a probe connected to a pink box labeled 'EUT'. The power meter is labeled 'Power Meter'.</p>		
Test Procedure	<p>789033 D02 General UNII Test Procedures New Rules v01</p> <p><u>Measurement using a Power Meter (PM)</u> Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.</p> <ul style="list-style-type: none"> - Connect EUT's RF output power to power meter - Set EUT to be continuous transmission mode - Measurement the average output power using power meter and record the result - Repeat above steps for different test channel and other modulation type. 		
Test Date	11/25/2015	Environmental condition	Temperature 23°C Relative Humidity 44% Atmospheric Pressure 1021mbar
Remark	<p>Per KDB 662911 D01 Multiple Transmitter Output v02r01, the direction gain for horizontal polarization and vertical polarization is calculated separately. For 5Ghz band, peak antenna gain = 3.5 dBi, directional gain = 3 dB, total gain = 6.5 dBi Highest of total directional gain is 6.5 dBi. The power limit and PSD limit will be reduced by amount of 0.5 dB. For the Cross band channels, the output power of full bandwidth is compared to the power limit in 5.5G and 5.8G as the worst case.</p>		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A
Test Plot Yes (See below) N/A

Output Power measurement result for 5.3GHz

Type	Test mode	Freq (MHz)	CH	Conducted Power (dBm)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
Output	802.11a	5260	Low	14.80	15.05	15.81	14.75	21.14	23.5	Pass
Output	802.11a	5280	Mid	14.78	15.09	15.91	14.75	21.18	23.5	Pass
Output	802.11a	5320	High	15.04	15.07	15.82	14.99	21.26	23.5	Pass
Output	802.11n-20M	5260	Low	14.83	15.24	16.03	14.95	21.31	23.5	Pass
Output	802.11n-20M	5280	Mid	14.86	15.19	16.04	14.95	21.31	23.5	Pass
Output	802.11n-20M	5320	High	15.16	15.17	15.93	15.18	21.39	23.5	Pass
Output	802.11n-40M	5270	Low	14.90	15.25	16.16	15.02	21.38	23.5	Pass
Output	802.11n-40M	5310	Mid	14.95	15.24	16.17	14.96	21.38	23.5	Pass
Output	802.11ac-80M	5290	High	14.25	14.56	15.51	14.23	20.69	23.5	Pass

Output Power measurement result for 5.5GHz

Type	Test mode	Freq (MHz)	CH	Conducted Power (dBm)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
Output	802.11a	5500	Low	14.67	14.91	15.81	14.77	21.09	23.5	Pass
Output	802.11a	5580	Mid	14.54	14.76	15.82	14.63	20.99	23.5	Pass
Output	802.11a	5700	High	14.31	14.35	14.93	14.33	20.51	23.5	Pass
Output	802.11n-20M	5500	Low	14.68	14.92	15.97	14.88	21.16	23.5	Pass
Output	802.11n-20M	5580	Mid	14.55	14.79	15.99	14.76	21.08	23.5	Pass
Output	802.11n-20M	5700	High	14.37	14.43	15.02	14.48	20.60	23.5	Pass
Output	802.11n-40M	5510	Low	14.63	14.86	15.93	14.89	21.13	23.5	Pass
Output	802.11n-40M	5550	Mid	14.65	14.9	16.04	14.84	21.16	23.5	Pass
Output	802.11n-40M	5670	High	14.45	14.52	15.64	14.62	20.86	23.5	Pass
Output	802.11ac-80M	5530	Low	14.01	14.28	15.47	14.19	20.55	23.5	Pass
Output	802.11ac-80M	5610	High	13.90	14.22	15.10	14.15	20.39	23.5	Pass

Output Power measurement result for CROSS channels (in band 5470-5725MHz)

Type	Test mode	Freq (MHz)	CH	Conducted Power (dBm)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
Output	802.11a	5720	CROSS	14.51	14.34	15.01	14.58	20.64	23.5	Pass
Output	802.11n-20M	5720	CROSS	14.75	14.44	15.06	14.76	20.78	23.5	Pass
Output	802.11n-40M	5710	CROSS	14.82	14.58	15.2	14.73	20.86	23.5	Pass
Output	802.11ac-80M	5690	CROSS	14.04	13.99	15.01	14.19	20.35	23.5	Pass

Output Power measurement result for CROSS channels (in band 5725-5850MHz)

Type	Test mode	Freq (MHz)	CH	Conducted Power (dBm)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
Output	802.11a	5720	CROSS	14.48	14.35	14.97	14.56	20.62	29.5	Pass
Output	802.11n-20M	5720	CROSS	14.74	14.43	15.06	14.74	20.77	29.5	Pass
Output	802.11n-40M	5710	CROSS	14.82	14.58	15.24	14.70	20.86	29.5	Pass
Output	802.11ac-80M	5690	CROSS	14.10	14.01	15.00	14.20	20.37	29.5	Pass

PSD measurement result for 5.3GHz

Type	Test mode	Freq (MHz)	CH	Conducted PSD (dBm/MHz)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
PSD	802.11a	5260	Low	3.44	4.08	5.03	3.46	10.07	10.5	Pass
PSD	802.11a	5280	Mid	3.59	3.84	4.56	3.67	9.95	10.5	Pass
PSD	802.11a	5320	High	3.95	4.08	4.71	3.68	10.14	10.5	Pass
PSD	802.11n-20M	5260	Low	3.37	3.76	4.49	3.54	9.83	10.5	Pass
PSD	802.11n-20M	5280	Mid	3.25	3.62	4.71	3.34	9.79	10.5	Pass
PSD	802.11n-20M	5320	High	3.6	3.69	4.72	3.87	10.01	10.5	Pass
PSD	802.11n-40M	5270	Low	0.52	1.08	2.02	0.67	7.13	10.5	Pass
PSD	802.11n-40M	5310	Mid	0.64	1.05	1.83	0.86	7.14	10.5	Pass
PSD	802.11ac-80M	5290	High	-3.37	-3.28	-2.32	-3.41	2.95	10.5	Pass

PSD measurement result for 5.5GHz

Type	Test mode	Freq (MHz)	CH	Conducted PSD (dBm/MHz)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
PSD	802.11a	5500	Low	3.66	3.82	4.58	3.44	9.92	10.5	Pass
PSD	802.11a	5580	Mid	3.46	3.66	4.65	3.58	9.89	10.5	Pass
PSD	802.11a	5700	High	3.37	3.09	3.6	3.19	9.34	10.5	Pass
PSD	802.11n-20M	5500	Low	3.18	3.54	4.52	3.55	9.75	10.5	Pass
PSD	802.11n-20M	5580	Mid	3.26	3.13	4.27	3.49	9.58	10.5	Pass
PSD	802.11n-20M	5700	High	3.10	3.07	3.33	3.06	9.16	10.5	Pass
PSD	802.11n-40M	5510	Low	0.33	0.68	1.57	0.55	6.83	10.5	Pass
PSD	802.11n-40M	5550	Mid	0.40	0.71	1.62	0.51	6.86	10.5	Pass
PSD	802.11n-40M	5670	High	0.32	-0.18	1.13	0.44	6.47	10.5	Pass
PSD	802.11ac-80M	5530	Low	-3.68	-3.68	-1.96	-3.30	2.93	10.5	Pass
PSD	802.11ac-80M	5610	High	-3.83	-3.33	-2.70	-3.14	2.79	10.5	Pass

PSD measurement result for cross channels (in band 5470-5725MHz)


Type	Test mode	Freq (MHz)	CH	Conducted PSD (dBm/MHz)					Limit (dBm)	Result
				Chain1	Chain2	Chain3	Chain4	Combined Power		
PSD	802.11a	5720	CROSS	3.23	3.09	3.84	3.32	9.40	10.5	Pass
PSD	802.11n-20M	5720	CROSS	3.17	3.00	3.75	2.87	9.23	10.5	Pass
PSD	802.11n-40M	5710	CROSS	0.53	0.35	0.86	0.39	6.56	10.5	Pass
PSD	802.11ac-80M	5690	CROSS	-3.21	-3.47	-2.5	-3.47	2.88	10.5	Pass

PSD measurement result for cross channels (in band 5725-5850MHz)

Test mode	Freq (MHz)	CH	Conducted PSD (dBm/MHz)					Corrected Level (dBm/500kHz)	Limit (dBm/500kHz)	Result
			Chain1	Chain2	Chain3	Chain4	Combined PSD			
802.11a	5720	CROSS	-5.44	-5.96	-5.35	-5.70	0.41	7.4	30	Pass
802.11n-20M	5720	CROSS	-5.26	-5.71	-5.31	-5.56	0.56	7.55	30	Pass
802.11n-40M	5710	CROSS	-8.23	-8.39	-8.13	-8.84	-2.37	4.62	30	Pass
802.11ac-80M	5690	CROSS	-12.41	-12.75	-11.65	-12.59	-6.31	0.68	30	Pass

Correction factor=10*log(500/100)=6.99


Test Plots




PSD-802.11a-5260M-chain1




PSD-802.11a-5260M-chain2



PSD-802.11a-5260M-chain3




PSD-802.11a-5260M-chain4




PSD-802.11a-5280M-chain1




PSD-802.11a-5280M-chain2



PSD-802.11a-5280M-chain3




PSD-802.11a-5280M-chain4



PSD-802.11a-5320M-chain1




PSD-802.11a-5320M-chain2




PSD-802.11a-5320M-chain3




PSD-802.11a-5320M-chain4




PSD-802.11n-20M-5260M-chain1




PSD-802.11n-20M-5260M-chain2



PSD-802.11n-20M-5260M-chain3




PSD-802.11n-20M-5260M-chain4




PSD-802.11n-20M-5280M-chain1




PSD-802.11n-20M-5280M-chain2



PSD-802.11n-20M-5280M-chain3




PSD-802.11n-20M-5280M-chain4




PSD-802.11n-20M-5320M-chain1




PSD-802.11n-20M-5320M-chain2




PSD-802.11n-20M-5320M-chain3




PSD-802.11n-20M-5320M-chain4




PSD-802.11n-40M-5270M-chain1




PSD-802.11n-40M-5270M-chain2




PSD-802.11n-40M-5270M-chain3




PSD-802.11n-40M-5270M-chain4



PSD-802.11n-40M-5310M-chain1




PSD-802.11n-40M-5310M-chain2




PSD-802.11n-40M-5310M-chain3




PSD-802.11n-40M-5310M-chain4




PSD-802.11ac-80M-5290M-chain1




PSD-802.11ac-80M-5290M-chain2




PSD-802.11ac-80M-5290M-chain3




PSD-802.11ac-80M-5290M-chain4




PSD-802.11a-5500M-chain1




PSD-802.11a-5500M-chain2




PSD-802.11a-5500M-chain3




PSD-802.11a-5500M-chain4




PSD-802.11a-5580M-chain1




PSD-802.11a-5580M-chain2




PSD-802.11a-5580M-chain3




PSD-802.11a-5580M-chain4




PSD-802.11a-5700M-chain1




PSD-802.11a-5700M-chain2




PSD-802.11a-5700M-chain3




PSD-802.11a-5700M-chain4




PSD-802.11n-20M-5500M-chain1




PSD-802.11n-20M-5500M-chain2




PSD-802.11n-20M-5500M-chain3




PSD-802.11n-20M-5500M-chain4




PSD-802.11n-20M-5580M-chain1




PSD-802.11n-20M-5580M-chain2




PSD-802.11n-20M-5580M-chain3




PSD-802.11n-20M-5580M-chain4




PSD-802.11n-20M-5700M-chain1




PSD-802.11n-20M-5700M-chain2



PSD-802.11n-20M-5700M-chain3




PSD-802.11n-20M-5700M-chain4



PSD-802.11n-40M-5510M-chain1



PSD-802.11n-40M-5510M-chain2



PSD-802.11n-40M-5510M-chain3



PSD-802.11n-40M-5510M-chain4



PSD-802.11n-40M-5550M-chain1



PSD-802.11n-40M-5550M-chain2



PSD-802.11n-40M-5550M-chain3




PSD-802.11n-40M-5550M-chain4



PSD-802.11n-40M-5670M-chain1



PSD-802.11n-40M-5670M-chain2



PSD-802.11n-40M-5670M-chain3



PSD-802.11n-40M-5670M-chain4