Ruckus Wireless, Inc. FCC ID: S9GZF7372

4 FCC §15.407(f) & §2.1091 - RF Exposure

4.1 Applicable Standard

According to FCC §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 MPE Results

W52 Band:

Maximum peak output power at antenna input terminal (dBm): 23.58

Maximum peak output power at antenna input terminal (mW): 228.0342

Prediction distance (cm): 20 Prediction frequency (MHz): 5200 Maximum Antenna Gain, typical (dBi): 3

Maximum Antenna Gain (numeric): 1.995262
Power density of prediction frequency at 20.0 cm (mW/cm²): 0.090517

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1

^{* =} Plane-wave equivalent power density

Ruckus Wireless, Inc. FCC ID: S9GZF7372

W58 Band:

Maximum peak output power at antenna input terminal (dBm): 22.45

Maximum peak output power at antenna input terminal (mW): 175.7924

Prediction distance (cm): 20 Prediction frequency (MHz): 5745

Maximum Antenna Gain, typical (dBi): 3

Maximum Antenna Gain (numeric): 1.995262

Power density of prediction frequency at 20.0 cm (mW/cm²): 0.06978

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1

The device meets FCC MPE requirement for uncontrolled exposure environment at 20 cm distance.