

# **COVER LETTER**

### **Request For Transmitter Module Equipment Authorization**

# No. ARSQ00009

performed in accordance with FCC Rules: Code of Federal Regulations (CFR) no. 47 Part 15 Subpart C Section 15.212

PRODUCT	Ultra-low power RF-ready module
MODEL(s) TESTED	SPSGPE-915
FCC ID	S9NSPSGPE
TRADE MARK(s)	STMicroelectronics
APPLICANT	STMicroelectronics S.r.l. – Centro Direzionale Colleoni - Palazzo Andromeda 3 I-20864 Agrate Brianza (MB)

#### **Revision Sheet**

Release No.	Date	Revision Description
Rev. 0	2017-02-21	First edition

The results of tests and checks reported in this Test Report refer exclusively to the samples tested and described in the Report itself. This Report shall not be reproduced partially without the written approval of IMQ S.p.A.



### 1. REFERENCE DOCUMENT

	DOCUMENT	DATE	TITLE
$\square$	47 CFR Part 15	2014	Radio Frequency Device
$\square$	Publication Number: 996369	2013	Transmitter Module Equipment Authorization Guide
	PUBLIC NOTE DA 00-1407	2000	Part 15 Unlicensed Modular Transmitter Approval

## 2. MODULE-TYPE DEVICE APPROVAL OPTIONS

Single-modular transmitter	complete RF transmission sub-assembly, designed to be incorporated into another device, that must demonstrate compliance with FCC rules and policies independent of any host
Limited single-modular transmitter	single-modular transmitter that complies with the Section 15.212(a)(1) modular rules, only when constrained to specific operating host(s) and/or associated grants condition(s)
Limited single-modular transmitter	RF transmission system that complies with the requirements for a single-modular transmitter, that is separated into a radio front-end section and a control element section, and can demonstrate compliance for a range of similar type hosts
Limited split-modular transmitter	split-modular transmitter that complies with the definition and technical rules for split modules only when constrained to specific operating host(s), and/or associated grant condition(s)



## 3. **REQUIREMENTS**

POSSIBLE TEST CASE VERDICTS	
Test object does meet the requirement	PASS
Test object does not meet the requirement	FAIL
Test case does not apply to the test object	N/A

	Requirement	Description	Result
(i)	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	The radio module elements have their own shielding.	PASS
(ii)	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	The radio transmitter has buffered modulation/data inputs (if such inputs provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	PASS
(iii)	The modular transmitter must have its own power supply regulation.	The radio module contains an own voltage regulation	PASS
(iv)	The modular transmitter must comply with the antenna and transmission system requirements of §15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	The module complies with the antenna and transmission system requirements of §15.203, 15.204(b) and 15.204(c).	PASS



(v)	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).	The radio module meet the requirements under the operating conditions in which the transmitter will be use. The modular transmitter was tested in a stand-alone configuration (the module was not inside another device during testing for compliance with part 15 requirements, DC power lines and data input/output lines connected to the module not contain ferrites, no coupling was present between the case of the module and supporting equipment). Any accessories, peripherals, or support equipment connected to the module during testing were unmodified and commercially available.	PASS
(vi)	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.	The radio module is labelled with its own FCC ID number. When the radio module is installed inside the end-product, the label is not visible. The end-user/integrator is instructed how to apply the exterior label.	PASS
(vii)	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	The radio module is compliant with all applicable specific FCC rules or operating requirements that ordinarily apply to a complete transmitter. Detailed instruction are provided with the module to explain any such requirements.	PASS
(viii)	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The modular transmitter comply with any applicable RF exposure requirements in its final configuration.	PASS