

Description of Operation

Date: 2005/9/13

EUT is a 802.11b VoIP phone with 11 channels(2412MHz~2462MHz, Space 5MHz). It allows you to connect to other WLAN device. It is not able to be operated while in charge mode.

General Operational Description :

1. Time base of the transmission frequency:

For IF and RF frequency, Crystal is a clock reference.

2. Synthesizer:

Synthesizer inside Transceiver IC and operate frequency in 2.4GHz ISM Band. Internal voltage controlled oscillator (VCO) provides the desired LO signal base on the phase-locked loop (PLL) with a relatively wide tuning range for this application.

3. Transmission:

BBP IC has DSSS (BPSK/QPSK/CCK) modulation function, it provides transmission data rate are 1, 2, 5.5, 11 Mbps. Digital data signal will be converted to analog (TX IQ) signals through DAC in BBP IC, TX IQ pass through to low pass filter. TX I/Q signal use direct conversion (zero-IF) architecture converter to generate carrier frequency signal. Transceiver IC and external PA magnify output power.

4. Receiver:

Reverse direction isolation of LNA inside Transceiver IC suppresses unwanted radiation. Then 2.4GHz RF signal will be directly down to IF signal (RX IQ) and high frequency spurious emissions are suppressed by LPF. At last RX IQ signal will be demodulated digital data.

5. Base band Processing:

Channel Selection: Channel selection is controlled by BBP IC.

Data Modulation: DSSS (BPSK/QPSK/CCK) modulation type is controlled by BBP IC.

Power Control Level: BBP IC has the power leveling loop table are calibrated by manufacturer, then uses closed-loop power control function to limit RF output power level. Power leveling step accuracy is ± 0.5 dB.

Transmit/Receive Switch: EUT has Transmit/Receive Switch and Antenna switch

Data Link Layer:

Firmware implements the full IEEE 802.11 Wireless LAN MAC protocol. It supports BSS and IBSS operation under DCF, and operation under the optional Point Coordination Function (PCF). Lower level protocol functions such as RTS/CTS generation and acknowledgment, fragmentation and de-fragmentation, and automatic beacon monitoring are handled without host intervention. Active scanning is performed autonomously once initiated by host command. Host interface command and status handshakes allow concurrent operations from multi-threaded I/O drivers.

6. Interface: Not-applicable

7. Power: Input 5Vdc from power adapter. This power is provided to regulator components to regulated DC power.



General Description of Equipment under Test

Applicant

ADVANTAGE CENTURY TELECOMMUNICATION CORP.
4F, NO.41, TUNG-SING RD., TAIPEI, TAIWAN, R.O.C.

Manufacturer

Cameo Communications, Inc.
No.42, Section 6, Min-Chuan East Road, Taipei 114, Taiwan, R.O.C.

Basic Description of Equipment under Test

This product is a Wireless LAN VoIP phone with 802.11b wireless solution. The technical data has been listed on section " Features of Equipment under Test ".

Features of Equipment under Test

Items	Description
Type of Modulation	DSSS (CCK / DQPSK / DBPSK)
Number of Channels	11
Frequency Band	2400 MHz ~ 2483.5 MHz
Carrier Frequency	2412 MHz ~ 2462 MHz
Data Rate	1, 2, 5.5, 11 Mbps
Max. Conducted Output Power	16.00 dBm
Antenna Type	Chip Antenna
Communication Type	Half-Duplex
Testing Duty Cycle	100.00%
Test Power Source	5V DC from power adapter; Chargeable Battery
Temperature Range (Operating)	0 ~ 40 °C