


DRAFT 802.11n (20MHz) OFDM MODULATION - DUAL TX:


MODULATION TYPE	BPSK	TRANSFER RATE	7.2Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz		25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		


CHANNEL	CHANNEL			IN 3kHz BW (dBm) POWI				MAX. LIMIT	PASS /
	(MHz)	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		(dBm)	(dBm)	FAIL
1	2412	0.036	0.039	-14.49	-14.13	0.075	-11.25	8	PASS
6	2437	0.037	0.039	-14.32	-14.07	0.076	-11.19	8	PASS
11	2462	0.038	0.037	-14.23	-14.26	0.075	-11.25	8	PASS

FOR CHAIN 0: CH 1














FOR CHAIN 1: CH 1












DRAFT 802.11n (40MHz) OFDM MODULATION - DUAL TX:


MODULATION TYPE	BPSK	TRANSFER RATE	15.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		


CHANNEL	CHANNEL			IN 3kHz BW (dBm) POW		_		MAX. LIMIT	PASS /
	(MHz)	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		(dBm)	(dBm)	FAIL
1	2422	0.018	0.019	-17.47	-17.11	0.037	-14.32	8	PASS
4	2437	0.019	0.020	-17.20	-17.09	0.039	-14.09	8	PASS
7	2452	0.019	0.020	-17.24	-17.04	0.039	-14.09	8	PASS

FOR CHAIN 0: CH 1














FOR CHAIN 1: CH 1











4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



4.6.3 TEST PROCEDURE

For Single TX:

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 10Hz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW = VBW = 100kHz; Average RBW = 1MHz, VBW = 10Hz) are attached on the following pages.

For Dual TX:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW = VBW = 100kHz; Average RBW = 1MHz, VBW = 10Hz)

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation



4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 24 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION - SINGLE TX:

NOTE 1:

The band edge emission plot of DSSS technique on the next page shows 51.26dBc between carrier maximum power and local maximum emission in restrict band (2.38620GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 111.89dBuV/m (Peak), so the maximum field strength in restrict band is 111.89 – 51.26 = 60.63dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of DSSS technique on the next page shows 57.17dBc between carrier maximum power and local maximum emission in restrict band (2.38640GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.84dBuV/m (Average), so the maximum field strength in restrict band is 107.84 – 57.17 = 50.67dBuV/m which is under 54dBuV/m limit.


NOTE 2:

The band edge emission plot of DSSS technique on the next second page shows 52.94dBc between carrier maximum power and local maximum emission in restrict band (2.48774GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 111.94dBuV/m (Peak), so the maximum field strength in restrict band is 111.94 - 52.94 = 59.00dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of DSSS technique on the next third page shows $59.40 \, \text{dBc}$ between carrier maximum power and local maximum emission in restrict band ($2.48794 \, \text{GHz}$). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is $107.75 \, \text{dBuV/m}$ (Average), so the maximum field strength in restrict band is $107.75 - 59.40 = 48.35 \, \text{dBuV/m}$ which is under $54 \, \text{dBuV/m}$ limit.
























802.11g OFDM MODULATION – DUAL TX:

NOTE 1:

The band edge emission plot of OFDM technique on the next page shows 45.65dBc between carrier maximum power and local maximum emission in restrict band (2.38580GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 113.26dBuV/m (Peak), so the maximum field strength in restrict band is 113.26 – 45.65 = 67.61dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next page shows 52.50dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 102.84dBuV/m (Average), so the maximum field strength in restrict band is 102.84 – 52.50 = 50.34dBuV/m which is under 54dBuV/m limit.


NOTE 2:

The band edge emission plot of OFDM technique on the next second page shows 46.30 dBc between carrier maximum power and local maximum emission in restrict band (2.48350 GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 113.44 dBuV/m (Peak), so the maximum field strength in restrict band is 113.44 - 46.30 = 67.14 dBuV/m which is under 74 dBuV/m limit.


The band edge emission plot of OFDM technique on the next third page shows 51.56dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 103.16dBuV/m (Average), so the maximum field strength in restrict band is 103.16 - 51.56 = 51.60dBuV/m which is under 54dBuV/m limit.
























DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:

NOTE 1:

The band edge emission plot of OFDM technique on the next page shows 45.71Bc between carrier maximum power and local maximum emission in restrict band (2.36280GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 112.30dBuV/m (Peak), so the maximum field strength in restrict band is 112.30 – 45.71 = 66.59dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next page shows 52.48dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.15dBuV/m (Average), so the maximum field strength in restrict band is 103.15 – 52.48 = 50.67dBuV/m which is under 54dBuV/m limit.


NOTE 2:

The band edge emission plot of OFDM technique on the next second page shows 45.21dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 112.39dBuV/m (Peak), so the maximum field strength in restrict band is 112.39 - 45.21 = 67.18dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next third page shows 49.67 dBc between carrier maximum power and local maximum emission in restrict band (2.48350 GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 102.31 dBuV/m (Average), so the maximum field strength in restrict band is 102.31 - 49.67 = 52.64 dBuV/m which is under 54 dBuV/m limit.
























DRAFT 802.11n (40MHz) OFDM MODULATION – DUAL TX:

NOTE 1:

The band edge emission plot of OFDM technique on the next page shows 44.42dBc between carrier maximum power and local maximum emission in restrict band (2.34920GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.59dBuV/m (Peak), so the maximum field strength in restrict band is 107.59 – 44.42 = 63.17dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next page shows 49.56dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 98.01dBuV/m (Average), so the maximum field strength in restrict band is 98.01 – 49.56 = 48.45dBuV/m which is under 54dBuV/m limit.


NOTE 2:

The band edge emission plot of OFDM technique on the next second page shows 42.57dBc between carrier maximum power and local maximum emission in restrict band (2.49190GHz). The emission of carrier strength list in the test result of channel 7 at the item 4.2.7 is 107.46dBuV/m (Peak), so the maximum field strength in restrict band is 107.46 - 42.57 = 64.89dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next third page shows $45.40 \, \text{dBc}$ between carrier maximum power and local maximum emission in restrict band ($2.48350 \, \text{GHz}$). The emission of carrier strength list in the test result of channel 7 at the item $4.2.7 \, \text{is}$ $97.54 \, \text{dBuV/m}$ (Average), so the maximum field strength in restrict band is $97.54 - 45.40 = 52.14 \, \text{dBuV/m}$ which is under $54 \, \text{dBuV/m}$ limit.
























4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole antenna with UFL connector. The maximum Gain of the antenna is 4dBi.



5. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA FCC, UL, A2LA

Germany TUV Rheinland

Japan VCCI

Norway NEMKO

Canada INDUSTRY CANADA, CSA

R.O.C. CNLA, BSMI, DGT

Netherlands Telefication

Singapore PSB , GOST-ASIA(MOU)

Russia CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

<u>www.adt.com.tw/index.5/phtml</u>. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Hsin Chu EMC/RF Lab:

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB
No any modifications are made to the EUT by the lab during the test.