




SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	TRENDware International Inc.
Applicant Address	20675 Manhattan Place, Torrance, CA 90501 USA
FCC ID	S9ZTEW672GR
Manufacturer's company	TRENDware International Inc.
Manufacturer Address	20675 Manhattan Place, Torrance, CA 90501 USA

Product Name	Dual Band Wireless N Gigabit Router
Brand Name	TRENDnet
Model Name	TEW-672GR
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250MHz
Received Date	May. 28, 2008
Final Test Date	Jun. 6, 2008
Submission Type	Original Equipment



Statement

Test result included is only for the Draft n (5150 ~ 5250MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart E**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.





Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes.....	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units	7
3.8. Table for Parameters of Test Software Setting	7
3.9. Test Configurations	8
4. TEST RESULT	11
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. 99% Occupied Bandwidth Measurement	18
4.3. Maximum Conducted Output Power Measurement.....	23
4.4. Power Spectral Density Measurement	31
4.5. Peak Excursion Measurement.....	36
4.6. Radiated Emissions Measurement	41
4.7. Band Edge Emissions Measurement	57
4.8. Frequency Stability Measurement	61
4.9. Antenna Requirements	63
5. LIST OF MEASURING EQUIPMENTS	64
6. TEST LOCATION.....	66
7. TAF CERTIFICATE OF ACCREDITATION	67
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A13
APPENDIX B. TEST PHOTOS.....	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~ C5



History of This Test Report

Original Issue Date: Jun. 11, 2008

Report No.: FR852817AB

- No additional attachment.
- Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : Dual Band Wireless N Gigabit Router
Brand Name : TRENDnet
Model Name : TEW-672GR
Applicant : TRENDware International Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May. 28, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Wayne Hsu

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	2.31 dB
4.2	15.407(a)	26dB Spectrum Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	0.21 dB
4.4	15.407(a)	Power Spectral Density	Complies	0.39 dB
4.5	15.407(a)	Peak Excursion	Complies	7.24 dB
4.6	15.407(b)	Radiated Emissions	Complies	0.50 dB
4.7	15.407(b)	Band Edge Emissions	Complies	0.18 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.5dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
Peak Excursion	±0.5dB	Confidence levels of 95%
26dB Spectrum Bandwidth / Frequency Stability	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (2TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	Power Adapter
Modulation	see the below table for draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	5150 ~ 5250MHz
Channel Number	4 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	MCS8 (20MHz) : 17.76 MHz MCS8 (40MHz) : 36.20 MHz
Conducted Output Power	MCS8 (20MHz) : 16.69 dBm MCS8 (40MHz) : 16.79 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Multiple (2TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
802.11a	V	X	X	X
802.11b	V	X	X	X
802.11g	V	X	X	X
Draft n	X	X	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPS	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Power	Brand	Model	Rating
Adapter	LEI	MT12-4120100-A1	Input: 120VAC, 50/60Hz, 0.3A Output: 12VDC, 1.0A

3.3. Table for Filed Antenna

For 5GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
A	JOYMAX	TWF-152XMPXX-711	Dipole Antenna	Brass	3.00
B	JOYMAX	TWF-152XMPXX-711	Dipole Antenna	Brass	3.00
C	JOYMAX	TWF-152XMPXX-711	Dipole Antenna	Brass	3.00

Note:

(1) The EUT has three antennas .

(2) The EUT has three antenna ports, and the Port 1 and Port 3 have both TX/RX function , Port 2 have only RX function.

Port 1: Ant. A


Port 2: Ant. B

Port 3: Ant. C

Ant. A and Ant. C can both transmit simultaneously.

Ant. A, Ant. B and Ant. C can both receive simultaneously.

Both Ant. A and Ant. C were tested and recorded in the report.



3.4. Table for Carrier Frequencies

There are two bandwidth systems for draft n.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Antenna
AC Power Conducted Emission	Normal Link		Auto	-	-
Max. Conducted Output Power	MCS8/20MHz	Band 1	13Mbps	36/40/48	A / C / A+C
	MCS8/40MHz	Band 1	27Mbps	38/46	N/A
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement Power Spectral Density Peak Excursion	MCS8/20MHz	Band 1	13Mbps	36/40/48	N/A
	MCS8/40MHz	Band 1	27Mbps	38/46	N/A
Radiated Emission Below 1GHz	Normal Link		Auto	-	A+C
Radiated Emission Above 1GHz	MCS8/20MHz	Band 1	13Mbps	36/40/48	A+C
	MCS8/40MHz	Band 1	27Mbps	38/46	A+C
Band Edge Emission	MCS8/20MHz	Band 1	13Mbps	36/48	A+C
	MCS8/40MHz	Band 1	27Mbps	38/46	A+C
Frequency Stability	Un-modulation		-	40	N/A

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D520	E2KWM3945ABG
Notebook	DELL	D520	E2KWM3945ABG
Notebook	DELL	1200	E2K4965AGNM
Switch Hub	EtherHub-16	N/A	DOC

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Draft n MCS8 20MHz

Test Software Version	QA		
Frequency	5180 MHz	5200 MHz	5240 MHz
Draft n Ant. A	06	05	04
Draft n Ant. C	05	05	04

Power Parameters of Draft n MCS8 40MHz

Test Software Version	QA	
Frequency	5190 MHz	5230 MHz
Draft n Ant. A	06	04
Draft n Ant. C	05	04

During the test, "Ping.exe" under WIN XP was executed to link with the remote workstation to receive and transmit signal by LAN and WLAN.


At the same time, "QA" was executed the test program to control the EUT continuously transmit RF signal.

3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 30KHz~1GHz

Test Mode: Ant. A + Ant. C




Test Configuration: above 1GHz

Test Mode: Ant. A + Ant. C



3.9.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	54%
Test Engineer	Rex Chiu	Phase	Line
Configuration	Normal Link		




	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.21055	34.05	-19.13	53.18	33.75	0.10	0.20	AVERAGE
2	0.21055	50.03	-13.15	63.18	49.73	0.10	0.20	QP
3	0.26528	33.08	-18.18	51.26	32.78	0.10	0.20	AVERAGE
4	0.26528	51.87	-9.39	61.26	51.57	0.10	0.20	QP
5	0.37154	48.57	-9.90	58.47	48.27	0.10	0.20	QP
6	0.37154	32.35	-16.12	48.47	32.05	0.10	0.20	AVERAGE
7	0.52855	44.44	-11.57	56.00	44.16	0.08	0.20	QP
8	0.52855	24.22	-21.79	46.00	23.94	0.08	0.20	AVERAGE
9	0.63623	46.79	-9.21	56.00	46.53	0.06	0.20	QP
10	0.63623	26.72	-19.28	46.00	26.46	0.06	0.20	AVERAGE
11	0.74142	45.71	-10.29	56.00	45.47	0.04	0.20	QP
12	0.74142	26.39	-19.61	46.00	26.15	0.04	0.20	AVERAGE
13	0.89761	43.25	-12.76	56.00	43.03	0.02	0.20	QP
14	0.89761	22.54	-23.47	46.00	22.32	0.02	0.20	AVERAGE
15	1.007	44.24	-11.76	56.00	44.04	0.00	0.20	QP
16	1.007	32.10	-13.90	46.00	31.90	0.00	0.20	AVERAGE
17	1.163	24.00	-22.00	46.00	23.84	0.00	0.16	AVERAGE
18	1.163	44.21	-11.79	56.00	44.05	0.00	0.16	QP
19	1.429	43.09	-12.91	56.00	42.98	0.00	0.11	QP
20	1.429	24.40	-21.60	46.00	24.29	0.00	0.11	AVERAGE
21	1.693	30.14	-15.86	46.00	30.00	0.00	0.14	AVERAGE



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
22	1.693	44.60	-11.40	56.00	44.46	0.00	0.14	QP
23	2.170	25.59	-20.41	46.00	25.39	0.00	0.20	AVERAGE
24	2.170	44.83	-11.17	56.00	44.63	0.00	0.20	QP
25	2.542	24.90	-21.10	46.00	24.70	0.00	0.20	AVERAGE
26	2.542	43.71	-12.29	56.00	43.51	0.00	0.20	QP
27	3.009	29.49	-16.51	46.00	29.29	0.00	0.20	AVERAGE
28	3.009	42.20	-13.80	56.00	42.00	0.00	0.20	QP

Temperature	23°C	Humidity	54%
Test Engineer	Rex Chiu	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.22083	31.82	-20.97	52.79	31.42	0.20	0.20	AVERAGE
2	0.22083	53.26	-9.53	62.79	52.86	0.20	0.20	QP
3	0.25083	47.37	-4.36	51.73	46.99	0.18	0.20	AVERAGE
4	0.25083	51.90	-9.83	61.73	51.52	0.18	0.20	QP
5	0.27442	30.42	-20.57	50.98	30.05	0.17	0.20	AVERAGE
6	0.27442	52.10	-8.89	60.98	51.73	0.17	0.20	QP
7	0.31403	46.16	-3.70	49.86	45.81	0.15	0.20	AVERAGE
8	0.31403	49.60	-10.26	59.86	49.25	0.15	0.20	QP
9	0.33562	47.10	-12.21	59.31	46.77	0.13	0.20	QP
10	0.33562	26.00	-23.31	49.31	25.67	0.13	0.20	AVERAGE
11	0.37643	48.29	-10.07	58.36	47.99	0.10	0.20	QP
12	0.37643	41.81	-6.55	48.36	41.51	0.10	0.20	AVERAGE
13	0.43803	49.32	-7.78	57.10	49.02	0.10	0.20	QP
14	0.43803	44.79	-2.31	47.10	44.49	0.10	0.20	AVERAGE
15	0.50233	46.28	-9.72	56.00	45.98	0.10	0.20	QP
16	0.50233	39.60	-6.40	46.00	39.30	0.10	0.20	AVERAGE
17	0.56433	48.45	-7.55	56.00	48.15	0.10	0.20	QP
18	0.56433	42.83	-3.17	46.00	42.53	0.10	0.20	AVERAGE
19	0.62723	40.54	-5.46	46.00	40.24	0.10	0.20	AVERAGE
20	0.62723	44.31	-11.69	56.00	44.01	0.10	0.20	QP
21	0.69003	47.39	-8.61	56.00	47.09	0.10	0.20	QP



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
22	0.69003	41.79	-4.21	46.00	41.49	0.10	0.20	AVERAGE
23	0.78345	22.57	-23.43	46.00	22.27	0.10	0.20	AVERAGE
24	0.78345	42.46	-13.54	56.00	42.16	0.10	0.20	QP
25	0.87871	45.93	-10.07	56.00	45.63	0.10	0.20	QP
26	0.87871	41.27	-4.73	46.00	40.97	0.10	0.20	AVERAGE
27	1.004	45.99	-10.01	56.00	45.69	0.10	0.20	QP
28	1.004	41.16	-4.84	46.00	40.86	0.10	0.20	AVERAGE
29	1.166	27.94	-18.06	46.00	27.68	0.10	0.16	AVERAGE
30	1.166	46.53	-9.47	56.00	46.27	0.10	0.16	QP
31	1.271	27.41	-18.59	46.00	27.17	0.10	0.14	AVERAGE
32	1.271	46.12	-9.88	56.00	45.88	0.10	0.14	QP
33	1.419	23.54	-22.46	46.00	23.33	0.10	0.11	AVERAGE
34	1.419	41.36	-14.64	56.00	41.15	0.10	0.11	QP
35	1.535	45.89	-10.11	56.00	45.68	0.10	0.11	QP
36	1.535	27.45	-18.55	46.00	27.24	0.10	0.11	AVERAGE
37	1.796	44.74	-11.26	56.00	44.48	0.10	0.16	QP
38	1.796	26.43	-19.57	46.00	26.17	0.10	0.16	AVERAGE
39	2.065	46.30	-9.70	56.00	46.00	0.10	0.20	QP
40	2.065	32.00	-14.00	46.00	31.70	0.10	0.20	AVERAGE
41	2.381	44.19	-11.81	56.00	43.89	0.10	0.20	QP
42	2.381	33.99	-12.01	46.00	33.69	0.10	0.20	AVERAGE
43	2.801	26.73	-19.27	46.00	26.43	0.10	0.20	AVERAGE
44	2.801	43.40	-12.60	56.00	43.10	0.10	0.20	QP
45	3.229	26.52	-19.48	46.00	26.17	0.10	0.25	AVERAGE
46	3.229	43.89	-12.11	56.00	43.54	0.10	0.25	QP
47	3.705	33.74	-12.26	46.00	33.34	0.10	0.30	AVERAGE
48	3.705	43.96	-12.04	56.00	43.56	0.10	0.30	QP
49	4.338	43.00	-13.00	56.00	42.60	0.10	0.30	QP
50	4.338	29.69	-16.31	46.00	29.29	0.10	0.30	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RB	300 kHz
VB	1000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 300 kHz and the video bandwidth of 1000 kHz were used.
3. Measured the spectrum width with power higher than 26dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyse through a combiner.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 99% Occupied Bandwidth

Temperature	26°C	Humidity	62%
Test Engineer	Sam Chen	Configurations	Draft n


Configuration Draft n MCS8 20MHz Ant. A + Ant. C

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	20.48	17.76
40	5200 MHz	20.48	17.76
48	5240 MHz	20.48	17.76

Configuration Draft n MCS8 40MHz Ant. A + Ant. C


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	40.64	36.16
46	5230 MHz	40.00	36.20

26 dB Bandwidth Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5180 MHz




Date: 3.JUN.2008 20:57:09

26 dB Bandwidth Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5200 MHz




Date: 3.JUN.2008 20:58:04

26 dB Bandwidth Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5240 MHz




Date: 3.JUN.2008 20:58:57

26 dB Bandwidth Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. C / 5190 MHz



Date: 3.JUN.2008 20:54:36

26 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. C / 5230 MHz



Date: 3.JUN.2008 20:55:33

4.3. Maximum Conducted Output Power Measurement

4.3.1. Limit

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW (17dBm) or $4 \text{ dBm} + 10\log B$, where B is the 26 dB emissions bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power and power density from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	PEAK
Trace	MAX HOLD
Sweep Time	Auto

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with FCC Public Notice DA 02-2138.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	61%
Test Engineer	Sam Chen	Configurations	Draft n

Configuration Draft n MCS8 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	13.96	17.00	Complies
40	5200 MHz	13.67	17.00	Complies
48	5240 MHz	13.74	17.00	Complies

Configuration Draft n MCS8 20MHz Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	13.33	17.00	Complies
40	5200 MHz	13.69	17.00	Complies
48	5240 MHz	13.51	17.00	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	16.66	17.00	Complies
40	5200 MHz	16.69	17.00	Complies
48	5240 MHz	16.64	17.00	Complies

Configuration Draft n MCS8 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	14.04	17.00	Complies
46	5230 MHz	13.39	17.00	Complies


Configuration Draft n MCS8 40MHz Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	13.47	17.00	Complies
46	5230 MHz	13.34	17.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. C


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	16.79	17.00	Complies
46	5230 MHz	16.38	17.00	Complies

Channel Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. A / 5180 MHz




Date: 3.JUN.2008 19:58:42

Channel Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. A / 5200 MHz




Date: 3.JUN.2008 19:57:07

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 5240 MHz




Date: 3.JUN.2008 19:39:23

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. C / 5180 MHz




Date: 3.JUN.2008 19:59:17

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 5190 MHz




Date: 3.JUN.2008 20:13:55

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 5230 MHz




Date: 3.JUN.2008 20:14:59

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. C / 5190 MHz



Date: 3.JUN.2008 20:13:10

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. C / 5230 MHz



Date: 3.JUN.2008 20:15:45

4.4. Power Spectral Density Measurement

4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15~5.25 GHz	4

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 3000kHz. Set Detector to Peak, Trace to Max Hold. Mark the frequency with maximum peak power as the center of the display of the spectrum.
3. Measuring multiple antennas, the connector is required to link with spectrum analyse through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

Temperature	26°C	Humidity	62%
Test Engineer	Sam Chen	Configurations	Draft n


Configuration Draft n MCS8 20MHz Ant. A + Ant. C

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	3.61	4.00	Complies
40	5200 MHz	3.31	4.00	Complies
48	5240 MHz	3.11	4.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. C


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	0.79	4.00	Complies
46	5230 MHz	0.09	4.00	Complies

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5180 MHz




Date: 3.JUN.2008 20:57:15

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5200 MHz




Date: 3.JUN.2008 20:58:10

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5240 MHz




Date: 3.JUN.2008 20:59:03

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. C / 5190 MHz



Date: 3.JUN.2008 20:54:43

Power Density Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. C / 5230 MHz



Date: 3.JUN.2008 20:55:40

4.5. Peak Excursion Measurement

4.5.1. Limit

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.

4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz (Peak Trace) / 1000 kHz (Average Trace)
VB	3000 kHz (Peak Trace) / 300 kHz (Average Trace)
Detector	Peak (Peak Trace) / Sample (Average Trace)
Trace	Max Hold
Sweep Time	60s

4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set the spectrum analyzer span to view the entire emissions bandwidth. The largest difference between the following two traces (Peak Trace and Average Trace) must be ≤ 13 dB for all frequencies across the emissions bandwidth. Submit a plot.
3. Peak Trace: Set RBW = 1 MHz, VBW ≥ 3 MHz with peak detector and max-hold settings.
4. Average Trace: Method #3—video averaging with max hold--and sum power across the band. Set span to encompass the entire emissions bandwidth (EBW) of the signal. Set sweep trigger to "free run". Set RBW = 1 MHz. Set VBW $\geq 1/T$ (Draft n VBW = 300kHz $\geq 1/4\mu$ s). Use sample detector mode if bin width (i.e., span/number of points in spectrum) < 0.5 RBW. Otherwise use peak detector mode . Set max hold. Allow max hold to run for 60 seconds.
5. Measuring multiple antennas, the connector is required to link with spectrum analyse through a combiner.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Peak Excursion

Temperature	26°C	Humidity	62%
Test Engineer	Sam Chen	Configurations	Draft n


Configuration Draft n MCS8 20MHz Ant. A + Ant. C

Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
36	5180 MHz	4.88	13	Complies
40	5200 MHz	5.26	13	Complies
48	5240 MHz	4.44	13	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. C


Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
38	5190 MHz	5.76	13	Complies
46	5230 MHz	5.00	13	Complies

Peak Excursion Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5180 MHz




Date: 3.JUN.2008 20:57:27

Peak Excursion Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5200 MHz




Date: 3.JUN.2008 20:58:22

Peak Excursion Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. C / 5240 MHz




Date: 3.JUN.2008 20:59:15

Peak Excursion Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. C / 5190 MHz



Date: 3.JUN.2008 20:54:55

Peak Excursion Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. C / 5230 MHz



Date: 3.JUN.2008 20:55:52

4.6. Radiated Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.25 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the 5.470-5.725 GHz band: all emissions outside of the 5.470-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the 5.725-5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBuV/m at 3m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). In addition, in case the emission falls within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 5GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Normal Link

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB	deg	cm
1	137.670	31.68	-11.82	43.50	46.96	10.76	27.41	1.38	0	100
2	214.300	34.74	-8.76	43.50	51.62	8.43	27.07	1.76	0	100
3 !	249.220	40.69	-5.31	46.00	54.24	11.56	27.00	1.90	0	100
4	374.350	39.44	-6.56	46.00	49.82	14.79	27.42	2.25	0	100
5	625.580	38.92	-7.08	46.00	44.89	19.05	28.07	3.05	0	100
6 !	874.870	40.35	-5.65	46.00	43.89	20.42	27.45	3.50	0	100

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	137.670	36.51	-6.99	43.50	51.78	10.76	27.41	1.38	Peak	0	400	VERTICAL
2	249.220	42.90	-3.10	46.00	56.44	11.56	27.00	1.90	Peak	125	110	VERTICAL
3	374.350	37.17	-8.83	46.00	47.55	14.79	27.42	2.25	Peak	0	400	VERTICAL
4	559.620	36.82	-9.18	46.00	43.55	18.55	28.10	2.82	Peak	0	400	VERTICAL
5	625.580	39.73	-6.27	46.00	45.70	19.05	28.07	3.05	Peak	0	400	VERTICAL
6	699.300	29.81	-16.19	46.00	35.21	19.30	28.00	3.30	QP	256	100	VERTICAL
7	874.870	37.76	-8.24	46.00	41.29	20.42	27.45	3.50	Peak	0	400	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~40GHz)


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draft n MCS8 20MHz Ch 36 / Ant. A + Ant. C

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	10366.320	69.39	-4.91	74.30	59.14	39.76	5.23	34.74	PEAK	122	276	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	10366.000	72.20	-2.10	74.30	61.95	39.76	5.23	34.74	PEAK	107	277	VERTICAL

Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draft n MCS8 20MHz Ch 40 / Ant. A + Ant. C


Horizontal



g

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	10400.240	67.63	-6.67	74.30	57.26	39.82	5.24	34.69	PEAK	110	259	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	10397.440	72.93	-1.37	74.30	62.56	39.82	5.24	34.69	PEAK	106	267	VERTICAL


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draft n MCS8 20MHz Ch 48 / Ant. A + Ant. C

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
			Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	10482.480	65.79	-8.51	74.30	55.18	39.97	5.26	34.62	PEAK	100	262 HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	10477.520	73.67	-0.63	74.30	63.06	39.97	5.26	34.62	PEAK	102	277	VERTICAL


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draff n MCS8 40MHz Ch 38 / Ant. A + Ant. C

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	10378.240	66.22	-8.08	74.30	55.91	39.79	5.24	34.72	PEAK	124	277	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	10378.160	68.83	-5.47	74.30	58.52	39.79	5.24	34.72	PEAK	106	276	VERTICAL


Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draft n MCS8 40MHz Ch 46 / Ant. A + Ant. C

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	10468.120	69.08	-5.22	74.30	58.53	39.94	5.25	34.64	PEAK	100	256	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	10468.000	73.80	-0.50	74.30	63.26	39.94	5.25	34.64	PEAK	103	277	VERTICAL

4.7. Band Edge Emissions Measurement

4.7.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.25 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the 5.470-5.725 GHz band: all emissions outside of the 5.470-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the 5.725-5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBuV/m at 3m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). In addition, in case the emission falls within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1 MHz / 1 MHz for Peak

4.7.3. Test Procedures

1. The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draft n MCS8 20MHz Ch 36, 40 / Ant. A + Ant. C
Test Date	Jun. 2, 2008		

Channel 36

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	5149.600	74.79	-5.21	80.00	37.29	34.00	3.50	0.00	PEAK	132	205	VERTICAL
2 @	5150.000	59.10	-0.90	60.00	21.60	34.00	3.50	0.00	AVERAGE	132	205	VERTICAL
3 @	5175.600	119.42			81.83	34.07	3.52	0.00	PEAK	132	205	VERTICAL
4 @	5187.200	108.81			71.22	34.07	3.52	0.00	AVERAGE	132	205	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	5147.200	70.77	-9.23	80.00	33.27	34.00	3.50	0.00	PEAK	117	93	VERTICAL
2 @	5147.720	59.76	-0.24	60.00	22.26	34.00	3.50	0.00	AVERAGE	117	93	VERTICAL
3 @	5202.800	110.91			73.28	34.10	3.53	0.00	AVERAGE	117	93	VERTICAL
4 @	5206.800	121.04			83.41	34.10	3.53	0.00	PEAK	117	93	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.



Temperature	26°C	Humidity	62%
Test Engineer	Roy Huang	Configurations	Draft n MCS8 40MHz Ch 38, 46 / Ant. A + Ant. C
Test Date	Jun. 2, 2008		

Channel 38

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	5144.000	74.31	-5.69	80.00	36.81	34.00	3.50	0.00	PEAK	117	100	VERTICAL
2 @	5150.000	59.82	-0.18	60.00	22.32	34.00	3.50	0.00	AVERAGE	117	100	VERTICAL
3 @	5197.600	118.47			80.84	34.10	3.53	0.00	PEAK	117	100	VERTICAL
4 @	5200.800	107.07			69.44	34.10	3.53	0.00	AVERAGE	117	100	VERTICAL

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	5150.000	58.97	-1.03	60.00	21.47	34.00	3.50	0.00	AVERAGE	103	198	VERTICAL
2	5150.000	72.81	-7.19	80.00	35.31	34.00	3.50	0.00	PEAK	103	198	VERTICAL
3 @	5240.400	110.15			72.44	34.17	3.54	0.00	AVERAGE	103	198	VERTICAL
4 @	5244.400	120.43			82.69	34.20	3.54	0.00	PEAK	103	198	VERTICAL

Item 3, 4 are the fundamental frequency at 5230 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

The limits above 5GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1.5m.

Distance extrapolation factor = 20 log (specific distance [3m] / test distance [1.5m]) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.8. Frequency Stability Measurement

4.8.1. Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emissions is maintained within the band of operation under all conditions of normal operation as specified in the user's manual or $\pm 20\text{ppm}$ (Draft n specification).

4.8.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RB	10 kHz
VB	10 kHz
Sweep Time	Auto

4.8.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than $\pm 20\text{ppm}$ (Draft n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature rule is $-30^\circ\text{C} \sim 50^\circ\text{C}$.
8. Measuring multiple antennas, the connector is required to link with spectrum analyser through a combiner.

4.8.4. Test Setup Layout



4.8.5. Test Deviation

There is no deviation with the original standard.

4.8.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.8.7. Test Result of Frequency Stability

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5200
126.50	5200.0411
110.00	5200.0358
93.50	5200.0287
Max. Deviation (MHz)	0.041100
Max. Deviation (ppm)	7.90

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5200
-30	5200.0478
-20	5200.0403
-10	5200.0387
0	5200.0234
10	5200.0157
20	5200.0059
30	5199.9981
40	5199.9885
50	5199.967
Max. Deviation (MHz)	0.047800
Max. Deviation (ppm)	9.19

4.9. Antenna Requirements

4.9.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.9.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2008	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2008	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz –30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2007	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Mar. 04, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 04, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
AC Power Source	HPC	HPB-500W	HPB-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Jan. 14, 2008	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Jan. 04, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Jan. 04, 2008	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

* Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection : Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.