

1.1. Test Result of RF Exposure Evaluation

- . Product: Wireless Print Server
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

1.1.1. Antenna Gain

The maximum Gain is 1.8 dBi.

1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

(1) Modulation Standard: IEEE 802.11b(11Mbps), TX0

Test Date: Jul. 09, 2008 Temperature: 20 Humidity: 60%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	20.55	0.034
06	2437	21.27	0.040
11	2462	20.40	0.030

(2) Modulation Standard: IEEE 802.11b(11Mbps), TX1

Test Date: Nov. 05, 2008 Temperature: 20 Humidity: 60%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	16.31	0.013
06	2437	17.15	0.016
11	2462	16.33	0.013

The MPE is calculated as $0.040\text{mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

For 2412-2462 MHz, the EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.