



# FCC TEST REPORT

According to

## FCC Rules and Regulations Part 15 Subpart C

Applicant : TRENDware International, Inc.  
Address : 20675 Manhattan Place, Torrance, CA 90501,  
U.S.A.  
Equipment : Wireless Print Server  
Model No. : TEW-P11G, TE100-P11  
FCC ID : S9ZTEWP11G  
Trade Name : TRENDnet

Laboratory Accreditation



- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Cerpass Technology Corp.**, the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



## Contents

<b>1. Report of Measurements and Examinations</b>	<b>5</b>
1.1 List of Measurements and Examinations	5
<b>2. Test Configuration of Equipment under Test</b>	<b>6</b>
2.1 RF Specifications	6
2.2 Feature of Equipment under Test	6
2.3 Test Manner	7
2.4 Description of Test System	7
2.5 Connection Diagram of Test System	8
2.6 Carrier Frequency of Channels	8
2.7 General Information of Test	9
2.8 Measurement Uncertainty	9
2.9 History of this test report	10
<b>3. Antenna Requirements</b>	<b>11</b>
3.1 Standard Applicable	11
3.2 Antenna Construction and Directional Gain	11
<b>4. Test of Conducted Emission</b>	<b>12</b>
4.1 Test Limit	12
4.2 Test Procedures	12
4.3 Typical Test Setup	13
4.4 Measurement Equipment	13
4.5 Test Result and Data	14
4.6 Test Photographs	16
<b>5. Test of Radiated Emission</b>	<b>17</b>
5.1 Test Limit	17
5.2 Test Procedures	17
5.3 Typical Test Setup	18
5.4 Measurement Equipment	18
5.5 Test Result and Data	19
5.6 Test Photographs	35
<b>6. 6dB Bandwidth Measurement Data</b>	<b>36</b>
6.1 Test Limit	36
6.2 Test Procedures	36
6.3 Test Setup Layout	36
6.4 Measurement Equipment	36
6.5 Test Result and Data	36
<b>7. Maximum Peak Output Power</b>	<b>40</b>
7.1 Test Limit	40
7.2 Test Procedures	40
7.3 Test Setup Layout	40
7.4 Measurement Equipment	40
7.5 Test Result and Data	40
<b>8. Band Edges Measurement</b>	<b>44</b>
8.1 Test Limit	44
8.2 Test Procedure	44
8.3 Test Setup Layout	44



8.4 Measurement Equipment..... 44

8.5 Test Result and Data..... 44

8.6 Restrict Band Emission Measurement Data ..... 49

**9. Power Spectral Density ..... 50**

9.1 Test Limit ..... 50

9.2 Test Procedures ..... 50

9.3 Test Setup Layout ..... 50

9.4 Measurement Equipment..... 50

9.5 Test Result and Data..... 50

**10. Restricted Bands of Operation ..... 54**

10.1 Labeling Requirement..... 54

**Appendix A. Photographs of EUT.....A1 ~ A10**



# CERTIFICATE OF COMPLIANCE

According to

## FCC Rules and Regulations Part 15 Subpart C

Applicant : TRENDware International, Inc.  
Address : 20675 Manhattan Place, Torrance, CA 90501,  
U.S.A.  
Equipment : Wireless Print Server  
Model No. : TEW-P11G, TE100-P11  
FCC ID : S9ZTEWP11G

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to

**FCC Rules and Regulations Part 15 Subpart C (2007).**

The test was carried out on Jul. 24, 2008 at CerpPASS Technology Corp.

Signature

Anson Chou  
EMC/RF B.U. Vice General Manager



# 1. Report of Measurements and Examinations

## 1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209 15.247(d)	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(d)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(e)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass



## 2. Test Configuration of Equipment under Test

### 2.1 RF Specifications

Spreading	802.11b: DSSS, CCK(QPSK, BPSK) 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
Frequency Range	802.11b/g: 2.4 ~ 2.4835GHz
Number of Channels	USA, Canada and Taiwan: 1 ~ 11 Japan: 1 ~ 14 Most European Countries: 1 ~ 13 France: 1 ~ 7
Data Rate	802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps
Modulation	802.11g: OFDM 802.11b: CCK, DQPSK, DBPSK
Antenna	Dipole Antenna Peak gain: 1.8dBi
Security	IEEE 802.1x and WPA (available in the future) WEP 64 bit, 128 bit
Transmit Power	FCC: 802.11b: 17 ~ 19 dBm 802.11g: 13~15 dBm
ETSI	802.11b: 17 ~ 19dBm 802.11g: 13~15dBm
Receive Sensitivity	11Mbps: -85dBm (Typical) 54Mbps: -72dBm (Typical)
Power Consumption	TX : 570mA RX : 300mA
TX and RX Throughput	TX : 22Mbps RX : 22Mbps

### 2.2 Feature of Equipment under Test

Power Consumption	5.5w max.
External Power Adapter	12V DC
LEDs	4
Parallel Port	1 Centronic female DB-25 connector
USB Port (1.1)	1
Ethernet Connector	10/100BaseT



### 2.3 Test Manner

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. The complete test system included Notebook, USB Mouse, Printer and EUT for RF test.
- c. An executive program, Hyper Terminal under WIN XP, which generates a continuous signal by the following frequency to test.
  - 802.11b/g:  
CH01: 2412MHz, CH06: 2437MHz, CH11: 2462MHz
- d. Series adapters:
  - America: MU12-2050200-A1
  - UK: MU12-2050200-B2
  - Australia: MU12-2050200-A3

### 2.4 Description of Test System


Device	Manufacturer	Model No.	Description
USB mouse	IBM	MO28VO	Data Cable, USB Shielding 1.85 m
Printer	HP	DeskJet 1300	Power Cable, Adapter Unshielding 1.8 m Data Cable, USB/Print Shielding 1.6 m
Notebook	TOSHIBA	PSA50T-05M00C	Power Cable, Unshielding 1.8 m

Use Cable:

Cable	Quantity	Description
RJ45	1	Unshielding, 1.5m



### 2.5 Connection Diagram of Test System



- 1. The RJ45 cable is connected from EUT to the Notebook.
- 2. The USB cable is connected from the Notebook to the USB Mouse.
- 3. The Print cable is connected from EUT to the Printer.
- 4. The USB cable is connected from EUT to the Printer.

### 2.6 Carrier Frequency of Channels

802.11b, 802.11g

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	12	---





## 2.7 General Information of Test

Test Site :	Cerpass Technology Corp. 4F-2, No. 28, Lane 78, Xing-Ai Rd. Nei-hu, Taipei City 114 Taiwan R.O.C.
Test Site Location (OATS1-SD):	No.68-1, Shihbachongsi, shihding Township, Taipei City 223, Taiwan, R.O.C. Registration Number: 632249.
FCC Registration Number :	632249
IC Registration Number :	4934B-1
VCCI Registration Number :	T-338 for Telecommunication Test C-2188 for Conducted emission test R-1902 for Radiated emission test
Test Voltage:	AC 120V
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30MHz Radiation: from 30MHz to 24620MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

## 2.8 Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	2.71 dB
Radiated Emission	30 MHz ~ 1GHz	Vertical	4.11 dB
		Horizontal	4.10 dB
6 dB Bandwidth	---	---	7500 Hz
Maximum Peak Output Power	---	---	1.4 dB
100kHz Bandwidth of Frequency Band Edges	---	---	2.2 dB
Power Spectral Density	---	---	2.2 dB





### 3. Antenna Requirements

#### 3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### 3.2 Antenna Construction and Directional Gain

Antenna type: Dipole Antenna

Antenna Gain: 1.8 dBi



## 4. Test of Conducted Emission

### 4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


\*Decreases with the logarithm of the frequency.

### 4.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



### 4.3 Typical Test Setup




### 4.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
Receiver	R&S	ESCI	100443	2007/09/27	2008/09/26
LISN	NNB-2/16Z	MESS TEC	02/10191	2008/06/03	2009/06/02
LISN	NNB-2/16Z	ROLF HEINE	03/10058	2008/04/19	2009/04/18



### 4.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: 802.11g, CH1	Temperature	: 26 °C
Memo	: MU12-2050200-A1	Humidity	: 60 %




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.15	45.61	0.11	45.72	65.96	-20.24	QP
2	0.15	30.09	0.11	30.20	55.96	-25.76	AVERAGE
3	0.16	34.33	0.11	34.44	55.23	-20.79	AVERAGE
4	0.16	47.17	0.11	47.28	65.23	-17.95	QP
5	0.38	39.14	0.11	39.25	48.33	-9.08	AVERAGE
6	0.38	41.04	0.11	41.16	58.33	-17.17	QP
7	0.44	34.73	0.12	34.85	47.02	-12.18	AVERAGE
8	0.44	36.98	0.12	37.09	57.02	-19.93	QP
9	0.59	37.87	0.13	38.00	56.00	-18.00	QP
10	0.59	33.83	0.13	33.96	46.00	-12.04	AVERAGE
11	14.06	30.93	0.44	31.36	50.00	-18.64	AVERAGE
12	14.06	38.41	0.44	38.84	60.00	-21.16	QP

- Remarks:
1. Level = Read Level + Factor
  2. Factor = LISN(ISN) Factor + Cable Loss
  3. All emission below 1GHz at 802.11g mode are all the same,so the 802.11g mode chosen as representative in final test.
  4. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
  5. The data is worse case.



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: 802.11g, CH1	Temperature	: 26 °C
Memo	: MU12-2050200-A1	Humidity	: 60 %



Trace: (Discrete)

Item	Freq MHz	Read Value dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dBuV	Remark
1	0.17	38.40	0.14	38.54	55.08	-16.54	AVERAGE
2	0.17	46.83	0.14	46.97	65.08	-18.10	QP
3	0.22	40.71	0.14	40.85	62.79	-21.94	QP
4	0.22	33.36	0.14	33.49	52.79	-19.30	AVERAGE
5	0.44	41.20	0.14	41.35	56.98	-15.63	QP
6	0.44	36.61	0.14	36.76	46.98	-10.22	AVERAGE
7	0.49	33.66	0.15	33.81	46.09	-12.28	AVERAGE
8	0.49	37.00	0.15	37.15	56.09	-18.94	QP
9	0.59	37.25	0.16	37.41	56.00	-18.59	QP
10	0.59	36.34	0.16	36.50	46.00	-9.50	AVERAGE
11	13.99	35.73	0.46	36.19	60.00	-23.81	QP
12	13.99	29.45	0.46	29.91	50.00	-20.09	AVERAGE

- Remarks:
1. Level = Read Level + Factor
  2. Factor = LISN(ISN) Factor + Cable Loss
  3. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
  4. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
  5. The data is worse case.

Test engineer: Ben



## 5. Test of Radiated Emission

### 5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated ( $\mu$ V / M)	Radiated (dB $\mu$ V/ M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB $\mu$ V/ M)
30-230	10	30
230-1000	10	37


### 5.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- “Cone of radiation” has been considered to be 3dB beamwidth of the measurement antenna.





### 5.3 Typical Test Setup




### 5.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Bilog Antenna	CBL6112B	Schaffner	2840	2008/05/15	2009/05/14
Signal Generator	8648B	HP	3629U00612	2007/10/09	2008/10/08
Amplifier	8447D	Agilent	2944A10593	2008/05/26	2009/05/25
EMI Receiver	SCR-3501	SCHAFFNER	437	2007/11/26	2008/11/25
Spectrum	FSP40	R&S	100047	2008/02/22	2009/02/21
Horn Antenna	3115	EMCO	31589	2008/04/01	2009/03/30
Amplifier	8449B	Agilent	3008A01954	2008/01/24	2009/01/23



5.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	75.01	53.82	-17.34	36.48	40.00	-3.52	QP	100	80
2	125.00	52.68	-13.29	39.39	43.50	-4.11	QP	100	95
3	150.00	48.62	-12.52	36.10	43.50	-7.40	Peak	100	78
4	166.68	49.55	-12.90	36.65	43.50	-6.85	Peak	100	78
5	175.01	47.48	-9.75	37.73	43.50	-5.77	QP	100	102
6	185.93	47.62	-9.78	37.84	43.50	-5.66	QP	100	91
7	200.03	50.11	-11.75	38.36	43.50	-5.14	QP	100	91
8	234.60	50.69	-9.75	40.94	46.00	-5.06	QP	100	110
9	251.10	49.70	-12.33	37.37	46.00	-8.63	Peak	100	80
10	300.60	41.87	-9.33	32.54	46.00	-13.46	Peak	100	80

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	301.40	41.84	-9.10	32.74	46.00	-13.26	Peak	100	80
2	400.04	51.47	-8.83	42.64	46.00	-3.36	QP	100	99
3	501.60	40.81	-4.92	35.89	46.00	-10.11	Peak	100	105
4	666.75	43.96	-3.88	40.08	46.00	-5.92	QP	100	120
5	752.90	36.27	0.38	36.65	46.00	-9.35	Peak	100	102
6	803.30	39.55	-2.76	36.79	46.00	-9.21	Peak	100	141

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	75.05	56.07	-22.15	33.92	40.00	-6.08	Peak	100	95
2	125.02	55.16	-19.54	35.62	43.50	-7.88	Peak	100	95
3	150.03	51.47	-18.33	33.14	43.50	-10.36	Peak	100	88
4	251.10	52.26	-17.31	34.95	46.00	-11.05	Peak	100	145
5	267.60	49.56	-15.44	34.12	46.00	-11.88	Peak	100	140
6	300.60	48.20	-14.43	33.77	46.00	-12.23	Peak	100	140

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	301.40	48.33	-14.33	34.00	46.00	-12.00	Peak	100	98
2	400.03	52.62	-11.30	41.32	46.00	-4.68	QP	100	98
3	502.50	42.31	-5.10	37.21	46.00	-8.79	Peak	100	142
4	666.71	47.82	-5.28	42.54	46.00	-3.46	QP	100	142
5	752.90	36.50	-0.03	36.47	46.00	-9.53	Peak	100	100
6	800.00	43.51	-0.54	42.97	46.00	-3.03	QP	100	155

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 11 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4823.95	29.97	5.67	35.64	54.00	-18.36	Average	150	217
2	4823.95	40.48	5.67	46.15	74.00	-27.85	Peak	150	217

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 11 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.60	42.03	5.67	47.70	74.00	-26.30	Peak	150	217
2	4824.60	30.73	5.67	36.41	54.00	-17.59	Average	150	229

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 6	Humidity	: 60 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 11 Mbps



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	41.06	5.80	46.86	74.00	-27.14	Peak	150	217
2	4874.00	29.87	5.80	35.67	54.00	-18.33	Average	150	217


Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.





Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 6	Humidity	: 60 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 11 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.23	36.84	5.80	42.65	54.00	-11.35	Average	150	215
2	4874.23	48.01	5.80	53.81	74.00	-20.19	Peak	150	215

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 11	Humidity	: 60 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 11 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	41.43	5.93	47.36	74.00	-26.64	Peak	150	217
2	4924.00	29.59	5.93	35.52	54.00	-18.48	Average	150	217

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 11	Humidity	: 60 %
Modulation Type	: 802.11b	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 11 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.95	48.66	5.80	54.46	74.00	-19.54	Peak	150	215
2	4873.95	36.86	5.80	42.66	54.00	-11.34	Average	150	215

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.15	41.18	5.67	46.85	74.00	-27.15	Peak	150	217
2	4824.15	29.50	5.67	35.18	54.00	-18.82	Average	150	217

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 1	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.40	48.46	5.67	54.13	74.00	-19.87	Peak	150	215
2	4824.40	36.88	5.67	42.55	54.00	-11.45	Average	150	215

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 6	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.13	30.90	5.80	36.70	54.00	-17.30	Average	150	217
2	4876.13	42.77	5.81	48.58	74.00	-25.42	Peak	150	217

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 6	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.03	48.60	5.80	54.40	74.00	-19.60	Peak	150	215
2	4874.03	36.85	5.80	42.65	54.00	-11.35	Average	150	215

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 11	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.55	30.86	5.93	36.79	54.00	-17.21	Average	150	217
2	4923.55	42.43	5.93	48.36	74.00	-25.64	Peak	150	217


Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.





Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Transmit / Receive	Temperature	: 30 °C
Operation Channel	: 11	Humidity	: 60 %
Modulation Type	: 802.11g	Atmospheric Pressure	: 1003 hPa
Memo	: MU12-2050200-A1	Rate	: 54 Mbps



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.20	48.12	5.93	54.05	74.00	-19.95	Peak	150	215
2	4924.20	36.87	5.93	42.80	54.00	-11.20	Average	150	215

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

Test engineer: Ben



## 6. 6dB Bandwidth Measurement Data


### 6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 6.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

### 6.3 Test Setup Layout



### 6.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2008/02/22	2009/02/21

### 6.5 Test Result and Data

Test Date : Jul. 09, 2008  
 Temperature : 20  
 Humidity : 60%  
 Atmospheric Pressure : 1008 hPa

(1) Modulation Standard: IEEE 802.11b (11Mbps)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	12.00
06	2437	11.90
11	2462	11.90

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	16.40
06	2437	16.40
11	2462	16.50




Modulation Standard: 802.11b (11Mbps)  
Channel: 01



Date: 9.JUL.2008 10:14:19


Modulation Standard: 802.11b (11Mbps)  
Channel: 06



Date: 9.JUL.2008 10:22:28




Modulation Standard: 802.11b (11Mbps)  
Channel: 11



Date: 9.JUL.2008 10:23:58


Modulation Standard: 802.11g (54Mbps)  
Channel: 01



Date: 9.JUL.2008 10:13:02




Modulation Standard: 802.11g (54Mbps)  
Channel: 06



Date: 9.JUL.2008 10:10:51

Modulation Standard: 802.11g (54Mbps)  
Channel: 11



Date: 9.JUL.2008 10:09:24



## 7. Maximum Peak Output Power


### 7.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

### 7.2 Test Procedures

The antenna port ( RF output ) of the EUT was connected to the input ( RF input ) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

### 7.3 Test Setup Layout



### 7.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2008/02/22	2009/02/21

### 7.5 Test Result and Data

Test Date : Jul. 09, 2008  
 Temperature : 20  
 Humidity : 60%  
 Atmospheric Pressure : 1008 hPa

(1) Modulation Standard: IEEE 802.11b (11Mbps)


Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	20.55	113.50
06	2437	21.27	134.00
11	2462	20.40	109.60

(2) Modulation Standard: IEEE 802.11g (06Mbps)

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	16.31	42.80
06	2437	17.15	51.90
11	2462	16.33	43.00




Modulation Standard: 802.11b (11Mbps)  
Channel: 01



Date: 9.JUL.2008 10:02:44


Modulation Standard: 802.11b (11Mbps)  
Channel: 06



Date: 9.JUL.2008 10:04:53




Modulation Standard: 802.11b (11Mbps)  
Channel: 11



Date: 9.JUL.2008 10:06:22

Modulation Standard: 802.11g (54Mbps)  
Channel: 01




Date: 9.JUL.2008 10:06:55






Modulation Standard: 802.11g (54Mbps)  
Channel: 06



Date: 9.JUL.2008 10:07:43

Modulation Standard: 802.11g (54Mbps)  
Channel: 11



Date: 9.JUL.2008 10:08:31



## 8. Band Edges Measurement


### 8.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

### 8.2 Test Procedure

- The transmitter output was connected to the spectrum analyzer via a low lose cable.
- Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- The band edges was measured and recorded.

### 8.3 Test Setup Layout



### 8.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2008/02/22	2009/02/21

### 8.5 Test Result and Data

Test Date : Jul. 09, 2008  
 Temperature : 20  
 Humidity : 60%  
 Atmospheric Pressure : 1008 hPa

(1) Modulation Standard: IEEE 802.11b (11Mbps)


Channel	Frequency	maximum value in frequency (MHz)	maximum value (dBm)
01	2412	2399.40	-34.73
11	2462	3256.00	-43.02

(2) Modulation Standard: IEEE 802.11g (54Mbps)


Channel	Frequency	maximum value in frequency (MHz)	maximum value (dBm)
01	2412	2399.40	-37.81
11	2462	3256.00	-43.49



Modulation Standard: 802.11b (11Mbps)  
Channel: 01




Date: 9.JUL.2008 10:27:52




Date: 9.JUL.2008 10:28:31



Modulation Standard: 802.11b (11Mbps)  
Channel: 11




Date: 9.JUL.2008 10:25:50




Date: 9.JUL.2008 10:26:31



Modulation Standard: 802.11g (54Mbps)  
Channel: 01




Date: 9.JUL.2008 10:30:24




Date: 9.JUL.2008 10:31:10



Modulation Standard: 802.11g (54Mbps)  
Channel: 11



Date: 9.JUL.2008 10:34:23



Date: 9.JUL.2008 10:34:59

**8.6 Restrict Band Emission Measurement Data**

Test Date : Jul. 10, 2008  
 Temperature : 30  
 Humidity : 60%  
 Atmospheric Pressure : 1003 hPa

Modulation Standard: IEEE 802.11b (11Mbps)

## a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.44	H	63.54	-3.26	60.28	Peak	74	54	-13.72	237	1.00
2390.27	H	46.78	-3.30	43.49	Ave	74	54	-10.51	237	1.00
2389.25	V	62.83	-3.30	59.53	Peak	74	54	-14.47	232	1.50
2389.97	V	49.43	-3.30	46.13	Ave	74	54	-7.87	232	1.50

## b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2492.17	H	58.48	-2.93	55.55	Peak	74	54	-18.45	237	1.00
2498.44	H	46.89	-2.91	43.98	Ave	74	54	-10.02	237	1.00
2484.50	V	61.91	-2.96	58.95	Peak	74	54	-15.05	232	1.50
2483.51	V	49.24	-2.96	46.28	Ave	74	54	-7.72	232	1.50

Modulation Standard: 802.11g (54Mbps)

## a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2392.52	H	51.04	-3.29	47.75	Peak	74	54	-26.25	237	1.00
2390.89	H	37.83	-3.29	34.53	Ave	74	54	-19.47	237	1.00
2388.44	V	59.78	-3.30	56.48	Peak	74	54	-17.52	232	1.50
2389.97	V	47.81	-3.30	44.51	Ave	74	54	-9.49	232	1.50

## b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2492.86	H	49.39	-2.93	46.47	Peak	74	54	-27.53	237	1.00
2496.54	H	37.73	-2.91	34.82	Ave	74	54	-19.18	237	1.00
2484.95	V	60.80	-2.95	57.84	Peak	74	54	-16.16	232	1.50
2483.51	V	47.79	-2.96	44.83	Ave	74	54	-9.17	232	1.50

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



### 9. Power Spectral Density


#### 9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

#### 9.2 Test Procedures

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=span/3KHz.
- c. The power spectral density was measured and recorded.
- d. The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

#### 9.3 Test Setup Layout



#### 9.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2008/02/22	2009/02/21

#### 9.5 Test Result and Data

Test Date : Jul. 24, 2008  
 Temperature : 20  
 Humidity : 60%  
 Atmospheric Pressure : 1008 hPa

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-15.63
06	2437	-13.56
11	2462	-11.80


(2) Modulation Standard: IEEE 802.11g (06Mbps)

Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-20.76
06	2437	-18.69
11	2462	-17.06






Modulation Standard: 802.11b (11Mbps)  
Channel: 01



Date: 24.JUL.2008 10:51:04


Modulation Standard: 802.11b (11Mbps)  
Channel: 06



Date: 24.JUL.2008 10:51:42




Modulation Standard: 802.11b (11Mbps)  
Channel: 11



Date: 24.JUL.2008 10:52:28


Modulation Standard: 802.11g (54Mbps)  
Channel: 01



Date: 24.JUL.2008 10:55:11




Modulation Standard: 802.11g (54Mbps)  
Channel: 06



Date: 24.JUL.2008 10:56:05

Modulation Standard: 802.11g (06Mbps)  
Channel: 11



Date: 24.JUL.2008 10:56:43



### 10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

\*\* : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

#### 10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.