

Airgo Networks Inc.

FCC ID: SA3-AGN1223AR0100

802.11 a/b/g True MIMO APx mini PCI modular radio
Request for transmitter modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	Device is equipped with Metal shielding to cover RF section. Refer to external photos
2	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the modules are buffered through logic or microprocessor inputs.
3	Have it own power supply regulation	Internal power regulator. Refer to Block diagram
4	Meet the antenna requirements of Section 15.203	Device is equipped with unique antenna (Hirose) connector. Refer to external photos
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested on an extender board connected to laptop. Refer to setup photos.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	FCC ID of label is to be placed on the module. OEM installation manual instructs installer to place required wording “Contains FCC ID:” on products containing device
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	Refer to “User’s Guide” Exhibit
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	MPE calculations submitted for 2/3 dBi antennas. Product will not be used in portable devices.