



Report No.: SZ12040136E01



FCC TEST REPORT

Issued to

Hisense International Co., Ltd.

For

CDMA EV-DO Smartphone

Model Name: E860
 Trade Name: Hisense
 Brand Name: Hisense
 FCC ID: SARHISENSEEE860
 Standard: 47 CFR Part 15 Subpart B
 Test date: May 7, 2012 - May 18, 2012
 Issue date: May 18, 2012

Shenzhen Morlab Communication Technology Co., Ltd.



Tested by Li Liang
 Li Liang
 Date 2012.5.18

Approved by Wei Yanqian
 Wei Yanqian
 Date 2012.5.18

Review by Huang Pulong
 Huang Pulong
 Date 2012.5.18



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1	EUT Description	3
1.2	Test Standards and Results	4
1.3	Facilities and Accreditations	5
1.3.1	Facilities	5
1.3.2	Test Environment Conditions	5
1.3.3	Measurement Uncertainty	5
2.	TEST CONDITIONS SETTING.....	6
2.1	Test Mode	6
2.2	Test Setup and Equipments List.....	7
2.2.1	Conducted Emission.....	7
2.2.2	Radiated Emission.....	8
3.	47 CFR PART 15B REQUIREMENTS	11
3.1	Conducted Emission	11
3.1.1	Requirement	11
3.1.2	Test Description	11
3.1.3	Test Result.....	11
3.2	Radiated Emission	13
3.2.1	Requirement	13
3.2.2	Test Description	13
3.2.3	Test Result.....	13

Change History		
Issue	Date	Reason for change
1.0	May 18, 2012	First edition



1. GENERAL INFORMATION

1.1 EUT Description

EUT Type CDMA EV-DO Smartphone
Serial No..... (n.a, marked #1 by test site)
Hardware Version..... V2.00
Software Version E527.6.02.01.00
Applicant..... Hisense International Co., Ltd.
F22, Hisense Tower, 17, Donghaixi Road, Qindao, China
Manufacturer Hisense Communications Co., Ltd
No.218, Qianwangang Road, Economic & Technological Development
Zone, Qingdao, China
Power Supply Battery
Brand Name: Hisense
Model No.: LI37120
Serial No.: (n.a. marked #1 by test site)
Capacitance: 4.44Wh(1200mAh)
Rated Voltage: 3.7V
Charge Limit: 4.2V

Note 1: The EUT is GSM Mobile Phone, it supports CDMA 800MHz, EVDO and ISM 2.4G Bluetooth bands.

Note 2: The EUT is equipped with a T-Flash card slot; equipped with a USB port which can be connected to the ancillary equipments supplied by the manufacturer e.g. the AC Adapter and the USB Cable.

Note 3: For a more detailed description, please refer to Specification or User’s Manual supplied by the applicant and/or manufacturer.



1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-09 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4 2009.

1.3 Facilities and Accreditations

1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	$\pm 1.8\text{dB}$
Uncertainty of Radiated Emission:	$\pm 3.1\text{dB}$

2. TEST CONDITIONS SETTING

2.1 Test Mode

- (1) The first test mode (USB)


The EUT configuration of the emission tests is TransFlash Card + EUT + Battery + PC.

In this test mode, the EUT with a TransFlash Card embedded is connected with a PC via a USB cable supplied by applicant. During the measurement, the data is transmitting between the PC and the TransFlash Card of the EUT.

2.2 Test Setup and Equipments List

2.2.1 Conducted Emission

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
EMC Analyzer	Agilent	E7405A	US44210471	2012.05
Receiver	Narda	PMM 9060	001WX11001	2011.12
Receiver	Narda	PMM 9010	595WX11007	2011.11
LISN	Schwarzbeck	NSLK 8127	812744	2012.05
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)
System Simulator	Agilent	E5515C	GB43130131	2012.05
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)


2.2.2 Radiated Emission

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz


B. Test Procedure

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range of 9KHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
EMC Analyzer	Agilent	E7405A	US44210471	2012.05
Receiver	Narda	PMM 9060	001WX11001	2011.12



Description	Manufacturer	Model	Serial No.	Cal. Date
Receiver	Narda	PMM 9010	595WX11007	2011.11
Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2012.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2012.05
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	9120D-963	2012.05
Test Antenna -Loop	Schwarzbeck	FMZB 1519	1519-022	2012.05
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)

3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description


See section 2.2.1 of this report.

3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

3.1.3.1 Test Mode

A. Test Plot and Suspicious Points:



(Plot A: L Phase)



(Plot B: N Phase)

Test Result: PASS

3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	($\mu\text{V/m}$)	(dBuV/m)
0.009 - 0.490	$2400/F(\text{KHz})$	300m	$10000 * 2400/F(\text{KHz})$	$20\log 2400/F(\text{KHz}) + 80$
0.490 - 1.705	$2400/F(\text{KHz})$	30m	$100 * 2400/F(\text{KHz})$	$20\log 2400/F(\text{KHz}) + 40$
1.705 - 30.00	30	30m	$100 * 30$	$20\log 30 + 40$
30.0 - 88.0	100	3m	100	$20\log 100$
88.0 - 216.0	150	3m	150	$20\log 150$
216.0 - 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by $20\log \text{Emission Level}(\mu\text{V/m})$.
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is $30\mu\text{V/m}$, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}$$

3.2.2 Test Description

See section 2.2.2 of this report.

3.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to


perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

A. Test Plots and Suspicious Points:

NOTE: The emissions are too small to be measured and are at least 6 dB below the limit, So all the data of marked are pass.




(Plot A: 9K – 30M)



(Plot A: Test Antenna Vertical)

Fre. (MHz)	Pk	QP	AV	Limit- PK	Limit- QP	Limit- AV	Antenna	Verdict
100.150	32.32	N.A	N.A	N.A	43.5	N.A	Vertical	Pass
332.369	36.12	N.A	N.A	N.A	46.0	N.A	Vertical	Pass
663.766	35.05	N.A	N.A	N.A	46.0	N.A	Vertical	Pass
1000.000	42.54	N.A	N.A	N.A	74.0	N.A	Vertical	Pass
1326.434	47.44	N.A	N.A	74.0	N.A	54.0	Vertical	Pass
2492.269	46.83	N.A	N.A	74.0	N.A	54.0	Vertical	Pass
4996.010	49.68	N.A	N.A	74.0	N.A	54.0	Vertical	Pass



(Plot B: Test Antenna Horizontal)

Fre. (MHz)	Pk	QP	AV	Limit- PK	Limit- QP	Limit- AV	Antenna	Verdict
204.165	35.07	N.A	N.A	N.A	43.5	N.A	Horizontal	Pass
276.733	38.80	N.A	N.A	N.A	46.0	N.A	Horizontal	Pass
666.185	36.15	N.A	N.A	N.A	46.0	N.A	Horizontal	Pass
1000.000	42.39	N.A	N.A	N.A	74.0	N.A	Horizontal	Pass
1326.434	43.77	N.A	N.A	74.0	N.A	54.0	Horizontal	Pass
2488.030	46.41	N.A	N.A	74.0	N.A	54.0	Horizontal	Pass
4971.322	49.16	N.A	N.A	74.0	N.A	54.0	Horizontal	Pass

Test Result: PASS

** END OF REPORT **