

---

# TEST REPORT FOR WLAN TESTING

---

Report No.: SRTC2021-9004(F)-21092301(F)

Product Name: BT/Wi-Fi Module

Applicant: Hisense Communication Co., Ltd.

Manufacturer: Hisense Communication Co., Ltd.

Specification: FCC Part 15 Subpart C (2020)

FCC ID: SARMW5031

The State Radio\_monitoring\_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District, Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

## CONTENTS

|   |           |
|---|-----------|
| <b>1. GENERAL INFORMATION.....</b>                            | <b>2</b>  |
| 1.1 Notes of the test report .....                            | 2         |
| 1.2 Information about the testing laboratory .....            | 2         |
| 1.3 Applicant’s details .....                                 | 2         |
| 1.4 Manufacturer’s details.....                               | 2         |
| 1.5 Test Environment.....                                     | 3         |
| <b>2 DESCRIPTION OF THE DEVICE UNDER TEST .....</b>           | <b>4</b>  |
| 2.1 Final Equipment Build Status.....                         | 4         |
| 2.2 Description of Test Modes.....                            | 5         |
| 2.2.1 Test Mode Applicability and Tested Channel Detail ..... | 5         |
| 2.3 EUT Operating conditions.....                             | 6         |
| 2.4 Support Equipment .....                                   | 6         |
| <b>3 REFERENCE SPECIFICATION.....</b>                         | <b>7</b>  |
| <b>4 KEY TO NOTES AND RESULT CODES.....</b>                   | <b>7</b>  |
| <b>5 RESULT SUMMARY .....</b>                                 | <b>8</b>  |
| <b>6 TEST RESULT .....</b>                                    | <b>9</b>  |
| 6.1 Peak Power Output.....                                    | 9         |
| 6.2 6dB Bandwidth.....  | 10        |
| 6.3 Transmitter Power Spectral Density .....                  | 11        |
| 6.4 Conducted Out of band emission measurement .....          | 12        |
| 6.5 Band-edge measurement .....                               | 13        |
| 6.6 Spurious Radiated Emissions.....                          | 14        |
| 6.7 AC Power line Conducted Emission .....                    | 19        |
| <b>7 MEASUREMENT UNCERTAINTIES .....</b>                      | <b>21</b> |
| <b>8 TEST EQUIPMENTS.....</b>                                 | <b>22</b> |
| <b>APPENDIX A – TEST DATA OF CONDUCTED EMISSION.....</b>      | <b>23</b> |
| <b>APPENDIX B – TEST DATA OF RADIATED EMISSION .....</b>      | <b>62</b> |

## **1. GENERAL INFORMATION**

### **1.1 Notes of the test report**

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC). The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### **1.2 Information about the testing laboratory**

|                      |  |
|----------------------|--|
| Company:             | The State Radio_monitoring_center Testing Center (SRTC)              |
| Address:             | 15th Building, No.30 Shixing Street, Shijingshan District, P.R.China |
| City:                | Beijing  |
| Country or Region:   | P.R.China  |
| Contacted person:    | Liu Jia  |
| Tel:                 | +86 10 57996183  |
| Fax:                 | +86 10 57996388  |
| Email:               | liujiaf@srtc.org.cn  |
| Designation Number:  | CN1267   |
| Registration number: | 239125   |

### **1.3 Applicant's details**

|          |  |
|----------|--|
| Company: | Hisense Communication Co., Ltd.  |
| Address: | Hisense Infor. Industrial Park Economic Technology Dev. District, Qingdao, China |

### **1.4 Manufacturer's details**

|          |  |
|----------|--|
| Company: | Hisense Communication Co., Ltd.  |
| Address: | Hisense Infor. Industrial Park Economic Technology Dev. District, Qingdao, China |

## 1.5 Test Environment

|   |            |
|---|------------|
| Date of Receipt of test sample at SRTC: | 2021-09-23 |
| Testing Start Date:                     | 2021-09-25 |
| Testing End Date:                       | 2021-10-14 |

| Environmental Data: | Temperature (°C) | Humidity (%) |
|---------------------|------------------|--------------|
| Ambient:            | 25               | 40           |
| Maximum Extreme:    | 70               | ---          |
| Minimum Extreme:    | -10              | ---          |

|  |      |
|--|------|
| Normal Supply Voltage (V d.c.):          | 5.00 |
| Maximum Extreme Supply Voltage (V d.c.): | 5.25 |
| Minimum Extreme Supply Voltage (V d.c.): | 4.75 |

## 2 DESCRIPTION OF THE DEVICE UNDER TEST

### 2.1 Final Equipment Build Status

|                              |   |
|------------------------------|---|
| Frequency Band:              | 2.412GHz~2.462GHz                         |
| Number of Channel For 20MHz: | 11  |
| Number of Channel For 40MHz: | 7   |
| Modulation Type:             | 802.11b<br>802.11g<br>802.11n (HT20/HT40) |
| Power Supply:                | Charger                                   |
| Software Revision:           | NA  |
| Hardware Revision:           | V1.00                                     |
| SN:                          | #08/#07/#03/#04/#05                       |
| Antenna type:                | Refer to Note                             |
| Antenna connector:           | Refer to Note                             |

#### **Note: Antenna requirement (FCC part 15.203)**

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The antenna(s) of the EUT are permanently attached.
- There are no provisions for connection to an external antenna.

Note: The antenna provides to the EUT, please refer to the following table:

| Brand | Model | Antenna gain | Frequency band (GHz) | Antenna type           | Connector Type |
|-------|-------|--------------|----------------------|------------------------|----------------|
| N/A   | N/A   | 0.5dBi       | 2.4GHz~2.4835GHz     | Fixed Internal Antenna | N/A            |

The antenna gain is provided by the customer and involved in the calculation and influence of the test results. Our laboratory takes the value declared by the customer as the criterion, and the customer is responsible for the antenna gain value. Manufacturers ensure that their designs will not be modified by the user or third party's arbitrary antenna parameters and performance.

Note: 802.11b/g cannot transmit at the same time. 802.11n MIMO is uncorrelated signal, Directional Gain is not a common character in 802.11n simultaneous transmitting modes.

#### 11n MIMO DG=0.5dBi

d) *Unequal antenna gains, with equal transmit powers.* For antenna gains given by  $G_1, G_2, \dots, G_N$  dBi

(i) If transmit signals are *correlated*, then

Directional gain =  $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$  dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

(ii) If all transmit signals are *completely uncorrelated*, then

Directional gain =  $10 \log[(10^{G_1/10} + 10^{G_2/10} + \dots + 10^{G_N/10}) / N_{ANT}]$  dBi

## 2.2 Description of Test Modes

11 channels are provided to this EUT:

| CHANNEL | FREQ. (MHz) | CHANNEL | FREQ. (MHz) |
|---------|-------------|---------|-------------|
| 1       | 2412        | 7       | 2442        |
| 2       | 2417        | 8       | 2447        |
| 3       | 2422        | 9       | 2452        |
| 4       | 2427        | 10      | 2457        |
| 5       | 2432        | 11      | 2462        |
| 6       | 2437        | ---     | ---         |

### 2.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|--------------------|---------------|-------|-----|------|-------------|
|                    | RE ≥ 1G       | RE<1G | PLC | APCM |             |
| -                  | √             | √     | √   | √    | -           |

Where

RE ≥ 1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

#### Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL                    | MODULATION TYPE | DATA RATE (Mbps)          |
|-------------------|-----------------------------------|-----------------|---------------------------|
| 1 to 11           | 1/6/11 For HT20<br>3/6/9 For HT40 | DBPSK/BPSK      | 1,6, 6.5,13.5<br>8.6,17.2 |

**Radiated Emission Test (Below 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL                    | MODULATION TYPE | DATA RATE (Mbps)          |
|-------------------|-----------------------------------|-----------------|---------------------------|
| 1 to 11           | 1/6/11 For HT20<br>3/6/9 For HT40 | DBPSK/BPSK      | 1,6, 6.5,13.5<br>8.6,17.2 |

**Power Line Conducted Emission Test:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TYPE | DATA RATE (Mbps) |
|-------------------|----------------|-----------------|------------------|
| 1 to 11           | 6              | DBPSK           | 1                |

**Antenna Port Conducted Measurement:**

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| AVAILABLE CHANNEL | TESTED CHANNEL                    | MODULATION TYPE | DATA RATE (Mbps)          |
|-------------------|-----------------------------------|-----------------|---------------------------|
| 1 to 11           | 1/6/11 For HT20<br>3/6/9 For HT40 | DBPSK/BPSK      | 1,6, 6.5,13.5<br>8.6,17.2 |

**2.3 EUT Operating conditions**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

**2.4 Support Equipment**

The following support equipment was used to exercise the DUT during testing:  
N/A

### **3 REFERENCE SPECIFICATION**

| Specification           | Version          | Title  |
|-------------------------|------------------|--|
| FCC part15<br>Subpart C | 2020             | Intentional radiators  |
| ANSI C63.10             | 2013             | Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices   |
| KDB 558074D01<br>V05R02 | April 2,<br>2019 | Guidance for compliance measurements on Digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules |




### **4 KEY TO NOTES AND RESULT CODES**

| Code | Meaning  |
|------|--|
| PASS | Test result shows that the requirements of the relevant specification have been met.     |
| FAIL | Test result shows that the requirements of the relevant specification have not been met. |
| N/T  | Test case is not tested.   |



## 5 RESULT SUMMARY

| No. | Test case                                  | Reference     | Verdict                    |
|-----|--|---------------|----------------------------|
| 1   | Transmitter Output Power                   | 15.247(b)(3)  | Pass                       |
| 2   | 6dB Bandwidth                              | 15.247(a)(2)  | Pass                       |
| 3   | Transmitter Power Spectral Density         | 15.247(e)     | Pass                       |
| 4   | Conducted Out of band emission measurement | 15.247(d)     | Pass                       |
| 5   | Band Edge                                  | 15.247(d)     | Pass                       |
| 6   | Spurious Radiated Emissions                | 15.205/15.209 | Pass                       |
| 7   | AC Power line Conducted Emission           | 15.207        | Pass                       |
| 8   | Antenna requirement                        | 15.203        | Pass(refer to section 2.1) |

|  |  |
|--|--|
| This Test Report Is Issued by:<br>Mr. Peng Zhen<br> | Checked by:<br>Mr. Li Bin<br> |
| Tested by:<br>Mr. Liu Ce<br>                        | Issued date:<br><br>20211014   |

## **6 TEST RESULT**

### **6.1 Peak Power Output**

#### **6.2.1 Test limit**

Part15.247 (b) (3)

The maximum permissible conducted output power is 1 Watt.

#### **6.2.2 Test Procedure Used**

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3

#### **6.2.3 Test Settings**

Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

#### **6.2.4 Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



#### **6.2.5 Test result**

The test results are shown in Appendix A.

## 6.2 6dB Bandwidth

### 6.1.1 Test limit

Part15.247 (a) (2)

The minimum permissible 6dB bandwidth is 500 kHz

### 6.1.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2


KDB 558074 D01 v05r02 – Section 8.2

### 6.1.3 Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100 kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

### 6.1.4 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.1.5 Test result

The test results are shown in Appendix A.

## 6.3 Transmitter Power Spectral Density

### 6.3.1 Test limit

Part15.247 (e)

The maximum permissible power spectral density is 8.0dBm in any 3 kHz band.

### 6.3.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD


KDB 558074 D01 v05r02 – Section 8.4

### 6.3.3 Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3 kHz
4. VBW = 10 kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### 6.3.4 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.3.5 Test result

The test results are shown in Appendix A.

## 6.4 Conducted Out of band emission measurement

### 6.4.1 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

### 6.4.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.5

### 6.4.3 Reference level measurement Settings

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  MHz
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 300$  kHz.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

### 6.4.4 Test Settings

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 300$  kHz.
- d) Detector = peak.
- e) Set span to encompass the spectrum to be examined
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level.

### 6.4.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.4.6 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.

## 6.5 Band-edge measurement

### 6.5.1 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

### 6.5.2 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3  
KDB 558074 D01 v05r02 – Section 8.7.2

### 6.5.3 Reference level measurement Settings

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  MHz
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 300$  kHz.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

### 6.5.4 Test Settings

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 300$  kHz.
- d) Detector = peak.
- e) Set span to encompass the spectrum to be examined
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level.

### 6.5.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.5.6 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.

## 6.6 Spurious Radiated Emissions

### 6.6.1 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

### 6.6.2 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209. The spectrum shall be investigated from the lowest radio frequency signal generated in the device

| Frequency [MHz] | Field strength [ $\mu\text{V/m}$ ] | Measured Distance [meters] |
|-----------------|------------------------------------|----------------------------|
| 0.009~0.490     | 2400/F(kHz)                        | 300                        |
| 0.490~1.705     | 24000/F(kHz)                       | 30                         |
| 1.705~30.0      | 30                                 | 30                         |
| 30~88           | 100                                | 3                          |
| 88~216          | 150                                | 3                          |
| 216~960         | 200                                | 3                          |
| Above 960       | 500                                | 3                          |

**Radiated Limits**

Part15.35(b):

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

**Used conversion factor: Limit (dB $\mu\text{V/m}$ ) = 20 log (Limit ( $\mu\text{V/m}$ )/1 $\mu\text{V/m}$ )**

| Frequency [MHz]  | Detector   | Unit (dB $\mu\text{V/m}$ ) |
|--|------------|----------------------------|
| 30~88  | Quasi-peak | 40.0                       |
| 88~216   | Quasi-peak | 43.5                       |
| 216~960  | Quasi-peak | 46.0                       |
| 960~1000   | Quasi-peak | 54.0                       |
| 1000~5th harmonic of the highest frequency<br>or 40GHz, whichever is lower | Average    | 54.0                       |
|  | Peak       | 74.0                       |

**Conversion Radiated limits**

### 6.6.3 Test Procedure Used

ANSI C63.10-2013

#### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and recorded the reading with Maximum Hold Mode.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer complied the following setting:

| Frequency  | RBW       |
|------------|-----------|
| 9-150kHz   | 200-300Hz |
| 0.15-30MHz | 9-10kHz   |

2. Signals below 30MHz are not recorded in the report because they are lower than the limits by more than 20dB.

#### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground in chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and recorded the reading with Maximum Hold Mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detector and recorded the reading with Maximum Hold Mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.



**For the radiated emission test above 1GHz:**

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

**6.6.4 Test Settings**

**Average Field Strength Measurements**

| Frequency | Detector         |
|-----------|------------------|
| <1000MHz  | Quasi-peak       |
| >1000MHz  | Peak and average |

**Peak Field Strength Measurements**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

| Frequency  | RBW        |
|------------|------------|
| 9-150kHz   | 200-300Hz  |
| 0.15-30MHz | 9-10kHz    |
| 30-1000MHz | 100-120kHz |
| >1000MHz   | 1MHz       |


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 6.6.5 Test Setup


#### For Radiated emission below 30MHz



#### For Radiated emission 30MHz to 1GHz



## For Radiated emission above 1GHz



### 6.6.6 Test result

The test results are shown in Appendix B.

## 6.7 AC Power line Conducted Emission

### 6.7.1 Test limit

FCC Part15.207

| Frequency of Emission (MHz) | Conducted Limit (dBuV) |            |
|-----------------------------|------------------------|------------|
|                             | Quasi-peak             | Average    |
| 0.15-0.5                    | 66 to 56 *             | 56 to 46 * |
| 0.5-5                       | 56                     | 46         |
| 5-30                        | 60                     | 50         |

\* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

### 6.7.2 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.


b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/240V/60Hz.

### 6.7.3 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.7.4 Test result

The test results are shown in Appendix B.

## 7 MEASUREMENT UNCERTAINTIES

| Items                                      | Uncertainty    |        |
|--|----------------|--------|
| 6dB Bandwidth                              | 3kHz           |        |
| Peak power output                          | 0.67dB         |        |
| Transmitter Power Spectral Density         | 0.75dB         |        |
| Band edge compliance                       | 1.20dB         |        |
| Conducted Out of band emission measurement | 30MHz~1GHz     | 2.83dB |
|  | 1GHz~12.75GHz  | 2.50dB |
|  | 12.75GHz~25GHz | 2.75dB |
| Spurious Radiated Emissions                | 30MHz~200MHz   | 4.88dB |
|  | 200MHz~1GHz    | 4.87dB |
|  | 1GHz~18GHz     | 4.58dB |
|  | 18GHz~40GHz    | 4.35dB |
| AC Power line Conducted Emission           | 3.92dB         |        |

## 8 TEST EQUIPMENTS

| No. | Name/ Model                                   | Manufacturer    | S/N              | Cal date   | Cal Due date |
|-----|---|-----------------|------------------|------------|--------------|
| 1.  | Spectrum Analyzer / FSV                       | ROHDE & SCHWARZ | 101065           | 2021.06.21 | 2022.06.20   |
| 2.  | Signal Analyzer / N9020A                      | Agilent         | MY48010771       | 2021.05.18 | 2022.05.17   |
| 3.  | Bluetooth Test Set / MT8852B                  | Anritsu         | 1329003          | 2021.06.21 | 2022.06.20   |
| 4.  | Power Divider / 11667A                        | HP              | 19632            | 2021.06.21 | 2022.06.20   |
| 5.  | Power Meter E4416A                            | Agilent         | MY52370013       | 2021.04.13 | 2022.04.12   |
| 6.  | Power Sensor E9323A                           | Agilent         | MY52150008       | 2021.04.13 | 2022.04.12   |
| 7.  | Signal Generator / SMBV100A                   | R&S             | 260910           | 2021.06.21 | 2022.06.20   |
| 8.  | Temperature chamber / SH241                   | ESPEC           | 92013758         | 2021.06.21 | 2022.06.20   |
| 9.  | Fully-Anechoic Chamber / 12.65m×8.03m×7.50m   | FRANKONIA       | ----             | ----       | ----         |
| 10. | Semi-Anechoic/Chamber / 23.18m×16.88m×9.60m   | FRANKONIA       | ---              | ----       | ----         |
| 11. | Turn table Diameter:1m                        | FRANKONIA       | ----             | ----       | ----         |
| 12. | Turn table Diameter:5m                        | FRANKONIA       | ----             | ----       | ----         |
| 13. | Antenna master FAC(MA4.0)                     | MATURO          | ----             | ----       | ----         |
| 14. | Antenna master SAC(MA4.0)                     | MATURO          | ----             | ----       | ----         |
| 15. | Shielding room / 9.080m×5.255m×3.525m         | FRANKONIA       | ----             | ----       | ----         |
| 16. | Double-Ridged Waveguide Horn Antenna / HF 907 | R&S             | 100512           | 2021.06.21 | 2022.06.20   |
| 17. | Double-Ridged Waveguide Horn Antenna / HF 907 | R&S             | 100513           | 2021.06.21 | 2022.06.20   |
| 18. | Ultra log antenna / HL562                     | R&S             | 100016           | 2021.06.21 | 2022.06.20   |
| 19. | Receive antenna /3160-09                      | SCHWARZ-BECK    | 002058-002       | 2021.06.21 | 2022.06.20   |
| 20. | EMI test receiver / ESI 40                    | R&S             | 100015           | 2021.06.21 | 2022.06.20   |
| 21. | EMI test receiver / ESCS30                    | R&S             | 100029           | 2021.06.21 | 2022.06.20   |
| 22. | Receive antenna / HL562                       | R&S             | 100167           | 2021.06.21 | 2022.06.20   |
| 23. | AMN / ENV216                                  | R&S             | 3560.6550.12     | 2021.06.21 | 2022.06.20   |
| 24. | WLAN AP WIA3300-20                            | SKSpruce        | 8152017060700339 | ---        | ---          |
| 25. | Notebook E470c                                | Lenovo          | PF10UZW7         | ---        | ---          |

## APPENDIX A – TEST DATA OF CONDUCTED EMISSION

ANT0

Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

### **Duty Cycle**

| Modulation Type | Frequency (MHz) | Chain  | Duty Cycle | Correction Factor(dB) |
|-----------------|-----------------|--------|------------|-----------------------|
| 802.11b         | 2412            | Chain0 | 99.88%     | 0                     |
| 802.11g         | 2412            | Chain0 | 99.61%     | 0                     |
| 802. 11n HT20   | 2412            | Chain0 | 99.51%     | 0                     |
| 802. 11n HT40   | 2422            | Chain0 | 99.41%     | 0                     |

Note: Correction Factor=10\*log (1/Duty Cycle)

### **Conducted power**

| Mode       | Tones/<br>RU Index | Freq(MHz) | Chain  | Peak power<br>output<br>(dBm) | Average power output<br>(dBm) |
|------------|--------------------|-----------|--------|-------------------------------|-------------------------------|
| 802.11b    | NA                 | 2412MHz   | Chain0 | 18.55                         | 14.84                         |
|            | NA                 | 2437MHz   | Chain0 | 18.74                         | 15.13                         |
|            | NA                 | 2462MHz   | Chain0 | 19.00                         | 15.40                         |
| 802.11g    | NA                 | 2412MHz   | Chain0 | 27.38                         | 17.99                         |
|            | NA                 | 2437MHz   | Chain0 | 26.67                         | 17.33                         |
|            | NA                 | 2462MHz   | Chain0 | 26.46                         | 17.11                         |
| 802.11n20M | NA                 | 2412MHz   | Chain0 | 25.48                         | 16.08                         |
|            | NA                 | 2437MHz   | Chain0 | 26.44                         | 17.08                         |
|            | NA                 | 2462MHz   | Chain0 | 26.32                         | 16.94                         |
| 802.11n40M | NA                 | 2422MHz   | Chain0 | 25.68                         | 15.17                         |
|            | NA                 | 2437MHz   | Chain0 | 24.96                         | 14.45                         |
|            | NA                 | 2452MHz   | Chain0 | 26.87                         | 16.32                         |




## 6dB Bandwidth


Test Mode:802.11b

| Carrier frequency (MHz) | Channel No. | Chain  | 6 dB bandwidth (MHz) |
|-------------------------|-------------|--------|----------------------|
| 2412MHz                 | 1           | Chain0 | 9.85                 |
| 2437MHz                 | 6           | Chain0 | 9.01                 |
| 2462MHz                 | 11          | Chain0 | 9.32                 |


Test Mode:802.11b Chain0



Test Mode:802.11b Chain0




Test Mode:802.11b Chain0




Test Mode:802.11g

| Carrier frequency (MHz) | Channel No. | Chain  | 6 dB bandwidth (MHz) |
|-------------------------|-------------|--------|----------------------|
| 2412MHz                 | 1           | Chain0 | 16.17                |
| 2437MHz                 | 6           | Chain0 | 16.36                |
| 2462MHz                 | 11          | Chain0 | 15.60                |


Test Mode:802.11g Chain0



Test Mode:802.11g Chain0




Test Mode:802.11g Chain0




Test Mode:802. 11n HT20

| Carrier frequency (MHz) | Channel No. | Chain  | 6 dB bandwidth (MHz) |
|-------------------------|-------------|--------|----------------------|
| 2412MHz                 | 1           | Chain0 | 15.75                |
| 2437MHz                 | 6           | Chain0 | 17.56                |
| 2462MHz                 | 11          | Chain0 | 17.34                |


Test Mode:802. 11n HT20 Chain0



Test Mode:802. 11n HT20 Chain0




Test Mode:802. 11n HT20 Chain0




Test Mode:802. 11n HT40

| Carrier frequency (MHz) | Channel No. | Chain  | 6 dB bandwidth (MHz) |
|-------------------------|-------------|--------|----------------------|
| 2422MHz                 | 3           | Chain0 | 33.88                |
| 2437MHz                 | 6           | Chain0 | 29.36                |
| 2452MHz                 | 9           | Chain0 | 33.31                |


Test Mode:802. 11n HT40 Chain0



Test Mode:802. 11n HT40 Chain0



Test Mode:802. 11n HT40 Chain0




## 99% Bandwidth


Test Mode:802.11b

| Carrier frequency (MHz) | Channel No. | Chain  | 99% bandwidth (MHz) |
|-------------------------|-------------|--------|---------------------|
| 2412MHz                 | 1           | Chain0 | 15.266              |
| 2437MHz                 | 6           | Chain0 | 15.295              |
| 2462MHz                 | 11          | Chain0 | 15.249              |


Test Mode:802.11b Chain0



Test Mode:802.11b Chain0




Test Mode:802.11b Chain0




Test Mode:802.11g

| Carrier frequency (MHz) | Channel No. | Chain  | 99% bandwidth (MHz) |
|-------------------------|-------------|--------|---------------------|
| 2412MHz                 | 1           | Chain0 | 16.611              |
| 2437MHz                 | 6           | Chain0 | 16.627              |
| 2462MHz                 | 11          | Chain0 | 16.512              |


Test Mode:802.11g Chain0



Test Mode:802.11g Chain0




Test Mode:802.11g Chain0




Test Mode:802. 11n HT20

| Carrier frequency (MHz) | Channel No. | Chain  | 99% bandwidth (MHz) |
|-------------------------|-------------|--------|---------------------|
| 2412MHz                 | 1           | Chain0 | 17.816              |
| 2437MHz                 | 6           | Chain0 | 17.818              |
| 2462MHz                 | 11          | Chain0 | 17.770              |


Test Mode:802. 11n HT20 Chain0



Test Mode:802. 11n HT20 Chain0



Test Mode:802. 11n HT20 Chain0







Test Mode:802. 11n HT40

| Carrier frequency (MHz) | Channel No. | Chain  | 99% bandwidth (MHz) |
|-------------------------|-------------|--------|---------------------|
| 2422MHz                 | 3           | Chain0 | 36.231              |
| 2437MHz                 | 6           | Chain0 | 36.131              |
| 2452MHz                 | 9           | Chain0 | 36.099              |


Test Mode:802. 11n HT40 Chain0



Test Mode:802. 11n HT40 Chain0



Test Mode:802. 11n HT40 Chain0





## Transmitter Power Spectral Density

Test Mode:802.11b

| Carrier frequency (MHz) | Channel No. | Chain  | Power Density (dBm) |
|-------------------------|-------------|--------|---------------------|
| 2412MHz                 | 1           | Chain0 | -8.649              |
| 2437MHz                 | 6           | Chain0 | -8.537              |
| 2462MHz                 | 11          | Chain0 | -8.427              |


Test Mode:802.11b Chain0



Test Mode:802.11b Chain0




Test Mode:802.11b Chain0




Test Mode:802.11g

| Carrier frequency (MHz) | Channel No. | Chain  | Power Density (dBm) |
|-------------------------|-------------|--------|---------------------|
| 2412MHz                 | 1           | Chain0 | -6.734              |
| 2437MHz                 | 6           | Chain0 | -7.488              |
| 2462MHz                 | 11          | Chain0 | -6.965              |


Test Mode:802.11g Chain0



Test Mode:802.11g Chain0




Test Mode:802.11g Chain0




Test Mode:802. 11n HT40

| Carrier frequency (MHz) | Channel No. | Chain  | Power Density (dBm) |
|-------------------------|-------------|--------|---------------------|
| 2422MHz                 | 3           | Chain0 | -10.745             |
| 2437MHz                 | 6           | Chain0 | -10.423             |
| 2452MHz                 | 9           | Chain0 | -11.475             |


Test Mode:802. 11n HT40 Chain0



Test Mode:802. 11n HT40 Chain0




Test Mode:802. 11n HT40 Chain0




Test Mode:802. 11n HT20

| Carrier frequency (MHz) | Channel No. | Chain  | Power Density (dBm) |
|-------------------------|-------------|--------|---------------------|
| 2412MHz                 | 1           | Chain0 | -7.106              |
| 2437MHz                 | 6           | Chain0 | -7.718              |
| 2462MHz                 | 11          | Chain0 | -7.710              |


Test Mode:802. 11n HT20 Chain0



Test Mode:802. 11n HT20 Chain0




Test Mode:802. 11n HT20 Chain0




## Conducted Out of band emission measurement

Test Mode:802.11b


Test Mode:802.11b Chain0 CH1



Test Mode:802.11b Chain0 CH6





Test Mode:802.11b Chain0 CH11




Test Mode:802.11g

Test Mode:802.11g Chain0 CH1

Test Mode:802.11g Chain0 CH6





Test Mode:802.11g Chain0 CH11




Test Mode:802. 11n HT20

Test Mode:802. 11n HT20 Chain0 CH1

Test Mode:802. 11n HT20 Chain0 CH6



Test Mode:802. 11n HT20 Chain0 CH11








Test Mode:802. 11n HT40

Test Mode:802. 11n HT40 Chain0 CH3

Test Mode:802. 11n HT40 Chain0 CH6



Test Mode:802. 11n HT40 Chain0 CH9







## Band edge measurement

Test Mode:802.11b

Test Mode:802.11b Chain0 CH1




Test Mode:802.11b Chain0 CH11




Test Mode:802.11g

Test Mode:802.11g Chain0 CH1




Test Mode:802.11g Chain0 CH11




Test Mode:802. 11n HT20

Test Mode:802. 11n HT20 Chain0 CH1




Test Mode:802. 11n HT20 Chain0 CH11




Test Mode:802. 11n HT40

Test Mode:802. 11n HT40 Chain0 CH3



Test Mode:802. 11n HT40 Chain0 CH9



ANT 1

Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

### Duty Cycle

| Modulation Type | Frequency (MHz) | Chain  | Duty Cycle | Correction Factor(dB) |
|-----------------|-----------------|--------|------------|-----------------------|
| 802.11b         | 2412            | Chain1 | 99.90%     | 0                     |
| 802.11g         | 2412            | Chain1 | 99.59%     | 0                     |
| 802.11n HT20    | 2412            | Chain1 | 99.59%     | 0                     |
| 802.11n HT40    | 2422            | Chain1 | 99.37%     | 0                     |

Note: Correction Factor=10\*log (1/Duty Cycle)

### Conducted power


| Mode       | Tones/<br>RU Index | Freq(MHz) | Chain  | Peak power<br>output<br>(dBm) | Average power output<br>(dBm) |
|------------|--------------------|-----------|--------|-------------------------------|-------------------------------|
| 802.11b    | NA                 | 2412MHz   | Chain1 | 19.37                         | 15.77                         |
|            | NA                 | 2437MHz   | Chain1 | 18.85                         | 15.28                         |
|            | NA                 | 2462MHz   | Chain1 | 18.35                         | 14.76                         |
| 802.11g    | NA                 | 2412MHz   | Chain1 | 25.25                         | 15.88                         |
|            | NA                 | 2437MHz   | Chain1 | 24.68                         | 15.32                         |
|            | NA                 | 2462MHz   | Chain1 | 24.19                         | 14.84                         |
| 802.11n20M | NA                 | 2412MHz   | Chain1 | 27.43                         | 18.09                         |
|            | NA                 | 2437MHz   | Chain1 | 26.83                         | 17.47                         |
|            | NA                 | 2462MHz   | Chain1 | 26.24                         | 16.93                         |
| 802.11n40M | NA                 | 2422MHz   | Chain1 | 27.72                         | 17.20                         |
|            | NA                 | 2437MHz   | Chain1 | 27.21                         | 16.70                         |
|            | NA                 | 2452MHz   | Chain1 | 26.91                         | 16.36                         |

## 6dB Bandwidth


Test Mode:802.11b

| Carrier frequency (MHz) | Channel No. | Chain  | 6 dB bandwidth (MHz) |
|-------------------------|-------------|--------|----------------------|
| 2412MHz                 | 1           | Chain1 | 10.11                |
| 2437MHz                 | 6           | Chain1 | 9.57                 |
| 2462MHz                 | 11          | Chain1 | 10.05                |

Test Mode:802.11b Chain1



Test Mode:802.11b Chain1



Test Mode:802.11b Chain1

