

---

## MPE REPORT

---

Report No.: SRTC2021-9004(F)-21070803(I)

Product Name: Wi-Fi Module

Product Model: MW506

Applicant: Hisense Communication Co., Ltd.

Manufacturer: Hisense Communication Co., Ltd.

Specification: FCC Part §2.1091, §2.1093, §1.1307(b), §1.1310 (2019)

FCC ID: SARMW506

The State Radio\_monitoring\_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

## CONTENTS

<b>1 GENERAL INFORMATION</b> .....	2
1.1 NOTES OF THE TEST REPORT .....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY .....	2
1.3 APPLICANT’S DETAILS .....	2
1.4 MANUFACTURER’S DETAILS .....	2
<b>2 DESCRIPTION OF THE DEVICE UNDER TEST</b> .....	3
2.1 FINAL EQUIPMENT BUILD STATUS .....	3
<b>3 REFERENCE SPECIFICATION</b> .....	4
<b>4 RESULT SUMMARY</b> .....	5
<b>5 TEST RESULTS</b> .....	6
5.1 AVERAGE POWER OUTPUT TEST RESULT .....	6
5.2 CALCULATION RESULT .....	7

## 1 GENERAL INFORMATION

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC). The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### 1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liuji@src.org.cn

### 1.3 Applicant's details

Company:	Qingdao Hisense Communication Co., Ltd.
Address:	No.218, Qianwangang Road, Economic and Technological Development Zone, Qingdao, Shandong Province,China
City:	Qingdao
Country or Region:	China
Contacted person:	Wang Haining
Tel:	0532-55756937
Email:	wanghaining@hisense.com

### 1.4 Manufacturer's details

Company:	Qingdao Hisense Communication Co., Ltd.
Address:	No.218, Qianwangang Road, Economic and Technological Development Zone, Qingdao, Shandong Province,China
City:	Qingdao
Country or Region:	China
Contacted person:	Wang Haining
Tel:	0532-55756937
Email:	wanghaining@hisense.com

## 2 DESCRIPTION OF THE DEVICE UNDER TEST

### 2.1 Final Equipment Build Status




Frequency Bands	WIFI2.4GHz: 2.412GHz~2.462GHz WIFI5GHz UNII-1: 5.180GHz-5.240GHz WIFI5GHz UNII-2A: 5.260GHz-5.320GHz WIFI5GHz UNII-2C: 5.500GHz-5.720GHz WIFI5GHz UNII-3: 5.745GHz-5.825GHz
Mode	WIFI2.4GHz: 802.11b/g/n HT20/n HT40 WIFI5GHz: 802.11a/n HT20/n HT40 802.11ac VHT20/ac VHT40/ac VHT80
Power Supply	DC Adapter
Hardware Version	V1.00
Software Version	---
IMEI or Sample	#1

### **3 REFERENCE SPECIFICATION**

Specification	Version	Title
2.1091	2019	Radio frequency radiation exposure evaluation: mobile devices.
2.1093	2019	Radio frequency radiation exposure evaluation: portable devices.
1.1307(b)	2019	Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
1.1310	2019	Radio frequency radiation exposure limits.
KDB447498	October 23, 2015	RF exposure procedures and equipment authorization policies for mobile and portable devices

**4 RESULT SUMMARY**

No.	Test case	FCC reference
1	MPE Calculation	FCC Part §2.1091, FCC Part §2.1093, FCC Part §1.1307(b) FCC Part §1.1310 KDB 447498

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. Du Wei 	Issued date:  20210720

## 5 TEST RESULTS

### 5.1 Average Power Output Test Result

Mode	Maximum Average power(dBm)
WiFi2.4GHz	21.00
WiFi5.2GHz	19.50
WiFi5.3GHz	18.00
WiFi5.6GHz	20.00
WiFi5.8GHz	18.00

5.2 Calculation result

FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz \*Plane-wave equivalent power density



Calculation procedure:

According to §2.1091, §2.1093, §1.1307(b) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Band	Freq. (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Power Density / Limit
WLAN2.4GHz Band	2442	3.72	21.00	24.72	296.48	0.059	1.000	0.059
WLAN5.2GHz Band	5220	4.07	19.50	23.57	227.51	0.045	1.000	0.045
WLAN5.3GHz Band	5260	4.07	18.00	22.07	161.06	0.032	1.000	0.032
WLAN5.6GHz Band	5700	4.07	20.00	24.07	255.27	0.051	1.000	0.051
WLAN5.8GHz Band	5785	4.07	18.00	22.07	161.06	0.032	1.000	0.032

Note:

For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.

---End of Test Report---