



Well Green Technology Co., Ltd


No. 20, Alley51 ,Lane 118,ShuangLian Sec.2,Mintzu Rd.,
PingJen City, TaoYuan Hsien, Taiwan, R.O.C
TEL: (03)420-6428 FAX: (03) 420-6418

X51


Antenna Test Report

RD Manager	Supervisor	RD engineer	Sales engineer
David	Johnson	Jason	Jerry

一、成品圖




二、零件圖




[illegible]

三、Antenna Testing Conditions:

1. Testing set up




2. Mechanical dimensions



四、電氣特性 (Antenna Electricity Characteristics)

1. Return Loss




Antenna	Center freq. @MHz	BW @MHz	Return Loss		
			824MHz	896MHz	
X51-R	860		-8.48	-14.26	

Antenna	Center freq. @MHz	BW @MHz	Return Loss		
			1710MHz	1880MHz	1990MHz
X51-R	1860		-7.42	-12.59	-6.53

精乘科技股份有限公司 Well Green Technology CO., Ltd	P/N : UWX51WIPI02B	Frequency Band : 824~960MHz 1710-2170MHz	Date : 23 MAR.,2006
---	--------------------	---	---------------------

2. VSWR




Antenna	Center freq. @MHz	BW @MHz	VSWR	
			824MHz	896MHz
X51-R	860		2.23	1.50

Antenna	Center freq. @MHz	BW @MHz	VSWR		
			1710MHz	1880MHz	1990MHz
X51-R	1860		2.48	1.60	2.78

精乘科技股份有限公司 Well Green Technology CO., Ltd	P/N : UWX51WIPI02B	Frequency Band : 824~960MHz 1710-2170MHz	Date : 23 MAR.,2006
---	--------------------	---	---------------------

3. Smith Chart



精乘科技股份有限公司
Well Green Technology
CO., Ltd


P/N : UWX51WIPI02B

Frequency Band : 824~960MHz
1710-2170MHz

Date : 23 MAR.,2006




4. Radiation Pattern of XY Plane(Azimuth)-(Open)



Center Frequency	850 MHz
Vertical peak Gain (dBi)	-3.80
Vertical Average Gain (dBi)	-9.37
Vertical Min	-24.06
Horizontal peak Gain (dBi)	-1.70
Horizontal Average Gain (dBi)	-8.63
Horizontal Min	-29.53
Hor _i +Vert peak Gain (dBi)	-0.54
Hor _i +Vert Average Gain (dBi)	-5.97
Hor _i +Vert Min	-16.87




5. Radiation Pattern of XY Plane(Azimuth)-(Open)



Center Frequency	900 MHz
Vertical peak Gain (dBi)	-4.42
Vertical Average Gain (dBi)	-10.16
Vertical Min	-20.58
Horizontal peak Gain (dBi)	-2.45
Horizontal Average Gain (dBi)	-9.08
Horizontal Min	-24.45
Hori+Vert peak Gain (dBi)	-1.83
Hori+Vert Average Gain (dBi)	-6.58
Hori+Vert Min	-17.38




6. Radiation Pattern of XY Plane(Azimuth)-(Open)



Center Frequency	1700 MHz
Vertical peak Gain (dBi)	-1.67
Vertical Average Gain (dBi)	-6.59
Vertical Min	-21.40
Horizontal peak Gain (dBi)	0.92
Horizontal Average Gain (dBi)	-6.42
Horizontal Min	-28.96
Hor _i +Vert peak Gain (dBi)	1.09
Hor _i +Vert Average Gain (dBi)	-3.49
Hor _i +Vert Min	-11.23



7. Radiation Pattern of XY Plane(Azimuth)-(Open)




Center Frequency	1800 MHz
Vertical peak Gain (dBi)	-0.45
Vertical Average Gain (dBi)	-4.65
Vertical Min	-15.99
Horizontal peak Gain (dBi)	0.96
Horizontal Average Gain (dBi)	-3.18
Horizontal Min	-28.68
Hor _i +Vert peak Gain (dBi)	1.66
Hor _i +Vert Average Gain (dBi)	-0.84
Hor _i +Vert Min	-6.76



Well Green Technology Co., Ltd

No. 20, Alley51 ,Lane 118,ShuangLian Sec.2,Mintzu Rd.,
PingJen City, TaoYuan Hsien, Taiwan, R.O.C
TEL: (03)420-6428 FAX: (03) 420-6418


8. Radiation Pattern of XY Plane(Azimuth)-(Open)



Center Frequency	1900 MHz
Vertical peak Gain (dBi)	-0.25
Vertical Average Gain (dBi)	-5.18
Vertical Min	-19.95
Horizontal peak Gain (dBi)	1.75
Horizontal Average Gain (dBi)	-3.65
Horizontal Min	-22.34
Hor _i +Vert peak Gain (dBi)	2.31
Hor _i +Vert Average Gain (dBi)	-1.34
Hor _i +Vert Min	-11.31



9. Radiation Pattern of XY Plane(Azimuth)-(Open)



Center Frequency	2170 MHz
Vertical peak Gain (dBi)	-4.91
Vertical Average Gain (dBi)	-11.45
Vertical Min	-27.18
Horizontal peak Gain (dBi)	-6.27
Horizontal Average Gain (dBi)	-10.30
Horizontal Min	-21.57
Hori+Vert peak Gain (dBi)	-4.72
Hori+Vert Average Gain (dBi)	-7.83
Hori+Vert Min	-15.05

五、SPECIFICATIONS:

● Electrical Properties

Frequency Range	: 824~960MHz
Impedance	: 50Ohms nominal
VSWR	: ≤ 2.0
Peak Gain	: -5.0dBi $\leq$ peak gain $\leq$ 3dBi
Standard Connector	: I-PEX Connector

Frequency Range	: 1710~2170MHz
Impedance	: 50Ohms nominal
VSWR	: ≤ 2.0
Peak Gain	: -5.0dBi $\leq$ peak gain $\leq$ 3dBi
Standard Connector	: I-PEX Connector