

ph: 949.221.9200 fax: 949.221.9218

Unit Label

November 6, 2009

Subject:

Unit Label

LampLinc[™] - INSTEON Plug-In Dimmer (Dual Band) 2457D2

FCC ID: SBP2457D2A IC: 5202A-2457D2A

smart abs LampLinc™ Dimmer Dual-Band #2457D2

Conforms to ANSI/UL STD 508-2005
Certified to CSA STD C22.2 #14-2005
Rated: 120VAC, 60Hz, 300W/300VA Max
Indoor use only. Utilisation d'intérieur seulement
FCC ID: SBP2457D2A IC: 5202A-2457D2A This
device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this
device must accept any interference and (2) this
device must accept any interference received, including
interference that may cause undesired operation.
Lampl.inc, the SmartLabs and INSTEON Compatible

patible Made in China U.S. Patent No. 7,345,998

Specs:

Width - 1.5 inches (38.1mm)

Height - 1.1 inches (27.94mm)

Surface Material: gloss white polyester face stock with a smooth,

absorbent ink-receptive top coating

Surface Material Thickness - .050 mm ± 10% ISO534 Base Material – Super-Calendared White Glassine Paper

Base Thickness - 0.070mm ± 10% ISO534 Adhesive Base - Acrylic .025mm Thickness

logos are trademarks of SmartLabs, Inc.

24 hour 90° Peel (st,st)-FTM 2: 7.5

Service Temperature Range: -40°C~+80°C (when applied to ABS plastic)

UL Recognized Listing # MH20558



