

August 18, 2014

Subject: Unit Label
 INSTEON® Micro Dimmer #2442-2
 INSTEON® Micro On/Off #2443-2
 INSTEON® Micro Open/Close #2444-2
 FCC ID: SBPMM01
 IC: 5202A-MM01

| | | |
|--|--|--|
| <p style="text-align: center; font-weight: bold; font-size: 1.2em;">I N S T E O N[®]</p> <p style="text-align: center; font-weight: bold;">Micro Dimmer</p> <p style="text-align: center;">Model: 2442-222</p> <hr/> <p>Rated: 100-240VAC, 50/60Hz, 200W Max Conforms to ANSI/UL STD 1472 Cert. to CAN/CSA Std. C22.2 #184.1</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-left: 5px;"> <p style="font-size: 0.8em;">Intertek 4006552</p> </div> </div> <p style="font-size: 0.8em;">FCC ID: SBPMM01 IC: 5202A-MM01 For control of permanently installed Incandescent, low-voltage, neon, cold cathode, and general inductive fixtures only.</p> <p style="font-size: 0.8em;">This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.</p> <hr/> <p style="font-weight: bold; font-size: 0.9em;">INSTEON.COM</p> <p style="font-size: 0.8em;">Protected under US and Foreign patents Made in China</p> | <p style="text-align: center; font-weight: bold; font-size: 1.2em;">I N S T E O N[®]</p> <p style="text-align: center; font-weight: bold;">Micro On/Off</p> <p style="text-align: center;">2443-222</p> <hr/> <p>Conforms to ANSI/UL STD 244A Certified to CSA/STD C22.2 #177 Rated: 100-240VAC, 50/60Hz, 15A Max Approved for resistive loads</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-left: 5px;"> <p style="font-size: 0.8em;">Intertek 4006552</p> </div> </div> <p style="font-weight: bold; font-size: 0.9em;">FCC ID: SBPMM01 IC: 5202A-MM01 Model: 2443-2</p> <hr/> <p style="font-size: 0.8em;">www.insteon.com</p> <p style="font-size: 0.8em;">Protected by US and Foreign patents Made in China</p> | <p style="text-align: center; font-weight: bold; font-size: 1.2em;">I N S T E O N[®]</p> <p style="text-align: center; font-weight: bold;">Micro Open/Close</p> <p style="text-align: center;">Model: 2444-222</p> <hr/> <p>Rated: 100-240VAC, 50/60Hz, 8A Max Conforms to ANSI/UL STD 244A Cert. to CAN/CSA Std. C22.2 #177 Approved for General Purpose Loads (Resistive, Tungsten, Ballast, and transformers)</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-left: 5px;"> <p style="font-size: 0.8em;">Intertek 4006552</p> </div> </div> <p style="font-weight: bold; font-size: 0.9em;">FCC ID: SBPMM01 IC: 5202A-MM01</p> <hr/> <p style="font-weight: bold; font-size: 0.9em;">INSTEON.COM</p> <p style="font-size: 0.8em;">Protected under U.S. and foreign patents Made in China</p> |
|--|--|--|

Specs: Width – 1.25 inches (31.8mm)
 Height – 1.5 inches (38.1mm)
 Surface Material: gloss white polyester face stock with a smooth, absorbent ink-receptive top coating
 Surface Material Thickness - .050 mm ± 10% ISO534
 Base Material – Super-Calendared White Glassine Paper
 Base Thickness - 0.070mm ± 10% ISO534
 Adhesive Base – Acrylic .025mm Thickness
 24 hour 90° Peel (st,st)-FTM 2: 7.5
 Service Temperature Range: -40°C~+80°C (when applied to polycarbonate)
 UL Recognized Listing # MH47798