

## Operational Description of the equipment

Utilizing 56-bit DES and 168-bit 3DES encryption, header authentication, and IKE key exchange access control, Multimedia Security Gateway's full IPSec Virtual Private Network (VPN) capability provides complete data privacy.

Functions supported are IP sharing, PPPoE, DHCP, DDNS, Firewall, VPN, content filtering, four USB 2.0 ports, a four-port switch hub, printer server, FTP server, web cam server, motion detection, a 802.11g access point, USB Storage, UPnP and many more.

Equipped with the most advanced technology available today, this router is the only TOTAL SOLUTION for your networking needs.

<b>PRODUCT</b>	Wireless 1 WAN 4 LAN Multimedia Security VPN Router
<b>MODEL NO.</b>	FL 1911G, Matrix 21, FL 1920
<b>POWER SUPPLY</b>	DC 5V, 3A from an external power adapter: Brand: SUNNY Model No.: SYS1298-1505-W2 I/P: 100-240V~1.0A MAX, 30-40VA, 50-60Hz O/P: +5V, 3.0A Unshielded power cable (1.5m)
<b>CABLE</b>	N/A
<b>I/O PORT</b>	RJ45, USB
<b>FREQUENCY BAND</b>	2400 ~ 2483.5MHz
<b>CARRIER FREQUENCY</b>	CH1: 2412MHz ~ CH11: 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>CHANNEL SPACING</b>	5MHz
<b>RATED RF OUTPUT POWER</b>	17dBm MAX. (EIRP), 14dBm +/- 1dBm (before antenna)
<b>I.F. &amp; L.O.</b>	I.F.: 374MHz, L.O.:2038~2088MHz
<b>MODULATION TYPE</b>	IEEE 802.11g: BPSK/QPSK/OFDM(64QAM, 16QAM) IEEE 802.11b: DBPSK/DQPSK/CCK
<b>BIT RATE OF TRANSMISSION</b>	54Mbps
<b>ANTENNA TYPE</b>	Single external dipole antenna
<b>ANTENNA GAIN</b>	3dBi

**NOTE :**

The EUT has three model numbers as above on market. They are identical in all aspects except for the following:

The model no.: FL 1911G is exactly the same as the model no.: FL 1920 except for software and addition stand was provided for the model no.: Matrix 21.

The model no.: FL 1911G was chosen as the representative for testing.

For more detailed information, please refer to the EUT's specification or user's manual provided by manufacturer.