



MPE/RF EXPOSURE EVALUATION REPORT

FCC CFR 47 Part 1.1310

TUVR116_FCC_MPE Rev B

Company: Sonos Inc.

Model Name: S23

MPE/RF EXPOSURE EVALUATION REPORT

Company: Sonos Inc.

Model Name: S23

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: TUVR116_FCC_MPE Rev B

This report supersedes: NONE

Applicant: Sonos Inc
614 Chapala St.
Santa Barbara, California 93101
USA

Issue Date: 24th June 2019

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1.1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

The calculations in the table below use the highest conducted power value together with the highest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
2400.0 - 2483.5 (BLE)	3.3	2.14	-6.62	0.22	0.000093	1.00	0.192
2400.0 - 2483.5 (WiFi 5.5 Mbit/s)	3.6	2.29	23.87	243.78	0.111	1.00	6.666
5725.0 - 5850.0	2.9	1.95	23.99	250.61	0.097	1.00	6.236

The following assessments are worst case exposure conditions where the Sonos Inc S23 contains 2 radio modules:- 2.4GHz/5GHz 802.11 and 2.4GHz BLE with both radios transmitting simultaneously;-

The following table is an assessment of worst case exposure conditions for the two radios in question

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance for Summation (cm)	Power Density Limit (mW/cm ²) E_{ref}	Power Density (mW/cm ²) @20cm	Summation E_i/E_{ref} @ 20 cm
2400.0 - 2483.5 (BLE)	3.3	2.14	-6.62	0.22				
2400.0 - 2483.5 (WiFi 5.5 Mbit/s)	3.6	2.29	23.87	243.78				
EIRP TOTAL (mW/EIRP) :				244.00	20 cm distance Total Evaluation:			0.112 mW/cm²

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Worst Case Simultaneous Operation

Assessment for simultaneous operation: 2.4GHz, BLE						
Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)
2400.0 - 2483.5 (BLE)	3.3	2.14	-6.62	0.22	0.000093	1.00
2400.0 - 2483.5 (WiFi 5.5 Mbit/s)	3.6	2.29	23.87	243.78	0.111	1.00
Evaluation for compliance of simultaneous transmission is determined by summation of the ratios of Pd Calc/Pd Limit < 1.						
Ratio = S BLEi + S Wi-Fi = 0.00009/1 + 0.111/1 = 0.112						

Specification

Maximum Permissible Exposure Limits

FCC §1.1310 Table 1
 300 to 1500MHz = f/1500 (mW/cm²)
 1500 to 100,000MHz = 1 mW/cm²



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com