



## **MPE/RF EXPOSURE EVALUATION REPORT**

**FCC CFR 47 Part 1.1310**

**SONO01 FCC MPE Rev A**

**Company: Sonos Inc.**

**Model Name: S26**

## MPE/RF EXPOSURE EVALUATION REPORT

FROM



**Company:** Sonos Inc.

**Model Name:** S26

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: SONO01\_FCC\_MPE

This report supersedes: NONE

Applicant: Sonos, Inc  
614 Chapala St.  
Santa Barbara, California 93101  
USA

Issue Date: 16th April 2020

### **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**

## 1. MAXIMUM PERMISSIBLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4*\pi*d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain =  $10^{(G \text{ (dBi)}/10)}$

The calculations in the table below use the highest conducted power values together with the highest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm <sup>2</sup> ) @ Safe Distance
2400.0 - 2483.5 (BLE)	6.10	4.07	-2.49	0.56	0.0005	1.00	1.00	1.00
2400.0 - 2483.5 (WiFi)	9.34	8.59	26.39	435.91	0.75	1.00	18.00	1.00
5725.0 - 5850.0	5.90	3.89	23.84	242.32	0.33	1.00	9.00	1.00

The Sonos Inc S26 contains 2 radio modules;- 2.4GHz/5GHz 802.11 and 2.4GHz BLE. The following assessment is for worst case exposure conditions with both radios transmitting simultaneously;-

Assessment for simultaneous operation:

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density E <sub>i</sub> (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit E <sub>ref</sub> (mW/cm <sup>2</sup> )	E <sub>i</sub> /E <sub>ref</sub>
2400.0 - 2483.5 (BLE)	6.10	4.07	-2.49	0.56	0.0005	1.00	0.0005
2400.0 - 2483.5 (WiFi)	9.34	8.59	26.39	435.91	0.75	1.00	0.75
<b>Total Evaluation</b>							<b>0.75</b>

The **Total Evaluation** was calculated using the formula:

$$\sum_{i=1}^n E_i / E_{ref} \leq 1$$

Where

E<sub>i</sub>: calculated power density for transmitter

E<sub>ref</sub>: power density limit

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)