



TEST REPORT

Report Number. : 14516849-E5V4

Applicant : SONOS INC.
614 CHAPALA ST.
SANTA BARBARA, CA, 93101, U.S.A.

Model : S44

Brand : SONOS

FCC ID : SBVRM044

IC : 5373A-RM044

EUT Description : 802.11 a/b/g/n/ac/ax 2x2 Client Device with BT and BLE

Test Standard(s) : FCC 47 CFR PART 15 SUBPART E
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5 + A1 + A2

Date Of Issue:
2023-05-25

Prepared by:
UL VERIFICATION SERVICES
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888



REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	2023-03-31	Initial Issue	
V2	2023-05-05	Updated Section 3, 6.6, 9.5.16 and 10.2	Kiya Kedida
V3	2023-05-17	Updated Section 6.6	Kiya Kedida
V4	2023-05-25	Section 6.6 updated the setup diagram and the description of test setup cable #3	Glenn Escano

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS.....	6
2. TEST RESULT SUMMARY.....	8
3. TEST METHODOLOGY	9
4. FACILITIES AND ACCREDITATION.....	9
5. DECISION RULES AND MEASUREMENT UNCERTAINTY.....	10
5.1. <i>METROLOGICAL TRACEABILITY</i>	10
5.2. <i>DECISION RULES</i>	10
5.3. <i>MEASUREMENT UNCERTAINTY.....</i>	10
5.4. <i>SAMPLE CALCULATION.....</i>	11
6. EQUIPMENT UNDER TEST	12
6.1. <i>EUT DESCRIPTION.....</i>	12
6.2. <i>MAXIMUM OUTPUT POWER.....</i>	12
6.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	13
6.4. <i>SOFTWARE AND FIRMWARE</i>	13
6.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	13
6.6. <i>DESCRIPTION OF TEST SETUP.....</i>	14
7. MEASUREMENT METHOD	16
8. TEST AND MEASUREMENT EQUIPMENT	17
9. ANTENNA PORT TEST RESULTS	18
9.1. <i>ON TIME AND DUTY CYCLE</i>	18
9.2. <i>26 dB BANDWIDTH</i>	20
9.2.1. 802.11a MODE IN THE 5.2 GHz BAND	21
9.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND	23
9.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND	25
9.2.4. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND	26
9.2.5. 802.11a MODE IN THE 5.3 GHz BAND	27
9.2.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND	29
9.2.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND	31
9.2.8. 802.11ac VHT80 MODE IN THE 5.3 GHz BAND	32
9.2.9. 802.11a MODE IN THE 5.6 GHz BAND	33
9.2.10. 802.11n HT20 MODE IN THE 5.6 GHz BAND	35

9.2.11.	802.11n HT40 MODE IN THE 5.6 GHz BAND	37
9.2.12.	802.11ac VHT80 MODE IN THE 5.6 GHz BAND.....	39
9.2.13.	802.11a MODE IN THE 5.8 GHz BAND.....	40
9.2.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	42
9.2.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	44
9.2.16.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND.....	45
9.3.	99% BANDWIDTH.....	46
9.3.1.	802.11a MODE IN THE 5.2 GHz BAND.....	47
9.3.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	49
9.3.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	51
9.3.4.	802.11ac VHT80 MODE IN THE 5.2 GHz BAND.....	52
9.3.5.	802.11a MODE IN THE 5.3 GHz BAND.....	53
9.3.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	55
9.3.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	57
9.3.8.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND.....	58
9.3.9.	802.11a MODE IN THE 5.6 GHz BAND.....	59
9.3.10.	802.11n HT20 MODE IN THE 5.6 GHz BAND	61
9.3.11.	802.11n HT40 MODE IN THE 5.6 GHz BAND	63
9.3.12.	802.11ac VHT80 MODE IN THE 5.6 GHz BAND.....	65
9.3.13.	802.11a MODE IN THE 5.8 GHz BAND.....	66
9.3.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	68
9.3.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	70
9.3.16.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND.....	71
9.4.	6 dB BANDWIDTH	72
9.4.1.	802.11a MODE IN THE 5.8 GHz BAND.....	73
9.4.2.	802.11n HT20 MODE IN THE 5.8 GHz BAND	75
9.4.3.	802.11n HT40 MODE IN THE 5.8 GHz BAND	77
9.4.4.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND.....	78
9.5.	OUTPUT POWER AND PSD	79
9.5.1.	802.11a MODE IN THE 5.2 GHz BAND.....	83
9.5.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	87
9.5.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	91
9.5.4.	802.11ac VHT80 MODE IN THE 5.2 GHz BAND.....	95
9.5.5.	802.11a MODE IN THE 5.3 GHz BAND.....	99
9.5.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	101
9.5.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	103
9.5.8.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND.....	105
9.5.9.	802.11a MODE IN THE 5.6 GHz BAND.....	107
9.5.10.	802.11n HT20 MODE IN THE 5.6 GHz BAND	109
9.5.11.	802.11n HT40 MODE IN THE 5.6 GHz BAND	111
9.5.12.	802.11ac VHT80 MODE IN THE 5.6 GHz BAND.....	113
9.5.13.	802.11a MODE IN THE 5.8 GHz BAND.....	115
9.5.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	117
9.5.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	119
9.5.16.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND.....	121
10.	RADIATED TEST RESULTS	123
10.1.	TRANSMITTER ABOVE 1 GHz.....	125
10.1.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.2 GHz BAND.....	125
10.1.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.2 GHz BAND.....	133

10.1.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.2 GHz BAND	141
10.1.4.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.2 GHz BAND	147
10.1.5.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.3 GHz BAND	151
10.1.6.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.3 GHz BAND	159
10.1.7.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.3 GHz BAND	167
10.1.8.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.3 GHz BAND	173
10.1.9.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.6 GHz BAND	177
10.1.10.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.6 GHz BAND	187
10.1.11.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.6 GHz BAND	197
10.1.12.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.6 GHz BAND	207
10.1.13.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.8 GHz BAND	215
10.1.14.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.8 GHz BAND	225
10.1.15.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.8 GHz BAND	235
10.1.16.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.8 GHz BAND	243
10.2.	<i>WORST CASE BELOW 30MHz</i>	249
10.3.	<i>WORST CASE BELOW 1 GHz</i>	251
10.4.	<i>WORST CASE 18-26 GHz</i>	253
10.5.	<i>WORST CASE 26-40 GHz</i>	255
11.	AC POWER LINE CONDUCTED EMISSIONS	257
12.	SETUP PHOTOS	260

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Sonos Inc.
614 Chapala St.
Santa Barbara, CA, 93101, U.S.A.

EUT DESCRIPTION: 802.11 a/b/g/n/ac/ax 2x2 Client Device with BT and BLE

MODEL: S44

BRAND: Sonos

SERIAL NUMBER: Radiated Sample: A100 2301WC C4-38-75-00-0F-40-9 and
A100 2301WC C4-38-75-00-0E-E0-F
Conducted Sample: A100 2301WC C4-38-75-00-0E-7C-0

SAMPLE RECEIPT DATE: 2023-02-20

DATE TESTED: 2023-02-24 To 2023-03-20

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR Part 15 Subpart E	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 5 + A1 + A2	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Dan Corona
Operations Leader
Consumer Technology Division
UL Verification Services Inc.

Prepared By:



Glenn Escano
Senior Test Engineer
Consumer Technology Division
UL Verification Services Inc.

1st Reviewed By:



Vien Tran
Senior Laboratory Engineer
Consumer Technology Division
UL Verification Services Inc.

2nd Reviewed By:



Kiya Kedida
Senior Project Engineer
Consumer Technology Division
UL Verification Services Inc.

2. TEST RESULT SUMMARY

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for the validity of results after the integration of the data provided by the customer.

FCC Clause	ISED Clause	Requirement	Result	Comment
See Comment		Duty Cycle	Reporting purposes only	Per ANSI C63.10, Section 12.2.
See Comment	RSS-GEN 6.7	26dB BW/99% OBW	Reporting purposes only	Per ANSI C63.10 Sections 6.9.2 and 6.9.3
15.407 (e)	RSS-247 6.2.4.1	6 dB BW	Compliant	None.
15.407 (a) (1-4), (h) (1)	RSS-247 6.2	Output Power	Compliant	None.
15.407 (a) (1-3, 5)	RSS-247 6.2	PSD	Compliant	None.
15.209, 15.205, 15.407 (b)	RSS-GEN 8.9, 8.10, RSS-247 6.2	Radiated Emissions	Compliant	None.
15.207	RSS-Gen 8.8	AC Mains Conducted Emissions	Compliant	None.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with:

- FCC 47 CFR Part 2
- FCC 47 CFR Part 15,
- FCC KDB 662911 D01 v02r01,
- FCC KDB 905462 D02 v02/D03 v01r02/D06 v02
- FCC KDB 789033 D02 v02r01,
- KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013,
- RSS-GEN Issue 5 + A1 + A2
- RSS-247 Issue 2

4. FACILITIES AND ACCREDITATION

UL Verification Services Inc. is accredited by A2LA, Certificate Number 0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input checked="" type="checkbox"/>	Building 1: 47173 Benicia Street Fremont, CA 94538, U.S.A	US0104	2324A	550739
<input type="checkbox"/>	Building 2: 47266 Benicia Street Fremont, CA 94538, U.S.A	US0104	22541	550739
<input checked="" type="checkbox"/>	Building 4: 47658 Kato Rd Fremont, CA 94538, U.S.A	US0104	2324B	550739

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Radio Frequency (Spectrum Analyzer)	141.16 Hz
Occupied Bandwidth	1.22%
Power Spectral Density	2.47 dB
RF Power Measurement Direct Method Using Power Meter	1.3 dB (PK) / 0.45 dB (AV)
Unwanted Emissions, Conducted	1.94 dB
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.78 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.40 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.87 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	6.01 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.73 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.51 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.29 dB
Time Domain Measurements	3.39%
Temperature	0.57°C
Humidity	3.39%
DC Supply Voltages	0.57%

Uncertainty figures are valid to a confidence level of 95%.

5.4. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

$$36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$$

MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided:

Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss.

$$36.5 \text{ dBuV} + 0 \text{ dB} + 10.1 \text{ dB} + 0 \text{ dB} = 46.6 \text{ dBuV}$$

6. EQUIPMENT UNDER TEST

6.1. EUT DESCRIPTION

The EUT is an 802.11 a/b/g/n/ac/ax 2x2 Client Device with BT and BLE.

This report covers non-ax 5GHz Wifi radio.

6.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

(FCC)

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.2 GHz band, 2TX			
5180-5240	802.11a	21.85	153.11
5180-5240	802.11n HT20	21.81	151.71
5190-5230	802.11n HT40	18.78	75.51
5210	802.11ac VHT80	16.24	42.07
5.3 GHz band, 2TX			
5260-5320	802.11a	21.71	148.25
5260-5320	802.11n HT20	21.57	143.55
5270-5310	802.11n HT40	21.07	127.94
5290	802.11ac VHT80	17.23	52.84
5.6 GHz band, 2TX			
5500 - 5700	802.11a	21.72	148.59
5500 - 5700	802.11n HT20	20.80	120.23
5510 - 5670	802.11n HT40	22.16	164.44
5530 - 5610	802.11ac VHT80	22.92	195.88
5.8 GHz band, 2TX			
5745 - 5825	802.11a	22.87	193.64
5745 - 5825	802.11n HT20	22.80	190.55
5755 - 5795	802.11n HT40	22.93	196.34
5775	802.11ac VHT80	22.22	166.72

(IC)

Frequency Range (MHz)	Mode	EIRP (dBm)	EIRP (mW)
5.2 GHz band, 2TX			
5180-5240	802.11a	19.12	81.66
5180-5240	802.11n HT20	18.23	66.53
5190-5230	802.11n HT40	15.30	33.88
5210	802.11ac VHT80	12.28	16.90

6.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a Monopole antenna, with a maximum gain as follows.

Frequency Range (MHz)	Peak Antenna Gain (dBi)			
	CHAIN 0		CHAIN 1	
	ANT1 (dBi)	ANT3 (dBi)	ANT2 (dBi)	ANT4 (dBi)
5150 – 5250	2.8	2.6	3.3	2.6
5250 – 5350	2.8	2.4	3.3	2.5
5500 – 5700	2.2	2.9	3.4	3.3
5725 - 5850	2.0	2.2	2.5	3.0

6.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was 74.0-39150-1-41.

The test utility software installed during testing was PrimaComplianceGUIInstaller _TESTBUILD3_17Nov22.

6.5. WORST-CASE CONFIGURATION AND MODE

Radiated emissions below 1GHz, above 18GHz, and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Band edge and radiated emissions between 1GHz and 18GHz were performed with the EUT set to transmit at the highest power on low, middle, and high channels.

The EUT can only be setup in desktop orientation; therefore, all radiated testing was performed with the EUT in desktop orientation.

The fundamental of the EUT was investigated with the antenna combinations, it was determined that:

_ANT3 and ANT2 was the worst case in the 5.2GHz & 5.6GHz band.

_ANT1 and ANT2 was the worst case in the 5.3GHz bands.

_ANT3 and ANT4 was the worst case in the 5.8GHz bands.

Therefore, all final testing was performed with ANT3 and ANT2, ANT1 and ANT2 and ANT3 and ANT4 as stated above.

Worst-case data rates as provided by the manufacturer were:

802.11a mode: 6 Mbps

802.11n HT20mode: MCS0

802.11n HT40mode: MCS0

802.11ac VHT80 mode: MCS0

Note: 802.11ac VHT20 and VHT40 has the same power as 802.11n HT20 and 802.11n HT40 so 802.11n HT20 and 802.11n HT40 were test as worst case.

6.6. DESCRIPTION OF TEST SETUP


SUPPORT TEST EQUIPMENT								
Description	Manufacturer	Model	Serial Number	FCC ID/ DoC				
Laptop	Lenovo	T460s	PC0JMBF8	Doc				
Laptop AC/DC Adapter	Lenovo	ADLX90NLC2A	11S45N0247Z1ZSHH448JEY	Doc				
AC Power	Sonos	CPS045180250U	N/A	Doc				
Power Supply	Sonos	EC2Y5EB	N/A	Doc				
USB-A to Ethernet Adapter	Plugable	USB2-E100	8CAE4CE46AFA	Doc				
USB-C to USB-A Female Adapter	Amazon Basics	L6LUC160-CS-R	N/A	Doc				
I/O CABLES (CONDUCTED TEST)								
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks		
1	AC	3	AC	Un-shielded	1.25	AC Mains to Spectrum Analyzer/AC/DC Adapter		
2	DC	1	DC	Un-shielded	1.0	AC/DC Adapter to Laptop		
3	USB-C	1	USB-C	Un-shielded	1.5	EUT to AC Power		
4	Ethernet	1	RJ45	Un-shielded	1.5	Laptop to USB Ethernet Adapter		
5	USB-A	1	USB-A	Shielded	0.05	USB Ethernet Adapter to USB		
6	USB-C	1	USB-C	Shielded	0.05	EUT to USB-C/USB-A Female Adapter		
7	SMA Cable	1	SMA	Un-Shielded	1.0	EUT to Spectrum Analyzer		
I/O CABLES (RADIATED TEST)								
Cable No.	Port	# Of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks		
1	AC	3	AC	Un-shielded	1.25	AC Mains to Spectrum Analyzer/AC/DC Adapter		
2	DC	1	DC	Un-shielded	1.0	AC/DC Adapter to Laptop		
3	USB-C	1	USB-C	Un-shielded	1.5	EUT to AC Power		
4	Ethernet	1	RJ45	Un-shielded	10	Laptop to USB Ethernet Adapter		
5	USB-A	1	USB-A	Shielded	0.05	USB Ethernet Adapter to USB		
6	USB-C	1	USB-C	Shielded	0.05	EUT to USB-C/USB-A Female Adapter		
7	SMA Cable	1	SMA	Un-Shielded	10	EUT to Horn Antenna		

TEST SETUP


The EUT is a stand-alone unit, and the radio is exercised remotely by Sonos Compliance GUI test utility software via ethernet.

SETUP DIAGRAM

Radiated Configuration



Conducted Configuration



7. MEASUREMENT METHOD

On Time and Duty Cycle: KDB 789033 D02 v02r01, Section B.

6 dB Emission BW: KDB 789033 D02 v02r01, Section C.2

26 dB Emission BW: KDB 789033 D02 v02r01, Section C.1

99% Occupied BW: KDB 789033 D02 v02r01, Section D.

Conducted Output Power: KDB 789033 D02 v02r01, Section E.3.b (Method PM-G) and KDB 789033 D02 v02r01, Section E.2.b (Method SA-1)

Power Spectral Density: KDB 789033 D02 v02r01, Section F

Unwanted emissions in restricted bands: KDB 789033 D02 v02r01, Sections G.3, G.4, G.5, and G.6.

Unwanted emissions in non-restricted bands: KDB 789033 D02 v02r01, Sections G.3, G.4, and G.5.

AC Power Line Conducted Emissions: ANSI C63.10-2013, Section 6.2.

Radiated Spurious Emissions Below 30MHz: ANSI C63.10-2013 Section 6.4

8. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
Antenna, Broadband Hybrid, 30MHz to 2GHz	Sunol Sciences Corp.	JB1	171862	2023-09-08	2022-09-08
Amplifier, 10KHz to 1GHz, 32dB	SONOMA INSTRUMENT	310N	29654	2023-04-24	2022-04-24
Antenna, Horn 1-18GHz	ETS-Lindgren (Cedar Park, Texas)	3117	223083	2023-10-25	2022-10-25
RF Filter Box, 1-18GHz	UL-FR1 (CTECH)	SAC 8 port rf box 1	197920	2023-04-19	2022-04-19
EMI TEST RECEIVER, with B8 option	Rohde & Schwarz	ESW44	191429	2024-02-29	2023-02-15
EMI TEST RECEIVER	Rohde & Schwarz	ESW44	225688	2024-02-29	2023-02-14
Antenna, Horn 18 to 26.5GHz	ARA	MWH-1826/B	199659	2023-06-12	2022-06-12
Amplifier 18-26.5GHz, +5Vdc, -54dBm P1dB	AMPLICAL	AMP18G26.5-60	234683	2024-03-29	2023-03-18
Antenna, Horn 26 to 40GHz	ARA	MWH-2640/B	199661	2023-12-06	2022-12-06
Amplifier 26-40GHz +5Vdc, -62dBm P1dB	AMPLICAL	AMP26G40-65	172345	2023-06-22	2022-06-22
Antenna, Passive Loop 30Hz - 1MHz	ELECTRO METRICS	EM-6871	170014	2023-07-19	2022-07-19
Antenna, Passive Loop 100KHz - 30MHz	ELECTRO METRICS	EM-6872	170016	2023-07-19	2022-07-19
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent Technologies	N9030A	80396	2024-01-31	2023-01-27
Power Meter, P-series single channel	Keysight Technologies Inc	N1911A	90719	2024-01-31	2023-01-26
Power Sensor, P - series, 50MHz to 18GHz, Wideband	Keysight Technologies Inc	N1921A	81319	2024-01-31	2023-01-25
10dB Fixed Attenuator	Pasternack Enterprises	PE7087-10	N/A	Verified	Verified
AC Line Conducted					
LISN	Fischer Custom Communications, Inc	FCC-LISN-50/250-25-2-01-480V	175765	2024-01-31	2023-01-27
EMI TEST RECEIVER	Rohde & Schwarz	ESR	175765	2024-02-29	2023-02-20
Transient Limiter	Com-Power	LIT-930	207996	2023-07-15	2022-07-15
UL TEST SOFTWARE LIST					
Radiated Software	UL	UL EMC		Ver 2023-01-18	
Antenna Port Software	UL	UL RF		Ver 2022-08-16	
AC Line Conducted Software	UL	UL EMC		Rev 9.5, 2022-02-17	

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE


KDB 558074 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Test Engineer:	JB 45256
Test Date:	2023-02-20 – 2023-02-21

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11a	1.390	2.015	0.690	68.98	1.61	0.719
802.11n HT20	1.300	1.920	0.677	67.71	1.69	0.769
802.11n HT40	0.646	1.278	0.505	50.53	2.96	1.549
802.11ac VHT80	0.324	0.952	0.340	34.00	4.69	3.091

DUTY CYCLE PLOTS



9.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.


RESULTS

9.2.1. 802.11a MODE IN THE 5.2 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5180	27.72	28.04
Mid	5200	27.52	27.96
High	5240	27.04	27.80


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL




9.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5180	27.36	28.32
Mid	5200	27.88	28.84
High	5240	27.08	28.96


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL




9.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5190	40.40	40.88
High	5230	40.88	40.96

LOW CHANNEL



HIGH CHANNEL




9.2.4. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND

2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Mid	5210	80.16	80.16

MID CHANNEL




9.2.5. 802.11a MODE IN THE 5.3 GHz BAND


2TX Antenna 1 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 1 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5260	27.68	26.68
Mid	5300	27.60	26.76
High	5320	27.76	26.44


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL




9.2.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND


2TX Antenna 1 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 1 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5260	28.96	27.00
Mid	5300	28.88	27.00
High	5320	28.76	27.20

LOW CHANNEL




MID CHANNEL



MID CHANNEL ANTENNA 1

MID CHANNEL ANTENNA 2

HIGH CHANNEL



HIGH CHANNEL ANTENNA 1


HIGH CHANNEL ANTENNA 2

9.2.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND


2TX Antenna 1 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 1 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5270	40.96	40.32
High	5310	41.12	41.20

LOW CHANNEL



HIGH CHANNEL




9.2.8. 802.11ac VHT80 MODE IN THE 5.3 GHz BAND

2TX Antenna 1 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 1 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Mid	5290	81.28	80.32

MID CHANNEL




9.2.9. 802.11a MODE IN THE 5.6 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5500	26.80	27.80
Mid	5580	26.16	27.64
High	5700	27.56	27.96

LOW CHANNEL




MID CHANNEL



MID CHANNEL ANTENNA 3

MID CHANNEL ANTENNA 2

HIGH CHANNEL



HIGH CHANNEL ANTENNA 3


HIGH CHANNEL ANTENNA 2

9.2.10. 802.11n HT20 MODE IN THE 5.6 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5500	25.68	26.88
Mid	5580	25.04	26.88
High	5700	25.20	26.88

LOW CHANNEL




MID CHANNEL



MID CHANNEL ANTENNA 3

MID CHANNEL ANTENNA 2

HIGH CHANNEL



HIGH CHANNEL ANTENNA 3


HIGH CHANNEL ANTENNA 2

9.2.11. 802.11n HT40 MODE IN THE 5.6 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5510	40.72	40.24
Mid	5550	40.56	41.12
High	5670	40.72	41.20


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL




9.2.12. 802.11ac VHT80 MODE IN THE 5.6 GHz BAND


2TX Antenna 3 + Antenna 2 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 2 (MHz)
Low	5530	80.64	81.12
High	5610	80.48	81.12

LOW CHANNEL



HIGH CHANNEL




9.2.13. 802.11a MODE IN THE 5.8 GHz BAND


2TX Antenna 3 + Antenna 4 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 4 (MHz)
Low	5745	27.92	26.92
Mid	5785	27.96	27.00
High	5825	27.80	27.96


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL




9.2.14. 802.11n HT20 MODE IN THE 5.8 GHz BAND


2TX Antenna 3 + Antenna 4 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 4 (MHz)
Low	5745	27.88	26.88
Mid	5785	27.84	26.88
High	5825	27.88	27.08

LOW CHANNEL




MID CHANNEL



MID CHANNEL ANTENNA 3

MID CHANNEL ANTENNA 4

HIGH CHANNEL



HIGH CHANNEL ANTENNA 3


HIGH CHANNEL ANTENNA 4

9.2.15. 802.11n HT40 MODE IN THE 5.8 GHz BAND


2TX Antenna 3 + Antenna 4 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 4 (MHz)
Low	5755	40.80	40.56
High	5795	40.96	40.56

LOW CHANNEL



HIGH CHANNEL



9.2.16. 802.11ac VHT80 MODE IN THE 5.8 GHz BAND

2TX Antenna 3 + Antenna 4 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 3 (MHz)	26 dB Bandwidth Antenna 4 (MHz)
Mid	5775	81.12	80.48

MID CHANNEL

