

APPLICATION FOR CERTIFICATION

On Behalf of

Electro Source LLC.

Game Light Gun

Model Number: PL-667

Prepared for : Electro Source LLC.

1840 East 27th Street Vernon CA90058 USA

Prepared By : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Rd., 52 Block,

Shenzhen Science & Industrial Park,

Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F04253

Date of Test : Aug.11~16, 2004

Date of Report : Aug. 18, 2004

## TABLE OF CONTENTS

Description	Page
FCC Test Report for Declaration of Conformity	
<b>1. GENERAL INFORMATION .....</b>	<b>1-1</b>
1.1. Description of Device (EUT) .....	1-1
1.2. Test Facility.....	1-2
1.3. Test Uncertainty .....	1-2
<b>2. POWER LINE CONDUCTED EMISSION TEST.....</b>	<b>2-1</b>
<b>3. RADIATED EMISSION TEST .....</b>	<b>3-1</b>
3.1. Test Equipment .....	3-1
3.2. Block Diagram of Test Setup .....	3-1
3.3. Radiated Emission Limit .....	3-2
3.4. EUT Configuration on Test.....	3-3
3.5. Operating Condition of EUT.....	3-3
3.6. Test Procedure.....	3-3
3.7. Radiated Emission Test Result.....	3-4
<b>4. 6dB BANDWIDTH MEASUREMENT .....</b>	<b>4-1</b>
4.1. Test Equipment .....	4-1
4.2. Block Diagram of Test Setup .....	4-1
4.3. Specification Limits (§15.247(a)(2)) .....	4-1
4.4. Operating Condition of EUT.....	4-1
4.5. Test Procedure.....	4-2
4.6. Test Results .....	4-2
<b>5. PEAK OUTPUT POWER MEASUREMENT.....</b>	<b>5-1</b>
5.1. Test Equipment .....	5-1
5.2. Block Diagram of Test Setup .....	5-1
5.3. Specification Limits (§15.247(b)-(3)).....	5-1
5.4. Operating Condition of EUT.....	5-1
5.5. Test Procedure.....	5-2
5.6. Test Results .....	5-2
<b>6. BAND EDGES MEASUREMENT.....</b>	<b>6-1</b>
6.1. Test Equipment .....	6-1
6.2. Block Diagram of Test Setup .....	6-1
6.3. Specification Limits (§15.247(c)) .....	6-1
6.4. Operating Condition of EUT.....	6-1
6.5. Test Procedure.....	6-2
6.6. Test Results .....	6-2
<b>7. POWER SPECTRAL DESITY MEASUREMENT .....</b>	<b>7-1</b>
7.1. Test Equipment .....	7-1
7.2. Block Diagram of Test Setup .....	7-1
7.3. Specification Limits (§15.247(d)).....	7-1
7.4. Operating Condition of EUT.....	7-1
7.5. Test Procedure.....	7-1
7.6. Test Results .....	7-2
<b>8. DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>8-1</b>
<b>9. PHOTOGRAPH.....</b>	<b>9-1</b>

9.1.	Photos of Radiated Emission Test (In Anechoic Chamber).....	9-1
9.2.	Photos of 6dB Bandwidth Measurement.....	9-3
9.3.	Photo of Peak Output Power Measurement .....	9-4
9.4.	Photos of Band Edges Measurement.....	9-4
9.5.	Photos of Power Spectral Density Measurement .....	9-5

APPENDIX I           (13 pages)

# TEST REPORT DECLARATION

Applicant : Electro Source LLC.  
 Manufacturer : Hong Xiang Electronics Co., Ltd.  
 EUT Description : Game Light Gun  
 (A) MODEL NO. : PL-667  
 (B) SERIAL NO. : F2004081801  
 (C) POWER SUPPLY : DC 3V

Test Procedure Used:  
 FCC Rules and Regulations Part 15 Subpart C Apr, 2004.

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both radiated and conducted emissions.

The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

This report must not be used by the applicant to claim product endorsement by NVLAP or any agency of the U.S. Government.

Date of Test : Aug.11~16, 2004

Prepared by : Elsa Wu  
 Elsa Wu / Assistant

Reviewer : Lake Wang  
 Lake Wang / Supervisor

Approved & Authorized Signer :



Name of the Representative of the Responsible Party : \_\_\_\_\_

Signature : \_\_\_\_\_

# 1. GENERAL INFORMATION

## 1.1. Description of Device (EUT)

Description : Game Light Gun  
This report is about transmitter FCC ID and the Receiver FCC DOC report please refer to AUDIX Number ACS-F04254

Modulation Technique : DSSS  
Range With -5dBi antenna : >10m (~33ft) indoor

Model Number : PL-667

Applicant : Electro Source LLC.  
1840 East 27th Street Vernon CA90058 USA

Manufacturer : Hong Xiang Electronics Co., Ltd.  
No.52, Sang Nan Rd., Sang Jao Chang An Town,  
Dong Guan City Guang Dong P.R.C.

Date of Test : Aug.11~16, 2004

## 1.2. Test Facility

### Site Description

- 3m Anechoic Chamber : Certificated by FCC, USA  
Registration Number : 90454  
Aug. 15, 2003
- 3m & 10m Anechoic Chamber : Certificated by FCC, USA  
Registration Number : 794232  
Mar. 15, 2004
- EMC Lab. : Certificated by DATech, German  
Registration Number : DAT-P-091/99-01  
Feb. 02, 2004
- Certificated by NVLAP, USA  
NVLAP Code: 200372-0  
Mar. 31, 2004
- Certificated by Nemko, Norway  
Aut. No.: ELA135  
April. 22, 2004
- Name of Firm : Audix Technology (Shenzhen) Co., Ltd.
- Site Location : No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

## 1.3. Test Uncertainty

Conducted Emission Uncertainty =  $\pm 2.66\text{dB}$

Radiated Emission Uncertainty =  $\pm 4.26\text{dB}$

## **2. POWER LINE CONDUCTED EMISSION TEST**

According to Paragraph (f) of FCC Part 15 section 15.107, Tests to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

### 3. RADIATED EMISSION TEST

#### 3.1. Test Equipment

The following test equipments are used during the radiated emission test:

##### 3.1.1. For Anechoic Chamber

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Spectrum	HP	8591EM	3628A00914	May 24, 04	1 Year
2.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May 24,04	1 Year
3.	Amplifier	HP	8447D	2944A07794	Mar.17, 04	1/2 Year
4.	Bilog Antenna	Schaffner	CBL6111C	2598	Jan. 13, 04	1 Year
5.	PC	N/A	586ATX3	N/A	N/A	N/A
6.	Printer	HP	Laserjet6P	SGCF019673	N/A	N/A
7.	RF Cable	MIYAZAKI	5D-2W	3# Chamber No.1	July 31, 04	1/2 Year
8.	RF Cable	MIYAZAKI	5D-2W	3# Chamber No.2	July 31, 04	1/2 Year
9.	RF Cable	FUJIKURA	RG-55/U	3# Chamber No.3	July 31, 04	1/2 Year
10.	RF Cable	FUJIKURA	RG-55/U	3# Chamber No.4	July 31, 04	1/2 Year
11.	Coaxial Switch	Anritsu	MP59B	M73989	May 27, 04	1/2 Year
12.	Spectrum	Agilent	E4407B	MY41440292	May 24, 04	1 Year
13.	Amp	HP	8449B	3008A00863	May 24. 04	1 Year
14.	Antenna	EMCO	3115	9607-4877	Jun. 15, 04	1.5 Year

#### 3.2. Block Diagram of Test Setup


##### 3.2.1. Block diagram of connection between the EUT and simulators

EUT

*(EUT: Game Light Gun)*

## 3.2.2. In Anechoic Chamber

## ANTENNA TOWER



## 3.3. Radiated Emission Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Local Oscillator: 114.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 94.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average) Other: 74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

- Remark :
- (1) Emission level  $(\text{dB})\mu\text{V} = 20 \log$  Emission level  $\mu\text{V}/\text{m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

### 3.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 3.4.1.Game Light Gun (EUT)

Model Number : PL-667  
Serial Number : F2004081801  
Manufacturer : Hong Xiang Electronics Co., Ltd.

3.4.2.Support Equipment : As Tested Supporting System Detail, in Section 1.2.

### 3.5.Operating Condition of EUT

1. Setup the EUT as shown in Section 3.2..
2. Let the EUT work in test mode (Tx (CH 1)/Tx (CH 2)) and test it.

### 3.6.Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it work normally, we use a keyboard test soft ware, let EUT working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver (R&S ESVS20) is set at 120KHz.

The frequency range from 30MHz to 24000MHz is checked.

The test mode (Tx (CH 1)/Tx (CH 2)) is tested in Anechoic Chamber, and all the scanning waveforms are attached in Appendix I.

### 3.7.Radiated Emission Test Result

**PASS.**

The frequency range from 30MHz to 24000MHz is investigated.  
Please see the following pages.

Date of Test :	<u>Aug.15, 2004</u>	Temperature :	<u>23.6°C</u>
EUT :	<u>Game Light Gun</u>	Humidity :	<u>56%</u>
Model No. :	<u>PL-667</u>	Test Mode :	<u>Tx (CH 1)</u>
Test Engineer:	<u>Richzhy</u>		

Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Over Limits dB	Limits dBμV/m
36.790	16.63	1.20	14.04	31.87	-8.13	40.00
109.540	11.29	2.09	18.76	32.14	-11.36	43.50
288.990	13.17	3.73	19.42	36.32	-9.68	46.00
590.660	18.78	6.08	10.16	35.02	-10.98	46.00
711.910	20.51	6.59	11.35	38.45	-7.55	46.00
<b>882.630</b>	<b>22.02</b>	<b>7.28</b>	<b>10.38</b>	<b>39.68</b>	<b>-6.32</b>	<b>46.00</b>

Remark: 1. All readings are Quasi-Peak values.

2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Reviewer:

Caife Wang

Date of Test : Aug.15, 2004      Temperature : 23.6°C  
 EUT : Game Light Gun      Humidity : 56%  
 Model No. : PL-667      Test Mode : Tx (CH 1)  
 Test Engineer: Richzhy

Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dB $\mu$ V	Emission Level Vertical dB $\mu$ V/m	Over Limits dB	Limits dB $\mu$ V/m
35.820	11.34	1.19	19.51	32.04	-7.96	40.00
48.430	7.52	1.34	23.26	32.13	-7.87	40.00
109.540	9.56	2.09	20.11	31.76	-11.74	43.50
590.660	19.00	6.08	12.98	38.06	-7.94	46.00
<b>710.940</b>	<b>21.16</b>	<b>6.50</b>	<b>12.46</b>	<b>40.12</b>	<b>-5.88</b>	<b>46.00</b>
882.630	22.28	7.28	8.61	38.17	-7.83	46.00

Remark: 1. All readings are Quasi-Peak values.

2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Reviewer:

Caife Wang

Date of Test : Aug.15, 2004      Temperature : 23.6°C  
 EUT : Game Light Gun      Humidity : 56%  
 Model No. : PL-667      Test Mode : Tx (CH 2)  
 Test Engineer: Richzhy

Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dB $\mu$ V	Emission Level Horizontal dB $\mu$ V/m	Over Limits dB	Limits dB $\mu$ V/m
36.790	16.63	1.20	12.92	30.75	-9.25	40.00
109.540	11.29	2.09	19.19	32.57	-10.93	43.50
433.520	16.71	4.89	11.59	33.19	-12.81	46.00
711.910	20.51	6.59	9.99	37.09	-8.91	46.00
848.680	22.00	7.47	7.03	36.49	-9.51	46.00
<b>882.630</b>	<b>22.02</b>	<b>7.28</b>	<b>10.67</b>	<b>39.97</b>	<b>-6.03</b>	<b>46.00</b>

Remark: 1. All readings are Quasi-Peak values.

2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Reviewer:

Caife Wang

Date of Test : Aug.15, 2004      Temperature : 23.6°C  
 EUT : Game Light Gun      Humidity : 56%  
 Model No. : PL-667      Test Mode : Tx (CH 2)  
 Test Engineer: Richzhy

Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dB $\mu$ V	Emission Level Vertical dB $\mu$ V/m	Over Limits dB	Limits dB $\mu$ V/m
35.820	11.34	1.19	20.79	33.32	-6.68	40.00
48.430	7.52	1.34	22.91	31.78	-8.22	40.00
109.540	9.56	2.09	19.40	31.05	-12.45	43.50
590.660	19.00	6.08	13.34	38.42	-7.58	46.00
712.880	21.08	6.59	11.54	39.21	-6.79	46.00
<b>737.130</b>	<b>21.14</b>	<b>6.74</b>	<b>11.51</b>	<b>39.39</b>	<b>-6.61</b>	<b>46.00</b>

Remark: 1. All readings are Quasi-Peak values.

2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Reviewer:

Caife Wang

Date of Test :	Aug.15, 2004	Temperature :	23.6°C
EUT :	Game Light Gun	Humidity :	56%
Model No. :	PL-667	Test Mode :	Tx (CH 1)
Test Engineer:	Richzhy		

Frequency MHz	Probe Factor dB	Cable Loss dB	Meter Reading Horizontal dB $\mu$ V	Emission Level Horizontal dB $\mu$ V/m	Over Limits dB $\mu$ V/m	Limits dB $\mu$ V/m	Remark
2465.000	28.17	3.25	25.34	56.76	-57.24	114.00	Peak
4930.000	33.13	4.71	18.22	56.06	-17.94	74.00	Peak
2465.000	28.17	3.25	20.34	51.76	-42.24	94.00	Average
4930.000	33.13	4.71	9.22	47.06	-6.94	54.00	Average

Remark: 1. All readings are Peak and Average values.

2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Frequency MHz	Probe Factor dB	Cable Loss dB	Meter Reading Vertical dB $\mu$ V	Emission Level Vertical dB $\mu$ V/m	Over Limits dB $\mu$ V/m	Limits dB $\mu$ V/m	Remark
2465.000	28.17	3.25	27.14	58.56	-55.44	114.00	Peak
4930.000	33.13	4.71	17.40	55.24	-18.76	74.00	Peak
2465.000	28.17	3.25	23.14	54.56	-39.44	94.00	Average
4930.000	33.13	4.71	9.40	47.24	-6.76	54.00	Average

Remark: 1. All readings are Peak and Average values.

2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Reviewer: Caibe Wang


Date of Test : Aug.11, 2004 Temperature : 24°C  
 EUT : Game Light Gun Humidity : 56%  
 Model No. : PL-667 Test Mode : Tx (CH 2)  
 Test Engineer: Richzhy

Frequency	Probe Factor	Cable Loss	Meter Reading Horizontal	Emission Level Horizontal	Over Limits	Limits	Remark
MHz	dB	dB	dBμV	dBμV/m	dBμV/m	dBμV/m	
2472.600	28.20	3.26	21.88	53.34	-60.66	114.00	Peak
4945.200	33.15	4.72	18.11	55.98	-18.02	74.00	Peak
2472.600	28.20	3.26	18.88	50.34	-43.66	94.00	Average
4945.200	33.15	4.72	10.11	47.98	-6.02	54.00	Average

Remark: 1. All readings are Peak and Average values.  
 2. Emission Level = Antenna Factor + Cable Loss + Meter Reading

Frequency	Probe Factor	Cable Loss	Meter Reading Vertical	Emission Level Vertical	Over Limits	Limits	Remark
MHz	dB	dB	dBμV	dBμV/m	dBμV/m	dBμV/m	
2472.600	28.20	3.26	27.80	59.6	-43.74	114.00	Peak
4945.200	33.15	4.72	16.64	54.51	-6.49	74.00	Peak
2472.600	28.20	3.26	18.80	50.26	-54.74	94.00	Average
4945.200	33.15	4.72	9.64	47.51	-19.49	54.00	Average

Remark: 1. All readings are Peak and Average values.  
 2. Emission Level = Antenna Factor + Cable Loss + Meter Reading


Reviewer: 



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
Tel: 0755-26639495~7  
Fax: 0755-26632877

Data#: 14 File#: Electro Source.EMIDate: 2004-08-15 Time: 18:15:57



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:

Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR HORIZONTAL  
EUT : Game Ligh Gun  
M/N : PL-667  
Power : DC 3V  
Engineer: Richzhv  
Comment : Temp:23.6°C Humi:56%  
Memo : Tx (CH 1)  
: 110cm 180deg

Page: 1


	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB
1	36.790	31.87	-8.13	40.00	14.04	16.63	1.20
2	109.540	32.14	-11.36	43.50	18.76	11.29	2.09
3	288.990	36.32	-9.68	46.00	19.42	13.17	3.73
4	590.660	35.02	-10.98	46.00	10.16	18.78	6.08
5	711.910	38.45	-7.55	46.00	11.35	20.51	6.59
6	882.630	39.68	-6.32	46.00	10.38	22.02	7.28



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: 13 File#: Electro Source.EMIDate: 2004-08-15 Time: 18:15:25



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:

Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR VERTICAL  
 RUT : Game Ligh Gun  
 M/N : PT-667  
 Power : DC 3V  
 Engineer: Richzhv  
 Comment : Temp:23.6°C Humi:56%  
 Memo : Tx (CH 1)  
 : 120cm 0deg

Page: 1


	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB
1	35.820	32.04	-7.96	40.00	19.51	11.34	1.19
2	48.430	32.13	-7.87	40.00	23.26	7.52	1.34
3	109.540	31.76	-11.74	43.50	20.11	9.56	2.09
4	590.660	38.06	-7.94	46.00	12.98	19.00	6.08
5 !	710.940	40.12	-5.88	46.00	12.46	21.16	6.50
6	882.630	38.17	-7.83	46.00	8.61	22.28	7.28



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: 15 File#: Electro Source.EMIDate: 2004-08-15 Time: 18:16:22



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:

Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR HORIZONTAL  
 EUT : Game Ligh Gun  
 M/N : PT-667  
 Power : DC 3V  
 Engineer: Richzhv  
 Comment : Temp:23.6°C Humi:56%  
 Memo : Tx (CH 2)  
 : 120cm 180deg

Page: 1


	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB
1	36.790	30.75	-9.25	40.00	12.92	16.63	1.20
2	109.540	32.57	-10.93	43.50	19.19	11.29	2.09
3	433.520	33.19	-12.81	46.00	11.59	16.71	4.89
4	711.910	37.09	-8.91	46.00	9.99	20.51	6.59
5	848.680	36.49	-9.51	46.00	7.03	22.00	7.47
6	882.630	39.97	-6.03	46.00	10.67	22.02	7.28



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: 16 File#: Electro Source.EMI Date: 2004-08-15 Time: 18:16:53



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:

Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR VERTICAL  
 RUT : Game Ligh Gun  
 M/N : PT-667  
 Power : DC 3V  
 Engineer: Richzhv  
 Comment : Temp:23.6°C Humi:56%  
 Memo : Tx (CH 2)  
 : 110cm 0deg

Page: 1

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB
1	35.820	33.32	-6.68	40.00	20.79	11.34	1.19
2	48.430	31.78	-8.22	40.00	22.91	7.52	1.34
3	109.540	31.05	-12.45	43.50	19.40	9.56	2.09
4	590.660	38.42	-7.58	46.00	13.34	19.00	6.08
5	712.880	39.21	-6.79	46.00	11.54	21.08	6.59
6	737.130	39.39	-6.61	46.00	11.51	21.14	6.74




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co.,Ltd.

No. 5, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 34 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)

	Freq	Level	Limit	Over Limit	Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	dB	
1	2465.000	56.76	-57.24	114.00	25.34	28.17	3.25	Peak	
2	4930.000	56.06	-17.94	74.00	18.22	33.13	4.71	Peak	




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 36 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15B(AV) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2465.000	51.76	-42.24	94.00	20.34	28.17	3.25	Average
2	4930.000	47.06	-6.94	54.00	9.22	33.13	4.71	Average




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 33 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DCSV  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)

	Freq	Level	Over Limit	Limit	Read	Probe	Cable	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2465.000	58.56	-55.44	114.00	27.14	28.17	3.25	Peak
2	4930.000	55.24	-18.76	74.00	17.40	33.13	4.71	Peak




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 35 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15B(AV) 3m 3115 FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)

	Freq	Level	Over Limit	Limit	Read	Probe	Cable	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2465.000	54.56	-39.44	94.00	23.14	28.17	3.25	Average
2	4930.000	47.24	-6.76	54.00	9.40	33.13	4.71	Average




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 37 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)

	Freq	Level	Over Limit	Limit	Read	Probe	Cable	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2472.600	53.34	-60.66	114.00	21.88	28.20	3.26	Peak
2	4945.200	55.98	-18.02	74.00	18.11	33.15	4.72	Peak




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 39 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15B(AV) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2472.600	50.34	-43.66	94.00	18.88	28.20	3.26	Average
2	4945.200	47.98	-6.02	54.00	10.11	33.15	4.72	Average




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 38 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2472.600	59.26	-54.74	114.00	27.80	28.20	3.26	Peak
2	4945.200	54.51	-19.49	74.00	16.64	33.15	4.72	Peak




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 40 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15B(AV) 3m 3115 FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2472.600	50.26	-43.74	94.00	18.80	28.20	3.26	Average
2	4945.200	47.51	-6.49	54.00	9.64	33.15	4.72	Average

## 4. 6dB BANDWIDTH MEASUREMENT

### 4.1. Test Equipment

The following test equipment were used during the Emission Bandwidth Test :

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4407B	MY41440292	May 24,04	1 Year
2.	Amp	HP	8449B	3008A00863	May 24,04	1 Year
3.	Antenna	EMCO	3115	9607-4877	Jun.15, 04	1.5 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May 24,04	1 Year

### 4.2. Block Diagram of Test Setup



*(EUT: Game Light Gun)*

### 4.3. Specification Limits (§15.247(a)(2))

The minimum 6dB bandwidth shall be at least 500kHz.

### 4.4. Operating Condition of EUT

1. Setup the EUT as shown in Section 4.2..
2. Let the EUT work in test mode (Tx (CH 1)/Tx (CH 2)) and test it.

#### 4.5. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. Power on the EUT and let it work normally, we use a keyboard test software, let EUT working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Horn antenna is used as receiving antenna.

The bandwidth of the fundamental frequency was measure by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

#### 4.6. Test Results

**PASSED.**

The testing data was attached in the next pages.

Date of Test :	<u>Aug.15, 2004</u>	Temperature :	<u>23.6°C</u>
EUT :	<u>Game Light Gun</u>	Humidity :	<u>56%</u>
Model No. :	<u>PL-667</u>	Test Mode :	<u>Tx (CH 1)/</u>
Test Engineer:	<u>Richzhy</u>		<u>Tx (CH 2)</u>

Channel.	Frequency	6dB Bandwidth
1	2464.800MHz	<b>890KHz</b>
2	2742.400MHz	<b>900KHz</b>

Reviewer: *Caik Wang*




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block S2,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 58 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)

	Over	Limit	Read	Probe	Cable		
Freq	Level	Limit	Line	Level	Factor	Loss	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2464.530	49.78	-64.22	114.00	18.36	28.17	3.25 Peak
2	2464.800	54.79	-59.21	114.00	23.37	28.17	3.25 Peak
3	2465.420	48.91	-65.09	114.00	17.49	28.17	3.25 Peak




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co.,Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 57 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15 (PEAK) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)

	Over	Limit	Read	Probe	Cable		
Freq	Level	Limit	Line	Level	Factor	Loss	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2472.130	56.03	-57.97	114.00	24.57	28.20	3.26 Peak
2	2472.100	61.99	-52.01	114.00	30.53	28.20	3.26 Peak
3	2473.030	56.09	-57.91	114.00	24.63	28.20	3.26 Peak


## 5. PEAK OUTPUT POWER MEASUREMENT

### 5.1. Test Equipment

The following test equipment were used during the Emission Bandwidth Test :

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4407B	MY41440292	May 24,04	1 Year
2.	Amp	HP	8449B	3008A00863	May 24,04	1 Year
3.	Antenna	EMCO	3115	9607-4877	Jun. 15, 04	1.5 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May 24,04	1 Year
5.	Power meter	HP	436A	2016A07891	NCR	-
6.	Power Sensor	Agilent	8482B	My41090514	May 24,04	1Year

### 5.2. Block Diagram of Test Setup



*(EUT: Game Light Gun)*

### 5.3. Specification Limits (§15.247(b)-(3))

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5MHz is : 1Watt. (30dBm)

### 5.4. Operating Condition of EUT

1. Setup the EUT as shown in Section 5.2..
2. Let the EUT work in test mode (Tx (CH 1)/Tx (CH 2)) and test it.

### 5.5. Test Procedure

Setup the EUT as shown in Section 5.2. Turn on the play station 2 and let the EUT working . The EUT is via the power sensor link to power meter. The test value reading is from power meter.

### 5.6. Test Results

**PASSED.**

The testing data was attached in the next pages.

Date of Test : Aug.15, 2004      Temperature : 23.6°C  
 EUT : Game Light Gun      Humidity : 56%  
 Model No. : PL-667      Test Mode : Tx (CH 1)  
 Test Engineer: Richzhy

Frequency	Reading dB $\mu$ V	Cable Loss dBm	Poer Density dBm	Limit dBm
2464.800MHz	-21.57	0.2	-21.37	30.00

Date of Test : Aug.15, 2004      Temperature : 23.6°C  
 EUT : Game Light Gun      Humidity : 56%  
 Model No. : PL-667      Test Mode : Tx (CH 2)  
 Test Engineer: Richzhy

Frequency	Reading dB $\mu$ V	Cable Loss dBm	Poer Density dBm	Limit dBm
2472.400MHz	-21.46	0.2	-21.26	30.00

Reviewer: *Case Wang*

## 6. BAND EDGES MEASUREMENT

### 6.1. Test Equipment

The following test equipment were used during the Emission Bandwidth Test :

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4407B	MY41440292	May 24,04	1 Year
2.	Amp	HP	8449B	3008A00863	May 24,04	1 Year
3.	Antenna	EMCO	3115	9607-4877	Jun. 15, 04	1.5 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May 24,04	1 Year

### 6.2. Block Diagram of Test Setup



*(EUT: Game Light Gun)*

### 6.3. Specification Limits (§15.247(c))

The highest level should be at least 20 dB below that in the 100kHz bandwidth.

### 6.4. Operating Condition of EUT

1. Setup the EUT as shown in Section 6.2..
2. Let the EUT work in test mode (Tx (CH 1)/Tx (CH 2)) and test it.

## 6.5. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it work normally, we use a keyboard test software, let EUT working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Horn antenna is used as receiving antenna.

Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100kHz bandwidth from band edge.

## 6.6. Test Results

**PASSED.**

The testing data was attached in the next pages.




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 69 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)

	Over	Limit	Read	Probe	Cable		
Freq	Level	Limit	Line	Level	Factor	Loss	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2399.900	28.96	-----	-----	32.68	28.07	3.21 Peak
2	2400.000	28.91	-----	-----	32.63	28.07	3.21 Peak
3	2464.820	56.25	-----	-----	59.81	28.19	3.25 Peak




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block S2,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 68 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)

	Over	Limit	Read	Probe	Cable		
Freq	Level	Limit	Line	Level	Factor	Loss Remark	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	
1	2472.370	62.76	-----	-----	31.29	28.21	3.26 Peak
2	2483.500	35.75	-----	-----	4.25	28.23	3.27 Peak
3	2483.600	35.75	-----	-----	4.25	28.23	3.27 Peak

## 7. POWER SPECTRAL DENSITY MEASUREMENT

### 7.1. Test Equipment

The following test equipment were used during the Emission Bandwidth Test :

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4407B	MY41440292	May 24,04	1 Year
2.	Amp	HP	8449B	3008A00863	May 24,04	1 Year
3.	Antenna	EMCO	3115	9607-4877	Jun.15, 04	1.5 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May 24,04	1 Year

### 7.2. Block Diagram of Test Setup



*(EUT: Game Light Gun)*

### 7.3. Specification Limits (§15.247(d))

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band.

### 7.4. Operating Condition of EUT

1. Setup the EUT as shown in Section 7.2..
2. Let the EUT work in test mode (Tx (CH 1)/Tx (CH 2)) and test it.

### 7.5. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. Power on the EUT and let it work normally, we use a keyboard test soft ware, let EUT working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Horn antenna is used as receiving antenna.

The bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz.

## 7.6.Test Results

### **PASSED.**

The testing data was attached in the next pages.

Date of Test :	<u>Aug.15, 2004</u>	Temperature :	<u>23.6°C</u>
EUT :	<u>Game Light Gun</u>	Humidity :	<u>56%</u>
Model No. :	<u>PL-667</u>	Test Mode :	<u>Tx (CH 1)</u>
Test Engineer:	<u>Richzhy</u>		

Frequency	Reading dBμV	Power Density dBm	Limit dBm
2464.7843MHz	49.97	-57.03	8.00

Remark:

Formulas used to calculate Power Density.

Using the relationship between field strength and RF power into an isotropic transmit antenna:

$$P(\text{Watts}) = (E(\text{V/m}) \times D: \text{meters})^2 / 30G \quad D = \text{Distance}$$

Antenna gain = -5dBi

$$G(\text{numeric}) = 10^{(G(\text{dBi})/10)} = 10^{(-5\text{dBi}/10)} = 0.32$$

$$69.38\text{dB}\mu\text{V} = 0.0029444216\text{V/m}$$

$$P(\text{Watt}) = (0.0029444216\text{V/m} \times 3\text{m})^2 / 9.6 = 8.1277673 \times 10^{-6}$$

$$10 * \log 8.1277673 \times 10^{-6} \times 10^3 = -20.9\text{dBm}$$

Reviewer:

Caik Wang

Date of Test : Aug.15, 2004      Temperature : 23.6°C  
 EUT : Game Light Gun      Humidity : 56%  
 Model No. : PL-667      Test Mode : Tx (CH 2)  
 Test Engineer: Richzhy

Frequency	Reading dB $\mu$ V	Power Density dBm	Limit dBm
2472.3843MHz	47.08	-59.92	8.00

Remark:

Formulas used to calculate Power Density.

Using the relationship between field strength and RF power into an isotropic transmit antenna:

$$P(\text{Watts}) = (E(\text{V/m}) \times D: \text{meters})^2 / 30G \quad D = \text{Distance}$$

Antenna gain = -5dBi

$$G(\text{numeric}) = 10^{(G(\text{dBi})/10)} = 10^{(-5\text{dBi}/10)} = 0.32$$

$$69.38\text{dB}\mu\text{V} = 0.0029444216\text{V/m}$$

$$P(\text{Watt}) = (0.0029444216\text{V/m} \times 3\text{m})^2 / 9.6 = 8.1277673 \times 10^{-6}$$


$$10 * \log 8.1277673 \times 10^{-6} \times 10^3 = -20.9\text{dBm}$$

Reviewer:

Caife Wang

Agilent 19:09:18 Aug 16, 2004

L




- Peak Search
- Meas Tools
- Next Peak
- Next Pk Right
- Next Pk Left
- Min Search
- Pk-Pk Search
- More  
1 of 2

Undefined header

Agilent 19:02:42 Aug 16, 2004

L



- Peak Search
- Meas Tools
- Next Peak
- Next Pk Right
- Next Pk Left
- Min Search
- Pk-Pk Search
- More  
1 of 2

Undefined header

## **8. DEVIATION TO TEST SPECIFICATIONS**

(None.)


# APPENDIX I



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: 2 File#: Electro Source.EMIDate: 2004-08-15 Time: 11:29:06



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:


Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR HORIZONTAL  
 EUT : Game Ligh Gun  
 M/N : PI-667  
 Power : DC 3V  
 Engineer: Richzhv  
 Comment : Temp:23.6°C Humi:56%  
 Memo : Tx (CH 1)

**AUDIX**<sup>®</sup>  
 AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: File#: Electro Source.EMIDate: 2004-08-15 Time: 11:27:52



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:

Ref Trace:


Condition: FCC PART 15B 3m 2598FACTOR VERTICAL  
 RUT : Game Ligh Gun  
 M/N : PT-667  
 Power : DC 3V  
 Engineer: Richzhv  
 Comment : Temp:23.6°C Humi:56%  
 Memo : Tx (CH 1)



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: 3 File#: Electro Source.EMIDate: 2004-08-15 Time: 11:30:27



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (# Chamber)

Trace:

Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR HORIZONTAL

EUT : Game Ligh Gun

M/N : PI-667

Power : DC 3V

Engineer: Richzhv

Comment : Temp:23.6°C Humi:56%


Memo : Tx (CH 2)



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

Shenzhen Science & Ind. Park  
 Tel: 0755-26639495~7  
 Fax: 0755-26632877

Data#: 4 File#: Electro Source.EMIDate: 2004-08-15 Time: 11:31:39



AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. (3# Chamber)

Trace:

Ref Trace:

Condition: FCC PART 15B 3m 2598FACTOR VERTICAL

EUT : Game Ligh Gun

M/N : PI-667

Power : DC 3V

Engineer: Richzhv

Comment: Temp:23.6°C Humi:56%

Memo : Tx (CH 2)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 26 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : RiChzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 1)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
 Shenzhen Science & Industry Park  
 Nantou, Shenzhen, Guangdong, China  
 Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 25 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
 Condition : FCC PART 15(PEAK) 3m 3115 FACTOR VERTICAL  
 EUT : Game Light Gun  
 M/N : PL-667  
 Power : DC3V  
 Test Engineer : Richzhy  
 Test Comment : Temp:24°C Himi:56%  
 Memo : Tx (CH 1)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 27 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15 (PEAK) 3m 3115 FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 28 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115 FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:24°C Himi:56%  
Memo : Tx (CH 2)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
 Shenzhen Science & Industry Park  
 Nantou, Shenzhen, Guangdong, China  
 Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 49 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
 Condition : FCC PART 15(PEAK) 3m 3115FACTOR HORIZONTAL  
 EUT : Game Light Gun  
 M/N : PL-667  
 Power : DC3V  
 Test Engineer : Richzhy  
 Test Comment : Temp:23°C Humi:54%  
 Memo : Tx (CH 1)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel: +86-755-26639496 Fax: +86-755-26632877

Data#: 50 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:23°C Humi:54%  
Memo : Tx(CH 1)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 51 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115FACTOR HORIZONTAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:23°C Humi:54%  
Memo : Tx(CH 2)




信華科技(深圳)有限公司

AUDIX Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Road, Block 52,  
Shenzhen Science & Industry Park  
Nantou, Shenzhen, Guangdong, China  
Tel:+86-755-26639496 Fax:+86-755-26632877

Data#: 52 File#: C:\EMI TEST DATA\E\Electro Source.EMI



Site : 1# Chamber  
Condition : FCC PART 15(PEAK) 3m 3115FACTOR VERTICAL  
EUT : Game Light Gun  
M/N : PL-667  
Power : DC3V  
Test Engineer : Richzhy  
Test Comment : Temp:23°C Humi:54%  
Memo : Tx(CH 2)