

APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Date of Issue: January 20, 2011

EUT Specification

EUT	802.11b/g /n USB Dongle
Frequency band (Operating)	 WLAN: 2.412GHz ~ 2.462GHz WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz WLAN: 5.745GHz ~ 5.825GHz Others
Device category	☐ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others
Exposure classification	 ✓ Occupational/Controlled exposure (S = 5mW/cm²) ✓ General Population/Uncontrolled exposure (S=1mW/cm²)
Antenna diversity	Single antenna Multiple antennas Tx diversity Rx diversity Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 19.08 dBm (80.90 mW) IEEE 802.11g mode: 18.67dBm (73.6 mW) IEEE 802.11n HT 20 MHz mode: 18.84 dBm (76.55 mW) IEEE 802.11n HT 40 MHz mode: 18.16 dBm (65.46 mW)
Antenna gain (Max)	 Gain: 3.22dBi (Numeric gain: 2.09) Gain: 4.16dBi (Numeric gain: 2.6)
Evaluation applied	
Remark: 1. The maximum output power is 19.08 dBm (80.90 mW) at 2437MHz (with 2.6 numeric antenna gain.) 2. DTS device is not subject to routine RF evaluation: MPF estimate is used to justify the compliance	

3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm2 even if the calculation indicates that the power density would be larger.

TEST RESULTS

No non-compliance noted.

Remark: Please refer to the separated SAR report.

Page 109 Rev. 00