

# FCC Test Report

Product Name	Touch Panel
Model No	TP7
FCC ID.	SCGTP72013

Applicant	CORE BRANDS, LLC
Address	1800 South McDowell Blvd., Petaluma, CA 94954

Date of Receipt	Aug. 19, 2014
Issue Date	Sep. 22, 2014
Report No.	1480420R-RFUSP25V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

# Test Report

Issue Date: Sep. 22, 2014

Report No.: 1480420R-RFUSP25V00



Product Name	Touch Panel
Applicant	CORE BRANDS, LLC
Address	1800 South McDowell Blvd., Petaluma, CA 94954
Manufacturer	CORE BRANDS, LLC
Model No.	TP7
FCC ID.	SCGTP72013
EUT Rated Voltage	DC 12V, 1A
EUT Test Voltage	AC 120V/60Hz
Trade Name	Core Brands, LLC
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2013 ANSI C63.10: 2009, KDB 558074 D01 DTS Meas Guidance v03r02
Test Result	Complied

Documented By

A handwritten signature in blue ink that reads "Genie Chang".

( Senior Adm. Specialist / Genie Chang )

Tested By

A handwritten signature in blue ink that reads "Benjamin Pan".

( Engineer / Benjamin Pan )

Approved By

A handwritten signature in black ink that reads "Vincent Lin".

( Director / Vincent Lin )

## TABLE OF CONTENTS

	Description	Page
<b>1.</b>	<b>GENERAL INFORMATION .....</b>	<b>5</b>
1.1.	EUT Description.....	5
1.2.	Operational Description .....	7
1.3.	Tested System Details.....	8
1.4.	Configuration of Tested System .....	8
1.5.	EUT Exercise Software .....	9
1.6.	Test Facility .....	10
<b>2.</b>	<b>Conducted Emission.....</b>	<b>11</b>
2.1.	Test Equipment.....	11
2.2.	Test Setup .....	11
2.3.	Limits .....	12
2.4.	Test Procedure .....	12
2.5.	Uncertainty .....	12
2.6.	Test Result of Conducted Emission.....	13
<b>3.</b>	<b>Peak Power Output .....</b>	<b>15</b>
3.1.	Test Equipment.....	15
3.2.	Test Setup .....	15
3.3.	Limits .....	15
3.4.	Test Procedure .....	15
3.5.	Uncertainty .....	15
3.6.	Test Result of Peak Power Output.....	16
<b>4.</b>	<b>Radiated Emission .....</b>	<b>19</b>
4.1.	Test Equipment.....	19
4.2.	Test Setup .....	19
4.3.	Limits .....	20
4.4.	Test Procedure .....	21
4.5.	Uncertainty .....	21
4.6.	Test Result of Radiated Emission.....	22
<b>5.</b>	<b>RF antenna conducted test.....</b>	<b>34</b>
5.1.	Test Equipment.....	34
5.2.	Test Setup .....	34
5.3.	Limits .....	34
5.4.	Test Procedure .....	34
5.5.	Uncertainty .....	35
5.6.	Test Result of RF antenna conducted test.....	36
<b>6.</b>	<b>Band Edge .....</b>	<b>39</b>
6.1.	Test Equipment.....	39
6.2.	Test Setup .....	39
6.3.	Limits .....	40
6.4.	Test Procedure .....	40
6.5.	Uncertainty .....	40
6.6.	Test Result of Band Edge .....	41

---

<b>7.</b>	<b>Occupied Bandwidth .....</b>	<b>53</b>
7.1.	Test Equipment.....	53
7.2.	Test Setup .....	53
7.3.	Limits .....	53
7.4.	Test Procedure .....	53
7.5.	Uncertainty .....	53
7.6.	Test Result of Occupied Bandwidth .....	54
<b>8.</b>	<b>Power Density .....</b>	<b>63</b>
8.1.	Test Equipment.....	63
8.2.	Test Setup .....	63
8.3.	Limits .....	63
8.4.	Test Procedure .....	63
8.5.	Uncertainty .....	63
8.6.	Test Result of Power Density .....	64
<b>9.</b>	<b>EMI Reduction Method During Compliance Testing .....</b>	<b>73</b>

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Touch Panel
Trade Name	Core Brands, LLC
Model No.	TP7
FCC ID.	SCGTP72013
Frequency Range	2412-2462MHz for 802.11b/g/n-20BW
Number of Channels	802.11b/g/n-20MHz: 11
Data Speed	802.11b: 1-11Mbps, 802.11g: 6-54Mbps, 802.11n: up to 72.2Mbps
Type of Modulation	802.11b:DSSS (DBPSK, DQPSK, CCK) 802.11g/n:OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	PIFA Antenna
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	ARISTOTLE	RFA-02-P396-70-60	PIFA Antenna	4dBi for 2.4 GHz

Note:

1. The antenna of EUT is conform to FCC 15.203.

## 802.11b/g/n-20MHz Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 01:	2412 MHz	Channel 02:	2417 MHz	Channel 03:	2422 MHz	Channel 04:	2427 MHz
Channel 05:	2432 MHz	Channel 06:	2437 MHz	Channel 07:	2442 MHz	Channel 08:	2447 MHz
Channel 09:	2452 MHz	Channel 10:	2457 MHz	Channel 11:	2462 MHz		

## Note:

1. The EUT is a Touch Panel with a built-in 2.4GHz WLAN transceiver.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps 、 802.11g is 6Mbps 、 802.11n(20M-BW) is 7.2Mbps.
4. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g/n transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.

Test Mode:	Mode 1: Transmit (802.11b 1Mbps)
	Mode 2: Transmit (802.11g 6Mbps)
	Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Notebook PC	DELL	PP18L	36119001664	Non-Shielded, 1.8m
2 Test Fixture	N/A	N/A	N/A	N/A
3 iPod nano	Apple	A1199	YM733325VQ5	N/A
4 Earphone	Dr.AV	CD-806B	N/A	N/A
5 Power Adapter	APD	WA-30B12	359114675-AAAG	N/A

Signal Cable Type	Signal cable Description
A USB Cable	Shielded, 2.0m, with one ferrite core bonded.
B Test Fixture Cable	Non-Shielded, 0.1m
C LAN Cable	Shielded, 3.0m
D iPod Cable	Shielded, 1.2m
E Earphone Cable	Non-Shielded, 1.0m
F Power Adapter Cable	Non-Shielded, 1.8m

### 1.4. Configuration of Tested System



## 1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4
- (2) Execute “Tera Term Pro v.2.3” program on the Notebook PC.
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Press “OK” to start the continuous Transmit.
- (5) Verify that the EUT works properly.

## 1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site: <http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site: <http://www.quietek.com/>

Site Description: File on  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046  
Registration Number: 92195

Site Name: Quietek Corporation  
Site Address: No.5-22, Ruishukeng,  
Linkou Dist. New Taipei City 24451,  
Taiwan, R.O.C.  
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
E-Mail : [service@quietek.com](mailto:service@quietek.com)

FCC Accreditation Number: TW1014

## 2. Conducted Emission


### 2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2014	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2014	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2014	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2014	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

### 2.2. Test Setup



### 2.3. Limits

<b>FCC Part 15 Subpart C Paragraph 15.207 (dB<math>\mu</math>V) Limit</b>		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

### 2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

### 2.5. Uncertainty

± 2.26 dB

## 2.6. Test Result of Conducted Emission

Product : Touch Panel  
 Test Item : Conducted Emission Test  
 Power Line : Line 1  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dB $\mu$ V	dB $\mu$ V	dB	dB $\mu$ V
<b>Line 1</b>					
<b>Quasi-Peak</b>					
0.185	9.651	36.600	46.251	-18.749	65.000
0.318	9.657	33.040	42.697	-18.503	61.200
0.412	9.662	34.400	44.062	-14.452	58.514
0.779	9.682	38.720	48.402	-7.598	56.000
1.720	9.743	22.240	31.983	-24.017	56.000
15.255	10.089	23.050	33.139	-26.861	60.000
<b>Average</b>					
0.185	9.651	0.000	9.651	-45.349	55.000
0.318	9.657	0.000	9.657	-41.543	51.200
0.412	9.662	0.000	9.662	-38.852	48.514
0.779	9.682	0.000	9.682	-36.318	46.000
1.720	9.743	0.000	9.743	-36.257	46.000
15.255	10.089	0.000	10.089	-39.911	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. ““ means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : Touch Panel  
 Test Item : Conducted Emission Test  
 Power Line : Line 2  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dB $\mu$ V	dB $\mu$ V	dB	dB $\mu$ V
<b>Line 2</b>					
<b>Quasi-Peak</b>					
0.185	9.660	36.190	45.850	-19.150	65.000
0.306	9.657	33.020	42.677	-18.866	61.543
0.427	9.663	35.390	45.053	-13.033	58.086
0.701	9.679	43.310	52.988	-3.012	56.000
0.873	9.697	37.420	47.117	-8.883	56.000
1.627	9.748	25.380	35.128	-20.872	56.000
<b>Average</b>					
0.185	9.660	0.000	9.660	-45.340	55.000
0.306	9.657	0.000	9.657	-41.886	51.543
0.427	9.663	0.000	9.663	-38.423	48.086
0.701	9.679	0.000	9.678	-36.322	46.000
0.873	9.697	0.000	9.697	-36.303	46.000
1.627	9.748	0.000	9.748	-36.252	46.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. ““ means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

### 3. Peak Power Output


#### 3.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Power Meter	Anritsu	ML2495A/6K00003357	May, 2014
X Power Sensor	Anritsu	MA2411B/0738448	Jun, 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

#### 3.2. Test Setup



#### 3.3. Limits

The maximum peak power shall be less 1 Watt.

#### 3.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 section 9.1.3 PKPM1 Peak power meter method.

#### 3.5. Uncertainty

± 1.27 dB

### 3.6. Test Result of Peak Power Output

Product : Touch Panel  
 Test Item : Peak Power Output Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit	Result
		1	2	5.5	11			
		Measurement Level (dBm)						
01	2412	15.17	--	--	--	17.35	<30dBm	Pass
06	2437	15.35	15.34	15.33	15.31	17.48	<30dBm	Pass
11	2462	15.12	--	--	--	17.37	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product : Touch Panel  
 Test Item : Peak Power Output Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		6	9	12	18	24	36	48	54			
		Measurement Level (dBm)										
01	2412	13.43	--	--	--	--	--	--	--	21.69	<30dBm	Pass
06	2437	13.45	13.21	13.02	12.86	12.58	12.49	12.41	12.34	21.52	<30dBm	Pass
11	2462	13.48	--	--	--	--	--	--	--	21.41	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product : Touch Panel  
 Test Item : Peak Power Output Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		7.2	14.4	21.7	28.9	43.3	57.8	65	72.2			
		Measurement Level (dBm)										
01	2412	10.13	--	--	--	--	--	--	--	17.33	<30dBm	Pass
06	2437	10.37	10.29	10.23	10.17	10.04	9.99	9.93	9.89	17.45	<30dBm	Pass
11	2462	10.44	--	--	--	--	--	--	--	17.50	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

## 4. Radiated Emission

### 4.1. Test Equipment

The following test equipment are used during the radiated emission test:


Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X Loop Antenna		Teseq	HLA6120 / 26739	Jul., 2014
	X Bilog Antenna		Schaffner Chase	CBL6112B/2673	Sep., 2014
	X Horn Antenna		Schwarzbeck	BBHA9120D/D305	Sep., 2014
	X Horn Antenna		Schwarzbeck	BBHA9170/208	Jul., 2014
	X Pre-Amplifier		Agilent	8447D/2944A09549	Sep., 2014
	X Spectrum Analyzer		Agilent	E4407B / US39440758	May, 2014
	X Test Receiver		R & S	ESCS 30/ 825442/018	Sep., 2014
	X Coaxial Cable		QuiTek	QTK-CABLE/ CAB5	Feb., 2014
	X Controller		QuiTek	QTK-CONTROLLER/ CTRL3	N/A
	X Coaxial Switch		Anritsu	MP59B/6200265729	N/A

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.


2. The test instruments marked with “X” are used to measure the final test results.

### 4.2. Test Setup

Radiated Emission Below 1GHz



### Radiated Emission Above 1GHz



### 4.3. Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dB $\mu$ V/m) = 20 log E field strength (uV/m)

#### **4.4. Test Procedure**

The EUT was setup according to ANSI C63.10: 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2009 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The frequency range from 9kHz to 10th harmonics is checked.

#### **4.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

#### 4.6. Test Result of Radiated Emission

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4824.000	3.261	44.590	47.851	-26.149	74.000
7236.000	10.650	34.740	45.390	-28.610	74.000
9648.000	13.337	34.720	48.056	-25.944	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4824.000	6.421	41.900	48.321	-25.679	74.000
7236.000	11.495	35.230	46.725	-27.275	74.000
9648.000	13.807	35.260	49.066	-24.934	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4874.000	3.038	42.870	45.907	-28.093	74.000
7311.000	11.795	33.610	45.404	-28.596	74.000
9748.000	12.635	34.590	47.225	-26.775	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4874.000	5.812	37.800	43.611	-30.389	74.000
7311.000	12.630	33.740	46.369	-27.631	74.000
9748.000	13.126	34.610	47.736	-26.264	74.000

**Average Detector:**

--

**Note:**

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)

Frequency MHz	Correct Factor	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------	--------------------------------	--------------------------------------	--------------	-----------------------

### Horizontal

#### Peak Detector:

4924.000	2.858	41.190	44.047	-29.953	74.000
7386.000	12.127	34.110	46.238	-27.762	74.000
9848.000	12.852	34.150	47.003	-26.997	74.000

#### Average Detector:

--

### Vertical

#### Peak Detector:

4924.000	5.521	38.670	44.190	-29.810	74.000
7386.000	13.254	33.460	46.714	-27.286	74.000
9848.000	13.367	34.510	47.877	-26.123	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Frequency MHz	Correct Factor	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------	--------------------------------	--------------------------------------	--------------	-----------------------

### Horizontal

#### Peak Detector:

4824.000	3.261	44.770	48.031	-25.969	74.000
7236.000	10.650	33.660	44.310	-29.690	74.000
9648.000	13.337	35.570	48.906	-25.094	74.000

#### Average Detector:

--

### Vertical

#### Peak Detector:

4824.000	6.421	40.200	46.621	-27.379	74.000
7236.000	11.495	34.650	46.145	-27.855	74.000
9648.000	13.807	33.290	47.096	-26.904	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

### Horizontal

#### Peak Detector:

4874.000	3.038	42.140	45.177	-28.823	74.000
7311.000	11.795	33.830	45.624	-28.376	74.000
9748.000	12.635	34.450	47.085	-26.915	74.000

#### Average Detector:

--

#### Peak Detector:

4874.000	5.812	36.420	42.231	-31.769	74.000
7311.000	12.630	32.590	45.219	-28.781	74.000
9748.000	13.126	33.540	46.666	-27.334	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)

Frequency MHz	Correct Factor	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------	--------------------------------	--------------------------------------	--------------	-----------------------

### Horizontal

#### Peak Detector:

4924.000	2.858	41.500	44.357	-29.643	74.000
7386.000	12.127	34.040	46.168	-27.832	74.000
9848.000	12.852	34.430	47.283	-26.717	74.000

#### Average Detector:

--

### Vertical

#### Peak Detector:

4924.000	5.521	36.160	41.680	-32.320	74.000
7386.000	13.254	32.800	46.054	-27.946	74.000
9848.000	13.367	32.980	46.347	-27.653	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)(2412MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m

### Horizontal

#### Peak Detector:

4824.000	3.261	40.120	43.381	-30.619	74.000
7236.000	10.650	33.940	44.590	-29.410	74.000
9648.000	13.337	34.500	47.836	-26.164	74.000

#### Average Detector:

--

### Vertical

#### Peak Detector:

4824.000	6.421	36.790	43.211	-30.789	74.000
7236.000	11.495	33.590	45.085	-28.915	74.000
9648.000	13.807	32.920	46.726	-27.274	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4874.000	3.038	39.550	42.587	-31.413	74.000
7311.000	11.795	33.230	45.024	-28.976	74.000
9748.000	12.635	33.750	46.385	-27.615	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4874.000	5.812	35.690	41.501	-32.499	74.000
7311.000	12.630	32.680	45.309	-28.691	74.000
9748.000	13.126	33.280	46.406	-27.594	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

### Horizontal

#### Peak Detector:

4924.000	2.858	37.440	40.297	-33.703	74.000
7386.000	12.127	32.660	44.788	-29.212	74.000
9848.000	12.852	34.250	47.103	-26.897	74.000

#### Average Detector:

--

### Vertical

#### Peak Detector:

4924.000	5.521	35.460	40.980	-33.020	74.000
7386.000	13.254	32.710	45.964	-28.036	74.000
9848.000	13.367	34.330	47.697	-26.303	74.000

#### Average Detector:

--

#### Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Touch Panel  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)(2437 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
120.210	-7.275	45.218	37.943	-5.557	43.500
240.490	-6.662	42.547	35.884	-10.116	46.000
456.800	2.432	32.905	35.337	-10.663	46.000
612.000	3.403	30.784	34.186	-11.814	46.000
800.180	6.417	34.681	41.098	-4.902	46.000
940.830	6.760	25.194	31.954	-14.046	46.000
<b>Vertical</b>					
131.850	-3.855	41.028	37.173	-6.327	43.500
227.880	-6.169	36.367	30.199	-15.801	46.000
379.200	0.881	24.810	25.691	-20.309	46.000
517.910	0.571	30.341	30.912	-15.088	46.000
672.140	-0.561	29.619	29.058	-16.942	46.000
967.020	3.889	24.963	28.852	-25.148	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : Touch Panel  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)(2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
134.760	-7.473	43.957	36.484	-7.016	43.500
203.630	-10.357	48.264	37.906	-5.594	43.500
455.830	2.028	37.065	39.093	-6.907	46.000
612.000	3.403	31.333	34.735	-11.265	46.000
800.180	6.417	34.741	41.158	-4.842	46.000
970.900	7.347	24.623	31.970	-22.030	54.000
<b>Vertical</b>					
120.210	-7.275	40.986	33.711	-9.789	43.500
179.380	-0.824	39.189	38.365	-5.135	43.500
456.800	-3.328	29.941	26.613	-19.387	46.000
611.030	2.009	33.299	35.309	-10.691	46.000
833.160	1.716	31.926	33.642	-12.358	46.000
963.140	3.581	24.493	28.074	-25.926	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : Touch Panel  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)(2437 MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
120.210	-7.275	46.039	38.764	-4.736	43.500
228.850	-8.333	41.874	33.541	-12.459	46.000
408.300	0.235	37.629	37.864	-8.136	46.000
612.970	3.262	31.821	35.083	-10.917	46.000
799.210	6.413	32.750	39.163	-6.837	46.000
971.870	7.268	22.617	29.885	-24.115	54.000
<b>Vertical</b>					
120.210	-3.535	39.658	36.123	-7.377	43.500
180.350	-1.132	38.530	37.398	-6.102	43.500
408.300	-4.445	31.555	27.110	-18.890	46.000
612.000	1.943	27.600	29.542	-16.458	46.000
833.160	1.716	31.343	33.059	-12.941	46.000
967.990	3.907	24.476	28.383	-25.617	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss -Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

## 5. RF antenna conducted test


### 5.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.  
2. The test instruments marked with "X" are used to measure the final test results.

### 5.2. Test Setup

#### RF antenna Conducted Measurement:



### 5.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


## 5.5. Uncertainty

The measurement uncertainty  
Conducted is defined as  $\pm 1.27\text{dB}$


## 5.6. Test Result of RF antenna conducted test

Product : Touch Panel  
Test Item : RF antenna conducted test  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit (802.11b 1Mbps)


### Channel 01 (2412MHz)



### Channel 06 (2437MHz)




### Channel 11 (2462MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : Touch Panel  
Test Item : RF Antenna Conducted Spurious  
Test Site : No.3 OATS  
Test Mode : Mode 2: Transmit (802.11g 6Mbps)


### Channel 01 (2412MHz)



### Channel 06 (2437MHz)




### Channel 11 (2462MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : Touch Panel  
Test Item : RF Antenna Conducted Spurious  
Test Site : No.3 OATS  
Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)


### Channel 01 (2412MHz)



### Channel 06 (2437MHz)



### Channel 11 (2462MHz)



Note: The above test pattern is synthesized by multiple of the frequency range.

## 6. Band Edge

### 6.1. Test Equipment

#### RF Radiated Measurement:

The following test equipments are used during the band edge tests:


Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2014
	X Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2014
	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2014
	X Pre-Amplifier	Agilent	8447D/2944A09549	Sep., 2014
	X Spectrum Analyzer	Agilent	E4407B / US39440758	May, 2014
	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2014
	X Coaxial Cable	QuiTek	QTK-CABLE/ CAB5	Feb., 2014
	X Controller	QuiTek	QTK-CONTROLLER/ CTRL3	N/A
	X Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note:

1. All instruments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

### 6.2. Test Setup

#### RF Radiated Measurement:



### **6.3. Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

### **6.4. Test Procedure**

The EUT was setup according to ANSI C63.10: 2009 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2009 on radiated measurement.

### **6.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

## 6.6. Test Result of Band Edge

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2386.600	31.496	27.131	58.627	74.00	54.00	Pass
01 (Peak)	2390.000	31.509	25.122	56.631	74.00	54.00	Pass
01 (Peak)	2400.000	31.561	34.581	66.142	--	--	--
01 (Peak)	2413.400	31.649	70.912	102.561	--	--	--
01 (Average)	2386.200	31.494	13.788	45.282	74.00	54.00	Pass
01 (Average)	2390.000	31.509	12.908	44.417	74.00	54.00	Pass
01 (Average)	2400.000	31.561	28.494	60.055	--	--	--
01 (Average)	2414.600	31.659	66.644	98.302	--	--	--

Figure Channel 01:

Horizontal (Peak)





Figure Channel 01:

Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

#### RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2388.000	30.925	26.033	56.958	74.00	54.00	Pass
01 (Peak)	2390.000	30.915	24.313	55.228	74.00	54.00	Pass
01 (Peak)	2400.000	30.912	33.757	64.669	--	--	--
01 (Peak)	2413.400	30.959	70.440	101.399	--	--	--
01 (Average)	2387.000	30.929	13.481	44.410	74.00	54.00	Pass
01 (Average)	2390.000	30.915	12.844	43.759	74.00	54.00	Pass
01 (Average)	2400.000	30.912	27.734	58.646	--	--	--
01 (Average)	2414.800	30.968	66.200	97.168	--	--	--

Figure Channel 01:

Vertical (Peak)





Figure Channel 01:

Vertical (Average)




Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “\*”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)


#### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2462.900	32.026	71.658	103.684	--	--	--
11 (Peak)	2483.500	32.182	25.676	57.858	74.00	54.00	Pass
11 (Average)	2461.300	32.014	67.779	99.793	--	--	--
11 (Average)	2483.500	32.182	14.093	46.275	74.00	54.00	Pass

**Figure Channel 11: Horizontal (Peak)**



**Figure Channel 11: Horizontal (Average)**



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

#### RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2462.900	31.296	69.328	100.624	--	--	--
11 (Peak)	2483.500	31.435	25.435	56.870	74.00	54.00	Pass
11 (Average)	2461.100	31.285	65.541	96.825	--	--	--
11 (Average)	2483.500	31.435	13.375	44.810	74.00	54.00	Pass

Figure Channel 11:

Vertical (Peak)





Figure Channel 11:

Vertical (Average)





Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2389.800	31.508	40.103	71.611	74.00	54.00	Pass
01 (Peak)	2390.000	31.509	38.859	70.368	74.00	54.00	Pass
01 (Peak)	2400.000	31.561	51.084	82.645	--	--	--
01 (Peak)	2414.800	31.660	71.592	103.252	--	--	--
01(Average)	2390.000	31.509	22.449	53.958	74.00	54.00	Pass
01(Average)	2400.000	31.561	34.492	66.053	--	--	--
01(Average)	2407.200	31.606	61.395	93.001	--	--	--

**Figure Channel 01:**
**Horizontal (Peak)**

**Figure Channel 01:**
**Horizontal (Average)**


Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “\*”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

#### RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	30.915	37.580	68.495	74.00	54.00	Pass
01 (Peak)	2400.000	30.912	50.001	80.913	--	--	--
01 (Peak)	2414.600	30.967	71.039	102.006	--	--	--
01 (Average)	2390.000	30.915	21.560	52.475	74.00	54.00	Pass
01 (Average)	2400.000	30.912	33.634	64.546	--	--	--
01 (Average)	2416.000	30.977	60.852	91.828	--	--	--

Figure Channel 01:

Vertical (Peak)





Figure Channel 01:

Vertical (Average)





Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “\*”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2467.900	32.064	71.526	103.590	--	--	--
11 (Peak)	2483.500	32.182	35.120	67.302	74.00	54.00	Pass
11 (Average)	2467.100	32.058	61.753	93.811	--	--	--
11 (Average)	2483.500	32.182	20.361	52.543	74.00	54.00	Pass

**Figure Channel 11:**
**Horizontal (Peak)**

**Figure Channel 11:**
**Horizontal (Average)**


Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.


Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

**RF Radiated Measurement (Vertical):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2459.300	31.272	69.684	100.956	--	--	--
11 (Peak)	2483.500	31.435	34.529	65.964	74.00	54.00	Pass
11 (Average)	2467.300	31.326	59.860	91.186	--	--	--
11 (Average)	2483.500	31.435	19.244	50.679	74.00	54.00	Pass


**Figure Channel 11:**

**Vertical (Peak)**



**Figure Channel 11:**

**Vertical (Average)**



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

#### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	31.509	37.863	69.372	74.00	54.00	Pass
01 (Peak)	2400.000	31.561	47.670	79.231	--	--	--
01 (Peak)	2408.800	31.617	68.273	99.890	--	--	--
01 (Average)	2390.000	31.509	19.238	50.747	74.00	54.00	Pass
01 (Average)	2400.000	31.561	28.921	60.482	--	--	--
01 (Average)	2406.600	31.603	57.907	89.510	--	--	--

Figure Channel 01:

Horizontal (Peak)





Figure Channel 01:

Horizontal (Average)





Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

**RF Radiated Measurement (Vertical):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
01 (Peak)	2390.000	30.915	36.627	67.542	74.00	54.00	Pass
01 (Peak)	2400.000	30.912	46.619	77.531	--	--	--
01 (Peak)	2415.400	30.972	67.587	98.559	--	--	--
01 (Average)	2390.000	30.915	18.679	49.594	74.00	54.00	Pass
01 (Average)	2400.000	30.912	28.177	59.089	--	--	--
01 (Average)	2415.200	30.971	57.412	88.383	--	--	--

**Figure Channel 01:**
**Vertical (Peak)**

**Figure Channel 01:**
**Vertical (Average)**




Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2458.900	31.997	69.130	101.126	--	--	--
11 (Peak)	2483.500	32.182	33.366	65.548	74.00	54.00	Pass
11 (Average)	2467.300	32.059	58.781	90.840	--	--	--
11 (Average)	2483.500	32.182	17.638	49.820	74.00	54.00	Pass

**Figure Channel 11:**
**Horizontal (Peak)**

**Figure Channel 11:**
**Horizontal (Average)**


Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : Touch Panel  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

#### RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
11 (Peak)	2458.900	31.270	67.200	98.469	--	--	--
11 (Peak)	2483.500	31.435	31.764	63.199	74.00	54.00	Pass
11 (Average)	2467.300	31.326	56.776	88.102	--	--	--
11 (Average)	2483.500	31.435	16.694	48.129	74.00	54.00	Pass

Figure Channel 11:

Vertical (Peak)





Figure Channel 11:

Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “\*”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correct Factor.
6. The average measurement was not performed when the peak measured data under the limit of average detection.

## 7. Occupied Bandwidth


### 7.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

### 7.2. Test Setup



### 7.3. Limits

The minimum bandwidth shall be at least 500 kHz.

### 7.4. Test Procedure

The EUT was setup according to ANSI C63.10: 2009; tested according to DTS test procedure of Jan KDB558074 for compliance to FCC 47CFR 15.247 requirements.

### 7.5. Uncertainty


± 150Hz

## 7.6. Test Result of Occupied Bandwidth

Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412	10200	>500	Pass


**Figure Channel 1:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6	2437	10200	>500	Pass


**Figure Channel 6:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11	2462	10150	>500	Pass


**Figure Channel 11:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412	16400	>500	Pass


**Figure Channel 1:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6	2437	16400	>500	Pass


**Figure Channel 6:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11	2462	16400	>500	Pass


**Figure Channel 11:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412	17150	>500	Pass


**Figure Channel 1:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6	2437	17400	>500	Pass


**Figure Channel 6:**



Product : Touch Panel  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11	2462	17400	>500	Pass

**Figure Channel 11:**



## 8. Power Density


### 8.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2014
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2014
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2014

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

### 8.2. Test Setup



### 8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

### 8.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2009; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using KDB 558074 section 10.2 PKPSD (peak PSD) method.

### 8.5. Uncertainty


± 1.27 dB

## 8.6. Test Result of Power Density

Product : Touch Panel  
Test Item : Power Density Data  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412	3.82	< 8dBm	Pass


Figure Channel 1:



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437	3.79	< 8dBm	Pass


**Figure Channel 6:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462	4.33	< 8dBm	Pass


**Figure Channel 11:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412	1.78	< 8dBm	Pass


**Figure Channel 1:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437	2.02	< 8dBm	Pass


**Figure Channel 6:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462	1.96	< 8dBm	Pass


**Figure Channel 11:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412	-1.35	< 8dBm	Pass


**Figure Channel 1:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437	-1.18	< 8dBm	Pass


**Figure Channel 6:**



Product : Touch Panel  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462	-1.21	< 8dBm	Pass

**Figure Channel 11:**



**9. EMI Reduction Method During Compliance Testing**

No modification was made during testing.