



Certification Exhibit

FCC ID: SDBGFLCI

FCC Rule Part: 47 CFR Part 2.1091

TÜV SÜD Project Number: 72144119.200

**Manufacturer: Sensus Metering Systems, Inc.
Model: GFL3CI**

RF Exposure

General Information:

Applicant: Sensus Metering Systems, Inc.
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Modified Monopole
 Antenna Gain: -1 dBi
 Maximum Transmitter Conducted Power: 30.57 dBm, 1140 mW
 Maximum System EIRP: 29.57 dBm, 906 mW
 Exposure Conditions: 20 centimeters or greater

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm²)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

| Transmit Frequency (MHz) | Radio Power (dBm) | Power Density Limit (mW/Cm ²) | Radio Power (mW) | Antenna Gain (dBi) | Antenna Gain (mW eq.) | Distance (cm) | Power Density (mW/cm ²) |
|--------------------------|-------------------|---|------------------|--------------------|-----------------------|---------------|-------------------------------------|
| 901 | 30.57 | 0.60 | 1140.25 | -1 | 0.794 | 20 | 0.180 |