



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: SDBVGBM4601**

**FCC Rule Part: CFR 47 Part 101 Subpart C**

**ACS Project Number: 12-2008**

Manufacturer: Sensus Metering Systems, Inc.  
Model: M4601

## **RF Exposure**

**General Information:**

Applicant: Sensus Metering Systems, Inc.  
 ACS Project: 12-2008  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: ASPG918 Elevated Feedpoint Antenna  
 Antenna Gain: 5.15 dBi  
 Maximum Transmitter Conducted Power: 34.01 dBm  
 Maximum System EIRP: 39.16 dBm, 8241.4 mW  
 Exposure Conditions: Greater than 33 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

| MPE Calculator for Mobile Equipment<br>Limits for General Population/Uncontrolled Exposure* |                   |   |                  |                    |                       |               |                                     |
|---|-------------------|---|------------------|--------------------|-----------------------|---------------|-------------------------------------|
| Transmit Frequency (MHz)  | Radio Power (dBm) | Power Density Limit (mW/Cm <sup>2</sup> ) | Radio Power (mW) | Antenna Gain (dBi) | Antenna Gain (mW eq.) | Distance (cm) | Power Density (mW/cm <sup>2</sup> ) |
| 959.925   | 34.01             | 0.64                                      | 2517.68          | 5.15               | 3.273                 | 33            | 0.602                               |

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 33 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.