



Shenzhen BCT Technology Co., Ltd.

Report No.: BCT1000101085JN

FCC ID TEST REPORT

for

Bluetooth keyboard

MODEL: BK02

FCC ID: SF4-BK02

Test Report Number: BCT1000101085JN

Issued Date: May 10, 2011

Issued for

ATI Electronics (ShenZhen) Co.,LTD

**2/F,A Tower,Tangyanshan Industrial Park Tangkeng
Village,Shiyan Town Shenzhen,China**

Issued By:

Shenzhen BCT Technology Co., Ltd.

**B Building Room8518, Multiple Use Building of Economic Cooperative, Team one, Anle
country, No. 44 of Xin'an Block, Bao'an Area, Shenzhen**

TEL: +86-755- 33865088

FAX: +86-755- 36933236

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen BCT Technology Co., Ltd. This document may be altered or revised by Shenzhen BCT Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



Revision History Of Report

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	BCT1000101085JN	Initial Issue	ALL	Kallen Wang



TABLE OF CONTENTS


1	TEST CERTIFICATION	4
3	EUT DESCRIPTION	6
4	TEST METHODOLOGY	7
	4.1. DECISION OF FINAL TEST MODE.....	7
	4.2. EUT SYSTEM OPERATION.....	7
5	SETUP OF EQUIPMENT UNDER TEST	8
	5.1. DESCRIPTION OF SUPPORT UNITS	8
	5.2. CONFIGURATION OF SYSTEM UNDER TEST	8
6	FACILITIES AND ACCREDITATIONS	9
	6.1. FACILITIES	9
	6.2. ACCREDITATIONS	9
	6.3. MEASUREMENT UNCERTAINTY.....	9
7	TEST REQUIREMENTS	10
	7.1. CONDUCTED EMISSION MEASUREMENT.....	10
	7.2. Radiation Emission Test	14
	7.3. Band edge test.....	21
	8. Antenna requirement.....	24
9	PHOTOGRAPHS OF THE TEST CONFIGURATION	25




1 TEST CERTIFICATION

Product:	Bluetooth keyboard
Model:	BK02
Applicant:	ATI Electronics (ShenZhen) Co.,LTD 2/F,A Tower,Tangyanshan Industrial Park Tangkeng Village,Shiyan Town Shenzhen,China
Factory:	ATI Electronics (ShenZhen) Co.,LTD 2/F,A Tower,Tangyanshan Industrial Park Tangkeng Village,Shiyan Town Shenzhen,China
Trade Mark:	N/A
Tested:	May 6, 2011 -May 10, 2011
Test Voltage:	DC 3.7 V Battery
Applicable Standards:	FCC Part 15:Subpart C ANSI C63.4:2003


The above equipment has been tested by World Standardization Certification & Testing Co., Ltd., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: 
(Davis zhou)

Date: May 10, 2011

Check By: 
(Mike mo)

Date: May 10, 2011

Approved By: 
(Kallen Wang)

Date: May 10, 2011



2 TEST RESULT SUMMARY

Standard	Item	Result
FCC Part 15 Subpart C: Clause 15.249	Conducted emission Test	PASS
	Radiation Emission Test	PASS
	Band Edge Test	PASS

- Note:**
1. The test result judgment is decided by the limit of test standard
 2. The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	Bluetooth keyboard
Trade Mark	N/A
Model	BK02
Applicant	ATI Electronics (ShenZhen) Co.,LTD
Serial Number	N/A
Antenna Type	PCB Antenna
EUT Power Rating	DC 3.7 V Battery
Temperature Range(Operating)	+15 ~+ 35°C
Operating Frequency	2402MHz to 2480MHz
Number of Channels	79 Channels

Note: N/A stand for no applicable.

Models difference

N/A



4 TEST METHODOLOGY

4.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and configuration, which produced the worst emission levels, was selected and recorded in this report.

The measurement was performed at 3 axis for lie orientation, side orientation and stand orientation. The lie orientation is the worst mode, so only the worst mode test data was reported.

The following test mode was recorder in this report.

Test item	Test mode
Conducted emission Test	N/A
Radiation Emission Test	CH1, CH40, CH79
Band Edge Test	CH1, CH79,

4.2. EUT SYSTEM OPERATION

1. Set up EUT with the support equipments.
2. Make sure the EUT transmitting continuously during the test.



5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Manufacturer	Description	Model	Serial Number	FCC
N/A	N/A	N/A	N/A	N/A

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST





6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **Building A, Baoshi Road, Baoshi Science & Technology Park, Bao'an District, Shenzhen, Guangdong, China**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC (The certificate registration number is 131628)
Canada	INDUSTRY CANADA (The certificated registration number is 46405-7700)
China	CNAS (The certificated registration number is L3732)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct.org.cn>

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty	
Conducted emissions	9kHz~30MHz	+/- 3.59dB	
Radiated emissions	Horizontal	30MHz ~ 200MHz	+/- 4.77dB
		200MHz ~1000MHz	+/- 4.93dB
	Vertical	30MHz ~ 200MHz	+/- 5.04dB
		200MHz ~1000MHz	+/- 4.93dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



7 TEST REQUIREMENTS

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. LIMITS

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	100005	06/23/2011
LISN	AFJ	LS16	16010222119	09/29/2011
LISN(EUT)	Mestec	AN3016	04/10040	09/28/2011

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).
2. N.C.R = No Calibration Request.

7.1.3. TEST PROCEDURES


The EUT was put on a wooden table which was 0.8metre high above the ground and connected to the AC mains through a Artificial Mains Network (A.M.N). The mains lead in excess of 1 m separating the EUT from the AMN was folded back and forth parallel to the lead so as to form a bundle with a length of 0.3m to 0.4m. The EUT was kept 0.4m from any other earthed conducting surface. Both sides of AC line were checked to find out the maximum conducted emission levels according to the test procedure during conducted emission test.

The bandwidth of the test receiver (ESCI) was set at 9KHz.

The frequency range from 150 KHz to 30 MHz was investigated.

The test data of the worst-case condition(s) was recorded.

7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


7.1.5. Test Result

Test model: Charging

PASS



Conducted Emission Measurement



Site 843 Shielded Room

Phase: L1

Temperature: 26

Humidity: 55 %


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2819	39.32	10.84	50.16	60.76	-10.60	QP	
2		0.2819	17.72	10.84	28.56	50.76	-22.20	AVG	
3		0.3700	31.26	10.75	42.01	58.50	-16.49	QP	
4		0.3700	14.69	10.75	25.44	48.50	-23.06	AVG	
5		0.6140	32.98	10.48	43.46	56.00	-12.54	QP	
6		0.6140	10.97	10.48	21.45	46.00	-24.55	AVG	
7		1.0980	32.35	10.25	42.60	56.00	-13.40	QP	
8		1.0980	10.71	10.25	20.96	46.00	-25.04	AVG	
9	*	2.5059	37.52	10.32	47.84	56.00	-8.16	QP	
10		2.5059	9.14	10.32	19.46	46.00	-26.54	AVG	
11		3.5420	34.67	10.36	45.03	56.00	-10.97	QP	
12		3.5420	10.61	10.36	20.97	46.00	-25.03	AVG	

*:Maximum data x:Over limit l:over margin

<Reference Only



Conducted Emission Measurement



Site 843 Shielded Room

Phase: N

Temperature: 26

Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2819	35.25	10.84	46.09	60.76	-14.67	QP	
2		0.2819	22.46	10.84	33.30	50.76	-17.46	AVG	
3		0.4220	33.94	10.67	44.61	57.41	-12.80	QP	
4		0.4220	20.03	10.67	30.70	47.41	-16.71	AVG	
5	*	0.5660	38.69	10.51	49.20	56.00	-6.80	QP	
6		0.5660	18.61	10.51	29.12	46.00	-16.88	AVG	
7		0.6940	35.29	10.43	45.72	56.00	-10.28	QP	
8		0.6940	12.00	10.43	22.43	46.00	-23.57	AVG	
9		1.6620	37.53	10.27	47.80	56.00	-8.20	QP	
10		1.6620	19.98	10.27	30.25	46.00	-15.75	AVG	
11		2.3460	34.97	10.30	45.27	56.00	-10.73	QP	
12		2.3460	19.19	10.30	29.49	46.00	-16.51	AVG	

*:Maximum data x:Over limit !:over margin

<Reference Only



7.2. Radiation Emission Test

7.2.1. Limits

According to 15.249 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency	Field Strength of Fundamental		Field Strength of Spurious	
	mV/meter	dBuV/meter	uV/meter	dBuV/meter
902-928MHz	50	94	500	54
2400-2483.5MHz	50	94	500	54
5725-5875MHz	50	94	500	54
24.0-24.25GHz	250	108	2500	68

The above field strength limits are specified at a distance of 3 meters. Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength uV/meter	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Frequency Range of Radiated Measurement

According to 15.33(a), the intentional radiator operates below 10GHz, must be measured up to the tenth harmonic of the highest fundamental frequency or 40GHz, whichever is lower



7.2.2. TEST INSTRUMENT

966 Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	06/23/2011
Spectrum Analyzer	R&S	FSU	100114	04/14/2012
Pre Amplifier	H.P.	HP8447E	2945A02715	06/23/2011
Pre-Amplifier	Compliance	PAM0118	1360976	06/04/2011
Bilog Antenna	SUNOL Sciences	JB3	A021907	06/10/2011
Horn Antenna	Compliance	CE18000	001	06/10/2011
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	06/09/2011
Cable	TIME MICROWAVE	--	--	06/09/2011
System-Controller	CCS	N/A	N/A	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R



7.2.3. Test procedure

The EUT was placed on a turn table which was 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on a antenna tower. At the frequency band of 30MHz to 1GHz, The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 to 4 m for horizontal and vertical polarizations. The broadband antenna (calibrated by dipole antenna) was used as a receiving antenna. At the frequency band of 1GHz to 18GHz, The measuring antenna moved from 1 to 4 m for horizontal and vertical polarization. The horn antenna was used as a receiving antenna.

The resolution bandwidth and video bandwidth of the test receiver was 120 KHz and 300KHz for Quasi-peak detection at frequency below 1GHz.

The resolution bandwidth and video bandwidth of the test receiver was 1MHz and 3MHz for Peak emission measurement above 1GHz .


For Average emission above 1GHz , the resolution bandwidth and video bandwidth of the test receiver was 1MHz and 10Hz.

The EUT was tested in Chamber Site.


The test data of the worst case condition(s) was reported on the following pages.

7.2.4 Test setup diagram

Below 1GHz



Above 1GHz





7.2.5. Test Result

A. Fundamental Radiated Emission Data

Product: Bluetooth keyboard Test mode: CH Low~CH High
Test Item: Fundamental Radiated Emission Data Temperature: 25°C
Test Voltage: DC 3.7V Battery Humidity: 56%RH
Test Result: PASS

CH Low

Freq. (MHz)	Emission(dBμV/m) Peak Detector/ AV	HORIZ/ VERT	Limits(dBμV/m) Peak/Average	Margin (dB)
2402.00	91.6/ 73.2	HORIZ	114/94	22.4/20.8
2402.00	94.6 / 76.7	VERT	114/94	19.4/17.3

CH Middle

Freq. (MHz)	Emission(dBμV/m) Peak Detector/ AV	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
2441.00	92.4/73.8	HORIZ	114/94	21.6/20.2
2441.00	93.6/74.2	VERT	114/94	20.4/19.8

CH High

Freq. (MHz)	Emission(dBμV/m) Peak Detector/ AV	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
2480.0	92.9/75.5	HORIZ	114/94	21.1/18.5
2480.0	94.3/77.0	VERT	114/94	19.7/17.0

**B.Harmonics Radiated Emission Data**

Product: Bluetooth keyboard Test mode: CH Low~CH High
Test Item: Radiated Emission Data Temperature: 25°C
Test Voltage: DC 3.7V Battery Humidity: 56%RH
Test Result: PASS

CH Low

Freq. (MHz)	Emission(dBuV/m) Peak Detector	HORIZ/ VERT	Limits(dBuV/m) Peak/ Average	Margin (dB)
4804.12	-	H/V	74.0/54.0	-
7206.18	-	H/V	74.0/54.0	-
9608.24	-	H/V	74.0/54.0	-
12010.3	-	H/V	74.0/54.0	-
14412.36	-	H/V	74.0/54.0	-
16814.42	-	H/V	74.0/54.0	-
19216.48	-	H/V	74.0/54.0	-
21618.54	-	H/V	74.0/54.0	-
24020.6	-	H/V	74.0/54.0	-

CH Mitte

Freq. (MHz)	Emission(dBuV/m) Peak Detector	HORIZ/ VERT	Limits(dBuV/m) Peak/ Average	Margin (dB)
4882.18	-	H/V	74.0/54.0	-
7323.27	-	H/V	74.0/54.0	-
9764.36	-	H/V	74.0/54.0	-
12205.45	-	H/V	74.0/54.0	-
14646.54	-	H/V	74.0/54.0	-
17087.63	-	H/V	74.0/54.0	-
19528.72	-	H/V	74.0/54.0	-
21969.81	-	H/V	74.0/54.0	-
24410.9	-	H/V	74.0/54.0	-



CH High

Freq. (MHz)	Emission(dBμV/m) Peak Detector	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
4960.26	-	H/V	74.0/54.0	-
7440.39	-	H/V	74.0/54.0	-
9920.52	-	H/V	74.0/54.0	-
12400.65	-	H/V	74.0/54.0	-
14880.78	-	H/V	74.0/54.0	-
17360.91	-	H/V	74.0/54.0	-
19841.04	-	H/V	74.0/54.0	-
22321.17	-	H/V	74.0/54.0	-
24801.3	-	H/V	74.0/54.0	-

Note: - means the emission is too low at least 20dB to the limit.

C. General Radiated Emission Data

Product:	Bluetooth keyboard	Test mode:	transmitting
Test Item:	Radiated Emission Data	Temperature:	25°C
Test Voltage:	DC 5.0V Battery	Humidity:	56%RH
Test Result:	PASS		

Freq. (MHz)	Emission(dBμV/m) Peak Detector	HORIZ/ VERT	Limits(dBμV/m) Peak/ Average	Margin (dB)
96.82	30.3	HORIZ	43.5	13.2
96.82	32.6	VERT	43.5	10.9
195.53	27.5	HORIZ	43.5	16.0
195.53	30.7	VERT	43.5	12.8
432.43	29.8	HORIZ	46	16.2
432.43	32.6	VERT	46	13.4



7.3. Band edge test

7.3.1. Limits

According 15.249(d), Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

7.3.2. TEST INSTRUMENT

Same as 7.2.2

7.3.3. Test procedure

1. The EUT was placed on a turntable which is 0.8m above ground plane.
2. Set EUT as continuous transmitting mode.
3. Set the EUT work on the CH1, CH79 individually.
4. Set SPA Frequency = Operation frequency, for PK: RBW = 1MHz, VBW = 3MHz
5. Set SPA trace max hold, then view.


7.3.4. Test setup diagram

Same as 7.2.4



7.3.5. Test result


Product:	Bluetooth keyboard	Test mode:	CH Low,CH High
Test Item:	bandedge	Temperature:	25°C
Test Voltage:	DC 3.7V Battery	Humidity:	56%RH
Test Result:	PASS		



Emission in the Restricted Bands

Frequency [MHz]	dBc [dB]	AV [dBμV/m]	Polarity (H/V)	AV limit [dBμV/m]
2310	-	34.6	V	54
2385	-	34.7	V	54
2390	-	34.8	V	54

The above field strength levels were measured in Vertical polarity which is the worst case.



Emission in the Restricted Bands

Frequency [MHz]	dBc [dB]	AV [dBμV/m]	Polarity (H/V)	AV limit [dBμV/m]
2483.5	-	32.87	V	54
2493.4	-	33.08	V	54
2500	-	33.83	V	54

The above field strength levels were measured in Vertical polarity which is the worst case.



8. Antenna requirement

8.1. Standard applicable


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2. Antenna connected construction

The antenna used in this product is PCB antenna and no consideration of replacement.

9 PHOTOGRAPHS OF THE TEST CONFIGURATION

RADIATED EMISSION TEST







CONDUCTED EMISSION TEST

