



Report No.: SZ12030133W01



# FCC TEST REPORT

Issued to

**Qingdao Haier Telecom Co., Ltd**

For

**Mobile phone**

Model Name: HC-C380  
 Brand Name: Haier  
 Trade Name: N/A  
 FCC ID: SG71204HC-C380  
 Standard: 47 CFR Part 2  
 47 CFR Part 22 Subpart H  
 47 CFR Part 24 Subpart E  
 Test date: 2012-3-13 to 2012-4-26  
 Issue date: 2012-4-28

**Shenzhen Morlab Communications Technology Co., Ltd.**



Tested by Lu Lei  
Lu Lei

Date 2012.4.28

Approved by Wang Huarui  
Wang Huarui

Date 2012.04.28

Review by Peng Huarui  
Peng Huarui

Date 2012.4.28



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



## TABLE OF CONTENTS

<b>1.</b>	<b>GENERAL INFORMATION .....</b>	<b>3</b>
<b>1.1</b>	<b>EUT Description .....</b>	<b>3</b>
<b>1.2</b>	<b>Test Standards and Results .....</b>	<b>4</b>
<b>1.3</b>	<b>Facilities and Accreditations .....</b>	<b>5</b>
<b>2.</b>	<b>47 CFR PART 2, PART 22H &amp; 24E REQUIREMENTS .....</b>	<b>6</b>
<b>2.1</b>	<b>Conducted RF Output Power .....</b>	<b>6</b>
<b>2.2</b>	<b>99% Occupied Bandwidth .....</b>	<b>11</b>
<b>2.3</b>	<b>Frequency Stability .....</b>	<b>15</b>
<b>2.4</b>	<b>Conducted Out of Band Emissions .....</b>	<b>17</b>
<b>2.5</b>	<b>Band Edge .....</b>	<b>20</b>
<b>2.6</b>	<b>Transmitter Radiated Power (EIRP/ERP) .....</b>	<b>23</b>
<b>2.7</b>	<b>Radiated Out of Band Emissions .....</b>	<b>27</b>

Change History		
Issue	Date	Reason for change
1.0	April 28, 2012	First edition

## 1. GENERAL INFORMATION

### 1.1 EUT Description

EUT Type .....: Mobile phone  
Model Name .....: HC-C380  
Serial No.....: (n.a, marked #1 by test site)  
Hardware Version .....: SP  
Software Version .....: HC-C380\_C-S010  
Applicant .....: Qingdao Haier Telecom Co., Ltd  
No.1 Haier Road, Hi-tech Zone,Qingdao,266101,P.R.China  
Qingdao Haier Telecom Co., Ltd  
Manufacturer .....: No.1 Haier Road, Hi-tech Zone,Qingdao,266101,P.R.China  
Frequency Range .....: CDMA 800MHz:  
Tx: 824.7-848.31 MHz;  
Rx: 869.7-893.31MHz  
CDMA 1900MHz:  
Tx: 1851.25 MHz-1908.75 MHz;  
Rx: 1931.25 MHz-1988.75 MHz  
  
Modulation Type.....: CDMA 1X  
Emission Designators .....: 1M29F9W  
Modulation Type.....: Chip Antenna

*Note 1:* The EUT is a model of mobile Phone operating in Cellular and PCS bands.

*Note 2:* The normal configuration for the EUT is the Mobile Phone (MS) associated with ancillary equipments e.g. the Battery and/or the AC Adapter (Charger).

*Note 3:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 1.2 Test Standards and Results

The objective of the report is to perform testing according to:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-09 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-09 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-09 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

N o.	Section in CFR	Description	Test Band	Result
1	2.1046	Conducted RF Output Power	CDMA 800/1900MHz	PASS
2	2.1049	Occupied Bandwidth	CDMA 800/1900MHz	PASS
3	2.1055 22.355 24.235	Frequency Stability	CDMA 800/1900MHz	PASS
4	2.1051 2.1057 22.917 24.238	Conducted Out of Band Emissions	CDMA 800/1900MHz	PASS
5	2.1051 2.1057 22.917 24.238	Band Edge	CDMA 800/1900MHz	PASS
6	22.913 24.232	Transmitter Radiated Power (EIPR/ERP)	CDMA 800/1900MHz	PASS
7	2.1053 2.1057 22.917 24.238	Radiated Out of Band Emissions	CDMA 800/1900MHz	PASS

NOTE: Measurement method according to ANSI/TIA-603-D 2010.



## **1.3 Facilities and Accreditations**

### **1.3.1 Facilities**

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### **1.3.2 Test Environment Conditions**

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

## 2. 47 CFR PART 2, PART 22H & 24E REQUIREMENTS


### 2.1 Conducted RF Output Power

#### 2.1.1 Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified

#### 2.1.2 Test Description

##### 1. Test Setup:



The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. A call is established between the EUT and the SS.

##### 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
System Simulator	Agilent	E5515C	GB43130131	2011.05
Spectrum Analyzer	Agilent	E7405A	US44210471	2011.05
Power Splitter	Weinschel	1506A	NW521	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)

#### 2.1.3 Test Result


Here the lowest, middle and highest channels are selected to perform testing to verify the conducted

RF output power of the EUT. For the CDMA 800MHz operates at maximum output Power, the rated conducted RF output power is 38.5dBm, and For the CDMA 1900MHz operates at maximum output Power, the rated conducted RF output power is 33dBm.


1. Test Verdict:

No.	Channel Number	Frequency (MHz)	Measured Power		Rated Power	
			dBm	W	dBm	W
CDMA 800MHz	1013	824.7	26.34	0.43053	38.5	7
	384	836.52	26.84	0.48306		
	777	848.31	27.01	0.50234		
CDMA 1900MHz	25	1850.2	25.64	0.36644	33	2
	600	1880.0	24.5	0.28184		
	1175	1909.8	24.23	0.26485		


2. Test Plots:



(Plot A: CDMA 800MHz Channel = 1013)




(Plot B: CDMA 800MHz Channel = 384)




(Plot C: CDMA 800MHz Channel = 777)






(Plot D: CDMA 1900MHz Channel = 25)



(Plot E: CDMA 1900MHz Channel = 600)



(Plot F: CDMA 1900MHz Channel = 1175)

## 2.2 99% Occupied Bandwidth

### 2.2.1 Definition

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth.

### 2.2.2 Test Description

See section 2.1.2 of this report.


### 2.2.3 Test Verdict

Here the lowest, middle and highest channels are tested to record the 99% occupied bandwidth.


#### 1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured 99% Occupied Bandwidth (MHz)	Refer to Plot
CDMA 800MHz	1013	824.7	1.2617 MHz	Plot A
	384	836.52	1.2658 MHz	Plot B
	777	848.31	1.2935 MHz	Plot C
CDMA 1900MHz	25	1850.2	1.2673 MHz	Plot D
	600	1880.0	1.2651 MHz	Plot E
	1175	1909.8	1.2075 MHz	Plot F


2. Test Plots:




(Plot A: CDMA 800MHz Channel = 1013)




(Plot B: CDMA 800MHz Channel = 384)




(Plot C: CDMA 800MHz Channel = 777)



(Plot D: CDMA 1900MHz Channel = 25)



(Plot E: CDMA 1900MHz Channel = 600)



(Plot F: CDMA 1900MHz Channel = 1175)

## 2.3 Frequency Stability


### 2.3.1 Requirement

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  at intervals of not more than  $10^{\circ}\text{C}$ .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

### 2.3.2 Test Description

#### 1. Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power. A call is established between the EUT and the SS via a Common Antenna.

#### 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
System Simulator	Agilent	E5515C	GB43130131	2011.05
DC Power Supply	Good Will	GPS-3030DD	EF920938	2011.05
Temperature Chamber	YinHe Experimental Equip.	HL4003T	(n.a.)	2011.05

### 2.3.3 Test Verdict

The nominal, highest and lowest extreme voltages are separately 3.7VDC, 4.2VDC and 3.4VDC, which are specified by the applicant; the normal temperature here used is  $25^{\circ}\text{C}$ . The frequency deviation limit of CDMA 800MHz band is  $\pm 2.5\text{ppm}$ , CDMA 1900MHz is  $\pm 1\text{ppm}$ .



Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 1013 (824.7MHz)		Channel = 384 (836.52MHz)		Channel = 777 (848.31MHz)		
			Hz	Limits	Hz	Limits	Hz	Limits	
CDMA 800MHz	3.7	-30	7.06	±2061.7 5	26.75	±2091. 30	-16.29	±2120.7 75	PASS
		-20	-21.13		-11.01		29.37		
		-10	17.01		11.54		-11.06		
		0	3.20		-4.85		35.04		
		+10	-5.17		13.32		-22.26		
		+20	14.51		5.09		35.09		
		+30	20.79		23.04		26.75		
		+40	-18.75		-10.26		-11.08		
		+50	17.43		21.09		21.44		
	4.2	+25	13.27	-17.85	-7.85				
3.4	+25	14.34	15.32	25.32					
Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 25 (1851.2MHz)		Channel = 600 (1880.0MHz)		Channel = 1175 (1908.8MHz)		
			Hz	Limits	Hz	Limits	Hz	Limits	
CDMA 1900MHz	3.7	-30	-16.11	±1851.2	15.06	±1880.0	-9.54	±1908.8	PASS
		-20	9.35		-25.16		18.17		
		-10	-25.42		24.03		-24.09		
		0	-2.21		-23.21		23.41		
		+10	-19.01		9.85		-16.07		
		+20	26.52		27.01		29.16		
		+30	-18.49		26.09		-17.54		
		+40	17.92		-8.15		11.74		
		+50	-10.25		27.23		28.05		
	4.2	+25	26.98	24.37	-20.13				
3.4	+25	7.39	24.26	33.70					



## 2.4 Conducted Out of Band Emissions

### 2.4.1 Requirement

According to FCC section 21051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

### 2.4.2 Test Description

See section 2.1.2 of this report.

### 2.4.3 Test Result



The measurement frequency range is from 30MHz to the 10<sup>th</sup> harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.

#### 1. Test Verdict:



No.	Channel	Frequency(MHz )	Measured Max Spurious Emission(dBm)	Limit(dBm)
CDMA 800MHz	1013	824.7	-24.36	-13
	384	836.52	-24.62	-13
	777	848.31	-24.36	-13
CDMA 1900MHz	25	1850.2	< -25	-13
	600	1880.0	< -25	-13
	1175	1909.8	< -25	-13

#### 2. Test Plots for the Whole Measurement Frequency Range:



Note: the power of the EUT transmitting frequency should be ignored.





(Plot A: CDMA 800MHz Channel = 1013, 30MHz to 9GHz)





(Plot B: CDMA 800MHz Channel = 384, 30MHz to 9GHz)





(Plot C: CDMA 800MHz Channel = 777, 30MHz to 9GHz)



(Plot D: CDMA 1900MHz Channel = 25, 30MHz to 20GHz)



(Plot E: CDMA 1900MHz Channel = 600, 30MHz to 20GHz)



(Plot F: CDMA 1900MHz Channel = 1175, 30MHz to 20GHz)

## 2.5 Band Edge

### 2.5.1 Requirement

According to FCC section 2.1051, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

### 2.5.2 Test Description

See section 2.1.2 of this report.


### 2.5.3 Test Result

The lowest and highest channels are tested to verify the band edge emissions.


1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Band Edge Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
CDMA 800MHz	1013	824.7	-16.48	Plot A	-13	PASS
	777	848.31	-15.41	Plot B		PASS
CDMA 1900MHz	25	1851.2	-15.14	Plot C	-13	PASS
	1175	1908.8	-18.95	Plot D		PASS

2. Test Plots:




(Plot A: CDMA 800MHz Channel = 1013)



(Plot B: CDMA 800MHz Channel = 777)



(Plot C: CDMA 1900MHz Channel = 25)



(Plot D: CDMA 1900MHz Channel = 1175)


## 2.6 Transmitter Radiated Power (EIRP/ERP)

### 2.6.1 Requirement

According to FCC section 22.913, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2Watts e.i.r.p. peak power.

### 2.6.2 Test Description

#### 1. Test Setup:



1. The resolution bandwidth of the Spectrum Analyzer is set to be comparable to the emission bandwidth of the transmitter, e.g. for GSM modulated signal (here used):  $RBW=VBW=1MHz$ , for CDMA modulated signal:  $RBW=VBW=3MHz$ .
2. The low, middle and the high channels are selected to perform tests respectively.
3. Employ the bi-log Test Antenna as the test system receiving antenna; set the polarization of the Test Antenna to be the same as that of the EUT transmitting antenna.

Set the frequency range of the Spectrum Analyzer suitably to capture the waveform; actuate the Turn Table to turn from 0 degrees to 360 degrees to find the maximum reading via the Spectrum Analyzer, mark the peak; finally record the peak and the plot.

-Maximum RF output power: CDMA800 27.01dBm, CDMA 1900 25.64dBm

- Step size (dB): 3dB

- Minimum RF power: CDMA800 -0.1dBm, CDMA 1900 -0.3dBm

## 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date
System Simulator	Agilent	E5515C	GB43130131	2011.05
Spectrum Analyzer	Agilent	E7405A	US44210471	2011.05
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2011.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2011.05
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2011.05

### 2.6.3 Test Result

The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST\_TX}} - P_{\text{SUBST\_RX}} - L_{\text{SUBST\_CABLES}} + G_{\text{SUBST\_TX\_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where  $A_{\text{SUBST}}$  is the final substitution correction including receive antenna gain.

$P_{\text{SUBST\_TX}}$  is signal generator level,

$P_{\text{SUBST\_RX}}$  is receiver level,

$L_{\text{SUBST\_CABLES}}$  is cable losses including TX cable,

$G_{\text{SUBST\_TX\_ANT}}$  is substitution antenna gain.

$A_{\text{TOT}}$  is total correction factor including cable loss and substitution correction

During the test, the data of  $A_{\text{TOT}}$  was added in the Test Spectrum Analyze, so Spectrum Analyze reading is the final values which contain the data of  $A_{\text{TOT}}$ .




1. Test Verdict:


No.	Channel	Frequency (MHz)	Measured ERP		Limit	
			dBm	W	dBm	W
CDMA 800MHz	1013	824.7	30.8	1.202264	38.5	7
	384	836.52	29.91	0.979490		
	777	848.31	28.54	0.714496		

No.	Channel	Frequency (MHz)	Measured EIRP		Limit	
			dBm	W	dBm	W
CDMA 1900MHz	25	1850.2	23.92	0.246604	33	2
	600	1880.0	22.27	0.168655		
	1175	1909.8	19.43	0.087711		

2. Test Plots:



(Plot A: CDMA 800MHz Channel = 1013,384, 777)



(Plot B: CDMA 1900MHz Channel = 25, 600, 1175)

## 2.7 Radiated Out of Band Emissions

### 2.7.1 Requirement

According to FCC section 2.1053, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

### 2.7.2 Test Description

See section 2.6.2 of this report.

Note: when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

### 2.7.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

#### 1. Test Verdict:


Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)		Refer to Plot	Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical			
CDMA 800MHz	1013	1649	< -25	< -25	Plot A.1/A.2	-13	PASS
	384	1673	< -25	< -25	Plot B.1/B.2		PASS
	777	1696	< -25	< -25	Plot C.1/C.2		PASS
CDMA 1900MHz	25	3700	< -25	< -25	Plot D.1/D.2	-13	PASS
	600	3760	< -25	< -25	Plot E.1/E.2		PASS
	1175	1909.8	< -25	< -25	Plot F.1/F.2		PASS

2. Test Plots for the Whole Measurement Frequency Range:


Note: the power of the EUT transmitting frequency should be ignored.




(Plot A.1: CDMA 800MHz Channel = 1013, Test Antenna Horizontal)




(Plot A.2: CDMA 800MHz Channel = 1013, Test Antenna Vertical)




(Plot B.1: CDMA 800MHz Channel = 384, Test Antenna Horizontal)




(Plot B.2: CDMA 800MHz Channel = 384, Test Antenna Vertical)




(Plot C.1: CDMA 800MHz Channel = 777, Test Antenna Horizontal)




(Plot C.2: CDMA 800MHz Channel = 777, Test Antenna Vertical)




(Plot D.1: CDMA 1900MHz Channel = 25, Test Antenna Horizontal)



(Plot D.2: CDMA 1900MHz Channel = 25, Test Antenna Vertical)




(Plot E.1: CDMA 1900MHz Channel = 600, Test Antenna Horizontal)




(Plot E.2: CDMA 1900MHz Channel = 600, Test Antenna Vertical)





(Plot F.1: CDMA 1900MHz Channel = 1175, Test Antenna Horizontal)



(Plot F.2: CDMA 1900MHz Channel = 1175, Test Antenna Vertical)

\*\* END OF REPORT \*\*